
tcolorbox 4.13
tcolorbox
tcolorbox 4.13
Manual for
version
4.13
(2018/03/22)
tcolorbox 4.13
tcolorbox 4.13
Thomas F. Sturm

Cover code

```
% \usepackage{incgraph}
\begin{inctext}
\begin{tikzpicture}
\definecolorseries{boxcol}{rgb}{last}{blue}{red}
\resetcolorseries[28]{boxcol}
\coordinate (A) at (0,0); \coordinate (B) at (21,29.7);
\path[use as bounding box] (A) rectangle coordinate (C) (B);
\node[transform shape,xslant=0.7,rotate=-10,xshift=0cm] at (C) {%
  \begin{tcbraster}[raster columns=4,title=tcolorbox \version,
    fonttitle=\small\bfseries,raster width=50cm]
  \foreach \b in {1,...,28} {\begin{tcolorbox}[enhanced,
    watermark text=\thetcbrasternum,
    colframe=boxcol!30!white,
    colback=boxcol!25!white!30!white,
    colbacktitle=boxcol!!+!50!black!30!white,
    colupper=black!30!white]\lipsum[2]\end{tcolorbox}}
  \end{tcbraster}%
};
\node at (C) {%
  \begin{tcbitemize}[title=tcolorbox \version,fonttitle=\small\bfseries,
    enhanced jigsaw,opacityback=0.5,opacitybacktitle=0.75,
    halign=center,valign=center,arc=5mm,
    raster width=16cm,raster column skip=8mm,raster halign=center,
    raster force size=false,
    raster row 1/.style={height=6cm},
    raster row 2/.style={width=6cm,height=4cm},
    raster column 1/.style={flushright title,
      frame style={left color=yellow!50!black,right color=green!50!black},
      title style={left color=yellow!50!blue,right color=blue!50!green!50!black},
      interior style={left color=yellow!70,right color=green!70},
      underlay={\draw[line width=6mm,line cap=round,black!60]
        ([shift={(0.4,-0.15)}]frame.north east)
        --([shift={(0.4,0.15)}]frame.south east); }},
    raster column 2/.style={
      frame style={left color=green!50!black,right color=yellow!50!black},
      title style={left color=blue!50!green!50!black,right color=yellow!50!blue},
      interior style={left color=green!70,right color=yellow!70}}]
  \tcbitem[fontupper=\Huge\bfseries,sharp corners=east,
    underlay={\draw[line width=6mm,line cap=round,black!60]
      ([shift={(0.4,0.30)}]frame.north east)-- coordinate(A) +(0,0.2);
      \draw[line width=1mm,line cap=round,black!60](A) -- +(30:1.5cm);
      \draw[line width=1mm,line cap=round,black!60](A) -- +(150:1.5cm);}]
    tcolorbox
  \tcbitem[fontupper=\large\bfseries,sharp corners=west]
    Manual for\\ version\\ \version\\(\datum)
  \tcbitem[sharp corners=northeast]
  \tcbitem[sharp corners=northwest] Thomas F.~Sturm
  \end{tcbitemize}%
};
\end{tikzpicture}
\end{inctext}
```

The tcolorbox package

Manual for version 4.13 (2018/03/22)

Thomas F. Sturm[1]

http://www.ctan.org/pkg/tcolorbox

https://github.com/T-F-S/tcolorbox

Abstract

tcolorbox provides an environment for colored and framed text boxes with a heading line. Optionally, such a box can be split in an upper and a lower part. The package tcolorbox can be used for the setting of LaTeX examples where one part of the box displays the source code and the other part shows the output. Another common use case is the setting of theorems. The package supports saving and reuse of source code and text parts.

Contents

1 Introduction **8**
- 1.1 Installation . . . 8
- 1.2 Loading the Package . . . 8
- 1.3 Libraries . . . 9

2 Quick Reference **11**

3 Macros for Box Creation **12**

4 Option Keys **18**
- 4.1 Title . . . 18
- 4.2 Subtitle . . . 21
- 4.3 Upper Part . . . 22
- 4.4 Lower Part . . . 24
- 4.5 Colors and Fonts . . . 27
- 4.6 Text Alignment . . . 30
- 4.7 Geometry . . . 34
  - 4.7.1 Width . . . 34
  - 4.7.2 Rules . . . 35
  - 4.7.3 Arcs . . . 36
  - 4.7.4 Spacing . . . 39
  - 4.7.5 Size Shortcuts . . . 44
  - 4.7.6 Toggle Left and Right . . . 46
- 4.8 Corners . . . 48
- 4.9 Transparency . . . 51
- 4.10 Height Control . . . 53
- 4.11 Box Content Additions . . . 64
- 4.12 Overlays . . . 71

[1]Prof. Dr. Dr. Thomas F. Sturm, Institut für Mathematik und Informatik, Universität der Bundeswehr München, D-85577 Neubiberg, Germany; email: thomas.sturm@unibw.de

4.13 Floating Objects . . . 76
4.14 Embedding into the Surroundings . . . 78
4.15 Bounding Box . . . 82
4.15.1 Shifting Bounding Box Borders . . . 82
4.15.2 Box Alignment . . . 85
4.15.3 Toggle Enlargements . . . 86
4.15.4 Spread Box to Page Borders . . . 87
4.15.5 Box Extrusion . . . 89
4.16 Layered Boxes and Every Box Settings . . . 91
4.17 Capture Mode . . . 94
4.18 Text Characteristics . . . 95
4.19 Files . . . 96
4.20 `\tcbox` Specials . . . 96
4.21 Counters, Labels, and References . . . 98
4.22 Even and Odd Pages . . . 101
4.23 Externalization . . . 105
4.24 Miscellaneous . . . 105

5 Initialization Option Keys 108
5.1 Numbered Boxes . . . 108
5.2 Lists of `tcolorboxes` . . . 115

6 Side by Side 116
6.1 Basic Settings . . . 116
6.2 Advanced Settings from the LIB xparse Library . . . 122

7 Saving and Loading of Verbatim Texts 126

8 Recording 128
8.1 Macros . . . 128
8.2 Options . . . 128
8.3 Example: Exercises . . . 129
8.4 Example: Solutions . . . 132

9 Technical Overview and Customization 134
9.1 Skins and Drawing Engines . . . 134
9.2 Code Option Keys . . . 138
9.3 Subskins . . . 141
9.4 Drawing Scheme . . . 142
9.5 Useful Properties . . . 146

10 Library LIB skins 148
10.1 Style Option Keys . . . 148
10.2 Boxed Title Option Keys . . . 155
10.2.1 Boxed Title Placement . . . 155
10.2.2 Options for the Boxed Title Placement . . . 157
10.2.3 Options for the Boxed Title Box . . . 158
10.3 Watermark Option Keys . . . 165
10.4 Clip Environments . . . 172
10.5 Border Line Option Keys . . . 177
10.6 Shadow Option Keys . . . 182
10.6.1 Common Shadows and Halos . . . 182

10.6.2 Lifted Shadows . . . 187
10.6.3 Generic Shadows . . . 188
10.6.4 TikZ Shadows . . . 191
10.7 TikZ Picture Option Keys . . . 192
10.8 Underlay Option Keys . . . 195
10.9 Finish Option Keys . . . 197
10.10 Hyper Option Keys . . . 199
10.11 Jigsaw Skin Variants . . . 201
10.12 Draft Mode . . . 203
10.13 Skin Family 'standard' . . . 204
10.14 Skin Family 'enhanced' . . . 206
10.15 Skin Family 'bicolor' . . . 219
10.16 Skin Family 'tile' . . . 224
10.17 Skin Family 'beamer' . . . 228
10.18 Skin Family 'widget' . . . 233
10.19 Skin Family 'empty' . . . 237
10.20 Skin 'spartan' . . . 247
10.21 Skin 'draft' . . . 248
10.22 Skin Family 'freelance' . . . 250

11 Inclusion of Boxed Image Files 251
11.1 Macros . . . 251
11.2 Option Keys . . . 254

12 TikZ Image and Picture Fill Extensions; Auxiliary Macros 256
12.1 Fill Plain . . . 256
12.2 Fill Stretch . . . 257
12.3 Fill Overzoom . . . 258
12.4 Fill Zoom . . . 259
12.5 Fill Shrink . . . 260
12.6 Fill Tile . . . 261
12.7 Filling Options . . . 262
12.8 Straightening of the Arcs . . . 263
12.9 Extracting Node Dimensions . . . 264
12.10 Hyper Nodes . . . 264

13 Library LIB vignette 265
13.1 Vignette Drawing . . . 265
13.2 Generic Geometry Settings . . . 266
13.3 Generic Color and Style Settings . . . 268
13.4 Generic Fading Settings . . . 270
13.5 Vignette as Underlay . . . 272
13.6 Vignette as Finish . . . 274

14 Library LIB raster 277
14.1 Concept of Rasters . . . 277
14.2 Macros of the Library . . . 279
14.3 Option Keys of the Library . . . 283
14.4 Adding Styles for Specific Boxes . . . 288
14.5 Combining Columns or Rows . . . 290
14.6 Rasters inside Rasters . . . 293
14.6.1 Raster Setup . . . 293

14.6.2 Placing Spaces 294

15 Libraries LIB listings, LIB listingsutf8, and LIB minted **298**
15.1 Loading the Libraries 298
15.1.1 Loading LIB listings 298
15.1.2 Loading LIB listingsutf8 298
15.1.3 Loading LIB minted 299
15.2 Common Macros of the Libraries 299
15.3 Option Keys of the LIB listings Library 305
15.4 Option Keys of the LIB listingsutf8 Library 307
15.5 Option Keys of the LIB minted Library 308
15.6 Common Option Keys of all Libraries 310
15.7 Option Keys for Processing and Full Document Examples 319
15.8 Creation of LaTeX Tutorials 326
15.9 Creation of LaTeX Exercises 333
15.10 List of Exercises 336
15.11 Solutions for the given LaTeX Exercises 337

16 Library LIB theorems **339**
16.1 Macros of the Library 339
16.2 Option Keys of the Library 343
16.3 Examples for Definitions and Theorems 357
16.4 Using other theorem environments with `tcolorbox` 362

17 Library LIB breakable **363**
17.1 Technical Overview 363
17.2 Limitations and Known Bugs 364
17.3 Main Option Keys 365
17.4 Option Keys for the Break Appearance 369
17.5 Extra Options for Partial Boxes 371
17.6 Breakable boxes and the `multicol` package 373
17.7 Break Point Insertion 376
17.8 Break Sequence for the Skins 377
17.9 Break by Hand (Faked Break) 386

18 Library LIB magazine **387**
18.1 Creation and Resetting of Box Arrays 387
18.2 Storing Content 388
18.3 Retrieving Content 390
18.4 Box Dimensions 393
18.5 Leaflet Example 395

19 Library LIB poster **397**
19.1 Overview 397
19.2 Main Poster Environment 398
19.3 Poster Settings 400
19.4 Coverage 401
19.5 Common Box Settings 402
19.6 Font Scaling 402
19.7 Box Placement 403

20 Library fitting **410**
20.1 Macros of the Library . . . 410
20.2 Option Keys of the Library . . . 412

21 Library hooks **421**
21.1 Concept of Hooks . . . 421
21.2 Box Content Additions . . . 423
21.3 Embedding into the Surroundings . . . 424
21.4 Overlays . . . 425
21.5 Watermarks . . . 427
21.6 Underlays . . . 429
21.7 Finishes . . . 430
21.8 Skin Code . . . 430
21.9 Extras . . . 432

22 Library xparse **433**
22.1 Option Keys . . . 433
22.2 Producing `tcolorbox` Environments and Commands . . . 435
22.3 Producing `tcbox` Commands . . . 438
22.4 Producing `tcblisting` Environments . . . 441
22.5 Producing `tcbinputlisting` Commands . . . 443
22.6 Producing `tboxfit` Commands . . . 444

23 Library external **446**
23.1 Preparation of a Document for Externalization . . . 447
23.2 Marking Externalization Snippets . . . 448
23.3 Customization . . . 453
23.4 Troubleshooting and FAQ . . . 457

24 Library documentation **458**
24.1 Macros of the Library . . . 458
24.2 Option Keys of the Library . . . 468
24.3 Predefined Colors of the Library . . . 475

A Picture Credits **476**

References **477**

Index **479**

1 Introduction

The package originates from the first edition of my book «*LaTeX – Einführung in das Textsatzsystem*» [21] in about 2006. For the LaTeX examples and tutorials given there, I wanted to have accentuated and colored boxes to display source code and compiled text in combination. Since, in my opinion, this type of boxes is also quite useful to highlight definitions and theorems, I applied them for my lecture notes in mathematics [18–20] as well. With this package, you are invited to apply these boxes for similar projects.

Starting with version 2.00, for all internal calculations ε-TeX [2] expressions are used in replacement of the package `calc`. The breaking news for version 2.00 is the support for breakable boxes. This new feature allows new applications of the package without affecting the core package too much if you do not need boxes to break automatically. With version 2.20, the often requested 'side by side' mode for listings has been added. With version 3.00, boxed titles are introduced together with improved customization options for overlays, underlays, finishes, and own code extensions.

Since the first public release in 2011, I received a lot of feedback from all over the world. I want to thank all who wrote me for supporting this package by sending bug reports and ideas for new or better features.

1.1 Installation

Typically, `tcolorbox` will be installed as part of a major LaTeX distribution and there is nothing special to do for a user.

If you intend to make a local installation *by hand*, see the `README` file of the `tcolorbox` package for some hints. The short story is: you have to install not only `tcolorbox.sty`, but also all `*.code.tex` files in the local `texmf` tree.

1.2 Loading the Package

The base package `tcolorbox` loads the packages `pgf` [22], `verbatim` [17], `etoolbox` [7], and `environ` [16]. `tcolorbox` itself is loaded in the usual manner in the preamble:

```
\usepackage{tcolorbox}
```

The package takes option keys in the key-value syntax. Alternatively, you may use these keys later in the preamble with `\tcbuselibrary` → P. 9 (see there). For example, the key to typeset listings is:

```
\usepackage[listings]{tcolorbox}
```

1.3 Libraries

The base package `tcolorbox` is extendable by program libraries. This is done by using option keys while loading the package or inside the preamble by applying the following macro with the same set of keys.

`\tcbuselibrary{`⟨*key list*⟩`}`

Loads the libraries given by the ⟨*key list*⟩.

```
\tcbuselibrary{listings,theorems}
```

The following keys are used inside `\tcbuselibrary` respectively `\usepackage` without the key tree path `/tcb/library/`.

`/tcb/library/skins` (LIB skins)

Loads the package `tikz` [22] and provides additional styles (skins) for the appearance of the colored boxes; see Section 10 from page 148.

`/tcb/library/vignette` (LIB vignette)

Provides code for more ornamental; see Section 13 from page 265.

`/tcb/library/raster` (LIB raster)

Provides additional macros and options for typesetting multiple boxes arranged in a kind of raster; see Section 14 from page 277.

`/tcb/library/listings` (LIB listings)

Loads the package `listings` [6] and provides additional macros for typesetting listings which are described in Section 15 from page 298.

`/tcb/library/listingsutf8` (LIB listingsutf8)

Loads the packages `listings` [6] and `listingsutf8` [10] for UTF-8 support. This is a variant of the library LIB listings and is described in Section 15 from page 298.

`/tcb/library/minted` (LIB minted)

Loads the package `minted` [12] to typeset listings with the `Pygments` [14] tool, also see Section 15 on page 298.

`/tcb/library/theorems` (LIB theorems)

Provides additional macros for typesetting theorems which are described in Section 16 from page 339.

`/tcb/library/breakable` (LIB breakable)

Provides support for automatic box breaking from one page to another; see Section 17 on page 363.

`/tcb/library/magazine` (LIB magazine)

Provides support for storing broken box parts to be used later or in interchanged order, Section 18 on page 387.

`/tcb/library/poster` (LIB poster)

Provides support for creating posters, Section 19 on page 397.

`/tcb/library/fitting` (LIB fitting)

Provides support for font size adaption of the box content to the box dimensions; see Section 20 from page 410.

`/tcb/library/hooks` (LIB hooks)

Extends several option keys to 'hookable' keys; see Section 21 from page 421.

`/tcb/library/xparse` (LIB xparse)

Provides document command production with `xparse` for `tcolorbox`; see Section 22 from page 433.

`/tcb/library/external` (LIB external)

Provides externalization support for stand-alone document snippets, see Section 23 on page 446.

`/tcb/library/documentation` (LIB documentation)

Provides additional macros for typesetting LaTeX documentations which are described in Section 24 from page 458.

`/tcb/library/many` (style, no value)

Loads the libraries LIB skins, LIB breakable, LIB raster, LIB hooks, LIB theorems, LIB fitting, and LIB xparse. Use this shortcut, if you want to use all features of `tcolorbox` with exception of typesetting listings and using the specialized LIB documentation library.

`/tcb/library/most` (style, no value)

Loads all libraries except LIB minted and LIB documentation. Use this shortcut, if you want to use all features of `tcolorbox` with exception of using the `minted` package and using the specialized LIB documentation library.

`/tcb/library/all` (style, no value)

Loads all libraries. Use this shortcut only, if you indend to use the LIB documentation library.



2 Quick Reference





3 Macros for Box Creation

`\begin{tcolorbox}`[⟨*options*⟩]
⟨*environment content*⟩
`\end{tcolorbox}`

This is the main environment to create an accentuated colored text box with rounded corners and, optionally, two parts. The appearance of this box is controlled by numerous options. In the most simple case the source code

```
\begin{tcolorbox}
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

creates the following compiled text box:

This is a **tcolorbox**.

The text content of the box can be divided in an upper and a lower part by the command `\tcblower`. Visually, both parts are separated by a line. For example:

```
\begin{tcolorbox}
This is another \textbf{tcolorbox}.
\tcblower
Here, you see the lower part of the box.
\end{tcolorbox}
```

This code gives the following box:

This is another **tcolorbox**.

Here, you see the lower part of the box.

The ⟨*options*⟩ control the appearance and several functions of the boxes, see Section 4 on page 18 for the complete list. A quick example is given here:

```
\begin{tcolorbox}[colback=red!5!white,colframe=red!75!black,title=My nice heading]
This is another \textbf{tcolorbox}.
\tcblower
Here, you see the lower part of the box.
\end{tcolorbox}
```

My nice heading

This is another **tcolorbox**.

Here, you see the lower part of the box.

`\tcblower`

Used inside `tcolorbox` to separate the upper box part from the optional lower box part. The upper and the lower part are treated as separate functional units. If you only want to draw a line, see `\tcbline` → P. 209.

`\tcbset{`⟨*options*⟩`}`

Sets options for every following `tcolorbox` → P. 12 inside the current TEX group. By default, this does not apply to nested boxes, see Section 4.16 on page 91.

For example, the colors of the boxes may be defined for the whole document by this:

```
\tcbset{colback=red!5!white,colframe=red!75!black}
```

`\tcbsetforeverylayer{`⟨*options*⟩`}`

Sets options for every following `tcolorbox` → P. 12 inside the current TEX group. In contrast to `\tcbset`, this does also apply to nested boxes, see Section 4.16 on page 91. Technically, the ⟨*options*⟩ are appended to the default values for every tcolorbox which are applied by `/tcb/reset` → P. 105.

You should not use this macro, if you are not completely sure that you want to have the ⟨*options*⟩ also for boxes in boxes (in boxes in boxes . . .).

```
\tcbset{colback=green!10!white}
\tcbsetforeverylayer{colframe=red!75!black}

\begin{tcolorbox}[title=All options for this box]
  This is a tcolorbox.\par\medskip
  \begin{tcolorbox}[title=Nested box]
    Note that this nested box has a red frame but no green background.
  \end{tcolorbox}
\end{tcolorbox}
\bigskip

\begin{tcolorbox}[reset]
  Options given with |\tcbsetforeverylayer| survive a |reset|.
\end{tcolorbox}
```

All options for this box

This is a tcolorbox.

Nested box

Note that this nested box has a red frame but no green background.

Options given with `\tcbsetforeverylayer` survive a `reset`.

`\tcbox[⟨options⟩]{⟨box content⟩}`

Creates a colored box which is fitted to the width of the given ⟨*box content*⟩. In principle, most ⟨*options*⟩ for a `tcolorbox` → P. 12 can be used for `\tcbox` with some restrictions. A `\tcbox` cannot have a lower part and cannot be broken.

```
\tcbset{colframe=blue!50!black,colback=white,colupper=red!50!black,
        fonttitle=\bfseries,nobeforeafter,center title}

Text \tcbox[tcbox raise base]{Hello World}\hfill
%
\tcbox[left=0mm,right=0mm,top=0mm,bottom=0mm,boxsep=0mm,
  toptitle=0.5mm,bottomtitle=0.5mm,title=My table]{%
  \arrayrulecolor{blue!50!black}\renewcommand{\arraystretch}{1.2}%
  \begin{tabular}{r|c|l}
  One    & Two    & Three \\\hline\hline
  Men    & Mice   & Lions \\\hline
  Upper & Middle & Lower
  \end{tabular}}\hfill
%
\tcbox[colback=blue!85!black,
  left=0mm,right=0mm,top=0mm,bottom=0mm,boxsep=1mm,arc=0mm,boxrule=0.5pt,
  title=My picture]{%
  \includegraphics[width=5cm]{Basilica_5.png}}
```

Text Hello World

My table		
One	Two	Three
Men	Mice	Lions
Upper	Middle	Lower

My picture



```
% \usepackage{tikz}
\tcbset{colframe=blue!50!black,colback=white,colupper=red!50!black,
        fonttitle=\bfseries,center title}

% Fixed width box
\begin{tcolorbox}Hello\\World!\end{tcolorbox}

% Fitted width box (like hbox or makebox)
\tcbox{Hello\\World!}

% Fitted width box (using a \tikzname\  node)
\tcbox[tikznode]{Hello\\World!}
```

Hello
World!

HelloWorld!

Hello
World!

See Section 22.2 on page 435 and Section 22.3 on page 438 for more elaborate methods to create new environments and commands.

`\newtcolorbox[⟨init options⟩]{⟨name⟩}[⟨number⟩][⟨default⟩]{⟨options⟩}`

Creates a new environment ⟨*name*⟩ based on `tcolorbox` [→ P. 12]. Basically, `\newtcolorbox` operates like `\newenvironment`. This means, the new environment ⟨*name*⟩ optionally takes ⟨*number*⟩ arguments, where ⟨*default*⟩ is the default value for the optional first argument. The ⟨*options*⟩ are given to the underlying `tcolorbox`. Note that `/tcb/savedelimiter` [→ P. 26] is set to the given ⟨*name*⟩ automatically. The ⟨*init options*⟩ allow setting up automatic numbering, see Section 5 from page 108.

```
\newtcolorbox{mybox}{colback=red!5!white,
  colframe=red!75!black}

\begin{mybox}
This is my own box.
\end{mybox}
```

This is my own box.

```
\newtcolorbox{mybox}[1]{colback=red!5!white,
  colframe=red!75!black,fonttitle=\bfseries,
  title=#1}

\begin{mybox}{Hello there}
This is my own box with a mandatory title.
\end{mybox}
```

Hello there

This is my own box with a mandatory title.

```
\newtcolorbox{mybox}[2][]{colback=red!5!white,
  colframe=red!75!black,fonttitle=\bfseries,
  colbacktitle=red!85!black,enhanced,
attach boxed title to top center={yshift=-2mm},
  title=#2,#1}

\begin{mybox}[colback=yellow]{Hello there}
This is my own box with a mandatory title
and options.
\end{mybox}
```

Hello there

This is my own box with a mandatory title and options.

Definition in the preamble:

```
\newtcolorbox[auto counter,number within=section]{pabox}[2][]{%
  colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
  title=Examp.~\thetcbcounter: #2,#1}
```

```
\begin{pabox}[colback=yellow]{Hello there}
This is my own box with a mandatory
numbered title and options.
\end{pabox}
```

Examp. 3.1: Hello there

This is my own box with a mandatory numbered title and options.

`\renewtcolorbox[⟨init options⟩]{⟨name⟩}[⟨number⟩][⟨default⟩]{⟨options⟩}`

Operates like `\newtcolorbox`, but based on `\renewenvironment` instead of `\newenvironment`. An existing environment is redefined.

`\newtcbox`[⟨*init options*⟩]{\⟨*name*⟩}[⟨*number*⟩][⟨*default*⟩]{⟨*options*⟩}

Creates a new macro \⟨*name*⟩ based on `\tcbox` → P. 14. Basically, `\newtcbox` operates like `\newcommand`. The new macro \⟨*name*⟩ optionally takes ⟨*number*⟩+1 arguments, where ⟨*default*⟩ is the default value for the optional first argument. The ⟨*options*⟩ are given to the underlying `tcbox`. The ⟨*init options*⟩ allow setting up automatic numbering, see Section 5 from page 108.

```
\newtcbox{\mybox}{colback=red!5!white,
  colframe=red!75!black}

\mybox{This is my own box.}
```

This is my own box.

```
\newtcbox{\mybox}[1]{colback=red!5!white,
  colframe=red!75!black,fonttitle=\bfseries,
  title=#1}

\mybox{Hello there}{This is my own box.}
```

Hello there

This is my own box.

```
\newtcbox{\mybox}[2][]{colback=red!5!white,
  colframe=red!75!black,fonttitle=\bfseries,
  title=#2,#1}

\mybox[colback=yellow]{Hello there}%
  {This is my own box.}
```

Hello there

This is my own box.

Definition in the preamble:

```
% counter from previous example
\newtcbox[use counter from=pabox]{\pbbox}[2][]{%
  colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
  title=(\thetcbcounter) #2,#1}
```

```
\pbbox[colback=yellow]{Hello there}%
  {This is my own box.}
```

(3.2) Hello there

This is my own box.

```
\newtcbox{\mybox}[1][red]{on line,
  arc=0pt,outer arc=0pt,colback=#1!10!white,colframe=#1!50!black,
  boxsep=0pt,left=1pt,right=1pt,top=2pt,bottom=2pt,
  boxrule=0pt,bottomrule=1pt,toprule=1pt}
\newtcbox{\xmybox}[1][red]{on line,
  arc=7pt,colback=#1!10!white,colframe=#1!50!black,
  before upper={\rule[-3pt]{0pt}{10pt}},boxrule=1pt,
  boxsep=0pt,left=6pt,right=6pt,top=2pt,bottom=2pt}

The \mybox[green]{quick} brown \mybox{fox} \mybox[blue]{jumps} over the
\mybox[green]{lazy} \mybox{dog}.\par
The \xmybox[green]{quick} brown \xmybox{fox} \xmybox[blue]{jumps} over the
\xmybox[green]{lazy} \xmybox{dog}.
```

The quick brown fox jumps over the lazy dog.
The quick brown fox jumps over the lazy dog.

`\renewtcbox`[⟨*init options*⟩]{\⟨*name*⟩}[⟨*number*⟩][⟨*default*⟩]{⟨*options*⟩}

Operates like `\newtcbox`, but based on `\renewcommand` instead of `\newcommand`. An existing macro is redefined.

N 2014-10-20 `\tcolorboxenvironment{⟨name⟩}{⟨options⟩}`

An existing environment ⟨*name*⟩ is redefined to be boxed inside a `tcolorbox` with the given ⟨*options*⟩.

```
% tcbuselibrary{skins}
\newenvironment{myitemize}{%
  \begin{itemize}}{\end{itemize}}

\tcolorboxenvironment{myitemize}{blanker,
  before skip=6pt,after skip=6pt,
  borderline west={3mm}{0pt}{red}}

Some text.
\begin{myitemize}
\item Alpha
\item Beta
\item Gamma
\end{myitemize}
More text.
```

Some text.

- Alpha
- Beta
- Gamma

More text.

See further examples in Section 16.4 on page 362.

4 Option Keys

For the ⟨*options*⟩ in `tcolorbox` → P. 12 respectively `\tcbset` → P. 13 the following `pgf` keys can be applied. The key tree path `/tcb/` is not to be used inside these macros. It is easy to add your own style keys using the syntax for `pgf` keys, see [21, 22] or the examples starting from page 326.

4.1 Title

`/tcb/title`=⟨*text*⟩ (no default, initially empty)

Creates a heading line with ⟨*text*⟩ as content.

```
\begin{tcolorbox}[title=My heading line]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My heading line

This is a **tcolorbox**.

`/tcb/notitle` (no value, initially set)

Removes the title line if set before.

`/tcb/adjusted title`=⟨*text*⟩ (style, no default, initially unset)

Creates a heading line with ⟨*text*⟩ as content. The minimal height of this line is adjusted to fit the text given by `/tcb/adjust text`. This option makes sense for single line headings if boxes are set side by side with equal height. Note that it is very easy to trick this adjustment.

```
\tcbset{colback=White,arc=0mm,width=(\linewidth-4pt)/4,
equal height group=AT,before=,after=\hfill,fonttitle=\bfseries}

The following titles are not adjusted:\\
\foreach \n in {xxx,ggg,AAA,\"Agypten}
{\begin{tcolorbox}[title=\n,colframe=red!75!black]
  Some content.\end{tcolorbox}}
Now, we try again with adjusted titles:\\
\foreach \n in {xxx,ggg,AAA,\"Agypten}
{\begin{tcolorbox}[adjusted title=\n,colframe=blue!75!black]
  Some content.\end{tcolorbox}}
```

The following titles are not adjusted:

xxx	ggg	AAA	Ägypten
Some content.	Some content.	Some content.	Some content.

Now, we try again with adjusted titles:

xxx	ggg	AAA	Ägypten
Some content.	Some content.	Some content.	Some content.

`/tcb/adjust text`=⟨*text*⟩ (no default, initially `Äpgjy`)

This sets the reference text for `/tcb/adjusted title`. If your texts never exceed 'Äpgjy' in depth and height you don't need to care about this option.

N 2014-11-24 **/tcb/squeezed title=**⟨*text*⟩ (style, no default, initially unset)

Creates a single heading line with ⟨*text*⟩ as content. If the ⟨*text*⟩ is longer than the available space, the text is squeezed to fit into the available space.

```
% \tcbuselibrary{raster}
\begin{tcbitemize}[raster columns=3,raster equal height,
  colframe=red!75!black,colback=red!5!white,fonttitle=\bfseries]
\tcbitem[squeezed title={Short title}]
  First box
\tcbitem[squeezed title={This is a very very long title}]
  Second box
\tcbitem[squeezed title={This title is clearly to long for this application}]
  Third box
\end{tcbitemize}
```



N 2014-11-24 **/tcb/squeezed title*=**⟨*text*⟩ (style, no default, initially unset)

This is a combination of /tcb/adjusted title → P. 18 and /tcb/squeezed title.

```
% \tcbuselibrary{raster}
\begin{tcbitemize}[raster columns=3,raster equal height,
  colframe=red!75!black,colback=red!5!white,fonttitle=\bfseries]
\tcbitem[squeezed title*={Short title}]
  First box
\tcbitem[squeezed title*={This is a very very long title}]
  Second box
\tcbitem[squeezed title*={This title is clearly to long for this application}]
  Third box
\end{tcbitemize}
```



`/tcb/detach title` (no value)

Detaches the title from its normal position. The text of the title is stored into `\tcbtitletext` and the formatted title is available by `\tcbtitle`. The main application is to move the title from its usual place to another one.

```
\newtcolorbox{mybox}[2][]{colbacktitle=red!10!white,
  colback=blue!10!white,coltitle=red!70!black,
  title={#2},fonttitle=\bfseries,#1}

\begin{mybox}{My title}
  This is a \textbf{tcolorbox}.
\end{mybox}
\begin{mybox}[detach title,before upper={\tcbtitle\quad}]{My title}
  This is a \textbf{tcolorbox}.
\end{mybox}
\begin{mybox}[detach title,after upper={\par\hfill\tcbtitle}]{My title}
  This is a \textbf{tcolorbox}.
\end{mybox}
```

My title

This is a **tcolorbox**.

My title This is a **tcolorbox**.

This is a **tcolorbox**.

My title

`/tcb/attach title` (no value)

Attaches the title to its normal position. This option is used to reverse `/tcb/detach title`.

U 2015-07-08 `/tcb/attach title to upper=`⟨*text*⟩ (style, default empty, initially unset)

Attaches the title to the begin of the upper part of the box content. The optional ⟨*text*⟩ is set between the formatted title and the box content.

```
\newtcolorbox{mybox}[2][]{colbacktitle=red!10!white,
  colback=blue!10!white,coltitle=red!70!black,
  title={#2},fonttitle=\bfseries,#1}

\begin{mybox}[attach title to upper={\ ---\ }]{My title}
  This is a \textbf{tcolorbox}.
\end{mybox}
\begin{mybox}[attach title to upper,after title={:\ }]{My title}
  This is a \textbf{tcolorbox}.
\end{mybox}
```

My title — This is a **tcolorbox**.

My title: This is a **tcolorbox**.

! More title options are documented in Section 4.11 on page 64 and Section 10.2 on page 155.

4.2 Subtitle

Inside the box content, one or more subtitles can be added. In general, a subtitle is a further tcolorbox → P. 12 which inherits some color and geometry options from the enclosing box. It may be customized just like any other tcolorbox → P. 12.

N 2014-10-10 **\tcbsubtitle**[⟨*options*⟩]{⟨*text*⟩}

Used inside a tcolorbox → P. 12 to add a subtitle box with the given ⟨*text*⟩. This is an independent tcolorbox → P. 12 which is formatted by several inherited properties of the enclosing box, by further settings from /tcb/subtitle style, and by the given ⟨*options*⟩.

```
\begin{tcolorbox}[title=My title,
    colback=red!5!white,
    colframe=red!75!black,
    fonttitle=\bfseries]
  This is a \textbf{tcolorbox}.
\tcbsubtitle[before skip=\baselineskip]%
  {My subtitle}
  Further text.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

My subtitle

Further text.

```
\begin{tcolorbox}[title=My title,
    colback=red!5!white,
    colframe=red!75!black,
    colbacktitle=yellow!50!red,
    coltitle=red!25!black,
    fonttitle=\bfseries]
  This is a \textbf{tcolorbox}.
\tcbsubtitle[before skip=\baselineskip]%
  {My subtitle}
  Further text.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

My subtitle

Further text.

N 2014-10-10 **/tcb/subtitle style**=⟨*options*⟩ (no default, initially empty)

Adds tcolorbox ⟨*options*⟩ to the settings for \tcbsubtitle.

```
\begin{tcolorbox}[title=My title,
  colback=red!5!white,
  colframe=red!75!black,
  colbacktitle=yellow!50!red,
  coltitle=red!25!black,
  fonttitle=\bfseries,
  subtitle style={boxrule=0.4pt,
    colback=yellow!50!red!25!white} ]
  This is a \textbf{tcolorbox}.
\tcbsubtitle{My subtitle}
  Further text.
\tcbsubtitle{Second subtitle}
  Further text.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

My subtitle

Further text.

Second subtitle

Further text.

4.3 Upper Part

The text content of a `tcolorbox` → P. 12 may be parted into a mandatory *upper part* and an optional *lower part*. These parts are separated by `\tcblower` → P. 12. If there is no `\tcblower` → P. 12 present, there is no *lower part* and the *upper part* forms the complete text content.

N 2015-01-06 **/tcb/upperbox=⟨*mode*⟩** (no default, initially `visible`)

Controls the treatment of the upper part of the box. If there is no lower part, this is the complete text content. Feasible values for ⟨*mode*⟩ are:

- `visible`: usual type setting of the upper part,
- `invisible`: empty space instead of the upper part contents.

```
\begin{tcolorbox}[upperbox=invisible,colback=white]
This is a \textbf{tcolorbox} (but invisible).
\end{tcolorbox}

\bigskip

\begin{tcolorbox}[upperbox=invisible,colback=white]
This is a \textbf{tcolorbox} (but invisible).
\tcblower
This is the lower part.
\end{tcolorbox}
```

This is the lower part.

N 2015-01-06 **/tcb/visible** (style, no value)

Shortcut for setting `/tcb/upperbox` and `/tcb/lowerbox` → P. 24 to be `visible`.

N 2015-01-06 **/tcb/invisible** (style, no value)

Shortcut for setting `/tcb/upperbox` and `/tcb/lowerbox` → P. 24 to be `invisible`.

```
\begin{tcolorbox}[invisible]
This is a \textbf{tcolorbox} (but invisible).
\end{tcolorbox}
```

N 2015-05-04 **/tcb/saveto=**⟨*file name*⟩ (no default, initially empty)

Saves the content of the box into a file for an optional later usage. This is the counterpart of /tcb/savelowerto → P. 24, but is saves not only the upper part but the whole content. If a lower part is present, it is also saved including \tcblower → P. 12.

! This option cannot be combined with /tcb/savelowerto → P. 24.

```
\begin{tcolorbox}[invisible,saveto=\jobname_mysave1.tex,colback=white]
This is a \textbf{tcolorbox} which seems to be empty.
The content is saved for later usage.
\end{tcolorbox}

Now, we load the saved text:\\
\input{\jobname_mysave1.tex}
```

Now, we load the saved text:
This is a **tcolorbox** which seems to be empty. The content is saved for later usage.

```
\begin{tcolorbox}[saveto=\jobname_mysave2.tex]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}

Now, we load the saved text:
\begin{tcolorbox}[colframe=red,colback=red!10,
  coltitle=black,colbacktitle=red!20,sidebyside,
  title=Here we see the saved content including the lower part]
\input{\jobname_mysave2.tex}
\end{tcolorbox}
```

This is a **tcolorbox**.

This is the lower part.

Now, we load the saved text:

Here we see the saved content including the lower part

This is a **tcolorbox**. | This is the lower part.

4.4 Lower Part

`/tcb/lowerbox`=⟨*mode*⟩ (no default, initially `visible`)

Controls the treatment of the lower part of the box. Feasible values for ⟨*mode*⟩ are:

- `visible`: usual type setting of the lower part,
- `invisible`: empty space instead of the lower part contents,
- `ignored`: the lower part is not used (here).

The last two values are usually applied in connection with `savelowerto`.

```
\begin{tcolorbox}[lowerbox=invisible,colback=white]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part (but invisible).
\end{tcolorbox}

\begin{tcolorbox}[lowerbox=ignored,colback=white]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part (but ignored).
\end{tcolorbox}
```

This is a **tcolorbox**.

This is a **tcolorbox**.

U 2014-11-28 `/tcb/savelowerto`=⟨*file name*⟩ (no default, initially empty)

Saves the content of the lower part into a file for an optional later usage.

```
\begin{tcolorbox}[lowerbox=invisible,savelowerto=\jobname_bspsave.tex,colback=white]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part which may be quite complex:
$\displaystyle f(x)=\frac{1+x^2}{1-x^2}$.
\end{tcolorbox}

Now, we load the saved text:\\
\input{\jobname_bspsave.tex}
```

This is a **tcolorbox**.

Now, we load the saved text:

This is the lower part which may be quite complex: $f(x) = \dfrac{1+x^2}{1-x^2}$.

`/tcb/lower separated=true|false` (default `true`, initially `true`)

If set to `true`, the lower part is visually separated from the upper part. It depends on the chosen skin how the visualization of the separation is done.

```
% \tcbuselibrary{skins,raster}
\begin{tcbraster}[colback=red!5!white,colframe=red!75!black,
  fonttitle=\bfseries,fontlower=\itshape]
%
\begin{tcolorbox}[title=Lower separated]
This is the upper part.
\tcblower
This is the lower part.
\end{tcolorbox}
%
\begin{tcolorbox}[title=Lower not separated,lower separated=false]
This is the upper part.
\tcblower
This is the lower part.
\end{tcolorbox}
%
\begin{tcolorbox}[sidebyside,title=Lower separated]
This is the upper part.
\tcblower
This is the lower part.
\end{tcolorbox}
%
\begin{tcolorbox}[sidebyside,title=Lower not separated,lower separated=false]
This is the upper part.
\tcblower
This is the lower part.
\end{tcolorbox}
%
\begin{tcolorbox}[beamer,title=Lower separated]
This is the upper part.
\tcblower
This is the lower part.
\end{tcolorbox}
%
\begin{tcolorbox}[beamer,title=Lower not separated,lower separated=false]
This is the upper part.
\tcblower
This is the lower part.
\end{tcolorbox}
%
\end{tcbraster}
```

Lower separated

This is the upper part.

This is the lower part.

Lower not separated

This is the upper part.

This is the lower part.

Lower separated

This is the upper part.

This is the lower part.

Lower not separated

This is the upper part.

This is the lower part.

Lower separated

This is the upper part.

This is the lower part.

Lower not separated

This is the upper part.

This is the lower part.

`/tcb/savedelimiter=`⟨*name*⟩ (no default, initially `tcolorbox`)

Used in connection with new environment definitions which extend `tcolorbox` and use or allow the option `savelowerto`. To catch the end of the new box environment ⟨*name*⟩ has to be the name of this environment. Additionally, the environment definition has to use `\tcolorbox` instead of `\begin{tcolorbox}` and `\endtcolorbox` instead of `\end{tcolorbox}`.

```
\newenvironment{mybox}[1]{%
  \tcolorbox[savedelimiter=mybox,
             savelowerto=\jobname_bspsave2.tex,lowerbox=ignored,
             colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
             title=#1]}%
  {\endtcolorbox}

\begin{mybox}{My Example}
Upper part.
\tcblower
Saved lower part!
\end{mybox}

Now, the saved part is used:
\begin{tcolorbox}[colback=green!5]
\input{\jobname_bspsave2.tex}
\end{tcolorbox}
```

My Example

Upper part.

Now, the saved part is used:

Saved lower part!

The `savedelimiter` is used implicitely with `\newtcolorbox` → P. 15 which allows a more convenient usage:

```
\newtcolorbox{mybox}[1]{%
             savelowerto=\jobname_bspsave2.tex,lowerbox=ignored,
             colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
             title=#1}%

\begin{mybox}{My Example}
Upper part.
\tcblower
Saved lower part!
\end{mybox}

Now, the saved part is used:
\begin{tcolorbox}[colback=green!5]
\input{\jobname_bspsave2.tex}
\end{tcolorbox}
```

My Example

Upper part.

Now, the saved part is used:

Saved lower part!

4.5 Colors and Fonts

`/tcb/colframe=`⟨*color*⟩ (no default, initially `black!75!white`)

Sets the frame ⟨*color*⟩ of the box.

```
\begin{tcolorbox}[colframe=red!50!white]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

`/tcb/colback=`⟨*color*⟩ (no default, initially `black!5!white`)

Sets the background ⟨*color*⟩ of the box.

```
\begin{tcolorbox}[colback=red!50!white]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

`/tcb/title filled=true|false` (default `true`, initially `false`)

Switches the drawing of the title background according to the given value. This option is set to `true` automatically by `/tcb/colbacktitle`, `/tcb/opacitybacktitle` → P. 51, and `/tcb/title style` → P. 151, and `/tcb/title code` → P. 140.

```
\begin{tcolorbox}[title=My title,title filled]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
\begin{tcolorbox}[title=My title,
  title filled=false]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

My title

This is a **tcolorbox**.

`/tcb/colbacktitle=`⟨*color*⟩ (no default, initially `black!50!white`)

Sets the background ⟨*color*⟩ of the title area of the box.

```
\begin{tcolorbox}[colbacktitle=red!50!white,
  title=My title,coltitle=black,
  fonttitle=\bfseries]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

`/tcb/colupper`=⟨*color*⟩ (no default, initially `black`)

Sets the text ⟨*color*⟩ of the upper part.

```
\begin{tcolorbox}[colupper=red!75!black]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

This is a **tcolorbox**.

This is the lower part.

`/tcb/collower`=⟨*color*⟩ (no default, initially `black`)

Sets the text ⟨*color*⟩ of the lower part.

```
\begin{tcolorbox}[collower=red!75!black]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

This is a **tcolorbox**.

This is the lower part.

`/tcb/coltext`=⟨*color*⟩ (style, no default, initially `black`)

Sets the text ⟨*color*⟩ of the box. This is an abbreviation for setting `colupper` and `collower` to the same value.

```
\begin{tcolorbox}[coltext=red!75!black]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

This is a **tcolorbox**.

This is the lower part.

`/tcb/coltitle`=⟨*color*⟩ (no default, initially `white`)

Sets the title text ⟨*color*⟩ of the box.

```
\begin{tcolorbox}[coltitle=red!75!black,
  colbacktitle=black!10!white,title=Test]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

Test

This is a **tcolorbox**.

/tcb/fontupper=⟨*text*⟩ (no default, initially empty)

Sets ⟨*text*⟩ before the content of the upper part (e. g. font settings).

```
\begin{tcolorbox}[fontupper=Hello!~\sffamily]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

Hello! This is a **tcolorbox**.

/tcb/fontlower=⟨*text*⟩ (no default, initially empty)

Sets ⟨*text*⟩ before the content of the lower part (e. g. font settings).

```
\begin{tcolorbox}[fontlower=\sffamily\bfseries]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

This is a **tcolorbox**.

This is the lower part.

/tcb/fonttitle=⟨*text*⟩ (no default, initially empty)

Sets ⟨*text*⟩ before the content of the title text (e. g. font settings).

```
\begin{tcolorbox}[fonttitle=\sffamily\bfseries\large,title=Hello]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

Hello

This is a **tcolorbox**.

More color options are provided by using skins documented in Section 10 from page 148.

4.6 Text Alignment

N 2015-05-07 **/tcb/halign=**⟨*alignment*⟩ (no default, initially **justify**)

If there is no lower part, **halign** determines the horizontal ⟨*alignment*⟩ of the text content. Otherwise, **halign** determines the horizontal ⟨*alignment*⟩ of the upper part of the box only. The feasible values for ⟨*alignment*⟩ are more or less identical to the corresponding **/tikz/align** settings, even if the implementation differs.

- **justify**: usual left and right justified type setting.
- **left**: left border justification in analogy to plain TEX.
- **flush left**: left border justification with **\raggedright** of LATEX.
- **right**: right border justification in analogy to plain TEX.
- **flush right**: right border justification with **\raggedleft** of LATEX.
- **center**: centering in analogy to plain TEX.
- **flush center**: centering with **\centering** of LATEX.

The differences between the flush and non-flush version are explained in detail in the TikZ manual [22]. The short story is that the non-flush versions will often look more balanced but with more hyphenations.

```
\tcbset{colback=red!5!white,colframe=red!75!black,size=small,
  fonttitle=\bfseries,width=3.5cm,box align=top,
  nobeforeafter}

\begin{tcolorbox}[adjusted title=flush center,halign=flush center]
This is a demonstration text for showing how line breaking works.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=flush left,halign=flush left]
This is a demonstration text for showing how line breaking works.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=flush right,halign=flush right]
This is a demonstration text for showing how line breaking works.
\end{tcolorbox}

\begin{tcolorbox}[adjusted title=center,halign=center]
This is a demonstration text for showing how line breaking works.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=left,halign=left]
This is a demonstration text for showing how line breaking works.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=right,halign upper=right]
This is a demonstration text for showing how line breaking works.
\end{tcolorbox}
```

flush center
This is a demonstration text for showing how line breaking works.

flush left
This is a demonstration text for showing how line breaking works.

flush right
This is a demonstration text for showing how line breaking works.

center
This is a demonstration text for showing how line breaking works.

left
This is a demonstration text for showing how line breaking works.

right
This is a demonstration text for showing how line breaking works.

N 2015-05-07 **/tcb/halign upper=**⟨*alignment*⟩ (no default, initially **justify**)

Alias for /tcb/halign.

N 2015-05-07 **/tcb/halign lower=⟨*alignment*⟩** (no default, initially **justify**)

halign lower determines the horizontal ⟨*alignment*⟩ of the lower part of the box. The feasible values for ⟨*alignment*⟩ are the same as for **/tcb/halign** → P. 30.

```
\begin{tcbraster}[raster columns=3,fonttitle=\bfseries,
  colback=red!5!white,colframe=red!75!black]

  \begin{tcolorbox}[adjusted title=flush center,halign lower=flush center]
    Upper part. \tcblower Lower part.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=flush left,halign lower=flush left]
    Upper part. \tcblower Lower part.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=flush right,halign lower=flush right]
    Upper part. \tcblower Lower part.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=center,halign lower=center]
    Upper part. \tcblower Lower part.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=left,halign lower=left]
    Upper part. \tcblower Lower part.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=right,halign lower=right]
    Upper part. \tcblower Lower part.
  \end{tcolorbox}

\end{tcbraster}
```

flush center
Upper part.
Lower part.

flush left
Upper part.
Lower part.

flush right
Upper part.
Lower part.

center
Upper part.
Lower part.

left
Upper part.
Lower part.

right
Upper part.
Lower part.

N 2015-05-07 **/tcb/halign title=⟨*alignment*⟩** (no default, initially **justify**)

halign lower determines the horizontal ⟨*alignment*⟩ of the title of the box. The feasible values for ⟨*alignment*⟩ are the same as for /tcb/halign → P. 30.

```
\begin{tcbraster}[raster columns=3,fonttitle=\bfseries,
  colback=red!5!white,colframe=red!75!black]

  \begin{tcolorbox}[adjusted title=flush center,halign title=flush center]
    This is a \textbf{tcolorbox}.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=flush left,halign title=flush left]
    This is a \textbf{tcolorbox}.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=flush right,halign title=flush right]
    This is a \textbf{tcolorbox}.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=center,halign title=center]
    This is a \textbf{tcolorbox}.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=left,halign title=left]
    This is a \textbf{tcolorbox}.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=right,halign title=right]
    This is a \textbf{tcolorbox}.
  \end{tcolorbox}

\end{tcbraster}
```

flush center
This is a **tcolorbox**.

flush left
This is a **tcolorbox**.

flush right
This is a **tcolorbox**.

center
This is a **tcolorbox**.

left
This is a **tcolorbox**.

right
This is a **tcolorbox**.

U 2015-05-07 **/tcb/flushleft upper** (style, no value)

Shortcut for setting /tcb/halign → P. 30 to **flush left**.

U 2015-05-07 **/tcb/center upper** (style, no value)

Shortcut for setting /tcb/halign → P. 30 to **flush center**.

U 2015-05-07 **/tcb/flushright upper** (style, no value)

Shortcut for setting /tcb/halign → P. 30 to **flush right**.

U 2015-05-07 **/tcb/flushleft lower** (style, no value)

Shortcut for setting /tcb/halign lower → P. 31 to **flush left**.

U 2015-05-07 **/tcb/center lower** (style, no value)

Shortcut for setting /tcb/halign lower → P. 31 to **flush center**.

U 2015-05-07 **/tcb/flushright lower** (style, no value)

Shortcut for setting /tcb/halign lower → P. 31 to **flush right**.

U 2015-05-07 **/tcb/flushleft title** (style, no value)

Shortcut for setting /tcb/halign title to **flush left**.

U 2015-05-07 **/tcb/center title** (style, no value)

Shortcut for setting /tcb/halign title to **flush center**.

U 2015-05-07 **/tcb/flushright title** (style, no value)

Shortcut for setting /tcb/halign title to **flush right**.

! The vertical alignment settings are only relevant for boxes which are larger than their natural height, see Section 4.10 on page 53.

U 2015-07-16 `/tcb/valign`=⟨*alignment*⟩ (no default, initially `top`)

If the height of a `tcolorbox` is not the natural height, `valign` determines the vertical ⟨*alignment*⟩ of the upper part. Feasible values are

- `top`: Anchor text at top.
- `center`: Anchor text at center.
- `bottom`: Anchor text at bottom.
- `scale`: Scale text vertically to fit into the available space. This is brutal and may not look very good. Consider Section 20 on page 410 alternatively.
- `scale*`: Like `scale`, but scaling is bounded by `/tcb/valign scale limit`.

For a box with natural height, these settings are meaningless.

```
\tcbset{width=(\linewidth-2mm)/4,before=,after=\hfill,
colframe=blue!75!black,colback=white,height=2cm}

\foreach \myalign in {top,center,bottom,scale}
{\begin{tcolorbox}[valign=\myalign]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}}
```



N 2015-05-07 `/tcb/valign upper`=⟨*alignment*⟩ (no default, initially `top`)

Alias for `/tcb/valign`.

`/tcb/valign lower`=⟨*alignment*⟩ (no default, initially `top`)

This key has the same meaning for the lower part as `valign` for the upper part, i. e., it determines the vertical ⟨*alignment*⟩ of the lower part with feasible values `top`, `center`, `bottom`, `scale`, and `scale*`.

N 2015-07-16 `/tcb/valign scale limit`=⟨*real number*⟩ (no default, initially `1.1`)

Sets an upper scale limit for the `scale*` setting in `/tcb/valign` and `/tcb/valign lower`. Note that this value is not reset by `/tcb/reset` → P. 105. So, changes also apply to embedded boxes.

Also see `/tcb/sidebyside align` → P. 117 for alignment settings when upper part and lower part are set side-by-side.

4.7 Geometry

4.7.1 Width

`/tcb/width`=⟨*length*⟩ (no default, initially `\linewidth`)

Sets the total width of the colored box to ⟨*length*⟩. See also `/tcb/height` → P. 53.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[width=\linewidth/2]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

N 2014-10-31 `/tcb/text width`=⟨*length*⟩ (style, no default)

Sets the text width of the upper part to ⟨*length*⟩. See also `/tcb/text height` → P. 54.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[text width=4cm]
This is a \textbf{tcolorbox} where the text has a width of 4cm.
\end{tcolorbox}
```

This is a **tcolorbox** where the text has a width of 4cm.

N 2014-11-07 `/tcb/add to width`=⟨*length*⟩ (style, no default)

Adds ⟨*length*⟩ to the current total width of the colored box.

```
\tcbset{width=4cm,colback=red!5!white,
  colframe=red!75!black}

\begin{tcolorbox}
This is a \textbf{tcolorbox}.
\end{tcolorbox}

\begin{tcolorbox}[add to width=1cm]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

This is a **tcolorbox**.

See Section 4.10 on page 53 for setting fixed height values.

4.7.2 Rules

`/tcb/toprule`=⟨*length*⟩ (no default, initially `0.5mm`)

Sets the line width of the top rule to ⟨*length*⟩.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[toprule=3mm]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

`/tcb/bottomrule`=⟨*length*⟩ (no default, initially `0.5mm`)

Sets the line width of the bottom rule to ⟨*length*⟩.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[bottomrule=3mm]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

`/tcb/leftrule`=⟨*length*⟩ (no default, initially `0.5mm`)

Sets the line width of the left rule to ⟨*length*⟩.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[leftrule=3mm]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

`/tcb/rightrule`=⟨*length*⟩ (no default, initially `0.5mm`)

Sets the line width of the right rule to ⟨*length*⟩.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[rightrule=3mm]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

/tcb/titlerule=⟨*length*⟩ (no default, initially 0.5mm)

Sets the line width of the rule below the title to ⟨*length*⟩.

```
\tcbset{enhanced,colback=red!5!white,colframe=red!75!black,
  colbacktitle=red!90!black}

\begin{tcolorbox}[titlerule=3mm,title=This is the title]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is the title

This is a **tcolorbox**.

/tcb/boxrule=⟨*length*⟩ (style, no default, initially 0.5mm)

Sets all rules of the frame to ⟨*length*⟩, i. e. /tcb/toprule → P. 35, /tcb/bottomrule → P. 35, /tcb/leftrule → P. 35, /tcb/rightrule → P. 35, and /tcb/titlerule.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[boxrule=3mm]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

! More options for drawing a /tcb/borderline → P. 177 are provided by using skins documented in Section 10 from page 148.

4.7.3 Arcs

/tcb/arc=⟨*length*⟩ (no default, initially 1mm)

Sets the inner radius of the four frame arcs to ⟨*length*⟩.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[arc=0mm]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
\begin{tcolorbox}[arc=3mm]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

This is a **tcolorbox**.

N 2015-05-05 **/tcb/circular arc** (style, no value)

Sets /tcb/arc → P. 36 to match the half of the inner width of the colored box. If width and height of the box are identical, this gives a circle.

! If the height of the box is smaller than the width, the result will look quite ugly.

```
\begin{tcolorbox}[width=3cm,
  colback=red!5!white,
  colframe=red!75!black,
  halign=center,valign=center,
  square,circular arc]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

N 2015-05-05 **/tcb/bean arc** (style, no value)

Sets /tcb/arc → P. 36 to match the smaller value of the half of the inner width and of the inner height of the colored box.

! This only works for a fixed /tcb/height → P. 53. Also, /tcb/bean arc must be used *after* width and height are set by option keys.

```
\tcbset{size=fbox,boxrule=0.5mm,
  colback=red!5!white,
  colframe=red!75!black,
  halign=center,valign=center}

\begin{tcolorbox}[width=3cm,height=2cm,
  bean arc]
Box A
\end{tcolorbox}

\begin{tcolorbox}[width=2cm,height=3cm,
  bean arc]
Box B
\end{tcolorbox}
```



N 2015-05-05 **/tcb/octogon arc** (style, no value)

Sets /tcb/arc → P. 36 to match $\frac{1}{2+\sqrt{2}}$ of the inner width of the colored box. If width and height of the box are identical, the interior is a regular octogon.

```
\begin{tcolorbox}[enhanced,
  size=minimal,auto outer arc,
  width=2.1cm,octogon arc,
  colback=red,colframe=white,colupper=white,
  fontupper=\fontsize{7mm}{7mm}\selectfont\bfseries\sffamily,
  halign=center,valign=center,
  square,arc is angular,
  borderline={0.2mm}{-1mm}{red}  ]
STOP
\end{tcolorbox}
```

N 2015-05-05 **/tcb/arc is angular** (no value, initially unset)

Using this options applies a patch which straightens the corners arcs of the boxes. The little arcs are replaced by little straight lines.

> ! This patch is considered as an experimental feature. It changes some of the original Ti*k*Z code. This change may break with future updates of Ti*k*Z.

```
\tcbset{colback=red!5!white,colframe=red!75!black,
  arc=3mm}

\begin{tcolorbox}[arc is angular]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
\begin{tcolorbox}[arc is curved]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

This is a **tcolorbox**.

N 2015-05-05 **/tcb/arc is curved** (no value, initially set)

This option resets the patch from /tcb/arc is angular. The original Ti*k*Z code is activated.

/tcb/outer arc=⟨*length*⟩ (no default, initially unset)

Sets the outer radius of the four frame arcs to ⟨*length*⟩.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[arc=4mm,outer arc=1mm]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

/tcb/auto outer arc (no value, initially set)

Sets the outer radius of the four frame arcs automatically in dependency of the inner radius given by /tcb/arc → P. 36.

4.7.4 Spacing

`/tcb/boxsep`=⟨*length*⟩ (no default, initially `1mm`)

Sets a common padding of ⟨*length*⟩ between the text content and the frame of the box. This value is added to the key values of `left`, `right`, `top`, `bottom`, and `middle` at the appropriate places.

```
\tcbset{colback=red!5!white,colframe=red!75!black,width=(\linewidth-4mm)/2,
  before=,after=\hfill}

\begin{tcolorbox}[boxsep=5mm]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
\begin{tcolorbox}[boxsep=5mm,draft]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```



`/tcb/left`=⟨*length*⟩ (style, no default, initially `4mm`)

Sets the left space between all text parts and frame (additional to `boxsep`). This is an abbreviation for setting `lefttitle`, `leftupper`, and `leftlower` to the same value.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[left=0mm]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```



N 2017-02-16 `/tcb/left*`=⟨*length*⟩ (style, no default)

Sets `/tcb/left` such that ⟨*length*⟩ is the distance between the left bounding box and the text parts.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

This is some text.
\begin{tcolorbox}[grow to left by=5mm,left*=0mm,
  enhanced,show bounding box]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```



`/tcb/lefttitle=`⟨*length*⟩ (no default, initially `4mm`)

Sets the left space between title text and frame (additional to `boxsep`).

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[lefttitle=3cm,title=My Title]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My Title

This is a **tcolorbox**.

`/tcb/leftupper=`⟨*length*⟩ (no default, initially `4mm`)

Sets the left space between upper text and frame (additional to `boxsep`).

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[leftupper=3cm,title=My Title]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My Title

This is a **tcolorbox**.

`/tcb/leftlower=`⟨*length*⟩ (no default, initially `4mm`)

Sets the left space between lower text and frame (additional to `boxsep`).

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[leftlower=3cm]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

This is a **tcolorbox**.

This is the lower part.

`/tcb/right=`⟨*length*⟩ (style, no default, initially `4mm`)

Sets the right space between all text parts and frame (additional to `boxsep`). This is an abbreviation for setting `righttitle`, `rightupper`, and `rightlower` to the same value.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[width=5cm,right=2cm]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcol-orbox**.

N 2017-02-16 **/tcb/right*=**⟨*length*⟩ (style, no default)

Sets /tcb/right such that ⟨*length*⟩ is the distance between the right bounding box and the text parts.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\flushright This is some text.
\begin{tcolorbox}[grow to right by=5mm,right*=0mm,
  halign=right,enhanced,show bounding box]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is some text.

This is a **tcolorbox**.

/tcb/righttitle=⟨*length*⟩ (no default, initially 4mm)

Sets the right space between title text and frame (additional to boxsep).

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[width=5cm,righttitle=2cm,title=My very long title text]
This is a \textbf{tcolorbox} with standard upper box dimensions.
\end{tcolorbox}
```

**My very long ti-
tle text**

This is a **tcolorbox** with standard upper box dimensions.

/tcb/rightupper=⟨*length*⟩ (no default, initially 4mm)

Sets the right space between upper text and frame (additional to boxsep).

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[width=5cm,rightupper=2cm,title=My very long title text]
This is a \textbf{tcolorbox} with compressed upper box dimensions.
\end{tcolorbox}
```

My very long title text

This is a **tcol-
orbox** with
compressed
upper box
dimensions.

/tcb/rightlower=⟨*length*⟩ (no default, initially 4mm)

Sets the right space between lower text and frame (additional to boxsep).

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[width=5cm,rightlower=2cm]
This is a \textbf{tcolorbox} with standard upper box dimensions.
\tcblower
This is the lower part with large space at right.
\end{tcolorbox}
```

This is a **tcolorbox** with standard upper box dimensions.

This is the lower part with large space at right.

/tcb/top=⟨*length*⟩ (no default, initially 2mm)

Sets the top space between text and frame (additional to boxsep).

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[top=0mm]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

This is a **tcolorbox**.

This is the lower part.

/tcb/toptitle=⟨*length*⟩ (no default, initially 0mm)

Sets the top space between title and frame (additional to boxsep).

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[toptitle=3mm,title=My title]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

/tcb/bottom=⟨*length*⟩ (no default, initially 2mm)

Sets the bottom space between text and frame (additional to boxsep).

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[bottom=0mm]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

This is a **tcolorbox**.

This is the lower part.

/tcb/bottomtitle=⟨*length*⟩ (no default, initially 0mm)

Sets the bottom space between title and frame (additional to boxsep).

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[bottomtitle=3mm,title=My title]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

/tcb/middle=⟨*length*⟩ (no default, initially 2mm)

Sets the space between upper and lower text to the separation line (additional to boxsep).

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[middle=0mm,boxsep=0mm]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

This is a **tcolorbox**.
This is the lower part.

4.7.5 Size Shortcuts

`/tcb/size`=⟨*name*⟩ (no default, initially `normal`)

Sets all geometry keys with exception of `/tcb/width` → P. 34 to predefined length values. For ⟨*name*⟩, the following values are feasible:

- `normal`: normal sized boxes e.g. of width `\linewidth`.
- `title`: title line sized boxes.
- `small`: small boxes e.g. for keyword highlighting.
- `fbox`: identical to the standard `\fbox`.
- `tight`: no padding space at all.
- `minimal`: no padding space, no box rules.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\foreach \s in {normal,title,small,fbox,tight,minimal} {
  \tcbox[size=\s,on line]{\s} }

\foreach \s in {normal,title,small,fbox,tight,minimal} {
  \tcbox[size=\s,on line,title=Test]{\s} }

\foreach \s in {normal,title,small,fbox,tight,minimal} {
  \begin{tcolorbox}[size=\s,on line,title=Test,width=2.2cm]
    \s \tcblower lower\end{tcolorbox} }
```

normal title small fbox tight minimal

Test normal Test title Test small Test fbox Test tight Test minimal

Test normal lower Test title lower Test small lower Test fbox lower Test tight lower Test minimal lower

Predefined values

	normal	title	small	fbox	tight	minimal
boxrule	0.5mm	0.4mm	0.3mm	0.4pt	0.4pt	0.0pt
boxsep	1.0mm	1.0mm	1.0mm	3.0pt	0.0pt	0.0pt
left	4.0mm	2.0mm	1.0mm	0.0pt	0.0pt	0.0pt
right	4.0mm	2.0mm	1.0mm	0.0pt	0.0pt	0.0pt
top	2.0mm	0.25mm	0.0mm	0.0pt	0.0pt	0.0pt
bottom	2.0mm	0.25mm	0.0mm	0.0pt	0.0pt	0.0pt
toptitle	0.0mm	0.0mm	0.0mm	0.0pt	0.0pt	0.0pt
bottomtitle	0.0mm	0.0mm	0.0mm	0.0pt	0.0pt	0.0pt
middle	2.0mm	0.75mm	0.5mm	1.0pt	0.2pt	0.0pt
arc	1.0mm	0.75mm	0.5mm	1.0pt	0.0pt	0.0pt
outer arc	auto	auto	auto	auto	0.0pt	0.0pt

`/tcb/oversize=`⟨*length*⟩ (style, default `0pt`)

Sets the text width of the upper part to the current line width plus an optional ⟨*length*⟩. This is achieved by changing the keys `/tcb/width` → P. 34 `/tcb/enlarge left by` → P. 83, and `/tcb/enlarge right by` → P. 83 appropriately. The resulting box is overlapping into the left and right margin of the page. Note that this style option has to be given *after* all other geometry keys! Also see `/tcb/grow sidewards by` → P. 85 and `/tcb/spread sidewards` → P. 88.

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\textit{Normal text for comparison:}\\
\lipsum[2]

\begin{tcolorbox}[oversize,title=Oversized box]
\lipsum[2]
\end{tcolorbox}

\begin{tcolorbox}[title=Normal box]
\lipsum[2]
\end{tcolorbox}
```

Normal text for comparison:

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Oversized box

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Normal box

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

4.7.6 Toggle Left and Right

U 2017-02-16 `/tcb/toggle left and right`=⟨*toggle preset*⟩ (default `evenpage`, initially `none`)

According to the ⟨*toggle preset*⟩, the left and the right settings of the `tcolorbox` are switched or not. Feasible values are:

- `none`: no switching.
- `forced`: the values of the left and right rules, spaces, and corners are switched.
- `evenpage`: if the page is an even page, the values of the left and right rules, spaces, and corners are switched. This value also sets `/tcb/check odd page` → P. 101 to `true`.

! Horizontal bounding box enlargements are not toggled by this option. They can be toggled independently by `/tcb/toggle enlargement` → P. 86. For example, `/tcb/oversize` → P. 45 changes the bounding box.

```
% \usepackage{lipsum}
% \usetikzlibrary{patterns}
% \tcbuselibrary{skins,breakable}
\begin{tcolorbox}[enhanced,breakable,
  toggle left and right,sharp corners,
  boxrule=0mm,top=0mm,bottom=0mm,left=1mm,right=1mm,
  rightrule=1cm,colupper=blue!25!black,
  interior style={fill overzoom image=lichtspiel.jpg,fill image opacity=0.25},
  frame style={pattern=crosshatch dots light steel blue},
  overlay={%
    \begin{tcbclipframe}
    \tcbifoddpage{\coordinate (X) at ([xshift=-5mm]frame.east);}
                 {\coordinate (X) at ([xshift=5mm]frame.west);}
    \fill[shading=ball,ball color=blue!50!white,opacity=0.5] (X) circle (4mm);
    \end{tcbclipframe}}]
\lipsum[1-6]
\end{tcolorbox}
```

This example switches a `1cm` thick rule from the left to the right side depending on the page number. Thereby, the rule is always on the outer side of the double-sided paper. Additionally, a ball is drawn on the outer side with help of an overlay.

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellen-

tesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

Fusce mauris. Vestibulum luctus nibh at lectus. Sed bibendum, nulla a faucibus semper, leo velit ultricies tellus, ac venenatis arcu wisi vel nisl. Vestibulum diam. Aliquam pellentesque, augue quis sagittis posuere, turpis lacus congue quam, in hendrerit risus eros eget felis. Maecenas eget erat in sapien mattis porttitor. Vestibulum porttitor. Nulla facilisi. Sed a turpis eu lacus commodo facilisis. Morbi fringilla, wisi in dignissim interdum, justo lectus sagittis dui, et vehicula libero dui cursus dui. Mauris tempor ligula sed lacus. Duis cursus enim ut augue. Cras ac magna. Cras nulla. Nulla egestas. Curabitur a leo. Quisque egestas wisi eget nunc. Nam feugiat lacus vel est. Curabitur consectetuer.

Suspendisse vel felis. Ut lorem lorem, interdum eu, tincidunt sit amet, laoreet vitae, arcu. Aenean faucibus pede eu ante. Praesent enim elit, rutrum at, molestie non, nonummy vel, nisl. Ut lectus eros, malesuada sit amet, fermentum eu, sodales cursus, magna. Donec eu purus. Quisque vehicula, urna sed ultricies auctor, pede lorem egestas dui, et convallis elit erat sed nulla. Donec luctus. Curabitur et nunc. Aliquam dolor odio, commodo pretium, ultricies non, pharetra in, velit. Integer arcu est, nonummy in, fermentum faucibus, egestas vel, odio.

4.8 Corners

The four corners of any `tcolorbox` can be set individually as `/tcb/sharp corners` or as `/tcb/rounded corners` → P. 49. These settings are also reflected in the behavior of `/tcb/borderline` → P. 177 and `/tcb/shadow` → P. 188 as one would expect.

By default, all four corners are *rounded*. So, only the `/tcb/sharp corners` option will be necessary for most use cases. The `/tcb/rounded corners` → P. 49 option can be used to revert a `/tcb/sharp corners` setting.

`/tcb/sharp corners`=⟨*position*⟩ (default `all`, initially unset)

The ⟨*position*⟩ denotes one or more of the four box corners to be set as *sharp* corners. The not assigned corners will retain their mode. Feasible values for ⟨*position*⟩ are:

- `northwest`
- `northeast`
- `southwest`
- `southeast`
- `north`
- `south`
- `east`
- `west`
- `downhill`
- `uphill`
- `all`

```
\begin{tcolorbox}[colback=red!5!white,
  colframe=red!75!black,
  sharp corners=northwest ]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

```
\begin{tcolorbox}[colback=red!5!white,
  colframe=red!75!black,
  sharp corners ]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

`/tcb/rounded corners`=⟨*position*⟩ (default `all`, initially `all`)

The `/tcb/rounded corners` can be used to revert a `/tcb/sharp corners` → P. 48 setting. The ⟨*position*⟩ denotes one or more of the four box corners to be set as *rounded* corners. The not assigned corners will retain their mode. Feasible values for ⟨*position*⟩ are[2]:

- `northwest`
- `northeast`
- `southwest`
- `southeast`
- `north`
- `south`
- `east`
- `west`
- `downhill`
- `uphill`
- `all`

```
\begin{tcolorbox}[colback=red!5!white,
  colframe=red!75!black,sharp corners,
  rounded corners=northwest ]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

`/tcb/sharpish corners` (style, no value)

Shortcut for setting `/tcb/arc` → P. 36 and `/tcb/outer arc` → P. 38 to `0pt`. With this setting, rounded corners will appear as quasi-sharp, but e. g. the shadow will be somewhat rounder than the shadow of really sharp corners.




```
\begin{tcolorbox}[colback=red!5!white,
  colframe=red!75!black,
  sharpish corners ]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

[2] The graphical examples assume that the boxes where set to have sharp corners before.

The following examples will show the differences between /tcb/rounded corners → P. 49, /tcb/sharpish corners → P. 49, and /tcb/sharp corners → P. 48. The later two give the same core box, but /tcb/borderline → P. 177 and /tcb/shadow → P. 188 settings are slightly different. The following examples use /tcb/drop fuzzy shadow → P. 182.

My title

This is a **tcolorbox**.

rounded corners



My title

This is a **tcolorbox**.

sharpish corners



My title

This is a **tcolorbox**.

sharp corners



4.9 Transparency

Transparency effects are likely to be used in conjunction with *jigsaw* skin variants, see Section 10.11 on page 201.

/tcb/opacityframe=⟨*fraction*⟩ (no default, initially `1.0`)

Sets the frame opacity of the box to the given ⟨*fraction*⟩.

```
\begin{tcolorbox}[opacityframe=0.25,
  colframe=red]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

/tcb/opacityback=⟨*fraction*⟩ (no default, initially `1.0`)

Sets the background opacity of the box to the given ⟨*fraction*⟩.

```
\begin{tcolorbox}[standard jigsaw,colframe=red,
  opacityframe=0.5, opacityback=0.5]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

/tcb/opacitybacktitle=⟨*fraction*⟩ (no default, initially `1.0`)

Sets the title background opacity of the box to the given ⟨*fraction*⟩.

```
\begin{tcolorbox}[standard jigsaw,colframe=red,
  opacityframe=0.5, opacitybacktitle=0.5,
  title filled, title=This is a title]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a title

This is a **tcolorbox**.

/tcb/opacityfill=⟨*fraction*⟩ (style, no default, initially `1.0`)

Sets the fill opacity for frame, interior and optionally the title background to the given ⟨*fraction*⟩.

```
\begin{tcolorbox}[standard jigsaw,colframe=red,
  opacityfill=0.7, title=This is a title]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a title

This is a **tcolorbox**.

/tcb/opacityupper=⟨*fraction*⟩ (no default, initially 1.0)

Sets the text opacity of the upper box part to the given ⟨*fraction*⟩.

```
\begin{tcolorbox}[enhanced,opacityupper=0.5,
  interior style={pattern=checkerboard light gray}]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

/tcb/opacitylower=⟨*fraction*⟩ (no default, initially 1.0)

Sets the text opacity of the lower box part to the given ⟨*fraction*⟩.

```
\begin{tcolorbox}[enhanced,opacitylower=0.5,
  interior style={pattern=checkerboard light gray}]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

This is a **tcolorbox**.

This is the lower part.

/tcb/opacitytext=⟨*fraction*⟩ (no default, initially 1.0)

Sets the text opacity of the upper and the lower box part to the given ⟨*fraction*⟩.

```
\begin{tcolorbox}[enhanced,opacitytext=0.5,
  interior style={pattern=checkerboard light gray}]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

This is a **tcolorbox**.

This is the lower part.

/tcb/opacitytitle=⟨*fraction*⟩ (no default, initially 1.0)

Sets the text opacity of the box title to the given ⟨*fraction*⟩.

```
\begin{tcolorbox}[enhanced,opacitytitle=0.7,
  coltitle=black,
  fonttitle=\bfseries,title=This is a title,
  title style={pattern=checkerboard light gray}]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a title

This is a **tcolorbox**.

```
\begin{tcolorbox}[enhanced jigsaw,fonttitle=\bfseries,title=This is a title,
  opacityframe=0.5,opacityback=0.25,opacitybacktitle=0.25,opacitytext=0.8,
  colback=red!5!white,colframe=red!75!black,colbacktitle=yellow!20!red]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a title

This is a **tcolorbox**.

4.10 Height Control

In a typical usage scenario, the height of a `tcolorbox` is computed automatically to fit the content. Nevertheless, the height can be set to a fixed value or to fit commonly for several boxes, e. g. if boxes are set side by side.

> ! The height control keys are only applicable to unbreakable boxes. If a box is set to be `/tcb/breakable` → P. 365, the height is always computed according to the *natural height*.

`/tcb/natural height` (no value, initially set)

Sets the total height of the colored box to its natural height depending on the box content.

`/tcb/height`=⟨*length*⟩ (no default)

Sets the total height of the colored box to ⟨*length*⟩ independent of the box content. ⟨*length*⟩ is the minimum height of the box, if `/tcb/height plus` is larger than zero.

```
\tcbset{width=(\linewidth-2mm)/3,before=,after=\hfill,
colframe=blue!75!black,colback=white}

\begin{tcolorbox}[height=1cm,valign=center]
  This box has a height of 1cm.
\end{tcolorbox}
\begin{tcolorbox}[height=2cm,valign=center]
  This box has a height of 2cm.
\end{tcolorbox}
\begin{tcolorbox}[height=3cm,split=0.5,valign=center,valign lower=center]
  This box has a height of 3cm.
  \tcblower
  Lower part.
\end{tcolorbox}
```

This box has a height of 1cm.

This box has a height of 2cm.

This box has a height of 3cm.

Lower part.

`/tcb/height plus`=⟨*length*⟩ (no default, initially `0pt`)

The box may extend a given fixed `/tcb/height` up to the given ⟨*length*⟩.

```
\tcbset{colback=red!5!white,colframe=red!75!black,left=1mm,top=1mm,bottom=1mm,
  right=1mm,boxsep=0mm,width=3cm,nobeforeafter}

\begin{tcolorbox}[height=1cm]
This is a tcolorbox.
\end{tcolorbox}
\begin{tcolorbox}[height=1cm,height plus=1cm]
This is a tcolorbox.
\end{tcolorbox}
\begin{tcolorbox}[height=1cm,height plus=1cm]
This is a tcolorbox. This is a tcolorbox. This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

This is a tcolorbox.

This is a tcolorbox. This is a tcolorbox. This is a tcolorbox.

/tcb/height from=⟨*min*⟩ to ⟨*max*⟩ (style, no default)

Sets the box height to a dimension between ⟨*min*⟩ and ⟨*max*⟩.

```
% \usepackage{lipsum}
\newtcolorbox{mybox}{colback=red!5!white,colframe=red!75!black,left=1mm,top=1mm,
  bottom=1mm,right=1mm,boxsep=0mm,width=4.5cm,nobeforeafter,
  height from=2cm to 8cm}

\begin{mybox}
This is a tcolorbox.
\end{mybox}
\begin{mybox}
This is a tcolorbox. This is a tcolorbox. This is a tcolorbox.
\end{mybox}
\begin{mybox}
\lipsum[2]
\end{mybox}
```

This is a tcolorbox.

This is a tcolorbox. This is a tcolorbox. This is a tcolorbox.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

N 2014-10-31 **/tcb/text height=⟨*length*⟩** (style, no default)

Sets the text height to ⟨*length*⟩. This is the length from the top of the upper part to the bottom of the optional lower part. See also /tcb/text width → P. 34.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[text height=2cm]
This is a \textbf{tcolorbox} where the text area has a height of 2cm.
\end{tcolorbox}
```

This is a **tcolorbox** where the text area has a height of 2cm.

N 2014-11-07 **/tcb/add to height=⟨*length*⟩** (style, no default)

Adds ⟨*length*⟩ to the current height of the colored box. /tcb/height → P. 53 has to be set before this key is used! If this option is used several times, then the /tcb/height → P. 53 is also increased several times.

```
\tcbset{height=2cm,
  valign=center,width=(\linewidth-2mm)/2,
  before=,after=\hfill,colframe=blue!75!black,colback=white}

\begin{tcolorbox}
  This box has a height of 2cm.
\end{tcolorbox}
\begin{tcolorbox}[add to height=1cm]
  This box has a height of 3cm.
\end{tcolorbox}
```

This box has a height of 2cm.

This box has a height of 3cm.

N 2016-02-16 **/tcb/add to natural height=⟨*length*⟩** (style, no default)

The application of this option generates a box with natural height plus the given ⟨*length*⟩. If this option is used several times, then the last setting of ⟨*length*⟩ wins. The resulting box is not considered a fixed height box and the implementation is quite different to /tcb/add to height.

```
\tcbset{valign=center,width=(\linewidth-2mm)/2,
  before=,after=\hfill,colframe=blue!75!black,colback=white}

\begin{tcolorbox}
  This box has natural height.
\end{tcolorbox}
\begin{tcolorbox}[add to natural height=1cm]
  This box has natural height plus 1 cm.
\end{tcolorbox}
```

This box has natural height.

This box has natural height plus 1 cm.

N 2014-09-22
U 2016-02-17

`/tcb/height fill=true|false|maximum` (default `true`, initially `false`)

If set to `true`, the height of the `tcolorbox` is set to the rest of the available vertical space of the current page. If set to `maximum`, the page is compressed as much as possible. Note that the `tcolorbox` is always set as its own paragraph using this option. Also see `/tcb/text fill` → P. 67.



This height control key is only applicable to unbreakable boxes, but it uses code from the library LIB breakable. The counterpart for breakable boxes is `/tcb/height fixed for` → P. 370.

This option can and should not be used for boxes in boxes, but it can be used for boxes inside a `tcbraster` → P. 279.

```
% \usepackage{lipsum}
% \tcbuselibrary{breakable}
\begin{tcolorbox}[height fill,
  colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
  title=Box which fills the rest of the page]
\lipsum[1]
\end{tcolorbox}
```

Box which fills the rest of the page

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

N 2017-06-28 **/tcb/inherit height=fraction** (default 1, initially unset)

If this option is used for a `tcolorbox` which is embedded inside another (outer) `tcolorbox` *and* if this outer `tcolorbox` has a fixed height, then the given ⟨*fraction*⟩ of the available text height of the outer `tcolorbox` is used as `/tcb/height` → P. 53 for the current `tcolorbox`. Otherwise, `/tcb/natural height` → P. 53 is applied for the current `tcolorbox`.

```
\tcbset{colframe=blue!75!black,colback=white,fonttitle=\bfseries}

\begin{tcolorbox}[title=Outer box with fixed height 4cm,height=4cm]
  \begin{tcolorbox}[title=Inner box,nobeforeafter,inherit height]
    This inner box matches the available space.
  \end{tcolorbox}
\end{tcolorbox}

\begin{tcolorbox}[title=Outer box with natural height]
  \begin{tcolorbox}[title=Inner box,nobeforeafter,inherit height]
    This inner box has its natural height.
  \end{tcolorbox}
\end{tcolorbox}

\begin{tcolorbox}[title=Outer box with fixed height 5cm,height=5cm]
  \begin{tcolorbox}[title=Inner box,nobeforeafter,inherit height]
    \begin{tcolorbox}[colframe=red,beforeafter skip=0pt,inherit height=0.6]
      Deeply nested box using 60 percent of the available space.
    \end{tcolorbox}
    \begin{tcolorbox}[colframe=red,beforeafter skip=0pt,inherit height=0.4]
      Deeply nested box using 40 percent of the available space.
    \end{tcolorbox}
  \end{tcolorbox}
\end{tcolorbox}
```

Outer box with fixed height 4cm

Inner box

This inner box matches the available space.

Outer box with natural height

Inner box

This inner box has its natural height.

Outer box with fixed height 5cm

Inner box

Deeply nested box using 60 percent of the available space.

Deeply nested box using 40 percent of the available space.

N 2015-05-05 **/tcb/square** (style, no value)

Sets /tcb/height → P. 53 to match the width of the colored box.

```
\begin{tcolorbox}[width=3cm,
  colback=red!5!white,
  colframe=red!75!black,
  halign=center,valign=center,
  square]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

/tcb/space=⟨*fraction*⟩ (no default, initially 0)

If the height of a `tcolorbox` is not the natural height, the space difference between the forced and the natural size is distributed between the upper and the lower part of the box. This space could also be negative. ⟨*fraction*⟩ with a value between 0 and 1 is the amount of space which is added to the upper part, the rest is added to the lower part. If there is no lower part, then all of the space is added to the upper part always.

```
\tcbset{width=(\linewidth-2mm)/3,before=,after=\hfill,
colframe=blue!75!black,colback=white,height=3cm}

\foreach \f in {0.2,0.4,0.7}
{\begin{tcolorbox}[space=\f]
    This is the upper part.
    \tcblower
    This is the lower part.
\end{tcolorbox}}
```

This is the upper part.

This is the lower part.

This is the upper part.

This is the lower part.

This is the upper part.

This is the lower part.

/tcb/space to upper (style)

This is an abbreviation for `space=1`, i. e. all extra space is added to the upper part.

/tcb/space to lower (style, initially set)

This is an abbreviation for `space=0`, i. e. all extra space is added to the lower part (if there is any).

`/tcb/space to both` (style)

This is an abbreviation for `space=0.5`, i. e. the extra space equally distributed between the upper and the lower part.

```
\tcbset{width=(\linewidth-2mm)/3,before=,after=\hfill,
colframe=blue!75!black,colback=white,height=3cm}

\foreach \myspace in {space to upper,space to both,space to lower}
{\begin{tcolorbox}[\myspace]
    This is the upper part.
    \tcblower
    This is the lower part.
\end{tcolorbox}}
```

This is the upper part.

This is the lower part.

This is the upper part.

This is the lower part.

This is the upper part.

This is the lower part.

N 2015-02-15 `/tcb/space to=`⟨*macro*⟩ (no default, initially unset)

If the height of a `tcolorbox` is not the natural height, the space difference between the forced and the natural size is saved into the given local ⟨*macro*⟩. This ⟨*macro*⟩ can and should be used inside the box content to add content which is vertically sized to match ⟨*macro*⟩.

- The actual length saved into ⟨*macro*⟩ is adapted dynamically during several compilations – at least two, but maybe more.
- Due to the adaption algorithm, objects can be sized with ⟨*macro*⟩ plus any offset length.
- Never ever use ⟨*macro*⟩ multiplied with a factor. The only exception to this rule is that the space can be split into parts which sum to ⟨*macro*⟩.
- Never use this in combination with `/tcb/fit` → P. 412.

```
\begin{tcolorbox}[colframe=blue!75!black,colback=white,height=3cm,
    space to=\myspace]
  This is my box of height 3cm. The space is filled with a picture:\\[2mm]
  \includegraphics[width=\linewidth,height=\myspace]{goldshade.png}\\[1mm]
  This is some other text.
\end{tcolorbox}
```

This is my box of height 3cm. The space is filled with a picture:

This is some other text.

```
\begin{tcolorbox}[colframe=blue!75!black,colback=white,height=3cm,
    space to=\myspace]
  \includegraphics[width=\linewidth,
    height=0.33\dimexpr\myspace]{blueshade.png}\\[1mm]
  This is my box of height 3cm.\\[2mm]
  \includegraphics[width=\linewidth,
    height=0.67\dimexpr\myspace]{goldshade.png}
\end{tcolorbox}
```



/tcb/split=⟨*fraction*⟩ (no default)

If the height of a **tcolorbox** is not the natural height, the ⟨*fraction*⟩ with a value between 0 and 1 determines the positioning of the segmentation between the upper and the lower part. Here, 0 stands for top and 1 for bottom. Note that the box is split regardless of the actual dimensions of the text parts!

```
\tcbset{width=(\linewidth-2mm)/3,before=,after=\hfill,height=3cm,
colback=white,colframe=blue!75!black,valign=center,valign lower=center}

\foreach \f in {0.1,0.5,0.8}
{\begin{tcolorbox}[split=\f]
This is the upper part.
\tcblower
This is the lower part with a lot of text in several lines.
\end{tcolorbox}}
```



U 2014-11-07 **/tcb/equal height group=**⟨*id*⟩ (no default)

Boxes which are members of an **equal height group** will all get the same height, i. e. the maximum of all their natural heights. The ⟨*id*⟩ serves to distinguish between different height groups. Note that you have to compile twice to see changes and that height groups are global definitions.

```
\tcbset{width=(\linewidth-2mm)/3,before=,after=\hfill,arc=0mm,
colframe=blue!75!black,colback=white,fonttitle=\bfseries}

\begin{tcolorbox}[equal height group=A,adjusted title={One}]
  My smallest box.
\end{tcolorbox}%
\begin{tcolorbox}[equal height group=A,adjusted title={Two}]
  This box is also small.
  \tcblower
  But with a lower part.
\end{tcolorbox}%
\begin{tcolorbox}[equal height group=A,adjusted title={Three}]
  This box contains a lot of text just to fill the space
  with word flowing and flowing and flowing until the box
  is filled with all of it.
\end{tcolorbox}\linebreak
%
\tcbset{width=(\linewidth-1mm)/2,before=,after=\hfill,arc=0mm,
colframe=red!75!black,colback=white}
%
\begin{tcolorbox}[equal height group=B]
  Now, we use another equal height group.
\end{tcolorbox}%
\begin{tcolorbox}[equal height group=B,after=]
  \begin{equation*}
    \int\limits_{0}^{1} x^2 = \frac13.
  \end{equation*}
\end{tcolorbox}
```

One

My smallest box.

Two

This box is also small.

But with a lower part.

Three

This box contains a lot of text just to fill the space with word flowing and flowing and flowing until the box is filled with all of it.

Now, we use another equal height group.

$$\int_0^1 x^2 = \frac{1}{3}.$$

See Section 14 on page 277 for more equal height options.

`/tcb/minimum for equal height group=`⟨*id*⟩`:`⟨*length*⟩ (no default, initially unset)

Plants a ⟨*length*⟩ into the equal height group with the given ⟨*id*⟩. This ensures that the height will not drop below ⟨*length*⟩. Note that you cannot reduce a computed height value by using this key with a small value. The difference to applying `/tcb/height` → P. 53 directly is that the boxes are never too small for their content.

```
\tcbset{colframe=blue!75!black,colback=white,arc=0mm,
  before=,after=\hfill,fonttitle=\bfseries,left=2mm,right=2mm,
  width=3.5cm,
  equal height group=C,
  minimum for equal height group=C:3.5cm}

\begin{tcolorbox}
  My first box. All boxes will get 3.5cm times 3.5cm
  if the content height is not too large.
\end{tcolorbox}%
\begin{tcolorbox}
  My second box.
  \tcblower
  This is the lower part.
\end{tcolorbox}%
\begin{tcblisting}{}
\textbf{Mixed}
with a listing.
\end{tcblisting}
\begin{tcolorbox}[title={Fourth box}]
  My final box.
\end{tcolorbox}%
```

My first box. All boxes will get 3.5cm times 3.5cm if the content height is not too large.

My second box.

This is the lower part.

`\textbf{Mixed}` with a listing.

Mixed with a listing.

Fourth box

My final box.

N 2016-03-24 `/tcb/minimum for current equal height group=`⟨*length*⟩ (no default, initially unset)

Sets `/tcb/minimum for equal height group` for the current equal height group. Apparently, this only works for an already known equal height group, i.e. `/tcb/equal height group` → P. 61 has to be set *before* this option is used. This option is likely to be used in combination with `/tcb/raster equal height` → P. 287

```
% \tcbuselibrary{raster}
\begin{tcbitemize}[raster equal height,colframe=blue!75!black,colback=white,
  raster every box/.style={minimum for current equal height group=2cm}]
  \tcbitem A
  \tcbitem B
\end{tcbitemize}
```

A

B

N 2015-11-27
U 2016-02-22

/tcb/use height from group=⟨*id*⟩ (style, default current group)

Sets the current box to a fixed /tcb/height → P. 53 which is copied from an equal height group with the given ⟨*id*⟩. If this height is not available during the current compilation, no fixed height setting is used. If ⟨*id*⟩ is omitted, the current equal height group is used which has to be set before by /tcb/equal height group → P. 61.

Note that the natural height of the current box is not considered for computation of the group height. The main application for /tcb/use height from group is that the height can be adapted further by /tcb/add to height → P. 55.

```
\begin{tcolorbox}[use height from group=C,add to height=-2cm,
  colframe=blue!75!black,colback=white]
Height from group 'C' of the previous example, but reduced by 2cm.
\end{tcolorbox}%
```

Height from group 'C' of the previous example, but reduced by 2cm.

```
% \tcbuselibrary{raster}
Every line is inside an equal height group:
\begin{tcbraster}[raster equal height=rows,
    title=Box \thetcbrasternum,
    enhanced,size=small,colframe=red!50!black,colback=red!10!white]
  \begin{tcolorbox}First line\\second line\\
    The height of this box rules.\end{tcolorbox}
  \begin{tcolorbox}[use height from group]Test\end{tcolorbox}
  \begin{tcolorbox}[use height from group]
    First line\\second line\end{tcolorbox}
  \begin{tcolorbox}The height of this box rules.\end{tcolorbox}
\end{tcbraster}
```

Every line is inside an equal height group:

Box 1
First line
second line
The height of this box rules.

Box 2
Test

Box 3
First line
second line

Box 4
The height of this box rules.

N 2015-11-27

\tcbheightfromgroup{⟨*macro*⟩}{⟨*id*⟩}

Saves the height from an equal height group with the given ⟨*id*⟩ to a ⟨*macro*⟩. If this height is not available during the current compilation, ⟨*macro*⟩ is set to `0pt`.

4.11 Box Content Additions

The following options introduce some arbitrary ⟨*code*⟩ to the content of a `tcolorbox`. These additions can be given at the beginning or at the ending of the title, the upper part, or the lower part.

`/tcb/before title=`⟨*code*⟩ (no default, initially unset)

The given ⟨*code*⟩ is placed *after* the color and font settings and *before* the content of the title.

```
\tcbset{before title={\textcolor{yellow}{\large Important:}~},
  colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[title=My title]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

Important: My title

This is a **tcolorbox**.

`/tcb/after title=`⟨*code*⟩ (no default, initially unset)

The given ⟨*code*⟩ is placed *after* the content of the title.

```
\tcbset{after title={\hfill\colorbox{Navy}{approved}},
  colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[title=My title]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title approved

This is a **tcolorbox**.

`/tcb/before upper=`⟨*code*⟩ (no default, initially unset)

The given ⟨*code*⟩ is placed *after* the color and font settings and *before* the content of the upper part.

```
\tcbset{before upper={\textit{The story:}\par},
  colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[title=My title]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title

The story:
This is a **tcolorbox**.

U 2016-10-21 `/tcb/after upper=`⟨*code*⟩ (no default, initially unset)

The given ⟨*code*⟩ is placed *after* the content of the upper part.

```
\tcbset{after upper={\par\hfill\textit{Read more next week}},
  colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[title=My title]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

Read more next week

```
\begin{tcolorbox}[before upper=\flqq,after upper=\frqq,
  colback=red!5!white,colframe=red!75!black]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

«This is a **tcolorbox**.»

! An `\unskip` is placed in front of the given ⟨*code*⟩. From version 3.80 to 3.94, this `\unskip` was omitted to avoid certain problems which (hopefully) should not occur with the new improved code.

N 2016-10-21
U 2016-10-21 `/tcb/after upper*=`⟨*code*⟩ (no default, initially unset)

Alias for `/tcb/after upper`. From version 3.80 to 3.94, it prepended an `\unskip` to the given ⟨*code*⟩. Now, this key is considered to be deprecated.

`/tcb/before lower=`⟨*code*⟩ (no default, initially unset)

The given ⟨*code*⟩ is placed *after* the color and font settings and *before* the content of the lower part.

```
\tcbset{before lower=\textit{Behold:~},colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

This is a **tcolorbox**.

Behold: This is the lower part.

U 2016-10-21 `/tcb/after lower=`⟨*code*⟩ (no default, initially unset)

The given ⟨*code*⟩ is placed *after* the content of the lower part.

```
\begin{tcolorbox}[before lower=$,after lower=$,
  colback=red!5!white,colframe=red!75!black]
This is a \textbf{tcolorbox}.
\tcblower
\sin^2(x)+\cos^2(x)=1.
\end{tcolorbox}
```

This is a **tcolorbox**.

$\sin^2(x) + \cos^2(x) = 1.$

```
\begin{tcolorbox}[after lower=\ \textit{This is the end.},
  colback=red!5!white,colframe=red!75!black]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

This is a **tcolorbox**.

This is the lower part. *This is the end.*

! An `\unskip` is placed in front of the given ⟨*code*⟩. From version 3.80 to 3.94, this `\unskip` was omitted to avoid certain problems which (hopefully) should not occur with the new improved code.

N 2016-10-21
U 2016-10-21 `/tcb/after lower*=`⟨*code*⟩ (no default, initially unset)

Alias for `/tcb/after lower`. From version 3.80 to 3.94, it prepended an `\unskip` to the given ⟨*code*⟩. Now, this key is considered to be deprecated.

If /tcb/text fill is used, one cannot have a lower part and the box is unbreakable.

N 2015-07-15 **/tcb/text fill** (style, no value)

This style sets /tcb/before upper →P. 65 and /tcb/after upper →P. 65 to embed the upper part with a minipage. If a fixed height was applied e.g. by /tcb/height →P. 53 or /tcb/height fill →P. 56, this minipage gets a matching height. This allows to use vertical glue macros like \vfill to act like expected. If the box has no fixed height, setting /tcb/text fill has no other effect as making the box unbreakable.

```
\begin{tcolorbox}[colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
  height=8cm,text fill,
  title=My filled box]
This is a \textbf{tcolorbox}.
\par\vfill
\begin{center}
  My middle text.
\end{center}
\par\vfill
This is the end of my box.
\end{tcolorbox}
```

My filled box

This is a **tcolorbox**.

My middle text.

This is the end of my box.

If /tcb/tabularx or /tcb/tabularx* are used, one cannot have a lower part.

/tcb/tabularx=⟨*preamble*⟩ (style)

This style sets /tcb/before upper→ P. 65 and /tcb/after upper→ P. 65 and several geometry keys to support a tabularx with the given ⟨*preamble*⟩. The packages tabularx [4], array, and colortbl have to be loaded separately.

```
% \usepackage{array,tabularx}
% \usepackage{colortbl} - or - \usepackage[table]{xcolor}
\newcolumntype{Y}{>{\raggedleft\arraybackslash}X}% see tabularx
\tcbset{enhanced,fonttitle=\bfseries\large,fontupper=\normalsize\sffamily,
  colback=yellow!10!white,colframe=red!50!black,colbacktitle=Salmon!30!white,
  coltitle=black,center title}

\begin{tcolorbox}[tabularx={X||Y|Y|Y|Y||Y},title=My table]
Group & One     & Two     & Three    & Four     & Sum\\\hline\hline
Red   & 1000.00 & 2000.00 &  3000.00 &  4000.00 & 10000.00\\\hline
Green & 2000.00 & 3000.00 &  4000.00 &  5000.00 & 14000.00\\\hline
Blue  & 3000.00 & 4000.00 &  5000.00 &  6000.00 & 18000.00\\\hline\hline
Sum   & 6000.00 & 9000.00 & 12000.00 & 15000.00 & 42000.00
\end{tcolorbox}
```

My table

Group	One	Two	Three	Four	Sum
Red	1000.00	2000.00	3000.00	4000.00	10000.00
Green	2000.00	3000.00	4000.00	5000.00	14000.00
Blue	3000.00	4000.00	5000.00	6000.00	18000.00
Sum	6000.00	9000.00	12000.00	15000.00	42000.00

/tcb/tabularx*={⟨*code*⟩}{⟨*preamble*⟩} (style)

This is a variant of /tcb/tabularx which adds some ⟨*code*⟩ before the table starts.

```
% \usepackage{array,tabularx}
% \usepackage{colortbl} - or - \usepackage[table]{xcolor}
\tcbset{enhanced,fonttitle=\bfseries\large,fontupper=\normalsize\sffamily,
  colback=yellow!10!white,colframe=red!50!black,colbacktitle=Salmon!30!white,
  coltitle=black,center title}

\begin{tcolorbox}[tabularx*={\arrayrulewidth0.5mm}{X|X|X},title=My table]
One     & Two     & Three \\\hline\hline
1000.00 & 2000.00 &  3000.00\\\hline
2000.00 & 3000.00 &  4000.00
\end{tcolorbox}
```

My table

One	Two	Three
1000.00	2000.00	3000.00
2000.00	3000.00	4000.00

/tcb/tikz upper=⟨*options*⟩ (style)

This style adds a centered `tikzpicture` environment to the start and end of the upper part. The ⟨*options*⟩ may be given as Ti*k*Z picture options.

```
% \usepackage{tikz}

\begin{tcolorbox}[tikz upper,fonttitle=\bfseries,colback=white,colframe=black,
                  title=\tikzname\ drawing]
  \path[fill=yellow,draw=yellow!75!red] (0,0) circle (1cm);
  \fill[red] (45:5mm) circle (1mm);
  \fill[red] (135:5mm) circle (1mm);
  \draw[line width=1mm,red] (215:5mm) arc (215:325:5mm);
\end{tcolorbox}
```

Ti*k*Z drawing

/tcb/tikz lower=⟨*options*⟩ (style)

This style adds a centered `tikzpicture` environment to the start and end of the lower part. The ⟨*options*⟩ may be given as Ti*k*Z picture options.

```
% \usepackage{tikz}
% \tcbuselibrary{skins,listings}
\tcbset{tikz lower,listing side text,fonttitle=\bfseries,
  bicolor,colback=LightBlue!50!white,colbacklower=white,colframe=black,
  righthand width=3cm}

\begin{tcblisting}{title=\tikzname\  drawing}
\path[fill=yellow,draw=yellow!75!red]
    (0,0) circle (1cm);
\fill[red] (45:5mm) circle (1mm);
\fill[red] (135:5mm) circle (1mm);
\draw[line width=1mm,red]
    (215:5mm) arc (215:325:5mm);
\end{tcblisting}
```

Ti*k*Z drawing

```
\path[fill=yellow,draw=yellow!75!red]
    (0,0) circle (1cm);
\fill[red] (45:5mm) circle (1mm);
\fill[red] (135:5mm) circle (1mm);
\draw[line width=1mm,red]
    (215:5mm) arc (215:325:5mm);
```

/tcb/tikznode upper=⟨*options*⟩ (style)

This style places the upper part content into a centered Ti*k*Z node. The ⟨*options*⟩ may be given as Ti*k*Z node options. This style is especially useful for boxes with multiline texts which are fitted to the text width.

```
% \usepackage{tikz}
\newtcbox{\headline}[1][]{enhanced,center,
  ignore nobreak,fontupper=\Large\bfseries,
  colframe=red!50!black,colback=red!10!white,
  drop fuzzy shadow=yellow,tikznode upper,#1}

\headline{Important\\Headline}
```

/tcb/tikznode lower=⟨*options*⟩ (style)

This style places the lower part content into a centered Ti*k*Z node. The ⟨*options*⟩ may be given as Ti*k*Z node options.

```
% \usepackage{tikz}
\begin{tcolorbox}[bicolor,colback=LightBlue!50!white,colbacklower=white,
  colframe=black,tikznode lower={inner sep=2pt,draw=red,fill=yellow}]
Upper part.
\tcblower
Lower part.
\end{tcolorbox}
```



/tcb/tikznode=⟨*options*⟩ (style)

Shortcut for setting /tcb/tikznode upper and /tcb/tikznode lower the same time.

/tcb/varwidth upper=⟨*length*⟩ (style, default /tcb/width → P. 34)

This style places the upper part content into a `varwidth` environment. This style needs the `varwidth` package [1] to be loaded manually. The resulting box has a maximal width of ⟨*length*⟩. This option is only senseful for a \tcbox → P. 14.

```
% \usepackage{varwidth}
\newtcbox{\varbox}{colframe=red!50!black,
  colback=red!10!white,varwidth upper}

\varbox{Short text.}
\varbox{This box contains is a longer text
  which is broken.}
```



4.12 Overlays

With an overlay, arbitrary ⟨*graphical code*⟩ can be added to a `tcolorbox`. This code is executed *after* the frame and interior are drawn and *before* the text content is drawn. Therefore, you can decorate the `tcolorbox` with your own extensions. Common special cases are *watermarks* which are implemented using overlays. See Subsection 10.3 from page 165 if you want to add *watermarks*.



If you use the core package only, the ⟨*graphical code*⟩ has to be `pgf` code and there is not much assistance for positioning. Therefore, the usage of the `/tcb/enhanced` →P. 206 mode from the library skins is recommended which allows `tikz` code and gives access to `/tcb/geometry nodes` →P. 137 for positioning.

`/tcb/overlay`=⟨*graphical code*⟩ (no default, initially unset)

Adds ⟨*graphical code*⟩ to the box drawing process. This ⟨*graphical code*⟩ is drawn *after* the frame and interior and *before* the text content.

```
% \tcbuselibrary{skins} % preamble
\tcbset{frogbox/.style={enhanced,colback=green!10,colframe=green!65!black,
  enlarge top by=5.5mm,
  overlay={\foreach \x in {2cm,3.5cm} {
    \begin{scope}[shift={([xshift=\x]frame.north west)}]
      \path[draw=green!65!black,fill=green!10,line width=1mm] (0,0) arc (0:180:5mm);
      \path[fill=black] (-0.2,0) arc (0:180:1mm);
    \end{scope}}}}}

\begin{tcolorbox}[frogbox,title=My title]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

```
% \usetikzlibrary{patterns} % preamble
% \tcbuselibrary{skins}     % preamble
\tcbset{ribbonbox/.style={enhanced,colback=red!5!white,colframe=red!75!black,
  fonttitle=\bfseries,
  overlay={\path[fill=blue!75!white,draw=blue,double=white!85!blue,
    preaction={opacity=0.6,fill=blue!75!white},
    line width=0.1mm,double distance=0.2mm,
    pattern=fivepointed stars,pattern color=white!75!blue]
    ([xshift=-0.2mm,yshift=-1.02cm]frame.north east)
    -- ++(-1,1) -- ++(-0.5,0) -- ++(1.5,-1.5) -- cycle;}}}

\begin{tcolorbox}[ribbonbox,title=My title]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```



/tcb/no overlay (style, no default, initially set)

Removes the overlay if set before.

/tcb/overlay broken=⟨*graphical code*⟩ (no default, initially unset)

If the box is set to be /tcb/breakable→ P. 365 and *is* broken actually, then the ⟨*graphical code*⟩ is added to the box drawing process. /tcb/overlay→ P. 71 overwrites this key.

/tcb/overlay unbroken=⟨*graphical code*⟩ (no default, initially unset)

If the box is set to be /tcb/breakable→ P. 365 but *is not* broken actually or if the box is set to be /tcb/unbreakable→ P. 366, then the ⟨*graphical code*⟩ is added to the box drawing process. /tcb/overlay→ P. 71 overwrites this key.

/tcb/overlay first=⟨*graphical code*⟩ (no default, initially unset)

If the box is set to be /tcb/breakable→ P. 365 and *is* broken actually, then the ⟨*graphical code*⟩ is added to the box drawing process for the *first* part of the break sequence. /tcb/overlay→ P. 71 overwrites this key.

/tcb/overlay middle=⟨*graphical code*⟩ (no default, initially unset)

If the box is set to be /tcb/breakable→ P. 365 and *is* broken actually, then the ⟨*graphical code*⟩ is added to the box drawing process for the *middle* parts (if any) of the break sequence. /tcb/overlay→ P. 71 overwrites this key.

/tcb/overlay last=⟨*graphical code*⟩ (no default, initially unset)

If the box is set to be /tcb/breakable→ P. 365 and *is* broken actually, then the ⟨*graphical code*⟩ is added to the box drawing process for the *last* part of the break sequence. /tcb/overlay→ P. 71 overwrites this key.

/tcb/overlay unbroken and first=⟨*graphical code*⟩ (no default, initially unset)

This is an optimized abbreviation for setting /tcb/overlay unbroken and /tcb/overlay first together. /tcb/overlay→ P. 71 overwrites this key.

/tcb/overlay middle and last=⟨*graphical code*⟩ (no default, initially unset)

This is an optimized abbreviation for setting /tcb/overlay middle and /tcb/overlay last together. /tcb/overlay→ P. 71 overwrites this key.

/tcb/overlay unbroken and last=⟨*graphical code*⟩ (no default, initially unset)

This is an optimized abbreviation for setting /tcb/overlay unbroken and /tcb/overlay last together. /tcb/overlay→ P. 71 overwrites this key.

N 2014-09-19 **/tcb/overlay first and middle=**⟨*graphical code*⟩ (no default, initially unset)

This is an optimized abbreviation for setting /tcb/overlay first and /tcb/overlay middle together. /tcb/overlay→ P. 71 overwrites this key.

This example demonstrates the application of break sequence specific overlay options. Here, we define an environment `myexample` based on `tcolorbox` where the visible drawing is done totally by overlay keys.
Here, the first application of `myexample` produces an unbroken `tcolorbox`. The frame is drawn by the code given with /tcb/overlay unbroken.
The second application of `myexample` is broken into several parts which are drawn by the codes given with /tcb/overlay first, /tcb/overlay middle, and /tcb/overlay last.

```
% Preamble:
%\usepackage{tikz,lipsum}
%\tcbuselibrary{skins,breakable}
%\newcounter{example}
\colorlet{colexam}{red!75!black}
\newtcolorbox[use counter=example]{myexample}{%
```

```
  empty,title={Example \thetcbcounter},attach boxed title to top left,
  boxed title style={empty,size=minimal,toprule=2pt,top=4pt,
    overlay={\draw[colexam,line width=2pt]
      ([yshift=-1pt]frame.north west)--([yshift=-1pt]frame.north east);}},
  coltitle=colexam,fonttitle=\Large\bfseries,
  before=\par\medskip\noindent,parbox=false,boxsep=0pt,left=0pt,right=3mm,top=4pt,
  breakable,pad at break*=0mm,vfill before first,
  overlay unbroken={\draw[colexam,line width=1pt]
    ([yshift=-1pt]title.north east)--([xshift=-0.5pt,yshift=-1pt]title.north-|frame.east)
    --([xshift=-0.5pt]frame.south east)--(frame.south west); },
  overlay first={\draw[colexam,line width=1pt]
    ([yshift=-1pt]title.north east)--([xshift=-0.5pt,yshift=-1pt]title.north-|frame.east)
    --([xshift=-0.5pt]frame.south east); },
  overlay middle={\draw[colexam,line width=1pt] ([xshift=-0.5pt]frame.north east)
    --([xshift=-0.5pt]frame.south east); },
  overlay last={\draw[colexam,line width=1pt] ([xshift=-0.5pt]frame.north east)
    --([xshift=-0.5pt]frame.south east)--(frame.south west);},%
}

\begin{myexample}
\lipsum[1]
\end{myexample}

\begin{myexample}
\lipsum[2-11]
\end{myexample}

\lipsum[12]% following text
```

Example 1

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Example 2

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent

euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

Fusce mauris. Vestibulum luctus nibh at lectus. Sed bibendum, nulla a faucibus semper, leo velit ultricies tellus, ac venenatis arcu wisi vel nisl. Vestibulum diam. Aliquam pellentesque, augue quis sagittis posuere, turpis lacus congue quam, in hendrerit risus eros eget felis. Maecenas eget erat in sapien mattis porttitor. Vestibulum porttitor. Nulla facilisi. Sed a turpis eu lacus commodo facilisis. Morbi fringilla, wisi in dignissim interdum, justo lectus sagittis dui, et vehicula libero dui cursus dui. Mauris tempor ligula sed lacus. Duis cursus enim ut augue. Cras ac magna. Cras nulla. Nulla egestas. Curabitur a leo. Quisque egestas wisi eget nunc. Nam feugiat lacus vel est. Curabitur consectetuer.

Suspendisse vel felis. Ut lorem lorem, interdum eu, tincidunt sit amet, laoreet vitae, arcu. Aenean faucibus pede eu ante. Praesent enim elit, rutrum at, molestie non, nonummy vel, nisl. Ut lectus eros, malesuada sit amet, fermentum eu, sodales cursus, magna. Donec eu purus. Quisque vehicula, urna sed ultricies auctor, pede lorem egestas dui, et convallis elit erat sed nulla. Donec luctus. Curabitur et nunc. Aliquam dolor odio, commodo pretium, ultricies non, pharetra in, velit. Integer arcu est, nonummy in, fermentum faucibus, egestas vel, odio.

Sed commodo posuere pede. Mauris ut est. Ut quis purus. Sed ac odio. Sed vehicula hendrerit sem. Duis non odio. Morbi ut dui. Sed accumsan risus eget odio. In hac habitasse platea dictumst. Pellentesque non elit. Fusce sed justo eu urna porta tincidunt. Mauris felis odio, sollicitudin sed, volutpat a, ornare ac, erat. Morbi quis dolor. Donec pellentesque, erat ac sagittis semper, nunc dui lobortis purus, quis congue purus metus ultricies tellus. Proin et quam. Class aptent taciti sociosqu ad litora torquent per conubia nostra, per inceptos hymenaeos. Praesent sapien turpis, fermentum vel, eleifend faucibus, vehicula eu, lacus.

Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Donec odio elit, dictum in, hendrerit sit amet, egestas sed, leo. Praesent feugiat sapien aliquet odio. Integer vitae justo. Aliquam vestibulum fringilla lorem. Sed neque lectus, consectetuer at, consectetuer sed, eleifend ac, lectus. Nulla facilisi. Pellentesque eget lectus. Proin eu metus. Sed porttitor. In hac habitasse platea dictumst. Suspendisse eu lectus. Ut mi mi, lacinia sit amet, placerat et, mollis vitae, dui. Sed ante tellus, tristique ut, iaculis eu, malesuada ac, dui. Mauris nibh leo, facilisis non, adipiscing quis, ultrices a, dui.

Morbi luctus, wisi viverra faucibus pretium, nibh est placerat odio, nec commodo wisi enim eget quam. Quisque libero justo, consectetuer a, feugiat vitae, porttitor eu, libero. Suspendisse sed mauris vitae elit sollicitudin malesuada. Maecenas ultricies eros sit amet ante. Ut venenatis velit. Maecenas sed mi eget dui varius euismod. Phasellus aliquet volutpat odio. Vestibulum ante ipsum primis in faucibus orci luctus et ultrices posuere cubilia Curae; Pellentesque sit amet pede ac sem eleifend consectetuer. Nullam elementum, urna vel imperdiet sodales, elit ipsum pharetra ligula, ac pretium ante justo a nulla. Curabitur tristique arcu eu metus. Vestibulum lectus. Proin mauris. Proin eu nunc eu urna hendrerit faucibus. Aliquam auctor, pede consequat laoreet varius, eros tellus scelerisque quam, pellentesque hendrerit ipsum dolor sed augue. Nulla nec lacus.

Suspendisse vitae elit. Aliquam arcu neque, ornare in, ullamcorper quis, commodo eu, libero. Fusce sagittis erat at erat tristique mollis. Maecenas sapien libero, molestie et, lobortis in,

sodales eget, dui. Morbi ultrices rutrum lorem. Nam elementum ullamcorper leo. Morbi dui. Aliquam sagittis. Nunc placerat. Pellentesque tristique sodales est. Maecenas imperdiet lacinia velit. Cras non urna. Morbi eros pede, suscipit ac, varius vel, egestas non, eros. Praesent malesuada, diam id pretium elementum, eros sem dictum tortor, vel consectetuer odio sem sed wisi.

Sed feugiat. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Ut pellentesque augue sed urna. Vestibulum diam eros, fringilla et, consectetuer eu, nonummy id, sapien. Nullam at lectus. In sagittis ultrices mauris. Curabitur malesuada erat sit amet massa. Fusce blandit. Aliquam erat volutpat. Aliquam euismod. Aenean vel lectus. Nunc imperdiet justo nec dolor.

Etiam euismod. Fusce facilisis lacinia dui. Suspendisse potenti. In mi erat, cursus id, nonummy sed, ullamcorper eget, sapien. Praesent pretium, magna in eleifend egestas, pede pede pretium lorem, quis consectetuer tortor sapien facilisis magna. Mauris quis magna varius nulla scelerisque imperdiet. Aliquam non quam. Aliquam porttitor quam a lacus. Praesent vel arcu ut tortor cursus volutpat. In vitae pede quis diam bibendum placerat. Fusce elementum convallis neque. Sed dolor orci, scelerisque ac, dapibus nec, ultricies ut, mi. Duis nec dui quis leo sagittis commodo.

Floating box from floatplacement

This floating box is placed at the top of a page.

4.13 Floating Objects

/tcb/floatplacement=⟨*values*⟩ (no default, initially htb)

Sets ⟨*values*⟩ as default values for the usage of /tcb/float and /tcb/float*. Feasible are the usual parameters for floating objects.

```
\tcbset{enhanced,colback=red!5!white,colframe=red!75!black,
   watermark color=red!15!white}

\begin{tcolorbox}[floatplacement=t,float,
                  title=Floating box from |floatplacement|,
                  watermark text={I am floating}]
  This floating box is placed at the top of a page.
\end{tcolorbox}
```

/tcb/float=⟨*values*⟩ (default from floatplacement)

Turns the box to a floating object where ⟨*values*⟩ are the usual parameters for such floating objects. If they are not used, the placement uses the default values given by floatplacement.

```
\begin{tcolorbox}[float, title=Floating box from |float|,
    enhanced,watermark text={I'm also floating}]
  This box floats to a feasible place automatically. You do not have to
  use a numbering for this floating object.
\end{tcolorbox}
```

Floating box from float

This box floats to a feasible place automatically. You do not have to use a numbering for this floating object.

/tcb/float*=⟨*values*⟩ (default from floatplacement)

Identical to /tcb/float, but for wide boxes spanning the whole page width of two column documents or in conjunction with the packages multicol or paracol. Note that you have to set width=\textwidth additionally, if the box should span the whole page width in these cases!

```
\begin{tcolorbox}[float*=b, title=Floating box from |float*|,width=\textwidth,
    enhanced,watermark text={I'm also floating}]
  In this single column document, you will see no difference to |float|.
\end{tcolorbox}
```

/tcb/nofloat (style, initially set)

Turns the floating behavior off.

Floating box from float*

In this single column document, you will see no difference to float.

N 2014-09-19 **/tcb/every float=**⟨*code*⟩ (no default, initially empty)

For floating objects, the /tcb/before → P. 78 and /tcb/after → P. 78 settings are ignored. Instead, the given ⟨*code*⟩ is inserted before a floating box. If the box is /tcb/breakable → P. 365, the given ⟨*code*⟩ is inserted before every part of the break sequence. The most common use case is every float=\centering.

```
\tcbox[float=htb,title={Floating box},every float=\centering,
  colback=blue!50!black,colframe=blue!50!white,colbacktitle=blue!10!white,
  coltitle=black,center title]
  {\includegraphics[height=6cm]{lichtspiel.jpg}}
```

Floating box

4.14 Embedding into the Surroundings

Typically, but not necessarily, a `tcolorbox` is put inside a separate paragraph and has some vertical space before and after it. This behavior is controlled by the keys `before` and `after`.

`/tcb/before=`⟨*code*⟩ (no default, initially see `/tcb/autoparskip`)
Sets the ⟨*code*⟩ which is executed before the colored box. It is not used for floating boxes. Also, it is not used, if the box follows a heading immediately and `/tcb/ignore nobreak` → P. 81 is set to `false`.

`/tcb/after=`⟨*code*⟩ (no default, initially see `/tcb/autoparskip`)
Sets the ⟨*code*⟩ which is executed after the colored box. It is not used for floating boxes.

U 2017-02-01 `/tcb/parskip` (style, no value)
Sets the keys `before` and `after` to values which are recommended, if the package `parskip` *is* used and there is no better idea for `before` and `after`. This is similar to:

```
\tcbset{parskip/.style={before={\par\pagebreak[0]\parindent=0pt},
                        after={\par}}}
```

U 2017-02-01 `/tcb/noparskip` (style, no value)
Sets the keys `before` and `after` to values which are recommended, if the package `parskip` is *not* used and there is no better idea for `before` and `after`. This is similar to:

```
\tcbset{noparskip/.style={before={\par\pagebreak[0]\smallskip\parindent=0pt},
                          after={\par\smallskip}}}
```

`/tcb/autoparskip` (style, no value, initially set)
Tries to detect the usage of the package `parskip` and sets the keys `before` and `after` accordingly. Actually, the following is done:

- If the length of `\parskip` is greater than `0pt` at the beginning of the document, `/tcb/parskip` is executed. Here, the usage of package `parskip` is *assumed*.
- Otherwise, if the length of `\parskip` is not greater than `0pt` at the beginning of the document, `/tcb/noparskip` is executed. Here, the absence of package `parskip` is *assumed*.

`autoparskip` is the default for the package `tcolorbox`, if `before` or `after` are not changed otherwise.

`/tcb/nobeforeafter` (style, no value)
Abbreviation for clearing the keys `before` and `after`. The colored box is not put into a paragraph and there is no space before or after the box.

```
\tcbset{myone/.style={colback=LightGreen,colframe=DarkGreen,
  equal height group=nobefaf,width=\linewidth/4,nobeforeafter}}
\begin{tcolorbox}[myone,title=Box 1]Box 1\end{tcolorbox}%
\begin{tcolorbox}[myone,title=Box 2]Box 2\end{tcolorbox}%
\begin{tcolorbox}[myone,title=Box 3]Box 3\end{tcolorbox}%
\begin{tcolorbox}[myone,title=Box 4]Box 4\end{tcolorbox}
```



`/tcb/forces nobeforeafter` (style, no value)
Forces the setting of `/tcb/nobeforeafter` even if `/tcb/before` and `/tcb/after` are set to other values later. Do not use this option globally unless you *really* know what you do. Note that embedded boxes do not inherit this forced clearance.

`/tcb/baseline=`⟨*length*⟩ (no default, initially `0pt`)

Used to set the `\pgfsetbaseline` value of the resulting `tcolorbox`.

```
\tcbset{colframe=red!50!white,width=4cm,nobeforeafter}
Some text\dotfill
\begin{tcolorbox}[baseline=3mm]
One line.
\end{tcolorbox}
\begin{tcolorbox}[baseline=3mm]
First line.\\Second line.
\end{tcolorbox}
```

Some text . . . . . One line. First line. Second line.

N 2014-10-10 `/tcb/box align=`⟨*alignment*⟩ (style, no default, initially `bottom`)

Used to set the `/tcb/baseline` value of the resulting `tcolorbox`. Feasible values for ⟨*alignment*⟩ are:

- `bottom`: alignment with the box bottom,
- `top`: alignment with the box top,
- `center`: alignment with the box center,
- `base`: alignment with the box content base. This option is not applicable for a `tcolorbox` → P. 12 but for a `\tcbox` → P. 14 only. It is an alias for `/tcb/tcbox raise base` → P. 96.

```
\tcbset{colframe=red!50!white,width=4cm,nobeforeafter}
Some text\dotfill
\begin{tcolorbox}[box align=bottom]
One line.
\end{tcolorbox}
\begin{tcolorbox}[box align=bottom]
First line.\\Second line.
\end{tcolorbox}
```

Some text . . . . . One line. First line. Second line.

```
\tcbset{colframe=red!50!white,width=4cm,nobeforeafter}
Some text\dotfill
\begin{tcolorbox}[box align=top]
One line.
\end{tcolorbox}
\begin{tcolorbox}[box align=top]
First line.\\Second line.
\end{tcolorbox}
```

Some text . . . . . One line. First line. Second line.

```
\tcbset{colframe=red!50!white,width=4cm,nobeforeafter}
Some text\dotfill
\begin{tcolorbox}[box align=center]
One line.
\end{tcolorbox}
\begin{tcolorbox}[box align=center]
First line.\\Second line.
\end{tcolorbox}
```

Some text . . . . . One line. First line. Second line.

```
\tcbset{colframe=red!50!white,nobeforeafter}
Some text\dotfill
\tcbox[nobeforeafter,box align=base]{One line}
\tcbox[nobeforeafter,box align=base,size=fbox]{Another line}
```

Some text . . . . . One line Another line

N 2014-10-10
U 2015-03-16

/tcb/before skip=⟨*glue*⟩ (style, no default)

Inserts some vertical space of the given ⟨*glue*⟩ before the colored box. This style sets /tcb/before → P. 78.

```
Some text.
\begin{tcolorbox}[before skip=1cm,
    colframe=red!50!white]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

Some text.

This is a **tcolorbox**.

N 2014-10-10
U 2017-02-01

/tcb/after skip=⟨*glue*⟩ (style, no default)

Inserts some vertical space of the given ⟨*glue*⟩ after the colored box. This style sets /tcb/after → P. 78.

```
\begin{tcolorbox}[after skip=1cm,
    colframe=red!50!white]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
Some text.
```

This is a **tcolorbox**.

Some text.

N 2014-10-10

/tcb/beforeafter skip=⟨*glue*⟩ (style, no default)

Inserts some vertical space of the given ⟨*glue*⟩ before *and* after the colored box. This style sets /tcb/before → P. 78 and /tcb/after → P. 78.

```
\tcbset{beforeafter skip=0pt,
  colframe=red!50!white}
\begin{tcolorbox}
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
\begin{tcolorbox}
  Second box.
\end{tcolorbox}
```

This is a **tcolorbox**.

Second box.

N 2014-11-07 **/tcb/left skip=⟨*length*⟩** (style, no default, initially 0mm)

Inserts some horizontal space of the given ⟨*length*⟩ before the colored box. This style sets /tcb/grow to left by →P. 84 with the negated ⟨*length*⟩, i.e. the bounding box and box width are changed.

```
\noindent\rule{\linewidth}{2pt}

\begin{tcolorbox}[left skip=1cm,
    colframe=red!50!white]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```



N 2014-11-07 **/tcb/right skip=⟨*length*⟩** (style, no default, initially 0mm)

Inserts some horizontal space of the given ⟨*length*⟩ after the colored box. This style sets /tcb/grow to right by →P. 84 with the negated ⟨*length*⟩, i.e. the bounding box and box width are changed.

```
\noindent\rule{\linewidth}{2pt}

\begin{tcolorbox}[right skip=1cm,
    colframe=red!50!white]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

N 2014-10-10 **/tcb/leftright skip=⟨*length*⟩** (style, no default)

Inserts some horizontal space of the given ⟨*length*⟩ before *and* after the colored box. This style changes the bounding box and the box width.

```
\noindent\rule{\linewidth}{2pt}

\begin{tcolorbox}[leftright skip=1cm,
    colframe=red!50!white]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```



N 2014-12-11 **/tcb/ignore nobreak=true|false** (default true, initially false)

After a heading, LaTeX tries to avoid a break by setting a nobreak boolean value. Starting from version 3.33, the /tcb/before →P. 78 respectively /tcb/before skip →P. 80 settings are not used after a heading if /tcb/ignore nobreak is set to true. For an unbreakable box, /tcb/before nobreak is used instead. Further, a /tcb/breakable →P. 365 box will also try to avoid a break between a heading and a directly following first part of a break sequence. Set /tcb/ignore nobreak to true, if nobreak should be ignored as prior to version 3.33. Also, such a setting may be used locally to enforce the /tcb/before →P. 78 setting.

N 2014-12-16 **/tcb/before nobreak=⟨*code*⟩** (no default, initially \noindent)

Sets the ⟨*code*⟩ which is executed before the colored box if it is unbreakable, if /tcb/ignore nobreak is not set, and if the box follows a heading.

N 2017-02-23 **/tcb/parfillskip restore=true|false** (default true, initially true)

If this option is set to be true, the minimum value of \parfillskip is tested at specific spots, if it is greater than 0pt. If so, \parfillskip is restored to \@flushglue which happens to be the default value.

These tests are executed for /tcb/parskip →P. 78, /tcb/noparskip →P. 78, /tcb/after skip →P. 80, /tcb/breakable →P. 365, and tcbraster →P. 279.

This option was created to automatically avoid overfull box warnings with \parfillskip changing packages.

4.15 Bounding Box

Normally, every `tcolorbox` has a bounding box which fits exactly to the dimensions of the outer frame. Therefore, LaTeX reserves exactly the space needed for the box. This behavior can be changed by enlarging (or shrinking) the bounding box. If the bounding box is enlarged, the `tcolorbox` will get some clearance around it. If the bounding box is shrunk, i. e. enlarged with negative values, the `tcolorbox` will overlap to other parts of the page. For example, the `tcolorbox` could be stretched into the page margin.



The following examples use `/tcb/show bounding box` → P. 179 to display the actual bounding box. For this, the library LIB skins has to be included and `/tcb/enhanced` → P. 206 has to be set.

4.15.1 Shifting Bounding Box Borders

`/tcb/enlarge top initially by=`⟨*length*⟩ (no default, initially `0mm`)

Enlarges the bounding box distance to the top of the box by ⟨*length*⟩. If the box is *breakable*, only the first box of the break sequence gets enlarged. `/tcb/enlarge top by` → P. 83 overwrites this key.

```
\tcbset{colframe=blue!75!black,colback=white}

\begin{tcolorbox}[enlarge top initially by=-5mm]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
\begin{tcolorbox}[enlarge top initially by=5mm,enhanced,show bounding box]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

This is a **tcolorbox**.

`/tcb/enlarge bottom finally by=`⟨*length*⟩ (no default, initially `0mm`)

Enlarges the bounding box distance to the bottom of the box by ⟨*length*⟩. If the box is *breakable*, only the last box of the break sequence gets enlarged. `/tcb/enlarge bottom by` → P. 83 overwrites this key.

```
\tcbset{colframe=blue!75!black,colback=white}

\begin{tcolorbox}[enlarge bottom finally by=5mm]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
\begin{tcolorbox}[enlarge bottom finally by=-5mm,enhanced,show bounding box]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

This is a **tcolorbox**.

`/tcb/enlarge top at break by=`⟨*length*⟩ (no default, initially `0mm`)

Enlarges the bounding box distance to the top of the box by ⟨*length*⟩, *if* the box is `/tcb/breakable` → P. 365. In this case, it is applied to *middle* and *last* parts in a break sequence. `/tcb/enlarge top by` overwrites this key.

`/tcb/enlarge bottom at break by=`⟨*length*⟩ (no default, initially `0mm`)

Enlarges the bounding box distance to the bottom of the box by ⟨*length*⟩, *if* the box is `/tcb/breakable` → P. 365. In this case, it is applied to *first* and *middle* parts in a break sequence. `/tcb/enlarge bottom by` overwrites this key.

`/tcb/enlarge top by=`⟨*length*⟩ (no default, initially `0mm`)

Enlarges the bounding box distance to the top of the box by ⟨*length*⟩. `/tcb/enlarge top initially by` → P. 82 and `/tcb/enlarge top at break by` are set to ⟨*length*⟩.

`/tcb/enlarge bottom by=`⟨*length*⟩ (no default, initially `0mm`)

Enlarges the bounding box distance to the bottom of the box by ⟨*length*⟩. `/tcb/enlarge bottom finally by` → P. 82 and `/tcb/enlarge bottom at break by` are set to ⟨*length*⟩.

`/tcb/enlarge left by=`⟨*length*⟩ (no default, initially `0mm`)

Enlarges the bounding box distance to the left side of the box by ⟨*length*⟩.

```
\tcbset{colframe=blue!75!black,colback=white}

\begin{tcolorbox}[enlarge left by=2cm,width=5cm,enhanced,show bounding box]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
\begin{tcolorbox}[enlarge left by=-2cm,width=\linewidth+2cm]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```



`/tcb/enlarge right by=`⟨*length*⟩ (no default, initially `0mm`)

Enlarges the bounding box distance to the right side of the box by ⟨*length*⟩.

```
\tcbset{colframe=blue!75!black,colback=white}

\begin{tcolorbox}[enlarge right by=-2cm,width=\linewidth+2cm,
  enhanced,show bounding box]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
\begin{tcolorbox}[enlarge right by=2cm,width=\linewidth-2cm]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```



`/tcb/enlarge by=`⟨*length*⟩ (no default, initially `0mm`)

Enlarges the bounding box distance to all sides of the box by ⟨*length*⟩.

```
\tcbset{colframe=blue!75!black,colback=white,width=5cm,nobeforeafter}

\begin{tcolorbox}
This is a \textbf{tcolorbox}.
\end{tcolorbox}
\begin{tcolorbox}[enlarge by=5mm,enhanced,show bounding box]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```



`/tcb/grow to left by=`⟨*length*⟩ (no default, initially `0mm`)

Enlarges the current box width by ⟨*length*⟩ and enlarges (shrinks) the bounding box distance to the left side of the box by $-\langle length \rangle$. Also see `/tcb/left skip` → P. 81.

```
\tcbset{colframe=blue!75!black,colback=white}

\begin{tcolorbox}[width=5cm,grow to left by=2cm,enhanced,show bounding box]
This is a \textbf{tcolorbox} with a width of 7cm.
\end{tcolorbox}
```



`/tcb/grow to right by=`⟨*length*⟩ (no default, initially `0mm`)

Enlarges the current box width by ⟨*length*⟩ and enlarges (shrinks) the bounding box distance to the right side of the box by $-\langle length \rangle$. Also see `/tcb/right skip` → P. 81.

```
\tcbset{colframe=blue!75!black,colback=white}

\begin{tcolorbox}[grow to right by=2cm,enhanced,show bounding box]
This is a \textbf{tcolorbox}.
\end{tcolorbox}

\bigskip

\begin{tcolorbox}[grow to right by=2cm,grow to left by=1cm,
  enhanced,show bounding box]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```



N 2018-03-22 **/tcb/grow sidewards by=**⟨*length*⟩ (no default, initially 0mm)

Shortcut for setting /tcb/grow to left by →P. 84 and /tcb/grow to right by →P. 84 to ⟨*length*⟩. Also see /tcb/oversize →P. 45 and /tcb/spread sidewards →P. 88.

```
\tcbset{colframe=blue!75!black,colback=white}

\begin{tcolorbox}[grow sidewards by=2cm,enhanced,show bounding box]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

4.15.2 Box Alignment

N 2015-11-20 **/tcb/flush left** (style, no value)

Enlarges the bounding box to the right side to fill the line completely.

```
\tcbset{colframe=blue!75!black,colback=white}

\begin{tcolorbox}[flush left,width=5cm,enhanced,show bounding box]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

N 2015-11-20 **/tcb/flush right** (style, no value)

Enlarges the bounding box to the left side to fill the line completely.

```
\tcbset{colframe=blue!75!black,colback=white}

\begin{tcolorbox}[flush right,width=5cm,enhanced,show bounding box]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

N 2015-11-20 **/tcb/center** (style, no value)

Enlarges the bounding box equally to both sides to fill the line completely.

```
\tcbset{colframe=blue!75!black,colback=white}

\begin{tcolorbox}[center,width=5cm,enhanced,show bounding box]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```



Floating box from `toggle enlargement`

This page is an even page. Therefore, the left and right enlargements are toggled. This box stretches to the right margin on odd pages and to the left margin on even pages. The current document is one-sided – this feature makes sense for two-sided documents only.

4.15.3 Toggle Enlargements

U 2015-11-13 `/tcb/toggle enlargement`=⟨*toggle preset*⟩ (default `evenpage`, initially `none`)

According to the ⟨*toggle preset*⟩, the left and the right enlargements of the bounding box are switched or not. Feasible values are:

- `none`: no switching.
- `forced`: the values of the left and right enlargement are switched.
- `evenpage`: if the page is an even page, the values of the left and right enlargement are switched. This value also sets `/tcb/check odd page` → P. 101 to `true`.

! See `/tcb/toggle left and right` → P. 46 to toggle geometry settings.

```
\tcbset{colframe=blue!75!black,colback=white,
  grow to left by=20mm,grow to right by=-5mm}

\begin{tcolorbox}[toggle enlargement=none,enhanced,show bounding box]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
\begin{tcolorbox}[toggle enlargement=forced]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
\begin{tcolorbox}[toggle enlargement=evenpage]
  This page is an \tcbifoddpage{odd}{even} page.
  Therefore, the left and right enlargements
  \tcbifoddpage{are not}{are} toggled.
\end{tcolorbox}
```

This is a **tcolorbox**.

This is a **tcolorbox**.

This page is an even page. Therefore, the left and right enlargements are toggled.

```
\begin{tcolorbox}[colframe=red!60!black,colback=red!15!white,
  fonttitle=\bfseries,title=Floating box from \texttt{toggle enlargement},
  width=\textwidth,grow to right by=2cm,toggle enlargement,float=t]
  This page is an \tcbifoddpage{odd}{even} page.
  Therefore, the left and right enlargements \tcbifoddpage{are not}{are} toggled.
  This box stretches to the right margin on odd pages and to the left
  margin on even pages. The current document is one-sided -- this feature makes
  sense for two-sided documents only.
\end{tcolorbox}
```

4.15.4 Spread Box to Page Borders

The following border options are *not* applicable to nested boxes, boxes insides tables, etc. For boxes inside lists, the options *may* work, but not necessarily. Also, boxes should be set with `\noindent` and full width.

N 2017-02-13 **/tcb/spread inwards=**⟨*length*⟩ (default `0pt`, initially unset)

Enlarges the current box width to match the inner page border (left-handed side for one-sided documents). If the optional ⟨*length*⟩ is greater than `0pt`, the box grows over the border, if ⟨*length*⟩ is lower than `0pt`, there is a margin between box and page border. `/tcb/toggle enlargement` → P. 86 is set automatically.

```
\begin{tcolorbox}[enhanced,spread inwards,
  colframe=blue!75!black,colback=white,show bounding box]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

N 2017-02-13 **/tcb/spread outwards=**⟨*length*⟩ (default `0pt`, initially unset)

Enlarges the current box width to match the outer page border (right-handed side for one-sided documents). If the optional ⟨*length*⟩ is greater than `0pt`, the box grows over the border, if ⟨*length*⟩ is lower than `0pt`, there is a margin between box and page border. `/tcb/toggle enlargement` → P. 86 is set automatically.

```
\begin{tcolorbox}[enhanced,spread outwards,
  colframe=blue!75!black,colback=white,show bounding box]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

N 2017-02-13 **/tcb/move upwards=**⟨*length*⟩ (default `0pt`, initially unset)

Starts a new page with the box at the very top page border. If the optional ⟨*length*⟩ is greater than `0pt`, the box moves over the border, if ⟨*length*⟩ is lower than `0pt`, there is a margin between box and page border.

N 2017-02-13 **/tcb/move upwards*=**⟨*length*⟩ (default `0pt`, initially unset)

Identical to `/tcb/move upwards`, but without starting a new page.

N 2017-02-13 **/tcb/fill downwards=**⟨*length*⟩ (default `0pt`, initially unset)

Enlarges the height of the box until the very bottom page border. The library LIB breakable has to be loaded, and `/tcb/height fill` → P. 56 is set automatically. If the optional ⟨*length*⟩ is greater than `0pt`, the box moves over the border, if ⟨*length*⟩ is lower than `0pt`, there is a margin between box and page border.

```
\begin{tcolorbox}[enhanced,fill downwards,
  colframe=blue!75!black,colback=white,show bounding box]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

This is an example for 'spread upwards'.

N 2017-02-13 **/tcb/spread upwards=**⟨*length*⟩ (default 0pt, initially unset)

Combination of /tcb/move upwards →P. 87, /tcb/spread inwards →P. 87, and /tcb/spread outwards →P. 87. The optional ⟨*length*⟩ is used for all these keys.

```
\begin{tcolorbox}[enhanced,spread upwards,sharp corners=north,height=3cm,
  colframe=blue!75!black,interior style={top color=blue!50,bottom color=white}]
This is an example for 'spread upwards'.
\end{tcolorbox}
```

N 2017-02-13 **/tcb/spread upwards*=**⟨*length*⟩ (default 0pt, initially unset)

Identical to /tcb/move upwards →P. 87, but without starting a new page.

N 2017-02-13 **/tcb/spread sidewards=**⟨*length*⟩ (default 0pt, initially unset)

Combination of /tcb/spread inwards →P. 87 and /tcb/spread outwards →P. 87. The optional ⟨*length*⟩ is used for all these keys. Also see /tcb/oversize →P. 45 and /tcb/grow sidewards by →P. 85.

```
\begin{tcolorbox}[enhanced,spread sidewards,
  colframe=blue!75!black,colback=white,show bounding box]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

N 2017-02-13 **/tcb/spread=**⟨*length*⟩ (default 0pt, initially unset)

Combination of /tcb/move upwards →P. 87, /tcb/fill downwards →P. 87, /tcb/spread inwards →P. 87, and /tcb/spread outwards →P. 87. Such, the box fills the whole page. The optional ⟨*length*⟩ is used for all these keys.

N 2017-02-13 **/tcb/spread downwards=**⟨*length*⟩ (default 0pt, initially unset)

Combination of /tcb/fill downwards →P. 87, /tcb/spread inwards →P. 87, and /tcb/spread outwards →P. 87. The optional ⟨*length*⟩ is used for all these keys.

```
\begin{tcolorbox}[enhanced,spread downwards,sharp corners=south,
  colframe=red!75!black,interior style={top color=white,bottom color=red!50}]
This is an example for 'spread downwards'.
\end{tcolorbox}
```

This is an example for 'spread downwards'.

4.15.5 Box Extrusion

The following keys should not be used with breakable boxes or boxes with a lower part.

/tcb/shrink tight (style, no value, initially unset)

The total colored box is shrunk to the dimensions of the upper part. There should be no lower part and no title. This style sets the /tcb/boxsep → P. 39 to 0pt and other geometry keys to fitting values. This option is likely to be used with the following extrusion keys.

```
\tcbset{colframe=blue!75!black,colback=white,arc=0mm,boxrule=0.4pt,
        nobeforeafter,tcbox raise base,shrink tight}

\begin{tcolorbox}
This is a \textbf{tcolorbox}.
\end{tcolorbox}

Lorem \tcbox{ipsum} dolor sit amet, consectetuer adipiscing elit.
```

This is a **tcolorbox**.
Lorem ipsum dolor sit amet, consectetuer adipiscing elit.

U 2014-09-19 **/tcb/extrude left by=**⟨*length*⟩ (style, no default, initially unset)

The (upper part of the) colored box is extruded by the given ⟨*length*⟩ to the left side. The inner width and the bounding box is kept unchanged and the operation is additive!

```
\tcbset{enhanced,colframe=red,colback=yellow!25!white,
  frame style={opacity=0.25},interior style={opacity=0.5},
  nobeforeafter,tcbox raise base,shrink tight,extrude by=2mm}

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit,
vestibulum ut, placerat ac, adipiscing vitae, felis.
\tcbox[extrude left by=1cm]{Curabitur} dictum gravida mauris.
Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna.
```

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna.

U 2014-09-19 **/tcb/extrude right by=**⟨*length*⟩ (style, no default, initially unset)

The (upper part of the) colored box is extruded by the given ⟨*length*⟩ to the right side. The inner width and the bounding box is kept unchanged and the operation is additive!

```
\tcbset{enhanced,colframe=red,colback=yellow!25!white,
  frame style={opacity=0.25},interior style={opacity=0.5},
  nobeforeafter,tcbox raise base,shrink tight,extrude by=2mm}

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit,
vestibulum ut, placerat ac, adipiscing vitae, felis.
\tcbox[extrude right by=1cm]{Curabitur} dictum gravida mauris.
Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna.
```

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna.

/tcb/extrude top by=⟨*length*⟩ (style, no default, initially unset)

The (upper part of the) colored box is extruded by the given ⟨*length*⟩ to the top side. The inner width and the bounding box is kept unchanged and the operation is additive!

```
\tcbset{enhanced,colframe=red,colback=yellow!25!white,
  frame style={opacity=0.25},interior style={opacity=0.5},
  nobeforeafter,tcbox raise base,shrink tight,extrude by=2mm}

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit,
vestibulum ut, placerat ac, adipiscing vitae, felis.
\tcbox[extrude top by=1cm]{Curabitur} dictum gravida mauris.
Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna.
```

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna.

/tcb/extrude bottom by=⟨*length*⟩ (style, no default, initially unset)

The (upper part of the) colored box is extruded by the given ⟨*length*⟩ to the bottom side. The inner width and the bounding box is kept unchanged and the operation is additive!

```
\tcbset{enhanced,colframe=red,colback=yellow!25!white,
  frame style={opacity=0.25},interior style={opacity=0.5},
  nobeforeafter,tcbox raise base,shrink tight,extrude by=2mm}

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit,
vestibulum ut, placerat ac, adipiscing vitae, felis.
\tcbox[extrude bottom by=1cm]{Curabitur} dictum gravida mauris.
Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna.
```

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna.

/tcb/extrude by=⟨*length*⟩ (style, no default, initially unset)

The (upper part of the) colored box is extruded by the given ⟨*length*⟩ to all sides. The inner width and the bounding box is kept unchanged and the operation is additive!

```
\tcbset{enhanced,colframe=red,colback=yellow!25!white,
  frame style={opacity=0.25},interior style={opacity=0.5},
  nobeforeafter,tcbox raise base,shrink tight,extrude by=2mm}

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit,
vestibulum ut, placerat ac, adipiscing vitae, felis. \tcbox{Curabitur} dictum
gravida mauris. \tcbox[colframe=Green,interior style={opacity=0.0}]{Nam}
arcu libero, nonummy eget, consectetuer id, \tcbox{vulputate} a, magna. Donec
vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus
et malesuada fames ac turpis egestas. \tcbox{Mauris ut leo.}
```

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo.

4.16 Layered Boxes and Every Box Settings

A `tcolorbox` may contain another `tcolorbox` and so on. The package takes track of the nesting level using a counter `tcblayer`. Counter values may be used for doing some fancy things, but you should never change the counter value yourself.

The package takes special care for the first four layers or nesting levels, called managed layers. Here, footnote texts are administrated to find their intended place and specific layer dependent options may be set by changing `/tcb/every box on layer n` → P. 92. If needed, the number of managed layers can be increased by setting `\tcbsetmanagedlayers` → P. 92 to a higher value than 4.

The following styles have a considerable influence on how layered boxes are processed. Note especially that nested boxes are getting a `/tcb/reset` → P. 105 by default. You can change this, but be prepared for suprises if you do.

If the defaults are *not changed*, a `tcolorbox` gets its options in the following order. Following options overwrite preceding options.

1. On package load, all options are set to default values.
2. Every `\tcbset` → P. 13 command adds or changes options for the following boxes inside the current TEX group.
3. While entering a `tcolorbox`, a `/tcb/every box on layer n` → P. 92 or `/tcb/every box on higher layers` → P. 92 option list is applied. With default settings this means:
   - For layer 1 (lowest layer), the `/tcb/every box` option list is applied. Not overwritten options given by a preceding `\tcbset` → P. 13 survive.
   - For layer 2 and above (nested boxes), a `/tcb/reset` → P. 105 followed by `/tcb/every box` option list is applied. Every resettable options given by a preceding `\tcbset` → P. 13 and by the sourrounding box(es) are reset.
4. The ⟨*options*⟩ given to the `tcolorbox` are applied. Or, if the box was generated by `\newtcolorbox` → P. 15 or friends, the ⟨*options*⟩ given there are applied.
5. If the box was generated by `\newtcolorbox` → P. 15 or friends, some automated options are applied.

`/tcb/every box` (style)

By default, this style is empty.

```
% default setting:
\tcbset{every box/.style={}}
```

It may be changed by redefining this style.

```
% setting all boxes to be enhanced:
\tcbset{every box/.style={enhanced}}
```



/tcb/every box on layer n (style)

Here, n has to be replaced by a number ranging from 1 to the highest managed layer number (4 by default).

```
% default settings:
\tcbset{
  every box on layer 1/.style={every box},
  every box on layer 2/.style={reset,every box},
  every box on layer 3/.style={reset,every box},
  every box on layer 4/.style={reset,every box},
  }
```

/tcb/every box on higher layers (style)

Higher layers are layers above the highest managed layer number (4 by default).

```
\tcbset{every box on higher layers/.style={reset,every box}}
```

\tcbsetmanagedlayers{⟨*number*⟩**}**

Replaces the highest managed layer number by ⟨*number*⟩ where 4 is the default. This macro can only be used inside the preamble. Using a ⟨*number*⟩ lower than 4 typically makes no sense, but is not forbidden.

```
% \usepackage{lipsum}
% \tcbuselibrary{skins,breakable}
\tcbset{colframe=red!75!black,fonttitle=\bfseries,
  colback=red!5!white,
  every box/.style={enhanced,watermark text=\thetcblayer,
    before=\par\smallskip,after=\par\smallskip},
  every box on layer 2/.style={reset,every box,colback=yellow!10!white,
    drop fuzzy shadow}}
\begin{tcolorbox}[enhanced jigsaw,breakable,title=Layer 1 Box]
Here comes a footnote\footnote{Footnote from layer 1 box}.
\lipsum[2]
  \begin{tcolorbox}[title=Layer 2 Box]
  abc\footnote{The footnote of abc}
  \end{tcolorbox}
  \begin{tcolorbox}[title=Another Box,ams equation]
    \tcbhighmath{\sum\limits_{n=1}^{\infty} \frac{1}{n}} = \infty.
  \end{tcolorbox}
Some text\footnote{Footnote from some text}.
  \begin{tcolorbox}[title=Yet Another Box]
    \tcboxfit[height=2cm]{\lipsum[1]}
    My text.
    \begin{tcolorbox}
      Another lipsum text\footnote{A lipsum text}. \lipsum[3]
      \begin{tcolorbox}[title=Layer 4,colframe=blue,colback=white]
        Layer 4\footnote{Layer 4 footnote}
      \end{tcolorbox}
      The End\footnote{Last footnote}.
    \end{tcolorbox}
  \end{tcolorbox}
\end{tcolorbox}
```

Layer 1 Box

Here comes a footnote[a]. Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras

nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Layer 2 Box

abc[a]

[a]The footnote of abc

Another Box

$$\sum_{n=1}^{\infty} \frac{1}{n} = \infty. \tag{1}$$

Some text[b].

Yet Another Box

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

My text.

Another lipsum text[a]. Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

Layer 4

Layer 4[a]

[a]Layer 4 footnote

The End[b].

[a]A lipsum text
[b]Last footnote

[a]Footnote from layer 1 box
[b]Footnote from some text

4.17 Capture Mode

`/tcb/capture`=⟨*mode*⟩ (no default, initially `minipage`)

The capture ⟨*mode*⟩ defines how the box content is processed.

Feasible values for ⟨*mode*⟩ are:

- `minipage`:
  This is the default ⟨*mode*⟩ for `tcolorbox` → P. 12. The content may have an upper and a lower part. Optionally, the box can be `/tcb/breakable` → P. 365. The box content is put into a minipage or into something similar to a minipage.
- `hbox`:
  This is the default ⟨*mode*⟩ for `\tcbox` → P. 14. The content cannot have a lower part and cannot be broken. The colored box is sized according to the dimensions of the content. A shortcut to set this mode is `/tcb/hbox`.
- `fitbox`: (needs the LIB fitting library)
  This is the default ⟨*mode*⟩ for `\tcboxfit` → P. 410. The content cannot have a lower part and cannot be broken. The content is sized according to the dimensions of the colored box. A shortcut to set this mode is `/tcb/fit` → P. 412.

```
\tcbset{colframe=blue!75!black,colback=white}

\begin{tcolorbox}[capture=minipage]
This is a tcolorbox.
\end{tcolorbox}

\begin{tcolorbox}[capture=hbox]
This is a tcolorbox.
\end{tcolorbox}

\begin{tcolorbox}[capture=fitbox,height=9mm]% needs the 'fitting' library
This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

This is a tcolorbox.

This is a tcolorbox.

`/tcb/hbox` (style, no default)

Shortcut for `capture=hbox`.

```
\tcbset{colframe=blue!75!black,colback=white}

\begin{tcolorbox}[hbox]
This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

`/tcb/minipage` (style, no default)

Shortcut for `capture=minipage`.

4.18 Text Characteristics

U 2015-10-14 `/tcb/parbox=true|false` (default `true`, initially `true`)

The text inside a `tcolorbox` is formatted using a LaTeX `minipage` if the box is unbreakable. If breakable, the box tries a mimicry of a `minipage`. In a `minipage` or `parbox`, paragraphs are formatted slightly different as the main text. If the key value is set to `false`, the normal main text behavior is restored. In some situations, this has some unwanted side effects. It is recommended that you use this experimental setting only where you really want to have this feature.

```
% \usepackage{lipsum}  % preamble
\tcbset{width=(\linewidth-2mm)/2,nobeforeafter,arc=1mm,
  colframe=blue!75!black,colback=white,fonttitle=\bfseries,fontupper=\small,
  left=2mm,right=2mm,top=1mm,bottom=1mm,equal height group=parbox}

\begin{tcolorbox}[parbox,adjusted title={parbox=true (normal)}]
  \lipsum[1-2]
\end{tcolorbox}\hfill%
\begin{tcolorbox}[parbox=false,adjusted title={parbox=false}]
  \lipsum[1-2]
\end{tcolorbox}%
```

parbox=true (normal)

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.
Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

parbox=false

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

`/tcb/hyphenationfix=true|false` (default `true`, initially `false`)

Long words at the beginning of paragraphs in very narrow boxes will not be hyphenated using `pdflatex`. This problem is circumvented by applying the `hyphenationfix` option.

```
\tcbset{colframe=blue!75!black,
  fontupper=\normalsize,
  colback=blue!5!white,width=4cm}

\begin{tcolorbox}
Rechnungsadjunktentochter.\par
Statthaltereikonzipist.
\end{tcolorbox}

\begin{tcolorbox}[hyphenationfix]
Rechnungsadjunktentochter.\par
Statthaltereikonzipist.
\end{tcolorbox}
```

Rechnungsadjunktentochter.
Statthaltereikonzipist.

Rechnungsad-
junktentochter.
Statthal-
tereikonzipist.

! `parbox=false` and `hyphenationfix` should not be used together. They are targeting different box types and they do not blend very well.

4.19 Files

`/tcb/tempfile=`⟨*file name*⟩ (no default, initially `\jobname.tcbtemp`)

Sets ⟨*file name*⟩ as name for the temporary file which is used inside `tcbwritetemp` → P. 126 and `\tcbusetemp` → P. 126 implicitely.

4.20 `\tcbox` Specials

The following options are applicable for `\tcbox` → P. 14 and `\tcboxmath` → P. 341 only.

`/tcb/tcbox raise=`⟨*length*⟩ (no default, initially `0pt`)

Raises the `\tcbox` → P. 14 by the given ⟨*length*⟩.

```
\tcbset{colframe=blue!50!black,colback=white,colupper=red!50!black,
        fonttitle=\bfseries,nobeforeafter,center title}

Test\dotfill
\tcbox[tcbox raise base]{Hello World 1}\dotfill
\tcbox{Hello World 2}\dotfill
\tcbox[tcbox raise=5mm]{Hello World 3}
```

Test . . . . . Hello World 1 . . . . . Hello World 2 . . . . . Hello World 3

`/tcb/tcbox raise base` (style, no value, initially unset)

Raises the `\tcbox` → P. 14 such that the base of its content matches the base of the environmental line; see example above.

`/tcb/on line` (style, no value, initially unset)

Combines `/tcb/tcbox raise base` with `/tcb/nobeforeafter` → P. 78. The resulting box behaves analogue to `\fbox`.

N 2015-03-23 **/tcb/tcbox width=⟨*mode*⟩** (no default, initially **auto**)

Controls how \tcbox → P. 14 respects a /tcb/width → P. 34 setting. Feasible values for ⟨*mode*⟩ are:

- **auto** (initial setting): ignore /tcb/width → P. 34 and set box width according to its content.
- **auto limited**: Set box width according to its content, if it is smaller than /tcb/width → P. 34. Otherwise, the content is set like in a tcolorbox → P. 12 with line breaks.
- **forced center**: Set box width according to /tcb/width → P. 34. The content is centered and may overlap the box borders.
- **forced left**: Set box width according to /tcb/width → P. 34. The content is left aligned and may overlap the box borders.
- **forced right**: Set box width according to /tcb/width → P. 34. The content is right aligned and may overlap the box borders.
- **minimum center**: Set box width according to /tcb/width → P. 34, if the content fits into. The content is centered and the box width may grow beyond /tcb/width → P. 34.
- **minimum left**: Set box width according to /tcb/width → P. 34, if the content fits into. The content is left aligned and the box width may grow beyond /tcb/width → P. 34.
- **minimum right**: Set box width according to /tcb/width → P. 34, if the content fits into. The content is right aligned and the box width may grow beyond /tcb/width → P. 34.

```
\tcbset{size=small,on line,before upper=\strut,
  colframe=blue!75!black,colback=blue!5!white,
  fontupper=\normalsize,width=4cm}

\tcbox[tcbox width=auto]{auto}\qquad
\tcbox[tcbox width=auto limited]{auto limited}\qquad
\tcbox[tcbox width=auto limited]{auto limited with long text}\\
\tcbox[tcbox width=forced center]{forced center}\qquad
\tcbox[tcbox width=forced center]{forced center with long text}\\
\tcbox[tcbox width=forced left]{forced left}\qquad
\tcbox[tcbox width=forced left]{forced left with long text}\\
\tcbox[tcbox width=forced right]{forced right}\qquad
\tcbox[tcbox width=forced right]{forced right with long text}\\
\tcbox[tcbox width=minimum center]{minimum center}\qquad
\tcbox[tcbox width=minimum center]{minimum center with long text}\\
\tcbox[tcbox width=minimum left]{minimum left}\qquad
\tcbox[tcbox width=minimum left]{minimum left with long text}\\
\tcbox[tcbox width=minimum right]{minimum right}\qquad
\tcbox[tcbox width=minimum right]{minimum right with long text}
```



4.21 Counters, Labels, and References

/tcb/phantom=⟨*code*⟩ (no default, initially unset)

The ⟨*code*⟩ is put in a box at the upper left corner of the `tcolorbox`. If the `tcolorbox` is breakable, the ⟨*code*⟩ is executed for the first box of the break sequence only. If there already was some phantom code given, the new ⟨*code*⟩ is appended.

The ⟨*code*⟩ is intended to be used for counter stepping, labelling, and related operations which do not produce visible text.

- The ⟨*code*⟩ is executed before the title and box content, i. e. counter values are ensured to be increased before usage.
- Labels are ensured to reference the correct page number.
- The ⟨*code*⟩ is executed only once even during fitting operations for title and box content.
- In combination with the `hyperref` package, the hyper anchor is set to the upper left corner of the `tcolorbox`, i. e. links inside the pdf document will jump to the box pleasantly.
- Since the ⟨*code*⟩ is executed inside a TEX group, only global operations can survive this group.

Examples for the `phantom` usage are given in Section 15.9 from page 333, e. g. Example 15.1 on page 334.

/tcb/nophantom (no value, initially set)

Removes the phantom code if set before.

/tcb/label=⟨*marker*⟩ (no default, initially unset)

The ⟨*marker*⟩ is set as label text for a reference with the `\ref` macro. Typically, this option is used for numbered boxes, see Subsection 5.1 from page 108, e. g. `/tcb/new/auto counter` → P. 108.

N 2014-11-28 **/tcb/phantomlabel**=⟨*marker*⟩ (no default, initially unset)

Equivalent to `/tcb/label` for an *unnumbered* box. A `\phantomsection` from the package `hyperref` [15] is used to set a correct hyperlink target. This is not needed for a numbered box.

/tcb/label type=⟨*type*⟩ (no default, initially unset)

This option key can be used only in conjunction with the `cleveref` package [5] which has to be loaded separately. ⟨*type*⟩ has to be a cross-reference type *known* to `cleveref` like `theorem`, `algorithm`, `result`, etc. References made with `cleveref` will use this type. Note that using `label type` will result in compilation errors, if `cleveref` is not loaded. For an example, see Theorem 16.3.5 on page 359.

/tcb/no label type (no value, initially set)

Removes a `/tcb/label type`, if set before.

/tcb/step=⟨*counter*⟩ (no default, initially unset)

Shortcut for `phantom={\refstepcounter{#1}}`. The given ⟨*counter*⟩ is increased and ready for labelling. This option is not needed when using the convenient automated numbering introduced with version 2.40, see Subsection 5.1 from page 108.

/tcb/step and label={⟨*counter*⟩}{⟨*marker*⟩} (no default, initially unset)

Shortcut for using `/tcb/step` and `/tcb/label`. This option is not needed when using the convenient automated numbering introduced with version 2.40, see Subsection 5.1 from page 108.

`/tcb/list entry=`⟨*text*⟩ (no default, initially unset)

If the «list of tcolorbox(es)» feature described in Subsection 5.2 from page 115 is used, this key describes the ⟨*text*⟩ for an entry into the generated list, e. g.

```
list entry={\protect\numberline{\thetcbcounter}My beautiful Example}
```

See Section 15.9 from page 333 for a complete example.

N 2014-09-19 `/tcb/list text=`⟨*text*⟩ (style, no default)

This is a shortcut for setting `/tcb/list entry` to `\protect\numberline{\thetcbcounter}`⟨*text*⟩. So, the following settings are identical:

```
list text={My beautiful Example},
list entry={\protect\numberline{\thetcbcounter}My beautiful Example}
```

See Section 15.9 from page 333 for a complete example.

`/tcb/add to list={`⟨*list*⟩`}{`⟨*type*⟩`}` (no default, initially unset)

If the «list of tcolorbox(es)» feature described in Subsection 5.2 from page 115 is used, list entries are generated automatically. With this key, you can enforce an entry to the given ⟨*list*⟩ with the given ⟨*type*⟩. This issues:
`\addcontentsline{`⟨*list*⟩`}{`⟨*type*⟩`}{`⟨*entry text*⟩`}`

N 2016-06-22 U 2016-11-18 `/tcb/nameref=`⟨*text*⟩ (no default, initially unset)

If the `nameref` package is loaded, the given ⟨*text*⟩ is used for corresponding `\nameref` macros. Typically, the ⟨*text*⟩ will be chosen to be identical or nearly identical to the one for `/tcb/title` → P. 18.

Definition in the preamble:

```
\newtcolorbox[auto counter,number within=section]{pabox}[2][]{%
  colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
  title=Examp.~\thetcbcounter: #2,#1}
```

```
\begin{pabox}[label={mynamelabel},nameref={Title or anything else}]{Title text}
This is a tcolorbox.
\end{pabox}
This box is automatically numbered with \ref{mynamelabel} on page
\pageref{mynamelabel}.

The box is titled '\nameref{mynamelabel}'.
```

Examp. 4.1: Title text

This is a tcolorbox.

This box is automatically numbered with 4.1 on page 99.
The box is titled 'Title or anything else'.

! `/tcb/nameref` is used automatically inside `\newtcbtheorem` → P. 339.

N 2017-02-03 **/tcb/hypertarget=**⟨*marker*⟩ (no default, initially unset)

A **\hypertarget** from the package **hyperref** [15] is used to create an internal link of an anchor ⟨*marker*⟩. This ⟨*marker*⟩ can be referenced by **\hyperlink** or **/tcb/hyperlink** → P. 199.

```
% \usepackage{hyperref}%
\begin{tcolorbox}[enhanced,
  colback=red!10,colframe=red!50!black,
  hypertarget=hypertwinA,
  hyperlink=hypertwinB,
  title=Box A]
Click me to jump to Box B.
\end{tcolorbox}
```

Box A

Click me to jump to Box B.

N 2017-02-10 **/tcb/bookmark=**⟨*text*⟩ (no default, initially unset)

Sets a PDF bookmark with the given ⟨*text*⟩, if the package **bookmark** [11] is loaded. This bookmark is set with an automated destination (the current box) and is set one level below the current bookmark level.

```
% \usepackage{bookmark}%
\begin{tcolorbox}[colback=blue!10,colframe=blue!50!black,
  bookmark=Example for using a bookmark,
  title=Example for using a bookmark]
Open the bookmark view of the previewer
to see the bookmark.
\end{tcolorbox}
```

Example for using a bookmark

Open the bookmark view of the previewer to see the bookmark.

N 2017-02-10 **/tcb/bookmark*=**{⟨*options*⟩}{⟨*text*⟩} (no default, initially unset)

Identical to **/tcb/bookmark**, but additional ⟨*options*⟩ from the package **bookmark** [11] can be given.

```
% \usepackage{bookmark}%
\begin{tcolorbox}[colback=red!10,colframe=red!50!black,
  bookmark*={color=red,italic,bold}%
            {Another bookmark example},
  title=Red and bold bookmark]
Open the bookmark view of the previewer
to see the bookmark.
\end{tcolorbox}
```

Red and bold bookmark

Open the bookmark view of the previewer to see the bookmark.

4.22 Even and Odd Pages

Also see /tcb/toggle left and right → P. 46 and /tcb/toggle enlargement → P. 86 for further even/odd options.

U 2015-11-13 **/tcb/check odd page=true|false** (default **true**, initially **false**)

If set to **true**, a precise even/odd page testing for the current box is applied. This is done by using labels. If a box moves to another page, the document has to be compiled twice for the correct settings. If set to **false**, even/odd page tests may give wrong results for the first box of a page.

/tcb/toggle left and right → P. 46, /tcb/toggle enlargement → P. 86, and /tcb/if odd page automatically set **check odd page**, but for \tcbifoddpage → P. 103 this option has to be set explicitely.

N 2015-11-13 **/tcb/if odd page={**⟨*odd options*⟩**}{**⟨*even options*⟩**}** (style, no default)

If the current box is on an odd page, the ⟨*odd options*⟩ are applied. On an even page, the ⟨*even options*⟩ are applied. /tcb/check odd page is automatically set for precise even/odd page testing.

```
\begin{tcolorbox}[if odd page={colback=yellow!50}{colback=red!50}]
  This box is colored in yellow on an odd page
  and is colored in red on an even page.
\end{tcolorbox}
```

This box is colored in yellow on an odd page and is colored in red on an even page.

If a box is /tcb/breakable → P. 365, using /tcb/if odd page only acts upon the *first* box. If the setting should be repeated for every partial box of the break sequence, the option should be packed into /tcb/extras → P. 371. In this case, /tcb/check odd page has to be set explicitely! Also see /tcb/if odd page* → P. 102.

N 2016-11-18 **/tcb/if odd page or oneside={**⟨*odd options*⟩**}{**⟨*even options*⟩**}** (style, no default)

For onesided documents, the ⟨*odd options*⟩ are applied always. For twosided documents, this style is identical to /tcb/if odd page.

N 2015-11-13 **/tcb/if odd page*={⟨*odd options*⟩}{⟨*even options*⟩}** (style, no default)

> ! This option needs the LIB breakable library, see Section 17 on page 363.

For breakable boxes, if the current partial box is on an odd page, the ⟨*odd options*⟩ are applied. On an even page, the ⟨*even options*⟩ are applied. /tcb/check odd page →P. 101 is automatically set for precise even/odd page testing.
In contrast to /tcb/if odd page →P. 101, /tcb/if odd page* is used on *every* partial box of a break sequences and not only on the *first* box. Another difference is that /tcb/if odd page* is applied quite *late* during option processing, while /tcb/if odd page →P. 101 is applied immediately.
/tcb/if odd page* is implemented as /tcb/if odd page →P. 101 packed into /tcb/extras →P. 371.

```
% \tcbuselibrary{breakable}
\begin{tcolorbox}[breakable,if odd page*={colback=yellow!50}{colback=red!50}]
  This breakable box is colored in yellow on an odd page
  and is colored in red on an even page. For every partial box, the
  test is repeated, i.e. this would give a yellow, red, yellow, red, \ldots\
  sequence for a long content.
\end{tcolorbox}
```

This breakable box is colored in yellow on an odd page and is colored in red on an even page. For every partial box, the test is repeated, i.e. this would give a yellow, red, yellow, red, . . . sequence for a long content.

N 2016-11-18 **/tcb/if odd page or oneside*={⟨*odd options*⟩}{⟨*even options*⟩}** (style, no default)

For onesided documents, the ⟨*odd options*⟩ are applied always. For twosided documents, this style is identical to /tcb/if odd page*.

N 2015-11-13 `\tcbifoddpage{⟨odd code⟩}{⟨even code⟩}`

If the current box is on an odd page, the ⟨*odd code*⟩ is executed. On an even page, the ⟨*even code*⟩ is executed. For precise even/odd page testing, the `/tcb/check odd page` → P. 101 has to be set manually inside the box options.

The macro `\tcbifoddpage` can be used inside underlay, overlay, or watermark code to test if the box is on an odd page. This will work also for boxes in a break sequence.

The macro can also be used inside the box **content text**. For unbreakable boxes, the correct page test is applied. But for `/tcb/breakable` → P. 365 boxes, `\tcbifoddpage` will always give the result for the page of the *first* box inside the box **content text**. If needed, the methods from the packages `changepage` or `ifoddpage` could be used here.

```
\tcbset{colframe=blue!75!black,colback=white,fonttitle=\bfseries}

\begin{tcolorbox}[enhanced,check odd page,
  title={Example for a box on an \tcbifoddpage{odd}{even} page},
  watermark text={\tcbifoddpage{Odd}{Even} page!}]
\lipsum[1]
\end{tcolorbox}
```

Example for a box on an odd page

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Odd page!

N 2016-11-18 `\tcbifoddpageoroneside{⟨odd code⟩}{⟨even code⟩}`

For onesided documents, the ⟨*odd code*⟩ is executed always. For twosided documents, this macro is identical to `\tcbifoddpage`.

N 2015-11-13 **\thetcolorboxnumber**

This is a unique identifier (arabic number) for a tcolorbox. It is locally defined inside boxes and has no meaning outside. It is used for precise even/odd page testing, but may also be valuable for elaborate user code.

```
\begin{tcolorbox}[colback=yellow!5,title=Box \thetcolorboxnumber]
  This box is \thetcolorboxnumber.
  \tcbox[on line,size=fbox]{This box is \thetcolorboxnumber} and
  \tcbox[on line,size=fbox]{this box is \thetcolorboxnumber}.
  This box is \thetcolorboxnumber.
\end{tcolorbox}
```

Box 1119

This box is 1119. This box is 1120 and this box is 1121. This box is 1119.

N 2015-11-13 **\thetcolorboxpage**

This macro contains the expanded arabic page number of the current tcolorbox. It is locally defined inside boxes and has no meaning outside. It is precise only, if `/tcb/check odd page` → P. 101 was set.

```
\begin{tcolorbox}[colback=yellow!5,check odd page,
    title=Box on page~\thetcolorboxpage]
  This box is located on page~\thetcolorboxpage.
\end{tcolorbox}
```

Box on page 104

This box is located on page 104.

4.23 Externalization

See Section 23 on page 446 for the LIB external library of tcolorbox.

If the *externalization* library of the tikz package is used and /tcb/graphical environment →P. 135 is set to tikzpicture, a tcolorbox could trigger the externalization process which will arise a compilation error.

To avoid this, there are two possible strategies:

- Ensure, that \tikzexternaldisable is set before a tcolorbox is used. If you typically use the pattern \tikzexternalenable *some picture* \tikzexternaldisable, there is nothing to care about.
- If *externalization* is enabled globally, use /tcb/shield externalize to shield any tcolorbox. The preamble code could look like this:

```
\usetikzlibrary{external}
\tikzexternalize
\tcbset{shield externalize}
```

/tcb/shield externalize=true|false (default true, initially false)

If set to true, the drawing part of the tcolorbox is not being externalized which is a good thing at the current state of art. Nevertheless, if the tcolorbox contains a tikzpicture, this picture is still externalized. Pictures drawn with help of /tcb/tikz upper →P. 69 or alike are *not* externalized.

If a tcolorbox is used inside a node of an encircling tikzpicture which is externalized, do *not* use \tikzexternaldisable in front of the tcolorbox. /tcb/shield externalize is deactivated automatically inside a tikzpicture.

/tcb/external=⟨*file name*⟩ (no default, initially unset)

Convenience option which calls \tikzsetnextfilename{⟨*file name*⟩}. Typically, it may be used inside the option list of a tcolorbox to set the externalization ⟨*file name*⟩ for the first tikzpicture which is discovered *inside* the box content. The package tikz [22] or the library LIB skins has to be loaded to use this option. Additionally, \usetikzlibrary{external} has to be used.

/tcb/remake=true|false (default true, initially false)

Convenience option which calls /tikz/external/remake next. Typically, it may be used inside the option list of a tcolorbox to force the remake of the first tikzpicture which is discovered *inside* the box content. The package tikz [22] or the library LIB skins has to be loaded to use this option. Additionally, \usetikzlibrary{external} has to be used.

4.24 Miscellaneous

/tcb/reset (no value, initially set)

Sets (nearly) all tcolorbox settings (including loaded libraries) back to their default values *plus* any settings given by \tcbsetforeverylayer →P. 13. /tcb/savedelimiter →P. 26 and /tcb/capture →P. 94 keep their values. Also, all raster values (see Section 14 on page 277) are not resetted.

This option is useful for boxes in boxes where the inner box should not inherit the settings of the outer box. Note that for boxes inside boxes the reset is done automatically, if the standard settings of the package are used (v2.40 and above), see Section 4.16 from page 91.

N 2015-01-09 **/tcb/only=<⟨*overlay specification*⟩>{⟨*options*⟩}** (style, no default, initially unset)

Sets the given `tcolorbox` ⟨*options*⟩ in dependency of a `beamer` ⟨*overlay specification*⟩. Note that this needs the `beamer` class. The ⟨*options*⟩ will only be used on the specified `beamer` frames.

```
\documentclass{beamer}
\usepackage[many]{tcolorbox}
\begin{document}

\begin{frame}
  \begin{tcolorbox}[title=My title,fonttitle=\bfseries,
      enhanced,colframe=red!50!black,colback=red!10,colbacktitle=red,
      sidebyside,righthand width=3cm,
      lowerbox=invisible,lower separated=false,
      drop lifted shadow,
      only=<1>{colbacktitle=yellow,coltitle=red!50!black,colframe=red},
      only=<3>{colback=yellow!50,watermark text={Attention!}},
      only=<3->{lowerbox=visible}  ]
    This is a test.
    \begin{itemize}[<+->]
      \item One
      \item Two
      \item \alert<3>{Three}
      \item Four
    \end{itemize}
  \tcblower
    \begin{equation*}
    \int\limits_{1}^{x} \frac{1}{t}~dt = \ln(x).
    \end{equation*}
  \end{tcolorbox}
\end{frame}

\end{document}
```

/tcb/code=⟨*code*⟩ (no default, initially unset)

The given ⟨*code*⟩ is executed immediately. This option is useful to place some arbitrary code into an option list.

```
\tcbset{colback=red!5!white,colframe=red!75!black,
  code={Useless at this spot but functional.},
  fonttitle=\bfseries}

\begin{tcolorbox}[code={\newcommand{\mycommand}{\textit{working}}},
  title=My \mycommand\ title]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

Useless at this spot but functional.

My *working* title

This is a **tcolorbox**.

N 2016-10-21 **/tcb/void** (no value, initially unset)

Annihilates the current `tcolorbox` as far as possible. Basically, this comments out the whole `tcolorbox` by using a key. If the option list of the current `tcolorbox` contains arbitrary code with global impact (like counter settings), these actions are not undone automatically. Nevertheless, the effects of /tcb/phantom → P. 98, /tcb/step → P. 98, /tcb/new/auto counter → P. 108, etc., are removed by /tcb/void.

```
A%
  \begin{tcolorbox}[
      title=This box is completely removed by the following key,
      void
    ]
  This is a \textbf{tcolorbox}.
  \end{tcolorbox}
B
```

AB

! This option key cannot be applied for every situation. For example, if several box environments with the same environment name are nested, for the outer environment /tcb/void cannot be used, since the end of the inner environment will be misinterpreted as end of the outer environment.

5 Initialization Option Keys

The *initialization* options are only applicable for the generation of new environments and commands based on `tcolorbox` and friends. Particularly, they can be used for

- `\newtcolorbox` → P. 15,
- `\newtcbox` → P. 16,
- `\newtcblisting` → P. 302,
- `\newtcbinputlisting` → P. 304,
- `\newtcbtheorem` → P. 339, and
- `\newtcboxfit` → P. 411.

! Typically, these options may generate counters and alike. It is **strongly** recommended that you use initialization options inside the preamble only. Otherwise, you may get trouble when using LaTeX's `\include` features.

5.1 Numbered Boxes

Counters assigned using the initialization options are administrated automatically. Especially, they are increased for each new box. Independent from the real counter name, the counter value can be referenced by `\thetcbcounter`, e. g. inside the title of the box. The real counter name is stored inside `\tcbcounter`.

`/tcb/new/auto counter` (no value, initially unset)

Creates a new counter automatically. With `/tcb/new/number format` → P. 110 and `/tcb/new/number within` → P. 110, the appearance and behavior of the counter can be changed. The counter value is referenced by `\thetcbcounter`.

Definition in the preamble:

```
\newtcolorbox[auto counter,number within=section]{pabox}[2][]{%
  colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
  title=Examp.~\thetcbcounter: #2,#1}
```

```
\begin{pabox}[label={myautocounter}]{Title with number}
This box is automatically numbered with \ref{myautocounter} on page
\pageref{myautocounter}. Inside the box, the \thetcbcounter\ can
also be referenced by |\thetcbcounter|.
The real counter name is \texttt{\tcbcounter}.
\end{pabox}
```

Examp. 5.1: Title with number

This box is automatically numbered with 5.1 on page 108. Inside the box, the 5.1 can also be referenced by `\thetcbcounter`. The real counter name is `tcb@cnt@pabox`.

`/tcb/new/use counter from`=⟨*tcolorbox*⟩ (no default, initially unset)

Here, a counter from another ⟨*tcolorbox*⟩ is reused. Note that the settings for `/tcb/new/number format` → P. 110 and `/tcb/new/number within` → P. 110 are inherited and cannot be changed. The counter value is referenced by `\thetcbcounter`.

```
\newtcolorbox[use counter from=pabox]{mybox}[2][]{%
colback=blue!5!white,colframe=blue!75!black,fonttitle=\bfseries,
title=Some Box \thetcbcounter: #2,#1}

\begin{mybox}[label={myusecounterfrom}]{Title with continued number}
This box is automatically numbered with \ref{myusecounterfrom} on page
\pageref{myusecounterfrom}. Inside the box, the \thetcbcounter\ can
also be referenced by |\thetcbcounter|.
The real counter name is \texttt{\tcbcounter}.
\end{mybox}
```

Some Box 5.2: Title with continued number

This box is automatically numbered with 5.2 on page 109. Inside the box, the 5.2 can also be referenced by `\thetcbcounter`. The real counter name is `tcb@cnt@pabox`.

`/tcb/new/use counter`=⟨*counter*⟩ (no default, initially unset)

Here, an ordinary existing LaTeX ⟨*counter*⟩ is used for numbering. With `/tcb/new/number format` → P. 110 and `/tcb/new/number within` → P. 110, the appearance and behavior of the counter can be changed. The counter value is referenced by `\thetcbcounter`.

```
% \newcounter{myexample}%  preamble
\newtcolorbox[use counter=myexample,number format=\Alph]{mybox}[2][]{%
colback=green!5!white,colframe=green!55!black,fonttitle=\bfseries,
title=Some Box \thetcbcounter: #2,#1}

\begin{mybox}[label={myusecounter}]{Title with \LaTeX\ number}
This box is automatically numbered with \ref{myusecounter} on page
\pageref{myusecounter}. Inside the box, the \thetcbcounter\ can
also be referenced by |\thetcbcounter|.
The real counter name is \texttt{\tcbcounter}.
\end{mybox}
```

Some Box A: Title with LaTeX number

This box is automatically numbered with A on page 109. Inside the box, the A can also be referenced by `\thetcbcounter`. The real counter name is `myexample`.

N 2014-09-19 `/tcb/new/use counter*`=⟨*counter*⟩ (no default, initially unset)

An existing LaTeX ⟨*counter*⟩ is used for numbering. In contrast to `/tcb/new/use counter`, the options `/tcb/new/number format` → P. 110 and `/tcb/new/number within` → P. 110 are ignored. Use this for counters which are already configured outside the `tcolorbox` package, e. g. the standard `figure` counter.

`/tcb/new/no counter` (no value, initially set)

The created boxes are not numbered. This is the default. The option may be used to overrule a previous option.

`/tcb/new/number within`=⟨*counter*⟩ (no default, initially unset)

The automatic counter is set to zero, if ⟨*counter*⟩ is increased. Additionally, during output, the value of ⟨*counter*⟩ is prepended to the value of the automatic counter.

To prepend the automatic counter with the chapter number and to reset it with every new chapter, use:

```
number within=chapter
```

See `/tcb/new/use counter` → P. 109 for a complete example.

`/tcb/new/number format`=⟨*format macro*⟩ (no default, initially `\arabic`)

Declares the format of the automatic counter. The ⟨*format macro*⟩ can be any valid LaTeX number formatting macro like `\arabic`, `\roman`, etc.

To display the counter value in large roman numbers, use:

```
number format=\Roman
```

See `/tcb/new/auto counter` → P. 108 for a complete example.

`/tcb/new/number freestyle`=⟨*code*⟩ (no default, initially unset)

Allows advanced control over the complete number format. This option overrules the format given by `/tcb/new/number within` and `/tcb/new/number format`. Nevertheless, you can combine it with `/tcb/new/number within` to get the desired reset property.

The ⟨*code*⟩ is some formatting code which should contain `\tcbcounter` to reference the automated counter. Since this ⟨*code*⟩ is expanded, you have to secure each macro with `\noexpand` with *exception* of `\tcbcounter`.

Definition in the preamble:

```
\newtcolorbox[auto counter,number within=section,
  number freestyle={(Q/\noexpand\thesection/\noexpand\Alph{\tcbcounter})},
  ]{phbox}[2][]{%
  colback=yellow!15!white,colframe=blue!75!black,fonttitle=\bfseries,
  title=Question~\thetcbcounter: #2,#1}
```

```
\begin{phbox}[label={myfreestyle}]{Title with freestyle number}
This box is automatically numbered with \ref{myfreestyle} on page
\pageref{myfreestyle}. Inside the box, the \thetcbcounter\ can
also be referenced by |\thetcbcounter|.
The real counter name is \texttt{\tcbcounter}.
\end{phbox}
```

Question (Q/5/A): Title with freestyle number

This box is automatically numbered with (Q/5/A) on page 110. Inside the box, the (Q/5/A) can also be referenced by `\thetcbcounter`. The real counter name is `tcb@cnt@phbox`.

The following options /tcb/new/crefname and /tcb/new/Crefname need to be set inside the preamble.

U 2014-12-01 **/tcb/new/crefname**={⟨*singular*⟩}{⟨*plural*⟩} (no default, initially unset)

This option key can be used only in conjunction with the `cleveref` package [5] which has to be loaded separately. It creates a cross-reference type for the new `tcolorbox`'es, where the lowercase ⟨*singular*⟩ and ⟨*plural*⟩ forms of the cross-reference are given. This type is the environment or macro name and /tcb/label type → P. 98 is set automatically. See /tcb/label type → P. 98 and [5] for more information.

U 2014-12-01 **/tcb/new/Crefname**={⟨*singular*⟩}{⟨*plural*⟩} (no default, initially unset)

This option key can be used only in conjunction with the `cleveref` package [5] which has to be loaded separately. It creates a cross-reference type for the new `tcolorbox`'es, where the uppercase ⟨*singular*⟩ and ⟨*plural*⟩ forms of the cross-reference are given. This type is the environment or macro name and /tcb/label type → P. 98 is set automatically. See /tcb/label type → P. 98 and [5] for more information.

Definition in the preamble:

```
% \usepackage{cleveref}
\newtcolorbox[auto counter,number within=section,
  crefname={bluebox}{blueboxes}]%
  {mybluebox}[2][]{colback=blue!5!white,colframe=blue!75!black,fonttitle=\bfseries,
     title=Bluebox \thetcbcounter: #2,#1}
```

```
% \usepackage{varioref}
% \usepackage{cleveref}
\begin{mybluebox}[label={myreference}]{My title}
This is an example.
\end{mybluebox}

\Cref{myreference}, \cref{myreference}.\\
\Cpageref{myreference}, \cpageref{myreference}.\\
\nameCref{myreference}, \namecref{myreference}.\\
\labelcref{myreference}, \labelcpageref{myreference}.\\
With \texttt{varioref}:\\
\Vref{myreference}, \vref{myreference}.\\
\Vref*{myreference}, \vref*{myreference}.
```

Bluebox 5.1: My title

This is an example.

Bluebox 5.1, bluebox 5.1.
Page 111, page 111.
Bluebox, bluebox.
5.1, 111.
With `varioref`:
Bluebox 5.1, bluebox 5.1.
Bluebox 5.1, bluebox 5.1.

N 2014-09-19 **/tcb/new/blend into=**⟨*name*⟩ (style, no default, initially unset)

Used to comfortably blend into an existing schema of naming and numbering for some selected cases. For example, a `tcolorbox` can be used to display and entitle an image pretending to be a standard `figure` environment. Here, `/tcb/title` → P. 18 is used instead of the standard `\caption` and `/tcb/list text` → P. 99 can be used instead of the optional parameter of the standard `\caption`.

Feasible values for ⟨*name*⟩ are:

- `figures`: blend into the standard `figure` environment.
- `tables`: blend into the standard `table` environment.
- `listings`: blend into the standard `lstlisting` environment of the package `listings` [6].

> **!** Note that `blend into=listings` can only be used in the document content or, preferably, inside a `\AtBeginDocument` clause! Using it without `\AtBeginDocument` inside the preamble does not work since the `listings` packages initializes its counter also inside `\AtBeginDocument`.

```
\begin{figure}[htb]
  \centering\includegraphics[height=4cm]{lichtspiel.jpg}
  \caption{A standard figure}
\end{figure}

\newtcolorbox[blend into=figures]{myfigure}[2][]{float=htb,capture=hbox,
  title={#2},every float=\centering,#1}

\begin{myfigure}{A tcolorbox figure}
  \includegraphics[height=4cm]{lichtspiel.jpg}
\end{myfigure}
```

Figure 1: A standard figure

Figure 2: A tcolorbox figure

N 2015-03-13 **/tcb/blend before title=**⟨*value*⟩ (no default, initially **colon**)

This option formats the title output of **/tcb/new/blend into** → P. 112. Note that this is a common **tcolorbox** option which should be set globally or in the normal option part of **\newtcolorbox** → P. 15.

Feasible values for ⟨*value*⟩ are:

- **colon**: use name/number plus colon.
- **dash**: use name/number plus dash.
- **colon hang**: use name/number plus colon with hanging indent.
- **dash hang**: use name/number plus dash with hanging indent.

```
\newtcolorbox[blend into=figures]{myfigure}[2][]{float=htb,capture=hbox,
  blend before title=dash hang,title={#2},every float=\centering,#1}

\begin{myfigure}{A tcolorbox figure with quite a long title}
  \includegraphics[height=5cm]{lichtspiel.jpg}
\end{myfigure}
```

Figure 3 – A tcolorbox figure with quite a long title

N 2015-03-13 **/tcb/blend before title code=**⟨*code*⟩ (no default)

This option formats the title output of /tcb/new/blend into → P. 112. The ⟨*code*⟩ takes one parameter, the name/number. Use this, if /tcb/blend before title → P. 113 is not flexible enough.

```
\newtcolorbox[blend into=figures]{myfigure}[2][]{float=htb,capture=hbox,
  blend before title code={\fbox{##1}\ },title={#2},every float=\centering,#1}

\begin{myfigure}{A tcolorbox figure}
  \includegraphics[height=6cm]{lichtspiel.jpg}
\end{myfigure}
```

Figure 4 A tcolorbox figure

5.2 Lists of tcolorboxes

For figures and tables, LaTeX provides the `\listoffigures` and `\listoftables` commands to create lists of these numbered entities. Also, a `tcolorbox` can be part of such a kind of list.

1. Assign a list ⟨*name*⟩ by the *initialization* option `/tcb/new/list inside`.
2. Optionally, a new ⟨*type*⟩ for list entries may be assigned by the *initialization* option `/tcb/new/list type`.
3. List entries a generated automatically within each new `tcolorbox` using the above initialization.
   - If `/tcb/list entry` → P. 99 is set, the entry is generated with it.
   - Otherwise, if `/tcb/title` → P. 18 is set, the entry is generated with it.
   - Otherwise, the entry is generated with the current number and the environment name.
4. The generated list is displayed by `\tcblistof`.

`/tcb/new/list inside`=⟨*name*⟩ (no default, initially unset)

Assigns a list or contents file to the generated `tcolorbox`es. Entries to this list are saved to a file which gets the ⟨*name*⟩ as file name extension. The list is referenced by this name in `\tcblistof`. For example:

```
list inside=exam
```

See Section 15.9 from page 333 for a complete example.

`/tcb/new/list type`=⟨*type*⟩ (no default, initially `tcolorbox`)

Optionally, some ⟨*type*⟩ can be assigned to the list entries. For a new ⟨*type*⟩, a macro `\l@`⟨*type*⟩ has to exist which controls the format of the list entry. The default type is defined by

```
\newcommand*\l@tcolorbox{\@dottedtocline{1}{1.5em}{2.3em}}
```

This is identical to the `\l@section` setting of LaTeX. `\l@tcolorbox` can be redefined or a new ⟨*type*⟩ can be assigned.

`\tcblistof`[⟨*macro*⟩]{⟨*name*⟩}{⟨*title text*⟩}

Displays the generated list of `tcolorbox`es with the given ⟨*name*⟩. The heading is generated by ⟨*macro*⟩{⟨*title text*⟩} where `\section` is the default setting for ⟨*macro*⟩.
To display the list inside a subsection, use for example:

```
\tcblistof[\subsection]{exam}{List of Exercises}
```

The result of the example is found as Subsection 15.10 on page 336.

> **!** The core of the list is generated by `\@starttoc{`⟨*name*⟩`}` which can be wrapped into an own macro.

6 Side by Side

A *side by side* box is a special `tcolorbox` → P. 12 where the upper and lower part of the box are set side by side. All boxes of this kind are unbreakable.

> **!** Further side by side options for code examples are `/tcb/listing side text` → P. 315, `/tcb/text side listing` → P. 315, `/tcb/listing outside text` → P. 315, and `/tcb/text outside listing` → P. 315.

6.1 Basic Settings

`/tcb/sidebyside=true|false` (default `true`, initially `false`)

Normally, the upper part and the lower part of the box have their positions as their names suggest. If `sidebyside` is set to `true`, the upper part is drawn *left-handed* and the lower part is drawn *right-handed*. Both parts are drawn together with the geometry settings of the upper part but the space is divided horizontally according to the following options. Colors, fonts, and box content additions are used individually. The resulting box is unbreakable.

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[title=My title,sidebyside]
  This is the upper (\textit{left-handed}) part.
\tcblower
  This is the lower (\textit{right-handed}) part.
\end{tcolorbox}
```

My title

This is the upper (*left-handed*) part.

This is the lower (*right-handed*) part.

```
% \usepackage{lipsum}
% \tcbuselibrary{skins}
\begin{tcolorbox}[bicolor,sidebyside,righthand width=3cm,
    sharp corners,boxrule=.4pt,colback=green!5,colbacklower=green!50!black!50]
  \lipsum[2]
\tcblower
  \includegraphics[width=\linewidth]{goldshade}%
\end{tcolorbox}
```

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

U 2015-02-06 **/tcb/sidebyside align=**⟨*alignment*⟩ (no default, initially **center**)

Sets the vertical ⟨*alignment*⟩ for the left-handed and right-handed part.

Feasible values for ⟨*alignment*⟩ are:

- **center**: identical to **minipage** option **c**.
- **top**: identical to **minipage** option **t** (aligns the top lines of the left-handed and right-handed side according to their baselines).
- **bottom**: identical to **minipage** option **b** (aligns the bottom lines of the left-handed and right-handed side according to their baselines).
- **center seam**: aligns the center of the left-handed and right-handed side.
- **top seam**: aligns the very top seam of the left-handed and right-handed side.
- **bottom seam**: aligns the very bottom seam of the left-handed and right-handed side.

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,nobeforeafter,
  left=2mm,right=2mm,sidebyside,sidebyside gap=6mm,width=(\linewidth-2mm)/3}

\begin{tcolorbox}[adjusted title=center,sidebyside align=center]
This is a text which is too long for one line.
\tcblower
This is a short text.
\end{tcolorbox}\hfill
\begin{tcolorbox}[adjusted title=top,sidebyside align=top]
This is a text which is too long for one line.
\tcblower
This is a short text.
\end{tcolorbox}\hfill
\begin{tcolorbox}[adjusted title=bottom,sidebyside align=bottom]
This is a text which is too long for one line.
\tcblower
This is a short text.
\end{tcolorbox}
```



center, **top**, and **bottom** are identical to the known corresponding **minipage** options. While this is the preferred approach for text content, the result for boxed content like tables or images may not be as expected.

For such content, one may use **center seam**, **top seam**, and **bottom seam**. For example, **top seam** aligns the very top seam of the left-handed and right-handed side.

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
  size=small,righthand width=4cm,sidebyside,sidebyside gap=6mm,lower separated=false}

\begin{tcolorbox}[adjusted title=center seam,sidebyside align=center seam]
  This is my description text for the pictures displayed on the right-handed side.
  \tcblower
  \includegraphics[width=\linewidth/2]{goldshade}%
  \includegraphics[width=\linewidth/2]{blueshade}
\end{tcolorbox}

\begin{tcolorbox}[adjusted title=top seam,sidebyside align=top seam]
  This is my description text for the pictures displayed on the right-handed side.
  \tcblower
  \includegraphics[width=\linewidth/2]{goldshade}%
  \includegraphics[width=\linewidth/2]{blueshade}
\end{tcolorbox}

\begin{tcolorbox}[adjusted title=bottom seam,sidebyside align=bottom seam]
  This is my description text for the pictures displayed on the right-handed side.
  \tcblower
  \includegraphics[width=\linewidth/2]{goldshade}%
  \includegraphics[width=\linewidth/2]{blueshade}
\end{tcolorbox}
```

center seam

This is my description text for the pictures displayed on the right-handed side.



top seam

This is my description text for the pictures displayed on the right-handed side.



bottom seam

This is my description text for the pictures displayed on the right-handed side.



/tcb/sidebyside gap=⟨*length*⟩ (no default, initially 10mm)

Sets the horizontal distance between the left-handed and right-handed part to ⟨*length*⟩.

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,nobeforeafter,
  sidebyside,width=(\linewidth-2mm)/2}

\begin{tcolorbox}[adjusted title=Wide gap,sidebyside gap=30mm]
This is a text which is too long for one line.
\tcblower
This is a short text.
\end{tcolorbox}\hfill
\begin{tcolorbox}[adjusted title=Narrow gap,sidebyside gap=1mm]
This is a text which is too long for one line.
\tcblower
This is a short text.
\end{tcolorbox}
```

Wide gap

This is a text which is too long for one line.

This is a short text.

Narrow gap

This is a text which is too long for one line.

This is a short text.

/tcb/lefthand width=⟨*length*⟩ (no default, initially unset)

Sets the width of the left-handed part to the given ⟨*length*⟩.

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[title=My title,sidebyside,lefthand width=3cm]
This is the upper (\textit{left-handed}) part.
\tcblower
This is the lower (\textit{right-handed}) part.
\end{tcolorbox}
```

My title

This is the upper (*left-handed*) part.

This is the lower (*right-handed*) part.

/tcb/righthand width=⟨*length*⟩ (no default, initially unset)

Sets the width of the right-handed part to the given ⟨*length*⟩.

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[title=My title,sidebyside,righthand width=3cm]
This is the upper (\textit{left-handed}) part.
\tcblower
This is the lower (\textit{right-handed}) part.
\end{tcolorbox}
```

My title

This is the upper (*left-handed*) part.

This is the lower (*right-handed*) part.

/tcb/lefthand ratio=⟨*fraction*⟩ (no default, initially 0.5)

Sets the width of the left-handed part to the given ⟨*fraction*⟩ of the available space. ⟨*fraction*⟩ is a value between 0 and 1.

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[title=My title,sidebyside,lefthand ratio=0.25]
This is the upper (\textit{left-handed}) part.
\tcblower
This is the lower (\textit{right-handed}) part.
\end{tcolorbox}
```

My title

This is the upper (*left-handed*) part.

This is the lower (*right-handed*) part.

/tcb/righthand ratio=⟨*fraction*⟩ (no default, initially 0.5)

Sets the width of the right-handed part to the given ⟨*fraction*⟩ of the available space. ⟨*fraction*⟩ is a value between 0 and 1.

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[title=My title,sidebyside,righthand ratio=0.25]
This is the upper (\textit{left-handed}) part.
\tcblower
This is the lower (\textit{right-handed}) part.
\end{tcolorbox}
```

My title

This is the upper (*left-handed*) part.

This is the lower (*right-handed*) part.

If one side of a side-by-side box should be adapted to the width of its content, this width has to be computed beforehand. The following example uses a savebox `\mysavebox` to store the picture to determine its width. A more convenient way to handle this task is to use the methods from Section 6.2 on page 122.

```
% \tcbuselibrary{skins,xparse}
% \usepackage{lipsum}
% \newsavebox\mysavebox  % preamble
\DeclareTotalTColorBox{\mysidebox}{ O{} +m +m }{
  bicolor,colback=white,colbacklower=yellow!10,
  fonttitle=\bfseries,center title,
  sidebyside,
  code={\sbox{\mysavebox}{#2}},
  lefthand width=\wd\mysavebox,
  drop lifted shadow,
  #1
}
{\usebox{\mysavebox}\tcblower#3}

\mysidebox[title=The Triangle]{%
  \begin{tikzpicture}
    \path[fill=red!20,draw=red!50!black]
      (0,0) node[below]{A} -- (3,1) node[right]{B}
      -- (1,4) node[above]{C} -- cycle;
  \end{tikzpicture}%
}{%
  \lipsum[1]
}
```

The Triangle



Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

6.2 Advanced Settings from the LIB xparse Library

> ! All following macros and options need the LIB xparse library to be loaded, see Section 22 on page 433.

N 2015-11-20 `\tcbsidebyside[⟨options⟩]{⟨left-handed content⟩}{⟨right-handed content⟩}`

Creates a colored box using more or less arbitrary ⟨*options*⟩ for a `tcolorbox` → P. 12. The `/tcb/sidebyside` → P. 116 option is set to `true` and the ⟨*left-handed content*⟩ and ⟨*right-handed content*⟩ is filled into the box appropriately. The resulting box is unbreakable. `\tcbsidebyside` is not only a shortcut for using a normal `tcolorbox` → P. 12 with `/tcb/sidebyside` → P. 116, but allows setting further options like `/tcb/sidebyside adapt` → P. 123 and `/tcb/sidebyside switch` → P. 125.

```
% \tcbuselibrary{skins,xparse}
% \usepackage{lipsum}
\tcbsidebyside[title=The Triangle,
  sidebyside adapt=left,
  bicolor,colback=white,colbacklower=yellow!10,
  fonttitle=\bfseries,center title,drop lifted shadow,
]{%
  \begin{tikzpicture}
    \path[fill=red!20,draw=red!50!black]
      (0,0) node[below]{A} -- (3,1) node[right]{B}
      -- (1,4) node[above]{C} -- cycle;
  \end{tikzpicture}%
}{%
  \lipsum[1]
}
```

The Triangle



Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

N 2015-11-20 **/tcb/sidebyside adapt=**⟨*side(s)*⟩ (no default, initially **none**)

The option allows the left-handed and/or right-handed side to determine the dimensions of the box. This option is only valid inside \tcbsidebyside → P. 122.

Feasible values for ⟨*side(s)*⟩ are:

- **none**: no measurement of left-handed and right-handed side.
- **left**: the actual width of the left-handed content is used to set /tcb/lefthand width → P. 119.
- **right**: the actual width of the right-handed content is used to set /tcb/righthand width → P. 119.
- **both**: the actual width of the left-handed and right-handed content is used to set /tcb/lefthand width → P. 119, /tcb/righthand width → P. 119, and the overall /tcb/width → P. 34.

```
% \tcbuselibrary{skins,xparse}
\tcbsidebyside[sidebyside adapt=left,
  title=Very important table,
  beamer,colframe=blue!50!black,colback=blue!10,
  lower separated=false,sidebyside gap=5mm
]{%
  \begin{tabular}{|l|c|r|}\hline
    left & center & right\\\hline
    A & B & C\\\hline
    D & E & F\\\hline
  \end{tabular}
}{%
  This table contains the most important figures for
  all future actions. You may notice that B follows A,
  C follows B, and so on.
}
```

Very important table

left	center	right
A	B	C
D	E	F

This table contains the most important figures for all future actions. You may notice that B follows A, C follows B, and so on.

```
% \tcbuselibrary{skins,xparse}
\tcbsidebyside[sidebyside adapt=right,
  blanker,sidebyside gap=5mm
]{%
  \lipsum[2]
}{%
\begin{tikzpicture}
  \path[fill=yellow,draw=yellow!75!red] (0,0) circle (1cm);
  \fill[red] (45:5mm) circle (1mm);
  \fill[red] (135:5mm) circle (1mm);
  \draw[line width=1mm,red] (215:5mm) arc (215:325:5mm);
\end{tikzpicture}
}
```

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

```
% \tcbuselibrary{skins,xparse}
\tcbsidebyside[sidebyside adapt=both,
  enhanced,center,
  title=Both sides adapted,
  attach boxed title to top center={yshift=-2mm},
  coltitle=black,boxed title style={colback=red!25},
  segmentation style=solid,colback=red!5,colframe=red!50
]{%
  \begin{tabular}{|l|c|r|}\hline
    left & center & right\\\hline
    A & B & C\\\hline
    D & E & F\\\hline
  \end{tabular}
}{%
\begin{tikzpicture}
  \path[fill=yellow,draw=yellow!75!red] (0,0) circle (1cm);
  \fill[red] (45:5mm) circle (1mm);
  \fill[red] (135:5mm) circle (1mm);
  \draw[line width=1mm,red] (215:5mm) arc (215:325:5mm);
\end{tikzpicture}
}
```

Both sides adapted

left	center	right
A	B	C
D	E	F

N 2015-11-20 **/tcb/sidebyside switch=true|false** (default `true`, initially `false`)

If set to `true`, the ⟨*left-handed content*⟩ and ⟨*right-handed content*⟩ of `\tcbsidebyside` → P. 122 are switched. Obviously, this option is only valid inside `\tcbsidebyside` → P. 122.

The side switching can be made even/odd page sensitive, if used inside `/tcb/if odd page` → P. 101.

```
% \tcbuselibrary{skins,xparse}
\tcbsidebyside{Left}{Right}

\tcbsidebyside[sidebyside switch]{Left}{Right}

\tcbsidebyside[title=Very important table,
  if odd page={sidebyside switch,sidebyside adapt=right,flushright title}%
              {sidebyside adapt=left},
  beamer,colframe=blue!50!black,colback=blue!10,
  lower separated=false,sidebyside gap=5mm
]{%
  \begin{tabular}{|l|c|r|}\hline
    left & center & right\\\hline
    A & B & C\\\hline
    D & E & F\\\hline
  \end{tabular}
}{%
  This table contains the most important figures for
  all future actions. You may notice that B follows A,
  C follows B, and so on.
}
```

Left | Right

Right | Left

Very important table

This table contains the most important figures for all future actions. You may notice that B follows A, C follows B, and so on.

left	center	right
A	B	C
D	E	F

7 Saving and Loading of Verbatim Texts

The following macros are slightly modified versions of the original macros from the known packages **moreverb** and **verbatim**. They are used implicitly inside of a **tcolorbox** environment, but they can be used outside also.

\begin{tcbverbatimwrite}{⟨*file name*⟩}
⟨*environment content*⟩
\end{tcbverbatimwrite}

Saves the ⟨*environment content*⟩ to a file named by ⟨*file name*⟩. TEX macros inside the environment are not expanded.

```
\begin{tcbverbatimwrite}{\jobname_verbexp.tex}
  This text is saved \textit{as is}.
\end{tcbverbatimwrite}

Now, we are using the file:\par
\input{\jobname_verbexp.tex}
```

Now, we are using the file:
This text is saved *as is*.

This environment may be used inside an own environment. Note, that inside the environment definition **\tcbverbatimwrite** has to be used instead of **\begin{tcbverbatimwrite}** and **\endtcbverbatimwrite** instead of **\end{tcbverbatimwrite}**.

```
\newenvironment{myverbatim}{%
  \begingroup\tcbverbatimwrite{\jobname_myverb.tex}}%
  {\endtcbverbatimwrite\endgroup}

\begin{myverbatim}
  This is the text which is saved by my own environment.
\end{myverbatim}

Now, we are using the file:\par
\input{\jobname_myverb.tex}
```

Now, we are using the file:
This is the text which is saved by my own environment.

\begin{tcbwritetemp}
⟨*environment content*⟩
\end{tcbwritetemp}

Has the same function as tcbverbatimwrite, but uses the key value of **tempfile** for the file name.

```
\begin{tcbwritetemp}
  This text is saved \textit{as is}.
\end{tcbwritetemp}

Now, we are using the file:\par
\tcbusetemp
```

Now, we are using the file:
This text is saved *as is*.

\tcbusetemp

Loads the current temporary file which was saved by tcbwritetemp.

N 2017-07-05 **/tcb/verbatim ignore percent=true|false** (default `true`, initially `false`)

If this option is set to be `true`, the percent sign % is silently ignored for `tcbverbatimwrite` → P. 126 and all macros and environments which are built using `tcbverbatimwrite` → P. 126, e.g. `tcbwritetemp` → P. 126, `tcblisting` → P. 299, or `dispExample` → P. 463.

This option may be useful for creating some special effects, but mainly it is intended to be applied for documentation with DocStrip. The creation of this option was motivated by Yudai Nakata. Note that this option is not getting reset by `/tcb/reset` → P. 105.

```
Normal usage:
\begin{tcbwritetemp}
%\begin{center}\bfseries
This is my text.
%\end{center}
\end{tcbwritetemp}

\tcbusetemp

\tcbset{verbatim ignore percent}
\bigskip Option applied:
\begin{tcbwritetemp}
%\begin{center}\bfseries
This is my text.
%\end{center}
\end{tcbwritetemp}

\tcbusetemp
```

Normal usage:
This is my text.

Option applied:
This is my text.

! Note that *every* percent sign is removed, also escaped ones.

```
% \tcbuselibrary{listings}
\def\percent{\%}

\begin{tcblisting}{title=Normal}
%\begin{center}\bfseries
This is my 5\percent\ text
and this is my 10\% text.
%\end{center}
\end{tcblisting}

\begin{tcblisting}{
  title=Option applied,
  verbatim ignore percent}
%\begin{center}\bfseries
This is my 5\percent\ text
and this is my 10\% text.
%\end{center}
\end{tcblisting}
```

Normal

```
%\begin{center}\bfseries
This is my 5\percent\ text
and this is my 10\% text.
%\end{center}
```

This is my 5% text and this is my 10% text.

Option applied

```
\begin{center}\bfseries
This is my 5\percent\ text
and this is my 10\ text.
\end{center}
```

This is my 5% text and this is my 10 text.

8 Recording

The package provides some macros and options to take *records* during compilation. This is done by LaTeX file operations to save some data to a file for later usage. The main application scenario is depicted in Section 8.3 on the next page where information about example solutions is recorded and read again in Section 8.4 on page 132.

8.1 Macros

N 2014-11-28 `\tcbstartrecording[`⟨*file name*⟩`]`

Opens a file denoted by ⟨*file name*⟩ for writing the records. The default file name is `\jobname.records`. See Section 8.3 on the next page for an example application.

N 2014-11-28 `\tcbrecord{`⟨*content*⟩`}`

Records any ⟨*content*⟩ to the record file. `\tcbrecord` is implemented as `\immediate\write`. `\tcbstartrecording` has to be called before; otherwise, `\tcbrecord` is silently ignored.

```
\tcbrecord{\string\solution{\thetcbcounter}{solutions/exercise-\thetcbcounter.tex}}
```

N 2014-11-28 `\tcbstoprecording`

Closes the current record file which was opened by `\tcbstartrecording` before.

N 2014-11-28 `\tcbinputrecords[`⟨*file name*⟩`]`

Opens a file denoted by ⟨*file name*⟩ for reading the records via `\input`. The default file name is the name of the last used record file for saving. `\tcbstoprecording` has to be called before.

8.2 Options

N 2014-11-28 `/tcb/record=`⟨*content*⟩ (style, no default)

Records any ⟨*content*⟩ to the record file, see `\tcbrecord`. This key can be used several times to write several lines.

```
record={\string\solution{\thetcbcounter}{solutions/exercise-\thetcbcounter.tex}}
```

N 2014-11-28 `/tcb/no recording`

Disables `\tcbrecord` and `/tcb/record` inside the current group.

8.3 Example: Exercises

The following application example creates exercises and their corresponding solutions. Each pair is generated inside a single `tcolorbox` where the solution is given below `\tcblower` → P. 12. For every example, the solution part is saved by `/tcb/savelowerto` → P. 24 to a file. The saving is recorded using `/tcb/record` → P. 128. To enlighten the possibilities, the second exercise has no solution. Finally, the solutions are input in Section 8.4 on page 132.

Definition in the preamble:

```
% \tcbuselibrary{skins,xparse}

\NewTColorBox[auto counter,number within=section]{exercise}{+O{}}{%
  enhanced,colframe=green!20!black,colback=yellow!10!white,coltitle=green!40!black,
  fonttitle=\bfseries,
  underlay={\begin{tcbclipinterior}
    \shade[inner color=green!80!yellow,outer color=yellow!10!white]
      (interior.north west) circle (2cm);
    \draw[help lines,step=5mm,yellow!80!black,shift={(interior.north west)}]
      (interior.south west) grid (interior.north east);
    \end{tcbclipinterior}},
  title={Exercise~\thetcbcounter:},
  label={exercise@\thetcbcounter},
  attach title to upper=\quad,
  after upper={\par\hfill\textcolor{green!40!black}%
    {\itshape Solution on page~\pageref{solution@\thetcbcounter}}},
  lowerbox=ignored,
  savelowerto=solutions/exercise-\thetcbcounter.tex,
  record={\string\solution{\thetcbcounter}{solutions/exercise-\thetcbcounter.tex}},
  #1
}

\NewTotalTColorBox{\solution}{mm}{%
  enhanced,colframe=red!20!black,colback=yellow!10!white,coltitle=red!40!black,
  fonttitle=\bfseries,
  underlay={\begin{tcbclipinterior}
    \shade[inner color=red!50!yellow,outer color=yellow!10!white]
      (interior.north west) circle (2cm);
    \draw[help lines,step=5mm,yellow!80!black,shift={(interior.north west)}]
      (interior.south west) grid (interior.north east);
    \end{tcbclipinterior}},
  title={Solution of Exercise~\ref{exercise@#1} on page~\pageref{exercise@#1}:},
  phantomlabel={solution@#1},
  attach title to upper=\par,
}{\input{#2}}

\tcbset{no solution/.style={no recording,after upper=}}
```

```
\tcbstartrecording

\begin{exercise}
  Compute the derivative of the following function:
  \begin{equation*}
    f(x)=\sin((\sin x)^2)
  \end{equation*}
\tcblower
  The derivative is:
  \begin{align*}
    f'(x) &= \left( \sin((\sin x)^2) \right)'
    =\cos((\sin x)^2) 2\sin x \cos x.
  \end{align*}
```

```
\end{exercise}

\begin{exercise}[no solution]
  It holds:
  \begin{equation*}
    \frac{d}{dx}\left(\ln|x|\right) = \frac{1}{x}.
  \end{equation*}
\end{exercise}

\begin{exercise}
  Compute the derivative of the following function:
  \begin{equation*}
    f(x)=(\sin(\sin x))^2
  \end{equation*}
\tcblower
  The derivative is:
  \begin{align*}
    f'(x) &= \left( (\sin(\sin x))^2 \right)'
    =2\sin(\sin x)\cos(\sin x)\cos x.
  \end{align*}
\end{exercise}

\begin{exercise}
  Compute the derivative of the following function:
  \begin{equation*}
    f(x)=\sqrt{x^3-6x^2+2x}
  \end{equation*}
\tcblower
  The derivative is:
  \begin{align*}
    f'(x) &= \left( \sqrt{x^3-6x^2+2x} \right)'
    = \frac{3x^2-12x+2}{2\sqrt{x^3-6x^2+2x}}.
  \end{align*}
\end{exercise}

\begin{exercise}
  Compute the derivative of the following function:
  \begin{equation*}
    f(x)=\left(\frac{2+3x}{1-2x}\right)^3
  \end{equation*}
\tcblower
  The derivative is:
  \begin{align*}
    f'(x) &= \left( \left(\frac{2+3x}{1-2x}\right)^3 \right)'
    = 3 \left(\frac{2+3x}{1-2x}\right)^2 \frac{(1-2x)3-(2+3x)(-2)}{(1-2x)^2}
    = \frac{21(2+3x)^2}{(1-2x)^4}.
  \end{align*}
\end{exercise}

\begin{exercise}
  Compute the derivative of the following function:
  \begin{equation*}
    f(x)=\frac{\cos x}{(\tan 2x)^2}
  \end{equation*}
\tcblower
  The derivative is:
  \begin{align*}
    f'(x) &= \left( \frac{\cos x}{(\tan 2x)^2} \right)'
    = \left( \frac{\cos x (\cos 2x)^2}{(\sin 2x)^2} \right)'\\
    &= \frac{(\sin 2x)^2 [(-\sin x)(\cos 2x)^2+(\cos x)4\cos 2x (-\sin 2x)]
       - \cos x (\cos 2x)^2 4\sin 2x \cos 2x}{(\sin 2x)^4}\\
    &= -\frac{\cos(2x) [\sin x \sin 2x \cos 2x+ 4\cos x(\sin 2x)^2
       + 4 \cos x (\cos 2x)^2]}{(\sin 2x)^3}\\
```

```
    &= -\frac{\cos(2x) [\sin x \sin 2x \cos 2x+ 4\cos x]}{(\sin 2x)^3}.
  \end{align*}
\end{exercise}

\begin{exercise}
  Compute the derivative of the following function:
  \begin{equation*}
    f(x)=\cos((2x^2+3)^3)
  \end{equation*}
\tcblower
  The derivative is:
  \begin{align*}
    f'(x) &= \left( \cos((2x^2+3)^3) \right)'
    =-\sin((2x^2+3)^3) 3(2x^2+3)^2 2\cdot 2x\\
    &=-12x(2x^2+3)^2\sin((2x^2+3)^3).
  \end{align*}
\end{exercise}

\begin{exercise}
  Compute the derivative of the following function:
  \begin{equation*}
    f(x)=(x^2+1)\sqrt{x^4+1}
  \end{equation*}
\tcblower
  The derivative is:
  \begin{align*}
    f'(x) &= \left( (x^2+1)\sqrt{x^4+1} \right)'
    = 2x\sqrt{x^4+1} + \frac{2x^3(x^2+1)}{\sqrt{x^4+1}}.
  \end{align*}
\end{exercise}

\tcbstoprecording
```

Exercise 8.1: Compute the derivative of the following function:

$$f(x) = \sin((\sin x)^2)$$

Solution on page 132

Exercise 8.2: It holds:

$$\frac{d}{dx}(\ln \mathtt{x}) = \frac{1}{x}.$$

Exercise 8.3: Compute the derivative of the following function:

$$f(x) = (\sin(\sin x))^2$$

Solution on page 132

Exercise 8.4: Compute the derivative of the following function:

$$f(x) = \sqrt{x^3 - 6x^2 + 2x}$$

Solution on page 132

Exercise 8.5: Compute the derivative of the following function:

$$f(x) = \left(\frac{2+3x}{1-2x}\right)^3$$

Solution on page 133

Exercise 8.6: Compute the derivative of the following function:

$$f(x) = \frac{\cos x}{(\tan 2x)^2}$$

Solution on page 133

Exercise 8.7: Compute the derivative of the following function:

$$f(x) = \cos((2x^2+3)^3)$$

Solution on page 133

Exercise 8.8: Compute the derivative of the following function:

$$f(x) = (x^2+1)\sqrt{x^4+1}$$

Solution on page 133

8.4 Example: Solutions

This concludes the example given in Section 8.3 on page 129. Now, the saved and recorded solutions are included.

```
\tcbinputrecords
```

Solution of Exercise 8.1 on page 131:
The derivative is:

$$f'(x) = \Big(\sin((\sin x)^2)\Big)' = \cos((\sin x)^2)2\sin x\cos x.$$

Solution of Exercise 8.3 on page 131:
The derivative is:

$$f'(x) = \Big((\sin(\sin x))^2\Big)' = 2\sin(\sin x)\cos(\sin x)\cos x.$$

Solution of Exercise 8.4 on page 131:
The derivative is:

$$f'(x) = \Big(\sqrt{x^3-6x^2+2x}\Big)' = \frac{3x^2-12x+2}{2\sqrt{x^3-6x^2+2x}}.$$

Solution of Exercise 8.5 on page 132:
The derivative is:

$$f'(x) = \left(\left(\frac{2+3x}{1-2x}\right)^3\right)' = 3\left(\frac{2+3x}{1-2x}\right)^2 \frac{(1-2x)3-(2+3x)(-2)}{(1-2x)^2} = \frac{21(2+3x)^2}{(1-2x)^4}.$$

Solution of Exercise 8.6 on page 132:
The derivative is:

$$\begin{aligned} f'(x) &= \left(\frac{\cos x}{(\tan 2x)^2}\right)' = \left(\frac{\cos x(\cos 2x)^2}{(\sin 2x)^2}\right)' \\ &= \frac{(\sin 2x)^2[(-\sin x)(\cos 2x)^2 + (\cos x)4\cos 2x(-\sin 2x)] - \cos x(\cos 2x)^2 4\sin 2x\cos 2x}{(\sin 2x)^4} \\ &= -\frac{\cos(2x)[\sin x \sin 2x \cos 2x + 4\cos x(\sin 2x)^2 + 4\cos x(\cos 2x)^2]}{(\sin 2x)^3} \\ &= -\frac{\cos(2x)[\sin x \sin 2x \cos 2x + 4\cos x]}{(\sin 2x)^3}. \end{aligned}$$

Solution of Exercise 8.7 on page 132:
The derivative is:

$$\begin{aligned} f'(x) &= \left(\cos((2x^2+3)^3)\right)' = -\sin((2x^2+3)^3)3(2x^2+3)^2 2\cdot 2x \\ &= -12x(2x^2+3)^2\sin((2x^2+3)^3). \end{aligned}$$

Solution of Exercise 8.8 on page 132:
The derivative is:

$$f'(x) = \left((x^2+1)\sqrt{x^4+1}\right)' = 2x\sqrt{x^4+1} + \frac{2x^3(x^2+1)}{\sqrt{x^4+1}}.$$

9 Technical Overview and Customization

This section provides a technical overview of the skin concept of `tcolorbox`. For most applications of `tcolorbox`, one will not need to know the bells and whistles described herein. You may proceed to Section 10 on page 148 where the customization options for most users are documented.

The following explanations also cover options and settings from the LIB skins library, see Section 10 on page 148.

9.1 Skins and Drawing Engines

From a technical point of view, a *skin* is a style definition for the appearance of a `tcolorbox`. The core package provides some additional option keys for skins but only two skins called `standard` → P. 204 and `standard jigsaw` → P. 205. The LIB skins library adds several more skins. To change to a skin, only one option from the core package has to be set.

`/tcb/skin`=⟨*name*⟩ (style, no default, initially `standard`)

Sets the current skin to ⟨*name*⟩. This is a style definition which sets all the following keys, i. e. for many use cases there is nothing more to do.

```
\tcbset{colback=Salmon!50!white,colframe=FireBrick!75!black,
  width=(\linewidth-8mm)/2,before=,after=\hfill,equal height group=ske}

\begin{tcolorbox}[adjusted title=My title]
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}[skin=beamer,beamer,adjusted title=My title]
  This is my content.
\end{tcolorbox}
```



`/tcb/skin first`=⟨*name*⟩ (style, no default, initially `standard`)

If the box is set to be `/tcb/breakable` → P. 365 and *is* broken actually, then the skin for the *first* part of the break sequence is set to ⟨*name*⟩, see Subsection 17.8 on page 377. Typically, this key is set by a `/tcb/skin`.

`/tcb/skin middle`=⟨*name*⟩ (style, no default, initially `standard`)

If the box is set to be `/tcb/breakable` → P. 365 and *is* broken actually, then the skin for the *middle* parts (if any) of the break sequence is set to ⟨*name*⟩, see Subsection 17.8 on page 377. Typically, this key is set by a `/tcb/skin`.

`/tcb/skin last`=⟨*name*⟩ (style, no default, initially `standard`)

If the box is set to be `/tcb/breakable` → P. 365 and *is* broken actually, then the skin for the *last* part of the break sequence is set to ⟨*name*⟩, see Subsection 17.8 on page 377. Typically, this key is set by a `/tcb/skin`.

`/tcb/graphical environment`=⟨*name*⟩ (no default, initially `pgfpicture`)

Sets the graphical environment for the `tcolorbox` to ⟨*name*⟩. Feasible values are `pgfpicture` and `tikzpicture` or environments which inherit from one of these two. This key is set by a `/tcb/skin` → P. 134 and may seldom be used directly.

The skin of a `tcolorbox` is drawn by up to four *engines*. Afterwards, the text content is drawn which is not part of a skin. The four steps are:

1. The *frame* of the box, drawn by `/tcb/frame engine`.
2. The *interior* of the box. The interior of a box with title is drawn differently from a box without title. `/tcb/interior titled engine` or `/tcb/interior engine` → P. 136 is used to draw the interior.
3. The *segmentation* (line) of the box, if there is a lower part; drawn by `/tcb/segmentation engine` → P. 136.
4. The *title area* of the box, if there is a title and `/tcb/title filled` → P. 27 is set to `true`; drawn by `/tcb/title engine` → P. 136.

`/tcb/frame engine`=⟨*name*⟩ (no default, initially `standard`)

Sets the *frame* drawing engine for a box to ⟨*name*⟩. Typically, this key is set by a `/tcb/skin` → P. 134. Feasible values for ⟨*name*⟩ are:

- `standard`: the original code from the core package,
- `path`: a `tikz` path which is controlled by `/tcb/frame style` → P. 148,
- `pathjigsaw`: a `tikz` path which is controlled by `/tcb/frame style` → P. 148,
- `pathfirst`: a `tikz` path which is controlled by `/tcb/frame style` → P. 148,
- `pathfirstjigsaw`: a `tikz` path which is controlled by `/tcb/frame style` → P. 148,
- `pathmiddle`: a `tikz` path which is controlled by `/tcb/frame style` → P. 148,
- `pathmiddlejigsaw`: a `tikz` path which is controlled by `/tcb/frame style` → P. 148,
- `pathlast`: a `tikz` path which is controlled by `/tcb/frame style` → P. 148,
- `pathlastjigsaw`: a `tikz` path which is controlled by `/tcb/frame style` → P. 148,
- `freelance`: deprecated.
- `spartan`: a quite spartan code.
- `empty`: draw nothing.

`/tcb/interior titled engine`=⟨*name*⟩ (no default, initially `standard`)

Sets the *interior* drawing engine for a titled box to ⟨*name*⟩. Typically, this key is set by a `/tcb/skin` → P. 134. Feasible values for ⟨*name*⟩ are:

- `standard`: the original code from the core package,
- `path`: a `tikz` path which is controlled by `/tcb/interior style` → P. 149,
- `pathfirst`: a `tikz` path which is controlled by `/tcb/interior style` → P. 149,
- `pathmiddle`: a `tikz` path which is controlled by `/tcb/interior style` → P. 149,
- `pathlast`: a `tikz` path which is controlled by `/tcb/interior style` → P. 149,
- `freelance`: deprecated.
- `spartan`: a quite spartan code.
- `empty`: draw nothing.

`/tcb/interior engine`=⟨*name*⟩ (no default, initially `standard`)

Sets the *interior* drawing engine for an untitled box to ⟨*name*⟩. Typically, this key is set by a `/tcb/skin` → P. 134. Feasible values for ⟨*name*⟩ are:

- `standard`: the original code from the core package,
- `path`: a `tikz` path which is controlled by `/tcb/interior style` → P. 149,
- `pathfirst`: a `tikz` path which is controlled by `/tcb/interior style` → P. 149,
- `pathmiddle`: a `tikz` path which is controlled by `/tcb/interior style` → P. 149,
- `pathlast`: a `tikz` path which is controlled by `/tcb/interior style` → P. 149,
- `freelance`: deprecated.
- `spartan`: a quite spartan code.
- `empty`: draw nothing.

`/tcb/segmentation engine`=⟨*name*⟩ (no default, initially `standard`)

Sets the *segmentation* (line) drawing engine for a box to ⟨*name*⟩. Typically, this key is set by a `/tcb/skin` → P. 134. Feasible values for ⟨*name*⟩ are:

- `standard`: the original code from the core package,
- `path`: a `tikz` path which is controlled by `/tcb/segmentation style` → P. 151,
- `freelance`: deprecated.
- `spartan`: a quite spartan code.
- `empty`: draw nothing.

`/tcb/title engine`=⟨*name*⟩ (no default, initially `standard`)

Sets the *title area* drawing engine for a titled box to ⟨*name*⟩. Typically, this key is set by a `/tcb/skin` → P. 134. Feasible values for ⟨*name*⟩ are:

- `standard`: the original code from the core package,
- `path`: a `tikz` path which is controlled by `/tcb/title style` → P. 151,
- `pathfirst`: a `tikz` path which is controlled by `/tcb/title style` → P. 151,
- `pathmiddle`: a `tikz` path which is controlled by `/tcb/title style` → P. 151,
- `pathlast`: a `tikz` path which is controlled by `/tcb/title style` → P. 151,
- `freelance`: deprecated.
- `spartan`: a quite spartan code.
- `empty`: draw nothing.



`/tcb/geometry nodes=true|false` (default `true`, initially `false`)

If set to `true`, up to four `tikz` nodes are defined for a `tcolorbox` which are named `frame`, `interior`, `segmentation`, and `title`. These nodes describe the boundaries of the equally named parts of a `tcolorbox`. They are used by most engines based on Ti*k*Z. Typically, this key is set automatically by a `/tcb/skin` → P. 134.

```
\tcbset{colback=Salmon!50!white,colframe=FireBrick!75!black,
  width=(\linewidth-8mm)/2,before=,after=\hfill,equal height group=geon}

\begin{tcolorbox}[adjusted title=The title]
  The upper part.\tcblower The lower part.
\end{tcolorbox}
\begin{tcolorbox}[enhanced,adjusted title=The title,
  frame code={\path[draw=red,fill=red!25]
      (frame.south west) rectangle (frame.north east);},
  interior titled code={\path[draw=blue,fill=blue!25]
      (interior.south west) rectangle (interior.north east);},
  segmentation code={\path[draw=green,fill=green!25]
      (segmentation.south west) rectangle (segmentation.north east);},
  title code={\path[draw=black,fill=brown!75!black]
      (title.south west) rectangle (title.north east);}]
  The upper part.\tcblower The lower part.
\end{tcolorbox}
```



9.2 Code Option Keys

The following code options are applicable for all skins. The used ⟨*graphical code*⟩ can be any `pgf` code. For all skins with exception of `standard` → P. 204 and `standard jigsaw` → P. 205, the ⟨*graphical code*⟩ can also be any Ti*k*Z code.

`/tcb/frame code=`⟨*graphical code*⟩ (code, default from `standard`)

The given ⟨*graphical code*⟩ is used for drawing the *frame* of the box.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[enhanced,frame code={
  \foreach \n in {north east,north west,south east,south west}
  {\path [fill=red!75!black] (interior.\n) circle (3mm); }; }]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```



`/tcb/frame empty` (style, no value)

This is a shortcut for setting `/tcb/frame code` to empty. This option removes the drawing of the frame. Alternatively, use `/tcb/frame hidden` → P. 149.

`/tcb/interior titled code=`⟨*graphical code*⟩ (code, default from `standard`)

The given ⟨*graphical code*⟩ is used for drawing the *interior* of the box, if the box comes with a title.

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[enhanced,title=My title,interior titled code={
  \path[draw=red!5!white,line width=5mm,line cap=round]
    ([xshift=3mm,yshift=-3mm]interior.north west)
    --([xshift=-3mm,yshift=3mm]interior.south east)
    ([xshift=3mm,yshift=3mm]interior.south west)
    --([xshift=-3mm,yshift=-3mm]interior.north east);}]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```



`/tcb/interior titled empty` (style, no value)

This is a shortcut for setting `/tcb/interior titled code` to empty. This option removes the drawing of the untitled interior. Alternatively, use `/tcb/interior hidden` → P. 150.

`/tcb/interior code=`⟨*graphical code*⟩ (code, default from `standard`)

The given ⟨*graphical code*⟩ is used for drawing the *interior* of the box, if the box is without a title.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[enhanced,interior code={
  \path[draw=red!5!white,line width=5mm,line cap=round]
    ([xshift=3mm,yshift=-3mm]interior.north west)
    --([xshift=-3mm,yshift=3mm]interior.south east)
    ([xshift=3mm,yshift=3mm]interior.south west)
    --([xshift=-3mm,yshift=-3mm]interior.north east);}]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```



`/tcb/interior empty` (style, no value)

This is a shortcut for setting `/tcb/interior code` to empty. This option removes the drawing of the interior. Alternatively, use `/tcb/interior hidden` → P. 150.

`/tcb/segmentation code=`⟨*graphical code*⟩ (code, default from `standard`)

The given ⟨*graphical code*⟩ is used for drawing the *segmentation* area of the box.

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[enhanced,title=My title,segmentation code={
  \path[top color=red!5!white,bottom color=red!5!white,middle color=blue]
  (segmentation.south west) rectangle (segmentation.north east);}]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```



`/tcb/segmentation empty` (style, no value)

This is a shortcut for setting `/tcb/segmentation code` to empty. This option removes the drawing of the segmentation line. Alternatively, use `/tcb/segmentation hidden` → P. 151.

`/tcb/title code=`⟨*graphical code*⟩ (code, default from `standard`)

The given ⟨*graphical code*⟩ is used for drawing the *title* area of the box.

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
  coltitle=black}

\begin{tcolorbox}[enhanced,title=My title,title code={
  \path[draw=yellow,solid,decorate,line width=2mm,
    decoration={coil,aspect=0,segment length=10.1mm}]
    ([xshift=1mm]title.west) -- ([xshift=-1mm]title.east);}]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

This is the lower part.

`/tcb/title empty` (style, no value)

This is a shortcut for setting `/tcb/title code` to empty. This option removes the drawing of the title area. Alternatively, use `/tcb/title hidden` → P. 152.

9.3 Subskins

A subskin is a new `/tcb/skin` → P. 134 based on an existing skin which is extended or changed.

> **!** Never use geometry settings or bounding box options inside a subskin definition! If one skin is replaced by another skin, the overall bounding box should stay constant. Especially, if a skin is used for a breakable box, unpredictable and unpleasant results could arise otherwise. If you want to change the geometry also, use an additional style. See the skin `beamer` → P. 228 and the style `/tcb/beamer` → P. 228 as pattern.

`\tcbsubskin{⟨name⟩}{⟨base skin⟩}{⟨options⟩}`

Creates a new skin ⟨*name*⟩ which inherits all properties of an existing ⟨*base skin*⟩ plus the given ⟨*options*⟩. The new skin ⟨*name*⟩ can be used as value for the keys `/tcb/skin` → P. 134, `/tcb/skin first` → P. 134, `/tcb/skin middle` → P. 134, and `/tcb/skin last` → P. 134. As ⟨*base skin*⟩, one can take `standard` → P. 204, `empty` → P. 237, `enhanced` → P. 206, or any skin from the LIB skins library, see Section 10 on page 148.

```
% \tcbuselibrary{skins}
\tcbsubskin{mycross}{empty}{frame code={%
  \draw[red,line width=5pt] (frame.south west)--(frame.north east);
  \draw[red,line width=5pt] (frame.north west)--(frame.south east);},
  skin first=mycross,skin middle=mycross,skin last=mycross }

\begin{tcolorbox}[skin=mycross]
  This is my content.
\end{tcolorbox}
```

`/tcb/skin first is subskin of={⟨base skin⟩}{⟨options⟩}` (no default, initially unset)

Creates a new unnamed skin which inherits all properties of an existing ⟨*base skin*⟩ plus the given ⟨*options*⟩. This skin is set as `/tcb/skin first` → P. 134.
See a detailed example on page 243.

`/tcb/skin middle is subskin of={⟨base skin⟩}{⟨options⟩}` (no default, initially unset)

Creates a new unnamed skin which inherits all properties of an existing ⟨*base skin*⟩ plus the given ⟨*options*⟩. This skin is set as `/tcb/skin middle` → P. 134.
See a detailed example on page 243.

`/tcb/skin last is subskin of={⟨base skin⟩}{⟨options⟩}` (no default, initially unset)

Creates a new unnamed skin which inherits all properties of an existing ⟨*base skin*⟩ plus the given ⟨*options*⟩. This skin is set as `/tcb/skin last` → P. 134.
See a detailed example on page 243.

9.4 Drawing Scheme

Depending on the complexity of a `tcolorbox` definition, the resulting box is drawn in a more or less complex series of steps.

To document and demonstrate these drawing steps, we consider the following box definition:

```
\newtcolorbox{testbox}[1][]{enhanced,title=Test Box,
  boxrule=1mm,titlerule=0.5mm,colframe=blue!50!black,
  interior style={top color=blue!20!green!50!white,bottom color=blue!20!yellow!50!white},
  colbacktitle=blue!50!green!90!white,segmentation style={solid},
  fonttitle=\bfseries,drop fuzzy shadow,borderline={0.3mm}{0.35mm}{yellow!50!white},
  underlay={\path[fill image opacity=0.15,fill image scale=0.9,
    fill stretch picture={\draw[blue,line width=2mm] circle (1);}]
    (interior.south west) rectangle (interior.north east);},
  watermark text={Watermark},watermark color={green!20!white},
  finish={\begin{tcbclipframe}
    \path[bottom color=black,top color=black!50!white,opacity=0.1]
      (frame.south west) -- (frame.south east) -- (frame.north east) -- cycle;
    \path[top color=white,bottom color=black!50!white,opacity=0.1]
      (frame.south west) -- (frame.north east) -- (frame.north west) -- cycle;
    \end{tcbclipframe}},#1}
```

For this definition, we get the maximal number of drawing steps:



- Section 10.6 on page 182.



- `/tcb/colframe` → P. 27, `/tcb/opacityframe` → P. 51
- `/tcb/frame code` → P. 138
- `/tcb/frame style` → P. 148



- /tcb/colback → P. 27, /tcb/opacityback → P. 51
- /tcb/interior code → P. 139, /tcb/interior titled code → P. 138
- /tcb/interior style → P. 149



- /tcb/colbacktitle → P. 27, /tcb/opacitybacktitle → P. 51
- /tcb/title code → P. 140
- /tcb/title style → P. 151



- /tcb/lower separated → P. 25
- /tcb/segmentation code → P. 139
- /tcb/segmentation style → P. 151



- Section 10.5 on page 177



- Section 10.2 on page 155
- Section 10.8 on page 195



- Section 4.12 on page 71
- Section 10.3 on page 165

Test Box

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

9. text content

Lower part

- `/tcb/colupper` → P. 28, `/tcb/collower` → P. 28, `/tcb/coltitle` → P. 28
- `/tcb/fontupper` → P. 29, `/tcb/fontlower` → P. 29, `/tcb/fonttitle` → P. 29
- `/tcb/opacityupper` → P. 52, `/tcb/opacitylower` → P. 52, `/tcb/opacitytitle` → P. 52

Test Box

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

10. finish

Lower part

- Section 10.9 on page 197

All together, the box is drawn:

```
% \usepackage{lipsum}
\begin{testbox}
\lipsum[2]
\tcblower
Lower part
\end{testbox}
```

Test Box

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Lower part

9.5 Useful Properties

The following macros describe certain *properties* which may be used for the drawing scheme, see Section 9.4 on page 142. Sometimes, they are even available inside the box content. All of them are considered to be *read-only* and should never be redefined by the user.

N 2016-02-16 **\tcbheightspace**

If the height of a `tcolorbox` is not the natural height, the space difference between the forced and the natural size is hold by `\tcbheightspace`. This macro is not usable inside the box content, but for skins or inside `/tcb/underlay` → P. 195, `/tcb/overlay` → P. 71, etc. If such a space information is needed inside the box content, see `/tcb/space to` → P. 59 instead.

```
% \tcbuselibrary{skins}
\newtcolorbox{testbox}[2][]{enhanced,size=fbox,
  colframe=blue!75!black,colback=white,height=#2,
  underlay={\node[above,inner sep=3pt] at (interior.south){%
    \includegraphics[width=\tcbtextwidth,height=\tcbheightspace-3pt]{goldshade.png}};
    },
  #1}
\begin{testbox}{3cm}
  This is my box. The space is filled with a picture.
\end{testbox}
\begin{testbox}{2cm}
  This is my box. The space is filled with a picture.
\end{testbox}
```

This is my box. The space is filled with a picture.

This is my box. The space is filled with a picture.

N 2016-02-16 **\tcbtextwidth**

This property describes the box content width.

- If there also is a lower part, it describes the width of the upper part.
- For `/tcb/sidebyside` → P. 116 boxes, it describes the combined text width plus segmentation.
- This property can be used inside the box content text with exception of `/tcb/fit` → P. 412 boxes.
- `\tcbtextwidth` can be used for all box types for skins or inside `/tcb/underlay` → P. 195, `/tcb/overlay` → P. 71, etc.

```
\begin{tcolorbox}[colframe=blue!75!black]
  Inside a box: \tcbtextwidth\ (=\the\linewidth).
\end{tcolorbox}
```

Inside a box: 370.74823pt (=370.74823pt).

N 2016-02-16 **\tcbtextheight**

This property describes the designated box content height. If the box is larger than the natural height, the actual content will be smaller than \tcbtextheight.

- For boxes with a fixed /tcb/height → P. 53, this property can be used inside the box content text. For other boxes, it denotes 0pt inside the box content.
- \tcbtextheight can be used for all box types for skins or inside /tcb/underlay → P. 195, /tcb/overlay → P. 71, etc.

```
% \tcbuselibrary{skins}
\begin{tcolorbox}[enhanced,colframe=blue!75!black,
    underlay={\node[left,red] at (frame.east) {Here: \tcbtextheight};}]
  Inside a box with natural height: \tcbtextheight.
\end{tcolorbox}
\begin{tcolorbox}[enhanced,colframe=blue!75!black,height=1cm,
    underlay={\node[left,red] at (frame.east) {Here: \tcbtextheight};}]
  Inside a box with fixed height: \tcbtextheight.
\end{tcolorbox}
```

Inside a box with natural height: 0pt. Here: 7.95pt

Inside a box with fixed height: 8.5359pt. Here: 8.5359pt

N 2017-04-25 **\tcbsegmentstate**

This macro contains 0, 1, or 2. Itis set for every unbroken box and every broken partial box with the following meaning:

- 0: The current (partial) box contains only an upper part.
- 1: The current (partial) box contains an upper and a lower part. The segmentation node can be used for positioning.
- 2: The current (partial) box contains only a lower part. This can only be true for parts of breakable boxes.

Skins like bicolor → P. 219 use this property to paint the (partial) boxes.

```
% \tcbuselibrary{skins,raster}
\begin{tcbraster}[raster equal height,enhanced,
    watermark text=\tcbsegmentstate]
  \begin{tcolorbox}Upper part\end{tcolorbox}
  \begin{tcolorbox}Upper part\tcblower Lower part\end{tcolorbox}
\end{tcbraster}
```

Upper part 0

Upper part

Lower part 1

10 Library LIB skins

The library is loaded by a package option or inside the preamble by:

```
\tcbuselibrary{skins}
```

This also loads the package `tikz` [22]. Typically but not necessarily, the following skins use `tikz` instead of `pgf`.

10.1 Style Option Keys

The following style options are applicable for all skins which use engines of type `path`, `pathfirst`, `pathmiddle`, or `pathlast`. Especially, the skin `enhanced` → P. 206 supports *all* of them and `standard` → P. 204 *none*.

`/tcb/frame style=`⟨`tikz` *keys*⟩ (style, no default)

The ⟨`tikz` *keys*⟩ are used inside the `tikz` path command for drawing the *frame* of the box. This option is available if the `/tcb/frame engine` → P. 135 is set to `path`, `pathfirst`, `pathmiddle`, or `pathlast`. It is *not* available for `standard`.

```
\tcbset{colback=red!5!white,fonttitle=\bfseries}

\begin{tcolorbox}[enhanced,title=My title,
  frame style={left color=red!75!black,
               right color=blue!75!black}]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```



`/tcb/frame style image=`⟨*file name*⟩ (no default, initially unset)

Fills the frame with an external image referenced by ⟨*file name*⟩. For advanced features like blending of a picture with the background, use `/tcb/frame style` together with `/tikz/fill stretch image` → P. 257.

```
\tcbset{colback=red!5!white,fonttitle=\bfseries}

\begin{tcolorbox}[enhanced,title=My title,
  frame style image=blueshade.png]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```



`/tcb/frame style tile={⟨graphics options⟩}{⟨file name⟩}` (no default, initially unset)

Fills the frame with a tile pattern based on an external image referenced by ⟨*file name*⟩. The ⟨*graphics options*⟩ are given to the underlying `\includegraphics` command. For advanced features like blending of a picture with the background, use `/tcb/frame style` → P. 148 together with `/tikz/fill tile image` → P. 261.

```
\tcbset{colback=red!5!white,coltitle=red!30!black,
  opacityback=0.75,fonttitle=\bfseries}

\begin{tcolorbox}[enhanced,title=My title,
  frame style tile={width=1cm}{pink_marble.png}]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```



`/tcb/frame hidden` (style, no value)

This is a shortcut for `frame style={draw=none,fill=none}`. Depending on the skin, this option switches off the drawing of the frame. Alternatively, use `/tcb/frame empty` → P. 138.

```
\tcbset{colback=red!5!white,colframe=red!75!black,
  fonttitle=\bfseries,coltitle=black}

\begin{tcolorbox}[enhanced,title=My title,
  frame hidden]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```



`/tcb/interior style=`⟨`tikz` *keys*⟩ (style, no default)

The ⟨`tikz` *keys*⟩ are used inside the `tikz` path command for drawing the *interior* of the box. They are used for the titled and for the untitled version as well.

This option is available if the `/tcb/interior titled engine` → P. 135 or `/tcb/interior engine` → P. 136 is set to `path`, `pathfirst`, `pathmiddle`, or `pathlast`. It is *not* available for `standard`.

```
\tcbset{colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[enhanced,title=My title,
  interior style={left color=red!20!white,
                  right color=yellow!50!white}]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```



`/tcb/interior style image=`⟨*file name*⟩ (no default, initially unset)

Fills the interior with an external image referenced by ⟨*file name*⟩. For advanced features like blending of a picture with the background, use `/tcb/interior style` → P. 149 together with `/tikz/fill stretch image` → P. 257.

```
\tcbset{colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[enhanced,title=My title,
  interior style image=goldshade.png]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```



`/tcb/interior style tile={`⟨*graphics options*⟩`}{`⟨*file name*⟩`}` (no default, initially unset)

Fills the interior with a tile pattern based on an external image referenced by ⟨*file name*⟩. The ⟨*graphics options*⟩ are given to the underlying `\includegraphics` command. For advanced features like blending of a picture with the background, use `/tcb/interior style` → P. 149 together with `/tikz/fill tile image` → P. 261.

```
\tcbset{colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[enhanced,title=My title,
  interior style tile={width=2cm}{crinklepaper.png}]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```



`/tcb/interior hidden` (style, no value)

This is a shortcut for `interior style={draw=none,fill=none}`. Depending on the skin, this option switches off the drawing of the interior. Alternatively, use `/tcb/interior empty` → P. 139 and/or `/tcb/interior titled empty` → P. 138.

```
\tcbset{frame style={top color=red!20!white,
  bottom color=red!20!white!75!black},
  fonttitle=\bfseries,coltitle=black}

\begin{tcolorbox}[enhanced,title=My title,
  interior hidden]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```



`/tcb/segmentation style=`⟨`tikz` *keys*⟩ (style, no default)

The ⟨`tikz` *keys*⟩ are used inside the `tikz` path command for drawing the *segmentation* line of the box.

This option is available if the `/tcb/segmentation engine` → P. 136 is set to `path`. It is *not* available for `standard`.

```
\tcbset{colback=red!5!white,colframe=red!75!black,
  fonttitle=\bfseries}

\begin{tcolorbox}[enhanced,title=My title,
  segmentation style={double=white,draw=blue,
                  double distance=1pt,solid}]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```



`/tcb/segmentation hidden` (style, no value)

This is a shortcut for `segmentation style={draw=none,fill=none}`. Depending on the skin, this option switches off the drawing of the segmentation line. See also `/tcb/lower separated` → P. 25 which has the same effect for most skins. Alternatively, use `/tcb/segmentation empty` → P. 139.

```
\tcbset{colback=red!5!white,colframe=red!75!black,
  fonttitle=\bfseries}

\begin{tcolorbox}[title=My title,
  enhanced,segmentation hidden]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```



`/tcb/title style=`⟨`tikz` *keys*⟩ (style, no default)

The ⟨`tikz` *keys*⟩ are used inside the `tikz` path command for drawing the *title area* of the box.

This option is available if the `/tcb/title engine` → P. 136 is set to `path`, `pathfirst`, `pathmiddle`, or `pathlast`. It is *not* available for `standard`.

```
\tcbset{colback=red!5!white,colframe=red!75!black,
  coltitle=blue!50!black,fonttitle=\bfseries}

\begin{tcolorbox}[enhanced,title=My title,
  title style={left color=blue!15!yellow,
               right color=red!85!black}]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```



`/tcb/title style image=`⟨*file name*⟩ (no default, initially unset)

Fills the title area with an external image referenced by ⟨*file name*⟩. For advanced features like blending of a picture with the background, use `/tcb/title style` → P. 151 together with `/tikz/fill stretch image` → P. 257.

```
\tcbset{colback=blue!5!white,colframe=blue!75!black,
  fonttitle=\bfseries}

\begin{tcolorbox}[enhanced,title=My title,
  title style image=blueshade.png]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```



`/tcb/title style tile={`⟨*graphics options*⟩`}{`⟨*file name*⟩`}` (no default, initially unset)

Fills the title area with a tile pattern based on an external image referenced by ⟨*file name*⟩. The ⟨*graphics options*⟩ are given to the underlying `\includegraphics` command. For advanced features like blending of a picture with the background, use `/tcb/title style` → P. 151 together with `/tikz/fill tile image` → P. 261.

```
\tcbset{colback=red!5!white,colframe=red!75!black,
  coltitle=blue!50!black,fonttitle=\bfseries}

\begin{tcolorbox}[enhanced,title=My title,
  title style tile={width=1cm}{pink_marble.png}]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```



`/tcb/title hidden` (style, no value)

This is a shortcut for `title style={draw=none,fill=none}`. Depending on the skin, this option switches off the drawing of the title background. See also `/tcb/title filled` → P. 27 for a similar effect. Alternatively, use `/tcb/title empty` → P. 140.

```
\tcbset{colback=red!5!white,colframe=red!75!black,
  fonttitle=\bfseries}

\begin{tcolorbox}[title=My title,
  enhanced,title hidden]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```



N 2015-01-14 **/tcb/titlerule style=⟨tikz *keys*⟩** (style, no default)

The ⟨tikz *keys*⟩ are used to draw a title rule, i.e. a rule below the optional title. The width of the rule is controlled by /tcb/titlerule → P. 36. It may be set directly to a smaller width to create mixed effects with the standard rule. This option is implemented as an /tcb/underlay → P. 195. Thus, it is not available for standard → P. 204 and standard jigsaw → P. 205, but for all other skins, e.g. enhanced → P. 206. As an underlay, this option can be used multiple times and is removed by /tcb/no underlay → P. 195.

```
\begin{tcolorbox}[enhanced,
  colback=red!5!white,colframe=red!75!black,
  colbacktitle=red!50!yellow,fonttitle=\bfseries,
  title=My title,
  titlerule=1mm,
  titlerule style=yellow  ]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```




```
\begin{tcolorbox}[enhanced,
  colback=red!5!white,colframe=red!75!black,
  colbacktitle=red!50!yellow,fonttitle=\bfseries,
  title=My title,
  titlerule=1mm,
  titlerule style={yellow,line width=0.5mm}  ]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```




```
\begin{tcolorbox}[enhanced,
  colback=red!10!white,colframe=red!75!black,
  colbacktitle=red!50!yellow,fonttitle=\bfseries,
  frame hidden,
  title=My title,
  boxrule=0pt,titlerule=1mm,
  titlerule style=red!50!black  ]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```




```
%\usetikzlibrary{arrows.meta}
\begin{tcolorbox}[empty,
  coltitle=red!75!black,fonttitle=\bfseries,
  borderline horizontal={0.5mm}{0pt}{red!50!white},
  title=My title,
  titlerule style={red,
    arrows = {Hooks[arc=270]-Hooks[arc=270]}} ]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```



The combined Ti*k*Z style applied to frame, interior, and title background can used by authors in customizing code.

/tikz/tcb fill frame (style, no value)

This is a Ti*k*Z style which is finally applied to the *frame* of the box.

```
% \tcbuselibrary{hooks}
\tcbset{enhanced,colback=red!5!white,
  colframe=red!75!black,fonttitle=\bfseries,
  frame code app={\path[tcb fill frame]
    ([yshift=-2mm]frame.north)
        circle (8mm); }  }

\begin{tcolorbox}[title=My title]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```



/tikz/tcb fill interior (style, no value)

This is a Ti*k*Z style which is finally applied to the *interior* of the box.

```
% \tcbuselibrary{hooks}
\tcbset{enhanced,colback=red!5!white,
  colframe=red!75!black,fonttitle=\bfseries,
  interior titled code app={\path[tcb fill interior]
      ([yshift=-0.1pt]interior.north east)
    --([yshift=3pt]interior.north)
    --([yshift=-0.1pt]interior.north west)
    --cycle;}  }

\begin{tcolorbox}[title=My title]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```



/tikz/tcb fill title (style, no value)

This is a Ti*k*Z style which is finally applied to the *title area* of the box.

```
% \tcbuselibrary{hooks}
\tcbset{enhanced,colback=red!5!white,
  colframe=red!75!black,fonttitle=\bfseries,
  colbacktitle=blue!75!black,
  title code app={\path[tcb fill title]
    (title) circle (5mm); }  }

\begin{tcolorbox}[title=My title]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```



10.2 Boxed Title Option Keys

10.2.1 Boxed Title Placement

The following options place the title text into an own \tcbox→P. 14. This boxed title can be customized independently from the main box using /tcb/boxed title style→P. 159. The placement can be influenced by ⟨*boxtitle options*⟩.

/tcb/attach boxed title to top left={⟨*boxtitle options*⟩} (style, default empty)

The title is boxed with a \tcbox→P. 14 and attached to the top left corner of the main box.

```
\begin{tcolorbox}[enhanced,title=My title,
  attach boxed title to top left]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

/tcb/attach boxed title to top center={⟨*boxtitle options*⟩} (style, default empty)

The title is boxed with a \tcbox→P. 14 and attached to the top of the main box.

```
\begin{tcolorbox}[enhanced,title=My title,
  attach boxed title to top center]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

/tcb/attach boxed title to top right={⟨*boxtitle options*⟩} (style, default empty)

The title is boxed with a \tcbox→P. 14 and attached to the top right corner of the main box.

```
\begin{tcolorbox}[enhanced,title=My title,
  attach boxed title to top right]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

/tcb/attach boxed title to bottom left={⟨*boxtitle options*⟩} (style, default empty)

The title is boxed with a \tcbox→P. 14 and attached to the bottom left corner of the main box.

```
\begin{tcolorbox}[enhanced,title=My title,
  attach boxed title to bottom left]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

/tcb/attach boxed title to bottom center={⟨*boxtitle options*⟩} (style, default empty)

The title is boxed with a \tcbox→P. 14 and attached to the bottom of the main box.

```
\begin{tcolorbox}[enhanced,title=My title,
  attach boxed title to bottom center]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

/tcb/attach boxed title to bottom right={⟨*boxtitle options*⟩} (style, default empty)

The title is boxed with a \tcbox→P. 14 and attached to the bottom right corner of the main box.

```
\begin{tcolorbox}[enhanced,title=My title,
  attach boxed title to bottom right]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

N 2016-02-26 **/tcb/attach boxed title to top={⟨*boxtitle options*⟩}** (style, default empty)

This is a convenient style to mimic a standard title. It uses /tcb/attach boxed title to top center → P. 155, /tcb/minipage boxed title → P. 163, and sizes the boxed title to match the base box.

```
\begin{tcolorbox}[enhanced,title=My title,
  attach boxed title to top,
  boxed title style={colframe=red}]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```



N 2016-02-26 **/tcb/attach boxed title to top*={⟨*boxtitle options*⟩}** (style, default empty)

In contrast to /tcb/attach boxed title to top, this style uses smaller left and right rules to avoid previewer glitches. Typically, one would not use different colors for the frame as in the example below.

```
\begin{tcolorbox}[enhanced,title=My title,
  attach boxed title to top*,
  boxed title style={colframe=red}]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```



N 2016-02-26 **/tcb/attach boxed title to bottom={⟨*boxtitle options*⟩}** (style, default empty)

This is a convenient style to produce a standard-like title at the bottom of the box. It uses /tcb/attach boxed title to bottom center → P. 155, /tcb/minipage boxed title → P. 163, and sizes the boxed title to match the base box.

```
\begin{tcolorbox}[enhanced,title=My title,
  attach boxed title to bottom,
  boxed title style={colframe=red}]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```



N 2016-02-26 **/tcb/attach boxed title to bottom*={⟨*boxtitle options*⟩}** (style, default empty)

In contrast to /tcb/attach boxed title to top, this style uses smaller left and right rules to avoid previewer glitches.

```
\begin{tcolorbox}[enhanced,title=My title,
  attach boxed title to bottom*]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```



N 2016-02-26 **/tcb/flip title={⟨*options*⟩}** (style, default empty)

This style combines /tcb/attach boxed title to bottom* with /tcb/boxed title style → P. 159. The ⟨*options*⟩ are given to /tcb/boxed title style → P. 159.

```
\begin{tcolorbox}[tile,flip title={sharp corners},
  title=My title,colback=red!10,
  colbacktitle=red!75!black]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```



10.2.2 Options for the Boxed Title Placement

The ⟨*boxtitle options*⟩ of the keys described above are shift values. The dimensions of the boxed title are stored into two macros `\tcboxedtitleheight` and `\tcboxedtitlewidth`. These macros can be used inside the following ⟨*boxtitle options*⟩:

`/tcb/boxtitle/xshift`=⟨*length*⟩ (no default, initially `0pt`)

The boxed title is shifted by ⟨*length*⟩ in the horizontal direction.

```
\begin{tcolorbox}[enhanced,title=My title,
  attach boxed title to top left={xshift=-2mm},
  boxed title style={size=small,colback=blue}]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```



`/tcb/boxtitle/yshift`=⟨*length*⟩ (no default, initially `0pt`)

The boxed title is shifted by ⟨*length*⟩ in the vertical direction.

```
\begin{tcolorbox}[enhanced,title=My title,
  attach boxed title to top center=
    {yshift=-\tcboxedtitleheight/2},
  boxed title style={size=small,colback=blue}]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```



`/tcb/boxtitle/yshifttext`=⟨*length*⟩ (no default, initially `0pt`)

The text inside the main box by ⟨*length*⟩ to give room for e. g. a sunken title.

```
\begin{tcolorbox}[enhanced,title=My title,
  attach boxed title to top center=
    {yshift=-3mm,yshifttext=-1mm},
  boxed title style={size=small,colback=blue}]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```



`/tcb/boxtitle/yshift*`=⟨*length*⟩ (no default, initially `0pt`)

Sets `/tcb/boxtitle/yshift` and `/tcb/boxtitle/yshifttext` the same time. `/tcb/boxtitle/yshifttext` is only set if necessary.

```
\begin{tcolorbox}[enhanced,title=My title,
  attach boxed title to top center={yshift*=-3mm},
  boxed title style={size=small,colback=blue}]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```



! The bounding box of the resulting total `tcolorbox` is adapted automatically to the *vertical* dimensions of the boxed title. Possible horizontal enlargements are *not* automatically computed.

```
\begin{tcolorbox}[enhanced,title=My title,
  attach boxed title to top left=
    {xshift=-2mm,yshift=-2mm},
  boxed title style={size=small,colback=blue},
  show bounding box]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

10.2.3 Options for the Boxed Title Box

! The boxed title options are implemented as an underlay, see Section 10.8 on page 195. Therefore, a boxed title is not drawn, if a skin does not support underlays like `standard`→ P. 204. Still, the room for the boxed titles gets reserved in these cases.

! A TikZ node `title` is produced by a boxed title which can be used inside `/tcb/frame code`→ P. 138, `/tcb/interior code`→ P. 139, underlays, overlays, and finishes.

! A boxed title is almost always the first underlay. The only exceptions are underlays defined by `/tcb/underlay boxed title`→ P. 196 which are drawn before. Additionally, underlays defined by `/tcb/underlay boxed title`→ P. 196 are only drawn, if a boxed title is actually set. They are ignored, if there is no boxed title.

N 2016-02-26 `/tcb/boxed title size=`⟨*size*⟩ (no default, initially `title`)

This setting defines the basic size for the title box. Further settings can be applied using `/tcb/boxed title style`→ P. 159. Feasible values for ⟨*size*⟩ are:

- `title`: Sets the size according to `/tcb/size`→ P. 44`=title`.
- `standard`: No size setting. Typically, this is identical to `/tcb/size`→ P. 44`=normal`.
- `copy`: The size values for a title of the base box are copied for the title box.

```
% \tcbuselibrary{raster}
\begin{tcbraster}[raster columns=3,enhanced,boxrule=0.4pt,
    title=My title,attach boxed title to top center]
  \begin{tcolorbox}[boxed title size=title]
    This is a \textbf{tcolorbox}.
  \end{tcolorbox}
  \begin{tcolorbox}[boxed title size=standard]
    This is a \textbf{tcolorbox}.
  \end{tcolorbox}
  \begin{tcolorbox}[boxed title size=copy]
    This is a \textbf{tcolorbox}.
  \end{tcolorbox}
\end{tcbraster}
```



U 2016-02-26 `/tcb/boxed title style=`⟨*options*⟩ (style, initially empty)

By default, a boxed title is dimensioned with `/tcb/size` →P. 44`=title` and inherits the `/tcb/skin` →P. 134 and `/tcb/colframe` →P. 27 of the main box. Also, the `/tcb/colback` →P. 27 is inherited from the main `/tcb/colbacktitle` →P. 27. Font and color of the title text are set as usual. All other ⟨*options*⟩ are set by the `/tcb/boxed title style` key. Since a boxed title is set by `\tcbox` →P. 14, all `tcolorbox` options are applicable here. If `/tcb/boxed title style` is used several times, the ⟨*options*⟩ are is appended.

```
\begin{tcolorbox}[enhanced,title=My title,
  fonttitle=\bfseries,coltitle=green!25!black,
  attach boxed title to top center=
    {yshift=-2mm,yshifttext=-1mm},
  boxed title style={colframe=green!75!black,
    colback=yellow!50!green}]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

```
\begin{tcolorbox}[enhanced,title=My title,
  colframe=red!50!black,colback=red!10!white,
  arc=1mm,colbacktitle=red!10!white,
  fonttitle=\bfseries,coltitle=red!50!black,
  attach boxed title to top left=
    {xshift=3.2mm,yshift=-0.50mm},
  boxed title style={skin=enhancedfirst jigsaw,
    size=small,arc=1mm,bottom=-1mm,
    interior style={fill=none,
      top color=red!30!white,
      bottom color=red!20!white}}]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

```
\begin{tcolorbox}[enhanced,title=My title,
  colframe=blue!50!black,colback=blue!10!white,colbacktitle=blue!5!yellow!10!white,
  fonttitle=\bfseries,coltitle=black,attach boxed title to top center=
    {yshift=-0.25mm-\tcboxedtitleheight/2,yshifttext=2mm-\tcboxedtitleheight/2},
  boxed title style={boxrule=0.5mm,
    frame code={ \path[tcb fill frame] ([xshift=-4mm]frame.west)
    -- (frame.north west) -- (frame.north east) -- ([xshift=4mm]frame.east)
    -- (frame.south east) -- (frame.south west) -- cycle; },
    interior code={ \path[tcb fill interior] ([xshift=-2mm]interior.west)
    -- (interior.north west) -- (interior.north east)
    -- ([xshift=2mm]interior.east) -- (interior.south east) -- (interior.south west)
    -- cycle;}  }]
  \lipsum[2]
\end{tcolorbox}
```

My title

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

```
% \usepackage{varwidth}
\newtcolorbox{mybox}[2][]{enhanced,skin=enhancedlast jigsaw,
  attach boxed title to top left={xshift=-4mm,yshift=-0.5mm},
  fonttitle=\bfseries\sffamily,varwidth boxed title=0.7\linewidth,
  colbacktitle=blue!45!white,colframe=red!50!black,
  interior style={top color=blue!10!white,bottom color=red!10!white},
  boxed title style={empty,arc=0pt,outer arc=0pt,boxrule=0pt},
  underlay boxed title={
    \fill[blue!45!white] (title.north west) -- (title.north east)
      -- +(\tcboxedtitleheight-1mm,-\tcboxedtitleheight+1mm)
      -- ([xshift=4mm,yshift=0.5mm]frame.north east) -- +(0mm,-1mm)
      -- (title.south west) -- cycle;
    \fill[blue!45!white!50!black] ([yshift=-0.5mm]frame.north west)
      -- +(-0.4,0) -- +(0,-0.3) -- cycle;
    \fill[blue!45!white!50!black] ([yshift=-0.5mm]frame.north east)
      -- +(0,-0.3) -- +(0.4,0) -- cycle;  },
  title={#2},#1}

\begin{mybox}{My title}
  \lipsum[2]
\end{mybox}
```

My title

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

```
% \usepackage{varwidth}
\newtcolorbox{mybox}[2][]{enhanced,
  attach boxed title to top left={xshift=1cm,yshift=-2mm},
  fonttitle=\bfseries,varwidth boxed title=0.7\linewidth,
  colbacktitle=green!45!white,coltitle=green!10!black,colframe=green!50!black,
  interior style={top color=yellow!10!white,bottom color=green!10!white},
  boxed title style={boxrule=0.75mm,colframe=white,
    borderline={0.1mm}{0mm}{green!50!black},
    borderline={0.1mm}{0.75mm}{green!50!black},
    interior style={top color=green!10!white,bottom color=green!10!white,
      middle color=green!50!white},
    drop fuzzy shadow},
  title={#2},#1}

\begin{mybox}{My title}
  \lipsum[2]
\end{mybox}
```

My title

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

```
\newtcolorbox{flipbox}[2][]{
  enhanced,colframe=blue!50!black,colback=yellow!5,fonttitle=\bfseries,
  flip title={interior hidden},title={#2},#1}

\begin{flipbox}{My title}
\lipsum[2]
\end{flipbox}
```

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

My title

```
% \usepackage{varwidth}
\newtcolorbox{mybox}[2][]{skin=enhancedlast jigsaw,interior hidden,
  boxsep=0pt,top=0pt,colframe=red,coltitle=red!50!black,
  fonttitle=\bfseries\sffamily,
  attach boxed title to bottom center,
  boxed title style={empty,boxrule=0.5mm},
  varwidth boxed title=0.5\linewidth,
  underlay boxed title={
    \draw[white,line width=0.5mm]
      ([xshift=0.3mm-\tcboxedtitleheight*2,yshift=0.3mm]title.north west)
      --([xshift=-0.3mm+\tcboxedtitleheight*2,yshift=0.3mm]title.north east);
    \path[draw=red,top color=white,bottom color=red!50!white,line width=0.5mm]
    ([xshift=0.25mm-\tcboxedtitleheight*2,yshift=0.25mm]title.north west)
    cos +(\tcboxedtitleheight,-\tcboxedtitleheight/2)
    sin +(\tcboxedtitleheight,-\tcboxedtitleheight/2)
    -- ([xshift=0.25mm,yshift=0.25mm]title.south west)
    -- ([yshift=0.25mm]title.south east)
    cos +(\tcboxedtitleheight,\tcboxedtitleheight/2)
    sin +(\tcboxedtitleheight,\tcboxedtitleheight/2); },
  title={#2},#1}

\begin{mybox}{My title}
  \lipsum[2]
\end{mybox}
```

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

My title

```
% \usepackage{varwidth}
\newtcolorbox{mybox}[2][]{enhanced,
  before skip=2mm,after skip=2mm,
  colback=black!5,colframe=black!50,boxrule=0.2mm,
  attach boxed title to top left={xshift=1cm,yshift*=1mm-\tcboxedtitleheight},
  varwidth boxed title*=-3cm,
  boxed title style={frame code={
    \path[fill=tcbcol@back!30!black]
      ([yshift=-1mm,xshift=-1mm]frame.north west)
        arc[start angle=0,end angle=180,radius=1mm]
      ([yshift=-1mm,xshift=1mm]frame.north east)
        arc[start angle=180,end angle=0,radius=1mm];
    \path[left color=tcbcol@back!60!black,right color=tcbcol@back!60!black,
      middle color=tcbcol@back!80!black]
      ([xshift=-2mm]frame.north west) -- ([xshift=2mm]frame.north east)
      [rounded corners=1mm]-- ([xshift=1mm,yshift=-1mm]frame.north east)
      -- (frame.south east) -- (frame.south west)
      -- ([xshift=-1mm,yshift=-1mm]frame.north west)
      [sharp corners]-- cycle;
    },interior engine=empty,
  },
  fonttitle=\bfseries,
  title={#2},#1}

\begin{mybox}[colbacktitle=green]{My title}
\lipsum[2]
\end{mybox}
\begin{mybox}[colbacktitle=red]{My title}
\lipsum[3]
\end{mybox}
```

My title

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

My title

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

N 2016-02-26 **/tcb/no boxed title style** (style, initially set)

Removes all options which were set by /tcb/boxed title style → P. 159.

/tcb/hbox boxed title (no value, initially set)

The title text content is captured with a horizontal box. Especially, there are no linebreak possible.

```
\newtcolorbox{mybox}[1]{hbox boxed title,
  enhanced,attach boxed title to top center=
    {yshift=-3mm,yshifttext=-1mm},
  boxed title style={size=small,colback=red},
  title={#1}}

\begin{mybox}{Short title}
  This is a \textbf{tcolorbox}.
\end{mybox}\bigskip

\begin{mybox}{This title is not really very short}
  This is a \textbf{tcolorbox}.
\end{mybox}
```



/tcb/minipage boxed title=⟨*length*⟩ (initially unset)

The title text content is captured with a minipage with a width of ⟨*length*⟩. By default, the resulting boxed title is somewhat smaller than the main box.

```
\newtcolorbox{mybox}[1]{minipage boxed title,
  enhanced,attach boxed title to top center=
    {yshift=-3mm,yshifttext=-1mm},
  boxed title style={size=small,colback=red},
  center title,title={#1}}

\begin{mybox}{Short title}
  This is a \textbf{tcolorbox}.
\end{mybox}\bigskip

\begin{mybox}{This title is not really very short}
  This is a \textbf{tcolorbox}.
\end{mybox}
```



/tcb/minipage boxed title*=⟨*length*⟩ (initially unset)

The title text content is captured with a minipage with a width of main box width plus ⟨*length*⟩. By default, the resulting boxed title is somewhat smaller than the main box.

```
\newtcolorbox{mybox}[1]{minipage boxed title*=-2cm,
  enhanced,attach boxed title to top center=
    {yshift=-3mm,yshifttext=-1mm},
  boxed title style={size=small,colback=red},
  center title,title={#1}}

\begin{mybox}{Short title}
  This is a \textbf{tcolorbox}.
\end{mybox}\bigskip

\begin{mybox}{This title is not really very short}
  This is a \textbf{tcolorbox}.
\end{mybox}
```



/tcb/tikznode boxed title=⟨*options*⟩ (initially unset)

The title text content is captured with a Ti*k*Z node with given Ti*k*Z ⟨*options*⟩. The text is centered by default

```
\newtcolorbox{mybox}[1]{tikznode boxed title,
  enhanced,attach boxed title to top center=
    {yshift=-3mm,yshifttext=-1mm},
  boxed title style={size=small,colback=red},
  title={#1}}

\begin{mybox}{Short title}
  This is a \textbf{tcolorbox}.
\end{mybox}\bigskip

\begin{mybox}{This title\\is not really\\very short}
  This is a \textbf{tcolorbox}.
\end{mybox}
```



/tcb/varwidth boxed title=⟨*length*⟩ (initially unset)

The title text content is captured with a `varwidth` environment with a width of ⟨*length*⟩. This style needs the `varwidth` package [1] to be loaded manually. By default, the resulting boxed title is somewhat smaller than the main box.

```
% \usepackage{varwidth}
\newtcolorbox{mybox}[1]{varwidth boxed title,
  enhanced,attach boxed title to top center=
    {yshift=-3mm,yshifttext=-1mm},
  boxed title style={size=small,colback=red},
  center title,title={#1}}

\begin{mybox}{Short title}
  This is a \textbf{tcolorbox}.
\end{mybox}\bigskip

\begin{mybox}{This title is not really very short}
  This is a \textbf{tcolorbox}.
\end{mybox}
```



/tcb/varwidth boxed title*=⟨*length*⟩ (initially unset)

The title text content is captured with a `varwidth` environment with a width of main box width plus ⟨*length*⟩. This style needs the `varwidth` package [1] to be loaded manually. By default, the resulting boxed title is somewhat smaller than the main box.

```
% \usepackage{varwidth}
\newtcolorbox{mybox}[1]{varwidth boxed title*=-2cm,
  enhanced,attach boxed title to top center=
    {yshift=-3mm,yshifttext=-1mm},
  boxed title style={size=small,colback=red},
  center title,title={#1}}

\begin{mybox}{Short title}
  This is a \textbf{tcolorbox}.
\end{mybox}\bigskip

\begin{mybox}{This title is not really very short}
  This is a \textbf{tcolorbox}.
\end{mybox}
```



10.3 Watermark Option Keys

The following watermark options are applicable for all skins which use `tikzpicture` as `/tcb/graphical environment`→P. 135. Therefore, the skin `standard`→P. 204 does not support these watermarks, but all other skins, e. g. `enhanced`→P. 206.

> ! The watermark options rely on the more general overlay options described in Section 4.12 from page 71. Therefore, *watermarks* and *overlays* cannot be used mixed. But a mixture is possible with the LIB hooks library, see Section 21.

`/tcb/watermark text=`⟨*text*⟩ (no default, initially unset)

Writes some ⟨*text*⟩ in the center of the interior region of a `tcolorbox`. This ⟨*text*⟩ is written *after* the frame and interior are drawn and *before* the text content is drawn. It is zoomed or stretched according the values of `/tcb/watermark zoom`→P. 168 or `/tcb/watermark stretch`→P. 170.

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[enhanced,title=My title,watermark text=My Watermark]
\lipsum[1]
\tcblower
\lipsum[2]
\end{tcolorbox}
```

My title

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

My Watermark

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

`/tcb/watermark text on=`⟨*part*⟩ `is` ⟨*text*⟩ (no default, initially unset)

This option writes some ⟨*text*⟩ in the center of the interior region of a `tcolorbox` as described for `/tcb/watermark text`. But this is done only for boxes named ⟨*part*⟩ of a break sequence, see `/tcb/breakable`→P. 365.

Feasible values for ⟨*part*⟩ are:

- `broken`: all broken box parts,
- `unbroken`: unbroken boxes only,
- `first`: first parts of a break sequence,
- `middle`: middle parts of a break sequence,
- `last`: last parts of a break sequence,
- `unbroken and first`: unbroken boxes and first parts of a break sequence,
- `middle and last`: middle and last parts of a break sequence.
- `first and middle`: first and middle parts of a break sequence.

`/tcb/watermark graphics`=⟨*file name*⟩ (no default, initially unset)

Draws an external picture referenced by ⟨*file name*⟩ in the center of the interior region of a `tcolorbox`. The picture is drawn *after* the frame and interior are drawn and *before* the text content is drawn. It is zoomed or stretched according the values of `/tcb/watermark zoom` → P. 168 or `/tcb/watermark stretch` → P. 170.

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[enhanced,title=My title,watermark graphics=Basilica_5.png,
  watermark opacity=0.15]
\lipsum[1-2]
\tcblower
This example uses a public domain picture from\\
\url{http://commons.wikimedia.org/wiki/File:Basilica_5.png}
\end{tcolorbox}
```

My title

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

This example uses a public domain picture from
http://commons.wikimedia.org/wiki/File:Basilica_5.png

`/tcb/watermark graphics on`=⟨*part*⟩ `is` ⟨*file name*⟩ (no default, initially unset)

This option draws a picture referenced by ⟨*file name*⟩ in the center of the interior region of a `tcolorbox` as described for `/tcb/watermark graphics`. But this is done only for boxes named ⟨*part*⟩ of a break sequence, see `/tcb/breakable` → P. 365.

Feasible values for ⟨*part*⟩ are:

- `broken`: all broken box parts,
- `unbroken`: unbroken boxes only,
- `first`: first parts of a break sequence,
- `middle`: middle parts of a break sequence,
- `last`: last parts of a break sequence,
- `unbroken and first`: unbroken boxes and first parts of a break sequence,
- `middle and last`: middle and last parts of a break sequence.

`/tcb/watermark tikz=`⟨*graphical code*⟩ (no default, initially unset)

Draws the given `tikz` ⟨*graphical code*⟩ in the center of the interior region of a `tcolorbox`. The code is executed *after* the frame and interior are drawn and *before* the text content is drawn. The result is zoomed or stretched according the values of `/tcb/watermark zoom` → P. 168 or `/tcb/watermark stretch` → P. 170.

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[enhanced,title=My title,
  watermark tikz={\draw[line width=2mm] circle (1cm)
    node{\fontfamily{ptm}\fontseries{b}\fontsize{20mm}{20mm}\selectfont ?};}]
\lipsum[1]
\tcblower
\lipsum[2]
\end{tcolorbox}
```

My title

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

`/tcb/watermark tikz on=`⟨*part*⟩ `is` ⟨*graphical code*⟩ (no default, initially unset)

This option draws the given `tikz` ⟨*graphical code*⟩ in the center of the interior region of a `tcolorbox` as described for `/tcb/watermark tikz`. But this is done only for boxes named ⟨*part*⟩ of a break sequence, see `/tcb/breakable` → P. 365.

Feasible values for ⟨*part*⟩ are:

- `broken`: all broken box parts,
- `unbroken`: unbroken boxes only,
- `first`: first parts of a break sequence,
- `middle`: middle parts of a break sequence,
- `last`: last parts of a break sequence,
- `unbroken and first`: unbroken boxes and first parts of a break sequence,
- `middle and last`: middle and last parts of a break sequence.

`/tcb/no watermark` (style, no default, initially set)

Removes the watermark if set before. This is an alias for `/tcb/no overlay` → P. 72.

`/tcb/watermark opacity=`⟨*fraction*⟩ (no default, initially `1.00`)

Sets the opacity value ∈ [0, 1] for a watermark.

```
\tcbset{enhanced,colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
  watermark text=Watermark,nobeforeafter,width=(\linewidth-2mm)/2}

\begin{tcolorbox}[title=Opacity 1.00,watermark opacity=1.00]
\lipsum[2]
\end{tcolorbox}\hfill%
\begin{tcolorbox}[title=Opacity 0.50,watermark opacity=0.50]
\lipsum[2]
\end{tcolorbox}%
```

Opacity 1.00

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Opacity 0.50

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

`/tcb/watermark zoom=`⟨*fraction*⟩ (no default, initially `0.75`)

Sets the zoom value for a watermark. The zoom respects the aspect ratio. The value 1.0 means to fill the whole box until the watermark touches the frame.

```
\tcbset{enhanced,colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
  watermark text=Watermark,nobeforeafter,width=(\linewidth-2mm)/2}

\begin{tcolorbox}[title=Zoom 1.0,watermark zoom=1.0]
\lipsum[2]
\end{tcolorbox}\hfill%
\begin{tcolorbox}[title=Zoom 0.5,watermark zoom=0.5]
\lipsum[2]
\end{tcolorbox}%
```

Zoom 1.0

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Zoom 0.5

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

`/tcb/watermark shrink`=⟨*fraction*⟩ (no default, initially unset)

Identically to `/tcb/watermark zoom` → P. 168, but the watermark never gets enlarged. Thus, the watermark keeps its original size or is shrunk.

`/tcb/watermark overzoom`=⟨*fraction*⟩ (no default, initially unset)

Sets the overzoom value for a watermark. The overzoom respects the aspect ratio. The value 1.0 means to fill the whole box until the watermark touches all four sides of the frame.

```
\tcbset{enhanced,colback=white,colframe=blue!50!black,fonttitle=\bfseries,
  watermark opacity=0.5,
  watermark graphics=lichtspiel.jpg,nobeforeafter,width=(\linewidth-2mm)/2}

\begin{tcolorbox}[title=Zoom 1.0,watermark zoom=1.0]
\lipsum[1]
\end{tcolorbox}\hfill%
\begin{tcolorbox}[title=Overzoom 1.0,watermark overzoom=1.0]
\lipsum[1]
\end{tcolorbox}%
```

Zoom 1.0

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Overzoom 1.0

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

! If a `/tcb/watermark overzoom` value of `1.0` is used in connection with invisible top and bottom rules which still have a thickness greater than `0pt`, the space of these invisible rules may not be covered by the watermark. For example, this situation may occur during the breaking of `/tcb/enhanced` → P. 206 boxes. To avoid this optical glitch, just set `/tcb/pad at break` → P. 369 to any desired value.

`/tcb/watermark stretch=`⟨*fraction*⟩ (no default, initially unset)

Sets the stretch value for a watermark. The stretch value is applied to width and height in relation to the box dimensions. It does not respect the aspect ratio. The value 1.0 means to fill the whole box.

```
\tcbset{enhanced,colback=white,colframe=blue!50!black,fonttitle=\bfseries,
  watermark graphics=lichtspiel.jpg,watermark opacity=0.5,
  nobeforeafter,width=(\linewidth-2mm)/2}

\begin{tcolorbox}[title=Stretch 1.00,watermark stretch=1.00]
\lipsum[2]
\end{tcolorbox}\hfill%
\begin{tcolorbox}[title=Stretch 0.50,watermark stretch=0.50]
\lipsum[2]
\end{tcolorbox}%
```

Stretch 1.00

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Stretch 0.50

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

`/tcb/watermark color=`⟨*color*⟩ (no default, initially mixed background and frame color)

Sets the color for the watermark.

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[enhanced,title=My title,watermark text=My Watermark,
  watermark color=yellow!50!red]
\lipsum[1]
\end{tcolorbox}
```

My title

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

`/tcb/clip watermark=true|false` (default `true`, initially `true`)

Sets the watermark to be clipped to the interior area.

```
\tcbset{enhanced,colback=white,colframe=blue!50!white,fonttitle=\bfseries,
  watermark opacity=0.5,watermark stretch=1.00,arc=3mm,
  watermark graphics=lichtspiel.jpg}

\begin{tcolorbox}[title=Clip (default),clip watermark]
\lipsum[1]
\end{tcolorbox}

\begin{tcolorbox}[title=No clip,clip watermark=false]
\lipsum[1]
\end{tcolorbox}%
```

Clip (default)

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

No clip

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

10.4 Clip Environments

The following clip environments are applicable for all skins which use engines of type `path`, `pathfirst`, `pathmiddle`, or `pathlast`. Especially, the skin `enhanced` → P. 206 supports *all* of them and `standard` → P. 204 *none*. The typical area of application is inside overlay code, see Section 4.12 from page 71.

```
\begin{tcbclipframe}
  ⟨environment content⟩
\end{tcbclipframe}
```

Defines a `Tikz` scope which clips to the frame area path.

```
\makeatletter
\newtcolorbox{picturebox}[2][]{%
  enhanced,frame hidden,interior hidden,fonttitle=\bfseries,
  overlay={\begin{tcbclipframe}\node at (frame)
    {\includegraphics[width=\tcb@width,height=\tcb@height]{#2}};\end{tcbclipframe}%
    \begin{tcbclipinterior}\fill[white,opacity=0.75]
    (frame.south west) rectangle (frame.north east);\end{tcbclipinterior}},#1}
\makeatother

\begin{picturebox}[title=My Picture Box]{lichtspiel.jpg}
\lipsum[1]
\end{picturebox}
```

My Picture Box

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

```
\begin{tcbinvclipframe}
 ⟨environment content⟩
\end{tcbinvclipframe}
```

Defines a Tikz scope which clips to the *outside* of the frame area path.

```
\tcbset{enhanced jigsaw,fonttitle=\bfseries,opacityback=0.35,colback=blue!5!white,
  frame style={left color=red!75!black,right color=red!10!yellow}}

\begin{tikzpicture}% draw two balls
  \path[use as bounding box] (0,0.8) rectangle +(0.1,0.1);
  \shadedraw [shading=ball] (0,0) circle (1cm);
  \shadedraw [ball color=red] (3,-2.2) circle (1cm);
\end{tikzpicture}

\begin{tcolorbox}[title=A translucent box,
  overlay={\begin{tcbinvclipframe}
    \draw[red,line width=1cm] ([xshift=-2mm,yshift=2mm]frame.north west)
      --([xshift=2mm,yshift=-2mm]frame.south east);
    \draw[red,line width=1cm] ([xshift=-2mm,yshift=-2mm]frame.south west)
      --([xshift=2mm,yshift=2mm]frame.north east);
  \end{tcbinvclipframe}}]
  \lipsum[2]
\end{tcolorbox}
```



```
\begin{tcbclipinterior}
 ⟨environment content⟩
\end{tcbclipinterior}
```

Defines a `Tikz` scope which clips to the interior area path.

```
\begin{tcolorbox}[enhanced,title=My Title,
  overlay={\begin{tcbclipinterior}
    \draw[red,line width=1cm] (interior.north west)--(interior.south east);
    \draw[red,line width=1cm] (interior.south west)--(interior.north east);
  \end{tcbclipinterior}}]
\lipsum[1]
\end{tcolorbox}
```

My Title

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

```
\begin{tcbcliptitle}
 ⟨environment content⟩
\end{tcbcliptitle}
```

Defines a `Tikz` scope which clips to the title area path.

```
\begin{tcolorbox}[enhanced,title=My Title,colframe=blue,colback=yellow!10!white,
  overlay={\begin{tcbcliptitle}\node at (title)
  {\includegraphics[width=\linewidth]{lichtspiel.jpg}};\end{tcbcliptitle}}]
\lipsum[1]
\end{tcolorbox}
```

My Title

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

`/tcb/clip title=true|false` (default `true`, initially `false`)

Sets the title to be clipped to the title area.

```
\tcbset{enhanced,width=5cm,colframe=red!50!white,coltitle=black,
  colbacktitle=yellow!50!white}

\begin{tcolorbox}[title=\mbox{This is a title which is unbreakable and far too long}]
This is a tcolorbox.
\end{tcolorbox}

\begin{tcolorbox}[title=\mbox{This is a title which is unbreakable and far too long},
  clip title]
This is a tcolorbox.
\end{tcolorbox}
```

This is a title which is unbreakable and far too long

This is a tcolorbox.

This is a title which is unbreak

This is a tcolorbox.

`/tcb/clip upper=true|false` (default `true`, initially `false`)

Sets the upper part to be clipped to the interior area.

```
\newcommand{\mygraphics}[2][]{%
  \tcbox[enhanced,boxsep=0pt,top=0pt,bottom=0pt,left=0pt,
    right=0pt,boxrule=0.4pt,drop fuzzy shadow,clip upper,
    colback=black!75!white,toptitle=2pt,bottomtitle=2pt,nobeforeafter,
    center title,fonttitle=\small\sffamily,title=\detokenize{#2}]
  {\includegraphics[width=\the\dimexpr(\linewidth-4mm)/2\relax]{#2}}}

\mygraphics{lichtspiel.jpg}\hfill
\mygraphics{Basilica_5.png}
```

lichtspiel.jpg

Basilica_5.png



The example for /tcb/clip upper → P. 175 sizes the box according to the dimensions of the picture. To do it the other way around, the watermark options provide an easy solution.

```
\newcommand{\mygraphics}[2][]{%
  \tcbox[enhanced,capture=minipage,boxsep=0pt,top=0pt,bottom=0pt,left=0pt,
    right=0pt,boxrule=0.4pt,drop fuzzy shadow,nobeforeafter,
    colback=black!75!white,toptitle=2pt,bottomtitle=2pt,
    center title,fonttitle=\small\sffamily,title=\detokenize{#2},
    width=(\linewidth-4mm)/2,height=6cm,colbacktitle={black},
    watermark zoom=1.0,watermark graphics={#2}]{}}

\mygraphics{lichtspiel.jpg}\hfill
\mygraphics{Basilica_5.png}
```

lichtspiel.jpg



Basilica_5.png



/tcb/clip lower=true|false (default true, initially false)

Sets the lower part to be clipped to the interior area.

```
\tcbset{enhanced,width=5cm,colframe=red!50!black,text and listing}

\begin{tcblisting}{}
Donau\-dampf\-schiff\-fahrts\-ka\-pi\-t\"ans\-m\"ut\-zen\-fran\-sen
\end{tcblisting}

\begin{tcblisting}{clip lower}
Donau\-dampf\-schiff\-fahrts\-ka\-pi\-t\"ans\-m\"ut\-zen\-fran\-sen
\end{tcblisting}
```

Donaudampfschifffahrtska-
pitänsmützenfransen

```
Donau\-dampf\-schiff\-fahrts\-ka\-pi\-t\"ans\-m\"ut\-zen\-fran\-sen
```

Donaudampfschifffahrtska-
pitänsmützenfransen

```
Donau\-dampf\-schiff\-fa
```

10.5 Border Line Option Keys

The following borderline options are applicable for most skins which use `tikzpicture` as `/tcb/graphical environment` → P. 135. Therefore, the skin `standard` → P. 204 does not support these border lines, but most other skins, e. g. `enhanced` → P. 206.

The borderlines are independent from the normal `tcolorbox` rules. They may be used with or without the `/tcb/segmentation engine` → P. 136.

The borderlines are stackable, i. e. several different border lines can be used on the same `tcolorbox`. They are drawn *after* the box frame and box interior and *before* overlays or watermarks.



Technically, the normal `tcolorbox` rules result from a TikZ *filling* process. The border lines are created by a TikZ *drawing* process. This can be used to apply different effects.

`/tcb/borderline={`⟨*width*⟩`}{`⟨*offset*⟩`}{`⟨*options*⟩`}` (no default, initially unset)

Adds a new borderline to the stack of border lines. This border line is drawn with the given ⟨*width*⟩ and gets an ⟨*offset*⟩ computed from the frame outline. A positive ⟨*offset*⟩ value moves the borderline inside the `tcolorbox` and a negative ⟨*offset*⟩ value moves it outside without changing the bounding box.

The border line is drawn along a TikZ path with the given TikZ ⟨*options*⟩. Note that the TikZ `line width` option should not be used here.

The border lines adapt to the rounded corners of the `tcolorbox`. An inside borderline will switch to sharp corners if necessary, an outside borderline will always be rounded except for `/tcb/sharp corners` → P. 48.

```
\begin{tcolorbox}[enhanced,title=Rounded corners,fonttitle=\bfseries,boxsep=5pt,
  arc=8pt,
  borderline={0.5pt}{0pt}{red},
  borderline={0.5pt}{5pt}{blue,dotted},
  borderline={0.5pt}{-5pt}{green} ]
This is a tcolorbox.
\end{tcolorbox}
\bigskip
\begin{tcolorbox}[enhanced,title=Sharp corners,fonttitle=\bfseries,boxsep=5pt,
  arc=8pt,sharp corners=downhill,
  borderline={0.5pt}{0pt}{red},
  borderline={0.5pt}{5pt}{blue,dotted},
  borderline={0.5pt}{-5pt}{green} ]
This is a tcolorbox.
\end{tcolorbox}
```

Rounded corners

This is a tcolorbox.

Sharp corners

This is a tcolorbox.

```
% \usepackage{lipsum}
\begin{tcolorbox}[enhanced,arc=3mm,boxrule=1.5mm,boxsep=1.5mm,
  colback=yellow!20!white,
  colframe=blue,
  borderline={1mm}{1mm}{white},
  borderline={1mm}{2mm}{red} ]
  \lipsum[1]
\end{tcolorbox}
```

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

```
% \usepackage{lipsum}
\begin{tcolorbox}[enhanced,arc=3mm,boxrule=1.5mm,
  frame hidden,colback=blue!10!white,
  borderline={1mm}{0mm}{blue,dotted} ]
  \lipsum[2]
\end{tcolorbox}
```

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

```
% \usepackage{lipsum}
\begin{tcolorbox}[enhanced,skin=enhancedmiddle,
  frame hidden,interior hidden,top=0mm,bottom=0mm,boxsep=0mm,
  borderline={0.75mm}{0mm}{red},
  borderline={0.75mm}{0.75mm}{red!50!yellow},
  borderline={0.75mm}{1.5mm}{yellow}, ]
  \lipsum[3]
\end{tcolorbox}
```

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

```
% \usepackage{lipsum}
\newtcolorbox{mygreenbox}[2][]{%
  enhanced,width=\linewidth-6pt,
  enlarge top by=3pt,enlarge bottom by=3pt,
  enlarge left by=3pt,enlarge right by=3pt,
  title={#2},frame hidden,boxrule=0pt,top=1mm,bottom=1mm,
  colframe=green!30!black, colbacktitle=green!50!yellow,
  coltitle=black, colback=green!25!white,
  borderline={0.5pt}{-0.5pt}{green!75!blue},
  borderline={1pt}{-3pt}{green!50!blue},#1}

\begin{mygreenbox}{My title}
  \lipsum[4]
\end{mygreenbox}
```

My title

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

`/tcb/no borderline` (no default, initially set)

Removes all borderlines if set before.

`/tcb/show bounding box=`⟨*color*⟩ (default `red`, initially unset)

Displays the bounding box borderline of a `tcolorbox`. Its intended use is debugging and fine tuning. It should not be part of a final document. The optional ⟨*color*⟩ is the base color for the bounding box borderline.

```
\tcbset{enhanced,nobeforeafter,width=4cm,fonttitle=\bfseries}

\begin{tcolorbox}[show bounding box,title=Normal]
This is a tcolorbox.
\end{tcolorbox}%
\begin{tcolorbox}[show bounding box=blue,title=Shadow,drop fuzzy shadow]
This is a tcolorbox.
\end{tcolorbox}%
\begin{tcolorbox}[show bounding box=green,title=Enlarged,drop fuzzy shadow,
  enlarge by=2mm]
This is a tcolorbox.
\end{tcolorbox}
```

Normal

This is a tcolorbox.

Shadow

This is a tcolorbox.

Enlarged

This is a tcolorbox.

The following *partial* borderlines act slightly different from the complete borderlines described before. They ignore rounded corner settings, their length is not modified by their ⟨*offset*⟩, they ignore skin settings but adapt to breakable boxes.

N 2014-10-20 **/tcb/borderline north={⟨*width*⟩}{⟨*offset*⟩}{⟨*options*⟩}** (no default, initially unset)

Adds a new borderline with the given ⟨*width*⟩ to the north of the `tcolorbox`. A positive ⟨*offset*⟩ value moves the borderline inside the `tcolorbox` and a negative ⟨*offset*⟩ value moves it outside without changing the bounding box.

```
\begin{tcolorbox}[enhanced,
  borderline north={2pt}{-2pt}{red}]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

N 2014-10-20 **/tcb/borderline south={⟨*width*⟩}{⟨*offset*⟩}{⟨*options*⟩}** (no default, initially unset)

Adds a new borderline with the given ⟨*width*⟩ to the south of the `tcolorbox`. A positive ⟨*offset*⟩ value moves the borderline inside the `tcolorbox` and a negative ⟨*offset*⟩ value moves it outside without changing the bounding box.

```
\begin{tcolorbox}[enhanced,
  borderline south={2pt}{-2pt}{red}]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

N 2014-10-20 **/tcb/borderline east={⟨*width*⟩}{⟨*offset*⟩}{⟨*options*⟩}** (no default, initially unset)

Adds a new borderline with the given ⟨*width*⟩ to the east of the `tcolorbox`. A positive ⟨*offset*⟩ value moves the borderline inside the `tcolorbox` and a negative ⟨*offset*⟩ value moves it outside without changing the bounding box.

```
\begin{tcolorbox}[enhanced,
  borderline east={2pt}{-2pt}{red}]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

N 2014-10-20 **/tcb/borderline west={⟨*width*⟩}{⟨*offset*⟩}{⟨*options*⟩}** (no default, initially unset)

Adds a new borderline with the given ⟨*width*⟩ to the west of the `tcolorbox`. A positive ⟨*offset*⟩ value moves the borderline inside the `tcolorbox` and a negative ⟨*offset*⟩ value moves it outside without changing the bounding box.

```
\begin{tcolorbox}[enhanced,
  borderline west={2pt}{-2pt}{red}]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

N 2014-10-20 **/tcb/borderline horizontal={⟨*width*⟩}{⟨*offset*⟩}{⟨*options*⟩}** (no default, initially unset)

Adds a new borderline with the given ⟨*width*⟩ to the north and south of the `tcolorbox`. A positive ⟨*offset*⟩ value moves the borderlines inside the `tcolorbox` and a negative ⟨*offset*⟩ value moves them outside without changing the bounding box.

```
\begin{tcolorbox}[blanker,top=3mm,bottom=3mm,
   borderline horizontal={2pt}{0pt}{red}]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

N 2014-10-20 **/tcb/borderline vertical={⟨*width*⟩}{⟨*offset*⟩}{⟨*options*⟩}** (no default, initially unset)

Adds a new borderline with the given ⟨*width*⟩ to the east and west of the `tcolorbox`. A positive ⟨*offset*⟩ value moves the borderlines inside the `tcolorbox` and a negative ⟨*offset*⟩ value moves them outside without changing the bounding box.

```
\begin{tcolorbox}[blanker,left=3mm,right=3mm,
   borderline vertical={2pt}{0pt}{red}]
  This is a \textbf{tcolorbox}.\\
  My second line.
\end{tcolorbox}
```

This is a **tcolorbox**.
My second line.

```
\begin{tcolorbox}[enhanced,colback=yellow!10!white,boxrule=0pt,frame hidden,
  borderline north={1mm}{-2mm}{red},
  borderline south={1mm}{-2mm}{blue},
  borderline west={1mm}{-2mm}{green},
  borderline east={1mm}{-2mm}{yellow}]
\lipsum[1]
\end{tcolorbox}
```

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

10.6 Shadow Option Keys

The following shadow options are applicable for most skins which use `tikzpicture` as `/tcb/graphical environment` → P. 135. Therefore, the skin `standard` → P. 204 does not support these shadows, but most other skins, e. g. `enhanced` → P. 206.

The shadows are stackable, i. e. several different shadows can be used on the same `tcolorbox`. They are drawn *before* the box frame is drawn.

`/tcb/no shadow` (no default)

Removes all shadows if set before.

10.6.1 Common Shadows and Halos

`/tcb/drop shadow=`⟨*color*⟩ (style, default `black!50!white`)

Adds a new shadow with standard dimensions to the stack of shadows. Optionally, the ⟨*color*⟩ for the shadow can be changed.

```
\tcbset{enhanced,colback=red!5!white,
  colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[drop shadow]
This is a tcolorbox.
\end{tcolorbox}\par\bigskip
\begin{tcolorbox}[title=Another shadow,
  drop shadow=blue]
This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

Another shadow

This is a tcolorbox.

`/tcb/drop fuzzy shadow=`⟨*color*⟩ (style, default `black!50!white`)

Adds a new fuzzy shadow with standard dimensions to the stack of shadows. Optionally, the ⟨*color*⟩ for the shadow can be changed.

```
\tcbset{enhanced,colback=red!5!white,
  colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[drop fuzzy shadow]
This is a tcolorbox.
\end{tcolorbox}\par\bigskip
\begin{tcolorbox}[title=Another shadow,
  drop fuzzy shadow=blue]
This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

Another shadow

This is a tcolorbox.

`/tcb/drop midday shadow=`⟨*color*⟩ (style, default `black!50!white`)

Adds a new shadow with standard dimensions to the stack of shadows. Optionally, the ⟨*color*⟩ for the shadow can be changed.

```
\tcbset{enhanced,colback=red!5!white,
  colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[drop midday shadow]
This is a tcolorbox.
\end{tcolorbox}\par\bigskip
\begin{tcolorbox}[title=Another shadow,
  drop midday shadow=blue]
This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

Another shadow

This is a tcolorbox.

`/tcb/drop fuzzy midday shadow=`⟨*color*⟩ (style, default `black!50!white`)

Adds a new fuzzy shadow with standard dimensions to the stack of shadows. Optionally, the ⟨*color*⟩ for the shadow can be changed.

```
\tcbset{enhanced,colback=red!5!white,
  colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[drop fuzzy midday shadow]
This is a tcolorbox.
\end{tcolorbox}\par\bigskip
\begin{tcolorbox}[title=Another shadow,
  drop fuzzy midday shadow=blue]
This is a tcolorbox.
\end{tcolorbox}
```



`/tcb/halo=`⟨*size*⟩ `with` ⟨*color*⟩ (style, default `0.9mm with yellow`)

Adds a new halo shadow with the given ⟨*color*⟩ which overlaps the colorbox an all sides by ⟨*size*⟩.

```
\tcbset{enhanced,colback=red!5!white,
  colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[title=My own halo,halo]
This is a tcolorbox.
\end{tcolorbox}
\par\bigskip\bigskip
\begin{tcolorbox}[title=Another halo,
  halo=2mm with green]
This is a tcolorbox.
\end{tcolorbox}
```



`/tcb/fuzzy halo=`⟨*size*⟩ `with` ⟨*color*⟩ (style, default `0.9mm with yellow`)

Adds a new fuzzy halo shadow with the given ⟨*color*⟩ which overlaps the colorbox an all sides by ⟨*size*⟩ plus `0.48mm`.

```
\tcbset{enhanced,colback=red!5!white,
  colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[title=My own halo,fuzzy halo]
This is a tcolorbox.
\end{tcolorbox}
\par\bigskip\bigskip
\begin{tcolorbox}[title=Another halo,
  fuzzy halo=2mm with green]
This is a tcolorbox.
\end{tcolorbox}
```




```
\begin{tcolorbox}[blank,enhanced jigsaw,boxsep=2pt,arc=2pt,
  fuzzy halo=2mm with red!50!white,
  fuzzy halo=1mm with white]
\lipsum[1]
\end{tcolorbox}
```

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

For all following shadows, the optionally given ⟨*color*⟩ for the shadow can be changed equivalent to the preceding examples.

`/tcb/drop shadow southeast=`⟨*color*⟩ (style, default `black!50!white`)

Adds a new shadow with standard dimensions to the stack of shadows. This shadow is identical to `/tcb/drop shadow` → P. 182.

```
\begin{tcolorbox}[drop shadow southeast,
  enhanced,colback=red!5!white,colframe=red!75!black]
  This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

`/tcb/drop shadow south=`⟨*color*⟩ (style, default `black!50!white`)

Adds a new shadow with standard dimensions to the stack of shadows. This shadow is identical to `/tcb/drop midday shadow` → P. 182.

```
\begin{tcolorbox}[drop shadow south,
  enhanced,colback=red!5!white,colframe=red!75!black]
  This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

`/tcb/drop shadow southwest=`⟨*color*⟩ (style, default `black!50!white`)

Adds a new shadow with standard dimensions to the stack of shadows.

```
\begin{tcolorbox}[drop shadow southwest,
  enhanced,colback=red!5!white,colframe=red!75!black]
  This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

`/tcb/drop shadow west=`⟨*color*⟩ (style, default `black!50!white`)

Adds a new shadow with standard dimensions to the stack of shadows.

```
\begin{tcolorbox}[drop shadow west,
  enhanced,colback=red!5!white,colframe=red!75!black]
  This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

`/tcb/drop shadow northwest=`⟨*color*⟩ (style, default `black!50!white`)

Adds a new shadow with standard dimensions to the stack of shadows.

```
\begin{tcolorbox}[drop shadow northwest,
  enhanced,colback=red!5!white,colframe=red!75!black]
  This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

`/tcb/drop shadow north=`⟨*color*⟩ (style, default `black!50!white`)

Adds a new shadow with standard dimensions to the stack of shadows.

```
\begin{tcolorbox}[drop shadow north,
  enhanced,colback=red!5!white,colframe=red!75!black]
  This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

`/tcb/drop shadow northeast=`⟨*color*⟩ (style, default `black!50!white`)

Adds a new shadow with standard dimensions to the stack of shadows.

```
\begin{tcolorbox}[drop shadow northeast,
  enhanced,colback=red!5!white,colframe=red!75!black]
  This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

`/tcb/drop shadow east=`⟨*color*⟩ (style, default `black!50!white`)

Adds a new shadow with standard dimensions to the stack of shadows.

```
\begin{tcolorbox}[drop shadow east,
  enhanced,colback=red!5!white,colframe=red!75!black]
  This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

`/tcb/drop fuzzy shadow southeast=`⟨*color*⟩ (style, default `black!50!white`)

Adds a new fuzzy shadow with standard dimensions to the stack of shadows. This shadow is identical to `/tcb/drop fuzzy shadow` → P. 182.

```
\begin{tcolorbox}[drop fuzzy shadow southeast,
  enhanced,colback=red!5!white,colframe=red!75!black]
  This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

`/tcb/drop fuzzy shadow south=`⟨*color*⟩ (style, default `black!50!white`)

Adds a new fuzzy shadow with standard dimensions to the stack of shadows. This shadow is identical to `/tcb/drop fuzzy midday shadow` → P. 183.

```
\begin{tcolorbox}[drop fuzzy shadow south,
  enhanced,colback=red!5!white,colframe=red!75!black]
  This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

`/tcb/drop fuzzy shadow southwest=`⟨*color*⟩ (style, default `black!50!white`)

Adds a new fuzzy shadow with standard dimensions to the stack of shadows.

```
\begin{tcolorbox}[drop fuzzy shadow southwest,
  enhanced,colback=red!5!white,colframe=red!75!black]
  This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

`/tcb/drop fuzzy shadow west=`⟨*color*⟩ (style, default `black!50!white`)

Adds a new fuzzy shadow with standard dimensions to the stack of shadows.

```
\begin{tcolorbox}[drop fuzzy shadow west,
  enhanced,colback=red!5!white,colframe=red!75!black]
  This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

`/tcb/drop fuzzy shadow northwest=`⟨*color*⟩ (style, default `black!50!white`)

Adds a new fuzzy shadow with standard dimensions to the stack of shadows.

```
\begin{tcolorbox}[drop fuzzy shadow northwest,
  enhanced,colback=red!5!white,colframe=red!75!black]
  This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

`/tcb/drop fuzzy shadow north=`⟨*color*⟩ (style, default `black!50!white`)

Adds a new fuzzy shadow with standard dimensions to the stack of shadows.

```
\begin{tcolorbox}[drop fuzzy shadow north,
  enhanced,colback=red!5!white,colframe=red!75!black]
  This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

`/tcb/drop fuzzy shadow northeast=`⟨*color*⟩ (style, default `black!50!white`)

Adds a new fuzzy shadow with standard dimensions to the stack of shadows.

```
\begin{tcolorbox}[drop fuzzy shadow northeast,
  enhanced,colback=red!5!white,colframe=red!75!black]
  This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

`/tcb/drop fuzzy shadow east=`⟨*color*⟩ (style, default `black!50!white`)

Adds a new fuzzy shadow with standard dimensions to the stack of shadows.

```
\begin{tcolorbox}[drop fuzzy shadow east,
  enhanced,colback=red!5!white,colframe=red!75!black]
  This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

10.6.2 Lifted Shadows

`/tcb/drop lifted shadow=`⟨*color*⟩ (style, default `black!50!white`)

Adds a new lifted shadow with standard dimensions to the stack of shadows. Optionally, the ⟨*color*⟩ for the shadow can be changed.

```
\tcbset{enhanced,colback=red!5!white,
  boxrule=0.4pt,sharp corners,
  colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[drop lifted shadow]
This is a tcolorbox.
\end{tcolorbox}\par\bigskip
\begin{tcolorbox}[title=Another shadow,
  drop lifted shadow=blue]
This is a tcolorbox.
\end{tcolorbox}
```



`/tcb/drop small lifted shadow=`⟨*color*⟩ (style, default `black!50!white`)

Adds a new small lifted shadow with standard dimensions to the stack of shadows. Optionally, the ⟨*color*⟩ for the shadow can be changed.

```
\tcbset{enhanced,colback=red!5!white,
  boxrule=0.4pt,sharp corners,
  colframe=red!75!black,fonttitle=\bfseries}

\tcbox[drop small lifted shadow,size=fbox]
  {This is a tcolorbox.}
\par\bigskip
\begin{tcolorbox}[title=Another shadow,
  drop small lifted shadow=black]
This is a tcolorbox.
\end{tcolorbox}
```



`/tcb/drop large lifted shadow=`⟨*color*⟩ (style, default `black!50!white`)

Adds a new large lifted shadow with standard dimensions to the stack of shadows. Optionally, the ⟨*color*⟩ for the shadow can be changed.

```
\tcbset{enhanced,colback=red!5!white,
  colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[drop large lifted shadow]
This is a tcolorbox.
\end{tcolorbox}\par\bigskip
\begin{tcolorbox}[title=Another shadow,
  drop large lifted shadow=blue]
This is a tcolorbox.
\end{tcolorbox}
```



10.6.3 Generic Shadows

`/tcb/shadow={⟨xshift⟩}{⟨yshift⟩}{⟨offset⟩}{⟨options⟩}` (no default)

Adds a new shadow to the stack of shadows. This shadow follows the outline of the `tcolorbox` but is shifted by ⟨*xshift*⟩ and ⟨*yshift*⟩. The ⟨*offset*⟩ value is a distance value from the frame outline. A positive ⟨*offset*⟩ value shrinks the shadow and a negative ⟨*offset*⟩ value enlarges the shadow. The shadow is filled along a Ti*k*Z path with the given Ti*k*Z ⟨*options*⟩.

The shadows adapt to the rounded corners of the `tcolorbox`. An shrinked shadow will switch to sharp corners if necessary, an enlarged shadow may become more rounded depending on several factors. But `/tcb/sharp corners` → P. 48 have sharp shadows.

> **!** Shadows are not considered for the bounding box computation by default. Large shadows may be overlaped by the following content. But, the bounding box can be adapted if necessary.

```
\tcbset{enhanced,colback=red!5!white,
  colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[title=My own shadow,
  shadow={2mm}{-1mm}{0mm}{black!50!white}]
This is a tcolorbox.
\end{tcolorbox}
\par\bigskip
\begin{tcolorbox}[title=Another shadow,
  shadow={-1mm}{-2mm}{0mm}{fill=blue,
    opacity=0.5}]
This is a tcolorbox.
\end{tcolorbox}
\par\bigskip
\begin{tcolorbox}[title=Double shadow,
  shadow={-1.5mm}{-1.5mm}{0mm}{fill=blue,
    opacity=0.25},
  shadow={1.5mm}{-1.5mm}{0mm}{fill=red,
    opacity=0.25}]
This is a tcolorbox.
\end{tcolorbox}
\par\bigskip
\begin{tcolorbox}[title=Far shadow,
  shadow={5.5mm}{-3.5mm}{2mm}{fill=black,
    opacity=0.25}]
This is a tcolorbox.
\end{tcolorbox}
\par\bigskip\bigskip
\begin{tcolorbox}[title=Halo shadow,
  shadow={0mm}{0mm}{-1.5mm}%
    {fill=yellow!75!red,opacity=0.5}]
This is a tcolorbox.
\end{tcolorbox}
```



`/tcb/fuzzy shadow={⟨xshift⟩}{⟨yshift⟩}{⟨offset⟩}{⟨step⟩}{⟨options⟩}` (no default)

Adds a new fuzzy shadow to the stack of shadows. Actually, this option adds several shadows which appear like a shadow with a fuzzy border. This fuzzy shadow follows the outline of the `tcolorbox` but is shifted by ⟨*xshift*⟩ and ⟨*yshift*⟩. The ⟨*offset*⟩ value is a distance value from the frame outline. A positive ⟨*offset*⟩ value shrinks the shadow and a negative ⟨*offset*⟩ value enlarges the shadow. The `{`⟨*step*⟩`}` value describes a shrink offset used for the combination of the partial shadows. The shadow is filled along a Ti*k*Z path with the given Ti*k*Z ⟨*options*⟩ but any `opacity` value will be ignored.

```
\tcbset{enhanced,colback=red!5!white,
  colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[title=My own shadow,
  fuzzy shadow={2mm}{-1mm}{0mm}{0.1mm}%
               {black!50!white}]
This is a tcolorbox.
\end{tcolorbox}
\par\bigskip
\begin{tcolorbox}[title=Another shadow,
  fuzzy shadow={-1mm}{-2mm}{0mm}{0.2mm}%
               {fill=blue}]
This is a tcolorbox.
\end{tcolorbox}
\par\bigskip
\begin{tcolorbox}[title=Double shadow,
  fuzzy shadow={-1.5mm}{-1.5mm}{0mm}{0.1mm}%
               {blue},
  fuzzy shadow={1.5mm}{-1.5mm}{0mm}{0.1mm}%
               {red}]
This is a tcolorbox.
\end{tcolorbox}
\par\bigskip
\begin{tcolorbox}[title=Far shadow,
  fuzzy shadow={5.5mm}{-3.5mm}{0mm}{0.3mm}%
               {black}]
This is a tcolorbox.
\end{tcolorbox}
\par\bigskip\bigskip
\begin{tcolorbox}[title=Glow shadow,
  fuzzy shadow={0mm}{0mm}{-1.5mm}{0.15mm}%
               {yellow!75!red}]
This is a tcolorbox.
\end{tcolorbox}
```

My own shadow

This is a tcolorbox.

Another shadow

This is a tcolorbox.

Double shadow

This is a tcolorbox.

Far shadow

This is a tcolorbox.

Glow shadow

This is a tcolorbox.

```
\newtcolorbox{mybox}[1][]{enhanced,
  fuzzy shadow={1.0mm}{-1.0mm}{0.12mm}{0mm}{blue!50!white},
  fuzzy shadow={-1.0mm}{-1.0mm}{0.12mm}{0mm}{red!50!white},
  fuzzy shadow={-1.0mm}{1.0mm}{0.12mm}{0mm}{green!50!white},
  fuzzy shadow={1.0mm}{1.0mm}{0.12mm}{0mm}{yellow!50!white},#1
}

\begin{mybox}[title=A multi shadow box]
This is a tcolorbox.
\end{mybox}
```

A multi shadow box

This is a tcolorbox.

N 2015-05-05 **/tcb/smart shadow arc=true|false** (default `true`, initially `true`)

If set to `true`, the shadow drawing algorithm tries to do a somewhat smart calculation of the arc for the shadow. The result is pleasing for typical boxes with rounded corners, but gives strange results for circular boxes.

```
\tcbset{enhanced,nobeforeafter,colback=red!5!white,
  colframe=red!75!black,width=3cm,square,halign=center,valign=center
  }

\begin{tcolorbox}[drop shadow]
Smart shadow arc (arguably better than normal)
\end{tcolorbox}
\hfill
\begin{tcolorbox}[smart shadow arc=false, drop shadow]
Normal shadow arc
\end{tcolorbox}
\hfill
\begin{tcolorbox}[circular arc, drop shadow]
Smart shadow arc (worse than normal)
\end{tcolorbox}
\hfill
\begin{tcolorbox}[circular arc, smart shadow arc=false, drop shadow]
Normal shadow arc
\end{tcolorbox}
```



/tcb/lifted shadow=`{`⟨*xshift*⟩`}{`⟨*yshift*⟩`}{`⟨*bend*⟩`}{`⟨*step*⟩`}{`⟨*options*⟩`}` (no default)

Adds a new lifted shadow to the stack of shadows. Actually, this option adds several shadows which appear like a shadow with a fuzzy border. This lifted shadow follows the outline of the `tcolorbox` but is shifted by ⟨*xshift*⟩ and ⟨*yshift*⟩ on the lower left corner and by −⟨*xshift*⟩ and ⟨*yshift*⟩ on the lower right corner. Additionally, there is a ⟨*bend*⟩ in the middle. The `{`⟨*step*⟩`}` value describes a shrink offset used for the combination of the partial shadows. The shadow is filled along a Ti*k*Z path with the given Ti*k*Z ⟨*options*⟩ but any `opacity` value will be ignored.

```
\tcbset{enhanced,colback=red!5!white,
  boxrule=0.1pt,
  colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[title=My own shadow,
  lifted shadow={1mm}{-2mm}{3mm}{0.1mm}%
                {black!50!white}]
This is a tcolorbox.
\end{tcolorbox}
```

10.6.4 Ti*k*Z Shadows

Alternativ to the package shadow options described before, shadows from the «Shadows Library» of Ti*k*Z can be used. Such shadows can be added directly to the frame path using `/tcb/frame style` → P. 148.

```
% \usetikzlibrary{shadows}
\begin{tcolorbox}[enhanced,
  colback=red!5!white,colframe=red!75!black,
  frame style={drop shadow} ]
  This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

```
% \usetikzlibrary{shadows}
\begin{tcolorbox}[enhanced,height=3cm,
  colback=red!5!white,colframe=red!75!black,
  halign=center,valign=center,
  frame style={circular drop shadow} ]
  This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

```
% \usetikzlibrary{shadows}
\begin{tcolorbox}[enhanced,width=2.5cm,
  square,circular arc,
  halign=center,valign=center,
  colback=red!5!white,colframe=red!75!black,
  frame style={circular glow={fill=red}} ]
  tcolorbox
\end{tcolorbox}
```

tcolorbox

10.7 TikZ Picture Option Keys

The following general options are applicable for skins which use `tikzpicture` as `/tcb/graphical environment` → P. 135. Therefore, the skin `standard` → P. 204 does not support these options, but most other skins, e. g. `enhanced` → P. 206.

`/tcb/tikz=`⟨*tikz option list*⟩ (no default, initially empty)

Adds the given ⟨*tikz option list*⟩ to the main `tikzpicture` environment used to draw the color box, see [22]. If this option is applied a second time, the new ⟨*tikz option list*⟩ is appended to the current option list.

```
\tcbset{enhanced,colback=red!5!white,
  colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[title=Transparent box,
  tikz={opacity=0.5,transparency group}]
This is a tcolorbox.
\end{tcolorbox}
```




```
\tcbset{enhanced,colback=red!5!white,
  colframe=red!75!black,fonttitle=\bfseries,
  fontupper=\bfseries\Huge,
  halign title=center,halign=center}

\begin{tcolorbox}[title=Rotated box,
  tikz={rotate=30}]
Sold!
\end{tcolorbox}
```

`/tcb/tikz reset` (initially set)

Removes all options given by `/tcb/tikz`.

`/tcb/at begin tikz=`⟨*tikz code*⟩ (no default, initially empty)

The given ⟨*tikz code*⟩ is executed at the beginning of the `tikzpicture` environment after the TikZ option `execute at begin picture` was applied. If this option is applied a second time, the new ⟨*tikz code*⟩ is appended to the current code.

`/tcb/at begin tikz reset` (initially set)

Removes all code given by `/tcb/at begin tikz`.

`/tcb/at end tikz=`⟨*tikz code*⟩ (no default, initially empty)

The given ⟨*tikz code*⟩ is executed at the ending of the `tikzpicture` environment before the TikZ option `execute at end picture` was applied. If this option is applied a second time, the new ⟨*tikz code*⟩ is appended to the current code.

`/tcb/at end tikz reset` (initially set)

Removes all code given by `/tcb/at end tikz`.

/tcb/rotate=⟨*angle*⟩ (no default, initially unset)

Rotates the `tcolorbox` by the given ⟨*angle*⟩. Note that this is a Ti*k*Z coordinate transformation i.e. not all graphical elements like shadings will really be rotated.

```
\tcbset{enhanced,colback=red!5!white,
  colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[title=Rotated box,rotate=30]
This is a tcolorbox.
\end{tcolorbox}
```



/tcb/scale=⟨*fraction*⟩ (no default, initially unset)

Scales the `tcolorbox` by the given ⟨*fraction*⟩. Note that this is a Ti*k*Z coordinate transformation i.e. not all graphical elements like line widths will really be scaled.

```
\tcbset{enhanced,colback=red!5!white,
  colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[title=Scaled box,scale=0.5]
This is a tcolorbox.
\end{tcolorbox}
\begin{tcolorbox}[title=Scaled box,scale=1.25]
This is a tcolorbox.
\end{tcolorbox}
```



/tcb/remember (style, initially unset)

Shortcut for `tikz={remember picture}`. This allows one to reference nodes in other Ti*k*Z pictures.

```
\begin{tcolorbox}[enhanced,remember,colback=red!5!white,colframe=red!75!black,
  fonttitle=\bfseries,title=The four corners of a paper,
  overlay={\draw[red!50!white,line width=1mm,opacity=0.5,shorten >=3mm]
    (frame.north west) edge[->] (current page.north west)
    (frame.north east) edge[->] (current page.north east)
    (frame.south west) edge[->] (current page.south west)
    (frame.south east) edge[->] (current page.south east);}]
This is a tcolorbox.
\end{tcolorbox}
```

`/tcb/remember as=`⟨*name*⟩ (style, no default, initially unset)

The `frame` node will be remembered by the given ⟨*name*⟩ to be referenced in other TikZ pictures.

```
% \usepackage{lipsum}
\newtcolorbox{mybox}[1][]{enhanced,colframe=blue!75!black,colback=blue!10!white,
  fonttitle=\bfseries,#1}

\begin{mybox}[title=First Box,nobeforeafter,width=\linewidth/4,remember as=one]
This is a test.
\end{mybox}
\hfill
\begin{mybox}[title=Second Box,nobeforeafter,width=\linewidth/4,remember as=two]
This is a test.
\end{mybox}
\hfill
\begin{mybox}[title=Third Box,nobeforeafter,width=\linewidth/4,remember as=three]
This is a test.
\end{mybox}

\lipsum[2]

\begin{mybox}[title=Fourth Box,remember as=four]
This is a test.
\end{mybox}

\begin{tikzpicture}[overlay,remember picture,line width=1mm,draw=red!75!black]
  \draw[->] (one.east) to[bend right] node[above] {A} (two.west);
  \draw[->] (two.east) to[bend left] node[above] {B} (three.west);
  \draw[->] (three.east) to[bend left=90] node[right] {C} (four.east);
  \draw[->] (four.west) to[bend left=90] node[left] {D} (one.west);
\end{tikzpicture}
```



10.8 Underlay Option Keys

Underlays are quite similar to overlays described in Section 4.12 on page 71. Underlays are drawn *after* the frame and interior are drawn and *before* overlays and the text content is drawn; see Section 9.4 on page 142 for the general drawing scheme.

The differences between underlays and overlays are:

- Underlays are not applicable for the skins `standard` → P. 204 and `standard jigsaw` → P. 205, whereas overlays are applicable also for these skins. The skin `spartan` → P. 247 supports underlays but no overlays.

  ! If an underlay is used with the `standard` → P. 204 skin, it is silently ignored.

- Underlays are stackable, i. e. several different underlays can be used on the same `tcolorbox`. Overlays are not stackable by default (but with some help of the library LIB hooks).
- Boxed titles are implemented with underlays (Section 10.2 on page 155), watermarks are implemented with overlays (Section 10.3 on page 165).

`/tcb/underlay`=⟨*graphical code*⟩ (no default, initially unset)

Adds ⟨*graphical code*⟩ to the box drawing process. This ⟨*graphical code*⟩ is drawn *after* the frame and interior and *before* the text content.

```
\newtcolorbox{mybox}[1][]{enhanced,colback=red!5!white,
  colbacktitle=red!85!black!50!white,
  colframe=red!75!black,fonttitle=\bfseries,watermark color=yellow!50!white,
  underlay={\begin{tcbclipinterior}
    \draw[red!40!white,line width=1cm] (interior.south west)--(interior.north east);
    \end{tcbclipinterior}},
  attach boxed title to top center={yshift=-2mm},#1}

\begin{mybox}[title=My box,watermark text=My Watermark]
\lipsum[2]
\end{mybox}
```

My box

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

My Watermark

`/tcb/no underlay` (style, no default, initially set)

Removes the underlay if set before.

`/tcb/underlay broken`=⟨*graphical code*⟩ (no default, initially unset)

If the box is set to be `/tcb/breakable` →P. 365 and *is* broken actually, then the ⟨*graphical code*⟩ is added to the box drawing process. `/tcb/underlay` →P. 195 overwrites this key.

`/tcb/underlay unbroken`=⟨*graphical code*⟩ (no default, initially unset)

If the box is set to be `/tcb/breakable` →P. 365 but *is not* broken actually or if the box is set to be `/tcb/unbreakable` →P. 366, then the ⟨*graphical code*⟩ is added to the box drawing process. `/tcb/underlay` →P. 195 overwrites this key.

`/tcb/no underlay unbroken` (style, no default, initially set)

Removes the unbroken underlay if set before.

`/tcb/underlay first`=⟨*graphical code*⟩ (no default, initially unset)

If the box is set to be `/tcb/breakable` →P. 365 and *is* broken actually, then the ⟨*graphical code*⟩ is added to the box drawing process for the *first* part of the break sequence. `/tcb/underlay` →P. 195 overwrites this key.

`/tcb/no underlay first` (style, no default, initially set)

Removes the first underlay if set before.

`/tcb/underlay middle`=⟨*graphical code*⟩ (no default, initially unset)

If the box is set to be `/tcb/breakable` →P. 365 and *is* broken actually, then the ⟨*graphical code*⟩ is added to the box drawing process for the *middle* parts (if any) of the break sequence. `/tcb/underlay` →P. 195 overwrites this key.

`/tcb/no underlay middle` (style, no default, initially set)

Removes the middle underlay if set before.

`/tcb/underlay last`=⟨*graphical code*⟩ (no default, initially unset)

If the box is set to be `/tcb/breakable` →P. 365 and *is* broken actually, then the ⟨*graphical code*⟩ is added to the box drawing process for the *last* part of the break sequence. `/tcb/underlay` →P. 195 overwrites this key.

`/tcb/no underlay last` (style, no default, initially set)

Removes the last underlay if set before.

`/tcb/underlay boxed title`=⟨*graphical code*⟩ (no default, initially unset)

If the box has a *boxed title*, see Section 10.2 on page 155, then the ⟨*graphical code*⟩ is added to the box drawing process *before* the boxed title is drawn.

`/tcb/no underlay boxed title` (style, no default, initially set)

Removes the boxed title underlay if set before.

`/tcb/underlay unbroken and first`=⟨*graphical code*⟩ (no default, initially unset)

This is an abbreviation for setting `/tcb/underlay unbroken` and `/tcb/underlay first` together. `/tcb/underlay` →P. 195 overwrites this key.

`/tcb/underlay middle and last`=⟨*graphical code*⟩ (no default, initially unset)

This is an abbreviation for setting `/tcb/underlay middle` and `/tcb/underlay last` together. `/tcb/underlay` →P. 195 overwrites this key.

`/tcb/underlay unbroken and last`=⟨*graphical code*⟩ (no default, initially unset)

This is an abbreviation for setting `/tcb/underlay unbroken` and `/tcb/underlay last` together. `/tcb/underlay` →P. 195 overwrites this key.

N 2014-09-19 `/tcb/underlay first and middle`=⟨*graphical code*⟩ (no default, initially unset)

This is an abbreviation for setting `/tcb/underlay first` and `/tcb/underlay middle` together. `/tcb/underlay` →P. 195 overwrites this key.

10.9 Finish Option Keys

Finishes are quite similar to underlays described in Section 10.8 on page 195 and overlays described in Section 4.12 on page 71. Finishes are drawn *after* the text content is drawn; see Section 9.4 on page 142 for the general drawing scheme. Therefore, a finish will reduce the readability of the text content.

Finishes are intended for special effects like highlights or glosses or text over text.

- Finishes are only applicable for the skins `enhanced`→ P. 206, `empty`→ P. 237, `freelance`→ P. 250, `bicolor`→ P. 219, `beamer`→ P. 228, and `widget`→ P. 233.

  ! If a finish is used with the `standard`→ P. 204 skin, it is silently ignored.

- Finishes are stackable, i. e. several different finishes can be used on the same `tcolorbox`.

`/tcb/finish`=⟨*graphical code*⟩ (no default, initially unset)

Adds ⟨*graphical code*⟩ to the box drawing process. This ⟨*graphical code*⟩ is drawn *after* the text content.

```
\newtcolorbox{mybox}[1][]{enhanced,colback=red!5!white,
  colbacktitle=red!85!black!50!white,colframe=red!75!black,fonttitle=\bfseries,
  finish={\begin{tcbclipframe}
    \path[bottom color=black,top color=black!50!white,opacity=0.1]
      (frame.south west) -- (frame.south east) -- (frame.north east) -- cycle;
    \path[top color=white,bottom color=black!50!white,opacity=0.1]
      (frame.south west) -- (frame.north east) -- (frame.north west) -- cycle;
    \end{tcbclipframe}},#1}

\begin{mybox}[title=My box]
\lipsum[2]
\end{mybox}
```

My box

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

```
\newtcolorbox{mybox}[1][]{enhanced,colback=red!5!white,
  colbacktitle=red!85!black!50!white,colframe=red!75!black,fonttitle=\bfseries,
  finish={\node[draw,fill=white,fill opacity=0.85,inner sep=5mm,
    rounded corners] at (frame.center) {\Huge\bfseries Finish!};},#1}

\begin{mybox}[title=My box]
\lipsum[2]
\end{mybox}
```

My box

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Finish!

`/tcb/no finish` (style, no default, initially set)

Removes the finish if set before.

`/tcb/finish broken`=⟨*graphical code*⟩ (no default, initially unset)

If the box is set to be `/tcb/breakable` → P. 365 and *is* broken actually, then the ⟨*graphical code*⟩ is added to the box drawing process. `/tcb/finish` → P. 197 overwrites this key.

`/tcb/finish unbroken`=⟨*graphical code*⟩ (no default, initially unset)

If the box is set to be `/tcb/breakable` → P. 365 but *is not* broken actually or if the box is set to be `/tcb/unbreakable` → P. 366, then the ⟨*graphical code*⟩ is added to the box drawing process. `/tcb/finish` → P. 197 overwrites this key.

`/tcb/no finish unbroken` (style, no default, initially set)

Removes the unbroken finish if set before.

`/tcb/finish first`=⟨*graphical code*⟩ (no default, initially unset)

If the box is set to be `/tcb/breakable` → P. 365 and *is* broken actually, then the ⟨*graphical code*⟩ is added to the box drawing process for the *first* part of the break sequence. `/tcb/finish` → P. 197 overwrites this key.

`/tcb/no finish first` (style, no default, initially set)

Removes the first finish if set before.

`/tcb/finish middle`=⟨*graphical code*⟩ (no default, initially unset)

If the box is set to be `/tcb/breakable` → P. 365 and *is* broken actually, then the ⟨*graphical code*⟩ is added to the box drawing process for the *middle* parts (if any) of the break sequence. `/tcb/finish` → P. 197 overwrites this key.

`/tcb/no finish middle` (style, no default, initially set)

Removes the middle finish if set before.

`/tcb/finish last`=⟨*graphical code*⟩ (no default, initially unset)

If the box is set to be `/tcb/breakable` → P. 365 and *is* broken actually, then the ⟨*graphical code*⟩ is added to the box drawing process for the *last* part of the break sequence. `/tcb/finish` → P. 197 overwrites this key.

`/tcb/no finish last` (style, no default, initially set)

Removes the last finish if set before.

`/tcb/finish unbroken and first`=⟨*graphical code*⟩ (no default, initially unset)

This is an abbreviation for setting `/tcb/finish unbroken` and `/tcb/finish first` together. `/tcb/finish` → P. 197 overwrites this key.

`/tcb/finish middle and last`=⟨*graphical code*⟩ (no default, initially unset)

This is an abbreviation for setting `/tcb/finish middle` and `/tcb/finish last` together. `/tcb/finish` → P. 197 overwrites this key.

`/tcb/finish unbroken and last`=⟨*graphical code*⟩ (no default, initially unset)

This is an abbreviation for setting `/tcb/finish unbroken` and `/tcb/finish last` together. `/tcb/finish` → P. 197 overwrites this key.

N 2014-09-19 `/tcb/finish first and middle`=⟨*graphical code*⟩ (no default, initially unset)

This is an abbreviation for setting `/tcb/finish first` and `/tcb/finish middle` together. `/tcb/finish` → P. 197 overwrites this key.

10.10 Hyper Option Keys

All options of this section need the package `hyperref` [15] to be loaded separately. All these options are implemented as `/tcb/finish` → P. 197 and can be disabled by `/tcb/no finish` → P. 198.

> **!** If the package `hyperref` [15] is not loaded or if the `standard` → P. 204 skin is used, all hyper option are silently ignored.

N 2017-02-03 **`/tcb/hyperref`=⟨*marker*⟩** (no default, initially unset)

The whole *frame* of a `tcolorbox` is make an active hyperlink for a ⟨*marker*⟩ which was given by `\label` or `/tcb/label` → P. 98 or `/tcb/phantomlabel` → P. 98. Such, the `tcolorbox` is made a clickable button (depending on the previewer).

```
% \section{Library skins}\label{sec:skins}%
\begin{tcolorbox}[beamer,colback=red!50,
  hyperref=sec:skins]
Jump to the heading of Section~\ref*{sec:skins}.
\end{tcolorbox}
```

Jump to the heading of Section 10.

N 2017-02-03 **`/tcb/hyperref interior`=⟨*marker*⟩** (no default, initially unset)

Identical to `/tcb/hyperref`, but only the *interior* of a `tcolorbox` is made a hyperlink (without frame and title).

N 2017-02-03 **`/tcb/hyperref title`=⟨*marker*⟩** (no default, initially unset)

Identical to `/tcb/hyperref`, but only the *title* of a `tcolorbox` is made a hyperlink.

N 2017-02-03 **`/tcb/hyperref node`={⟨*marker*⟩}{⟨*node*⟩}** (no default, initially unset)

Identical to `/tcb/hyperref`, but only the given Ti*k*Z ⟨*node*⟩ is made a hyperlink. This ⟨*node*⟩ may be `frame`, `interior`, `title`, or any other named node used for drawing the `tcolorbox`. The ⟨*node*⟩ may be defined inside `/tcb/underlay` → P. 195, `/tcb/overlay` → P. 71 or `/tcb/finish` → P. 197. If the later is used, define the node *before* `/tcb/hyperref node` is applied.

```
% \section{Library skins}\label{sec:skins}%
\begin{tcolorbox}[enhanced,colback=yellow!10,
  underlay={\node[red,fill=red!30,inner sep=3mm]
    (click) at (frame.center) {X};},
  hyperref node={sec:skins}{click}]
Jump to the heading of Section~\ref*{sec:skins}
(X marks the click point).
\end{tcolorbox}
```

Jump to the heading of Section 10 (X marks the click point).

N 2017-02-03 **`/tcb/hyperlink`=⟨*marker*⟩** (no default, initially unset)

The whole *frame* of a `tcolorbox` is make an active hyperlink for a ⟨*marker*⟩ which was given by `\hypertarget` or `/tcb/hypertarget` → P. 100. Such, the `tcolorbox` is made a clickable button (depending on the previewer).

```
% \usepackage{hyperref}%
\begin{tcolorbox}[enhanced,
  colback=blue!10,colframe=blue!50!black,
  hypertarget=hypertwinB,
  hyperlink=hypertwinA,
  title=Box B]
Click me to jump to Box A.
\end{tcolorbox}
```

Box B

Click me to jump to Box A.

N 2017-02-03 **/tcb/hyperlink interior=**⟨*marker*⟩ (no default, initially unset)

Identical to /tcb/hyperlink → P. 199, but only the *interior* of a `tcolorbox` is made a hyperlink (without frame and title).

N 2017-02-03 **/tcb/hyperlink title=**⟨*marker*⟩ (no default, initially unset)

Identical to /tcb/hyperlink → P. 199, but only the *title* of a `tcolorbox` is made a hyperlink.

N 2017-02-03 **/tcb/hyperlink node=**{⟨*marker*⟩}{⟨*node*⟩} (no default, initially unset)

Identical to /tcb/hyperlink → P. 199, but only the given Ti*k*Z ⟨*node*⟩ is made a hyperlink. This ⟨*node*⟩ may be `frame`, `interior`, `title`, or any other named node used for drawing the `tcolorbox`. The ⟨*node*⟩ may be defined inside /tcb/underlay → P. 195, /tcb/overlay → P. 71 or /tcb/finish → P. 197. If the later is used, define the node *before* /tcb/hyperlink node is applied.

N 2017-02-03 **/tcb/hyperurl=**⟨*url*⟩ (no default, initially unset)

The whole *frame* of a `tcolorbox` is make an active hyperlink for an ⟨*url*⟩ in the same manner as using `\href` or `\url`. Such, the `tcolorbox` is made a clickable button (depending on the previewer).

```
\begin{tcolorbox}[enhanced,colback=red!50,
  hyperurl=http://www.ctan.org/pkg/tcolorbox]
View CTAN with a browser.
\end{tcolorbox}
```

View CTAN with a browser.

N 2017-02-03 **/tcb/hyperurl interior=**⟨*url*⟩ (no default, initially unset)

Identical to /tcb/hyperurl, but only the *interior* of a `tcolorbox` is made a hyperlink (without frame and title).

N 2017-02-03 **/tcb/hyperurl title=**⟨*url*⟩ (no default, initially unset)

Identical to /tcb/hyperurl, but only the *title* of a `tcolorbox` is made a hyperlink.

N 2017-02-03 **/tcb/hyperurl node=**{⟨*url*⟩}{⟨*node*⟩} (no default, initially unset)

Identical to /tcb/hyperurl, but only the given Ti*k*Z ⟨*node*⟩ is made a hyperlink. This ⟨*node*⟩ may be `frame`, `interior`, `title`, or any other named node used for drawing the `tcolorbox`. The ⟨*node*⟩ may be defined inside /tcb/underlay → P. 195, /tcb/overlay → P. 71 or /tcb/finish → P. 197. If the later is used, define the node *before* /tcb/hyperurl node is applied.

N 2017-02-03 **/tcb/hyperurl*=**{⟨*options*⟩}{⟨*url*⟩} (no default, initially unset)

Identical to /tcb/hyperurl, but additional `hyperref` [15] ⟨*options*⟩ are applied.

```
\begin{tcolorbox}[enhanced,colback=green!50,
  hyperurl*={page=3,pdfnewwindow=true}%
            {tcolorbox-example.pdf}]
Open example file on Page~3.
\end{tcolorbox}
```

Open example file on Page 3.

N 2017-02-03 **/tcb/hyperurl* interior=**{⟨*options*⟩}{⟨*url*⟩} (no default, initially unset)

Identical to /tcb/hyperurl interior, but additional `hyperref` [15] ⟨*options*⟩ are applied.

N 2017-02-03 **/tcb/hyperurl* title=**{⟨*options*⟩}{⟨*url*⟩} (no default, initially unset)

Identical to /tcb/hyperurl title, but additional `hyperref` [15] ⟨*options*⟩ are applied.

N 2017-02-03 **/tcb/hyperurl* node=**{⟨*options*⟩}{⟨*url*⟩}{⟨*node*⟩} (no default, initially unset)

Identical to /tcb/hyperurl node, but additional `hyperref` [15] ⟨*options*⟩ are applied.

10.11 Jigsaw Skin Variants

As described in Section 9.1 on page 134, a `tcolorbox` is drawn by up to four *engines*. Typically, the *frame* engine fills the complete box area with color and the other engines fill certain areas with other colors. Finally, only the area which you see as *frame* of the box will display the frame color. For most applications, this is a good approach.

For certain boxes, a more delicate procedure is needed. E.g., if the box should be translucent, an already painted area cannot be made unpainted. Therefore, more elaborate frame engines saw holes into the frame where the interior area and optionally the title area will be painted. The resulting skins are called *jigsaw* skins. For `standard` → P. 204 and `enhanced` → P. 206, there are variants called `standard jigsaw` → P. 205 and `enhanced jigsaw` → P. 213.

```
\newcommand{\ballexample}{\begin{tikzpicture}
  \path[use as bounding box] (0,0.8) rectangle +(0.1,0.1);
  \shadedraw [shading=ball] (0,0) circle (1cm);
  \shadedraw [ball color=red] (3,-2.2) circle (1cm);
\end{tikzpicture}}

\tcbset{enhanced,colback=blue!5!white,
  frame style={left color=red!75!black,right color=red!10!yellow},
  fonttitle=\bfseries }

\ballexample

\begin{tcolorbox}[title=A normal box]
  \lipsum[2]
\end{tcolorbox}

\ballexample

\begin{tcolorbox}[title=A translucent jigsaw box,
  enhanced jigsaw,opacityback=0.35]
  \lipsum[2]
\end{tcolorbox}
```



```
\tcbset{enhanced,colback=red!10!white,coltitle=black,
  frame style={left color=red!75!black,right color=red!10!yellow},
  fonttitle=\bfseries,interior hidden,title hidden}

\begin{tcolorbox}[title=A normal box with hidden interior and title]
  This is a tcolorbox.
\end{tcolorbox}

\begin{tcolorbox}[enhanced jigsaw,
  title=A jigsaw box with hidden interior and title]
  This is a tcolorbox.
\end{tcolorbox}
```

A normal box with hidden interior and title

This is a tcolorbox.

A jigsaw box with hidden interior and title

This is a tcolorbox.

```
\newtcolorbox{mybox}{skin=enhancedmiddle jigsaw,leftrule=5mm,rightrule=5mm,
  boxsep=0mm,top=0mm,bottom=0mm,
  frame style={top color=blue,bottom color=red},interior hidden}

\begin{mybox}
  \lipsum[2]
\end{mybox}
```

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

10.12 Draft Mode

To reduce the compiliation time while drafting a document, the *draft mode* can be applied. Basically, it changes all skins to `spartan` → P. 247 and sets the `/tcb/fit algorithm` → P. 418 to `squeeze`. Especially, when fuzzy shadows are used, the speedup will be considerable high.

> **!** It is strongly recommended that the draft mode is *not* used for the final document. Use `spartan` → P. 247 directly, if you want to stay with it. The draft mode implementation may change in future.

> **!** Normally, switching to the draft mode should not alter the geometry of your document. Since overlays are deactivated, any code placed there (e.g. counter changes) is not executed anymore! Also, `/tcb/remember as` → P. 194 will not have any effect. You may exclude critical code with `\tcbinterruptdraftmode` / `\tcbcontinuedraftmode` from converting to draft mode.

`\tcbstartdraftmode`

Any following `tcolorbox` code is put into *draft mode*. All skin settings are overruled with `spartan` → P. 247. Overlays, watermarks, shadows, borderlines, and rounded corners are deactivated for all `tcolorbox` layers.

`\tcbstopdraftmode`

The *draft mode* is deactivated for the following code.

`\tcbinterruptdraftmode`

If the compilation is in *draft mode*, the *draft mode* is deactivated until a following `\tcbcontinuedraftmode` is detected.

If the compilation is not in *draft mode*, nothing happens and a following `\tcbcontinuedraftmode` will not start the *draft mode*.

> **!** The pair `\tcbinterruptdraftmode` and `\tcbcontinuedraftmode` cannot be used nested.

`\tcbcontinuedraftmode`

Continues the *draft mode* which was suspended by a preceding `\tcbinterruptdraftmode`. Nothing happens, if there was no draft mode before `\tcbinterruptdraftmode`.

> **!** Code, which is place between `\tcbinterruptdraftmode` and `\tcbcontinuedraftmode` is shielded from *draft mode*.

`/tcb/draftmode=true|false` (default `true`, initially `false`)

If set to `true`, the *draft mode* is started. If set to `false`, the *draft mode* is stopped.

```
\newtcolorbox{mybeamer}[2][]{beamer,colback=Salmon!50!white,
  colframe=FireBrick!75!black,adjusted title={#2},#1}

\begin{mybeamer}{Beamer box}
This box looks like a box provided by the \texttt{beamer} class.
\end{mybeamer}\par\medskip
\begin{mybeamer}[draftmode]{Beamer box}
This box looks like a box provided by the \texttt{beamer} class.
\end{mybeamer}
```

Beamer box

This box looks like a box provided by the `beamer` class.

Beamer box

This box looks like a box provided by the `beamer` class.

10.13 Skin Family 'standard'

Note that the option keys /tcb/frame style → P. 148, /tcb/interior style → P. 149, /tcb/segmentation style → P. 151, and /tcb/title style → P. 151 are not be applicable to the standard skin. Also, watermarks (see Subsection 10.3) are not usable with the standard skin.

/tcb/skin=standard (skin)

This is the standard skin from the core package. All drawing engines are set to type `standard`. The drawing is based on `pgf` commands and does not need the `tikz` package.

Environment and engines for the skin 'standard'

/tcb/graphical environment → P. 135:	pgfpicture
/tcb/frame engine → P. 135:	standard
/tcb/interior titled engine → P. 135:	standard
/tcb/interior engine → P. 136:	standard
/tcb/segmentation engine → P. 136:	standard
/tcb/title engine → P. 136:	standard

/tcb/standard (style, no value)

This is an abbreviation for setting `skin=standard`.

```
\begin{tcbraster}[standard,raster equal height,raster columns=4,
    colback=LightGreen,colframe=DarkGreen,colbacktitle=LimeGreen!75!DarkGreen,
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
  \begin{tcolorbox}
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

/tcb/skin=standard jigsaw (skin)

This is the standard jigsaw skin from the core package. It differs from the skin standard → P. 204 by its frame engine, see Section 10.11 on page 201.

Environment and engines for the skin 'standard jigsaw'

/tcb/graphical environment → P. 135:	pgfpicture
/tcb/frame engine → P. 135:	standardjigsaw
/tcb/interior titled engine → P. 135:	standard
/tcb/interior engine → P. 136:	standard
/tcb/segmentation engine → P. 136:	standard
/tcb/title engine → P. 136:	standard

/tcb/standard jigsaw (style, no value)

This is an abbreviation for setting skin=standard jigsaw.

```
\begin{tcbraster}[standard jigsaw,raster equal height,raster columns=4,
    colback=LightGreen,colframe=DarkGreen,colbacktitle=LimeGreen!75!DarkGreen,
    opacityframe=0.5,opacityback=0.5,opacitybacktitle=0.5,
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
  \begin{tcolorbox}
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

10.14 Skin Family 'enhanced'

If you like the standard appearance of a `tcolorbox` but you want to have some 'enhanced' features, the `enhanced` skin is what you are looking for.

`/tcb/skin=enhanced` (skin)

This skin translates the drawing commands of the core package into `tikz` path commands. Therefore, it allows all `tikz` high level options for these paths and has more flexibility compared to the `standard` → P. 204 skin. You pay for this with some prolonged compilation time. The `tikz` path options can be given with the option keys `/tcb/frame style` → P. 148, `/tcb/interior style` → P. 149, `/tcb/segmentation style` → P. 151, and `/tcb/title style` → P. 151.

Environment and engines for the skin 'enhanced'

`/tcb/graphical environment` → P. 135:	`tikzpicture`
`/tcb/frame engine` → P. 135:	`path`
`/tcb/interior titled engine` → P. 135:	`path`
`/tcb/interior engine` → P. 136:	`path`
`/tcb/segmentation engine` → P. 136:	`path`
`/tcb/title engine` → P. 136:	`path`

`/tcb/enhanced` (style, no value)

This is an abbreviation for setting `skin=enhanced`.

```
\begin{tcbraster}[enhanced,raster equal height,raster columns=4,
    colback=LightGreen,colframe=DarkGreen,colbacktitle=LimeGreen!75!DarkGreen,
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
  \begin{tcolorbox}
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

```
% \usetikzlibrary{shadings}          % preamble
\tcbset{skin=enhanced,fonttitle=\bfseries,
  frame style={upper left=blue,upper right=red,lower left=yellow,lower right=green},
  interior style={white,opacity=0.5},
  segmentation style={black,solid,opacity=0.2,line width=1pt}}

\begin{tcolorbox}[title=Nice box in rainbow colors]
  With the 'enhanced' skin, it is quite easy to produce fancy looking effects.
  \tcblower
  Note that this is still a \texttt{tcolorbox}.
\end{tcolorbox}
```

Nice box in rainbow colors

With the 'enhanced' skin, it is quite easy to produce fancy looking effects.

Note that this is still a `tcolorbox`.

```
% \usetikzlibrary{decorations.pathmorphing} % preamble
\tcbset{skin=enhanced,fonttitle=\bfseries,boxrule=1mm,
  frame style={draw=FireBrick,fill=Salmon},drop fuzzy shadow,
  interior style={draw=FireBrick,top color=Salmon!10,bottom color=Salmon!20},
  segmentation style={draw=FireBrick,solid,decorate,
        decoration={coil,aspect=0,segment length=10.1mm}}}

\begin{tcblisting}{title=A listing box with shadow and some specials}
Of course, skins can be used for listings also.
\begin{equation}
  \int\limits_1^2 \frac{1}{x}~dx = \ln(2).
\end{equation}
\end{tcblisting}
```

A listing box with shadow and some specials

```
Of course, skins can be used for listings also.
\begin{equation}
  \int\limits_1^2 \frac{1}{x}~dx = \ln(2).
\end{equation}
```

Of course, skins can be used for listings also.

$$\int_1^2 \frac{1}{x}\,dx = \ln(2). \tag{2}$$

`/tcb/enhanced standard` (style, no value)

For unbreakable boxes, this is identical to using `/tcb/enhanced` → P. 206. But, for breakable boxes, the *break sequence* is identical to the `standard` → P. 204 skin, see Section 17.8 from page 377.

`/tcb/blank` (style, initially unset)

This style relies on the skin `enhanced` → P. 206. All drawing operations are hidden and all margins are set to `0pt`. See `/tcb/blanker` → P. 238 for switching off the drawing engines.

```
\begin{tcolorbox}[blank,watermark text=A blank box]
\lipsum[1]
\end{tcolorbox}
```

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

A blank box

\tcbline

Sometimes, a line is only a line. With \tcblower → P. 12 you separate the box content into two functional units. \tcbline draws only a line which looks like the segmentation line between upper and lower part. Furthermore, you can use \tcbline more than just once. \tcbline always uses the path drawing engine. Therefore, the /tcb/segmentation style → P. 151 can be applied.

```
\tcbset{enhanced,colframe=blue!50!black,colback=white}

\begin{tcolorbox}[colupper=red!50!black,collower=green!50!black]
\lipsum[1]
\tcbline
\lipsum[2]
\tcblower
\lipsum[3]
\tcbline
\lipsum[4]
\end{tcolorbox}
```

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

\tcbline*

Equivalent to \tcbline, but in a breakable box, \tcbline* is removed if at a page/box break. Also, it is removed at the end of a box.

/tcb/skin=enhancedfirst (skin)

This is a flavor of enhanced → P. 206 which is used as a *first* part in a break sequence for enhanced → P. 206. Nevertheless, this skin can be applied independently.

Environment and engines for the skin 'enhancedfirst'

/tcb/graphical environment → P. 135:	tikzpicture
/tcb/frame engine → P. 135:	pathfirst
/tcb/interior titled engine → P. 135:	pathfirst
/tcb/interior engine → P. 136:	pathfirst
/tcb/segmentation engine → P. 136:	path
/tcb/title engine → P. 136:	pathfirst

```
\begin{tcbraster}[skin=enhancedfirst,raster equal height,raster columns=4,
    colback=LightGreen,colframe=DarkGreen,colbacktitle=LimeGreen!75!DarkGreen,
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
  \begin{tcolorbox}
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

/tcb/skin=enhancedmiddle (skin)

This is a flavor of enhanced → P. 206 which is used as a *middle* part in a break sequence for enhanced → P. 206. Nevertheless, this skin can be applied independently.

Environment and engines for the skin 'enhancedmiddle'

/tcb/graphical environment → P. 135:	tikzpicture
/tcb/frame engine → P. 135:	pathmiddle
/tcb/interior titled engine → P. 135:	pathmiddle
/tcb/interior engine → P. 136:	pathmiddle
/tcb/segmentation engine → P. 136:	path
/tcb/title engine → P. 136:	pathmiddle

```
\begin{tcbraster}[skin=enhancedmiddle,raster equal height,raster columns=4,
    colback=LightGreen,colframe=DarkGreen,colbacktitle=LimeGreen!75!DarkGreen,
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
  \begin{tcolorbox}
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

/tcb/skin=enhancedlast (skin)

This is a flavor of enhanced → P. 206 which is used as a *last* part in a break sequence for enhanced → P. 206. Nevertheless, this skin can be applied independently.

Environment and engines for the skin 'enhancedlast'

/tcb/graphical environment → P. 135:	tikzpicture
/tcb/frame engine → P. 135:	pathlast
/tcb/interior titled engine → P. 135:	pathlast
/tcb/interior engine → P. 136:	pathlast
/tcb/segmentation engine → P. 136:	path
/tcb/title engine → P. 136:	pathlast

```
\begin{tcbraster}[skin=enhancedlast,raster equal height,raster columns=4,
    colback=LightGreen,colframe=DarkGreen,colbacktitle=LimeGreen!75!DarkGreen,
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
  \begin{tcolorbox}
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

/tcb/skin=enhanced jigsaw (skin)

This is the jigsaw variant of skin enhanced → P. 206. It differs by its frame engine, see Section 10.11 on page 201.

Environment and engines for the skin 'enhanced jigsaw'

/tcb/graphical environment → P. 135:	tikzpicture
/tcb/frame engine → P. 135:	pathjigsaw
/tcb/interior titled engine → P. 135:	path
/tcb/interior engine → P. 136:	path
/tcb/segmentation engine → P. 136:	path
/tcb/title engine → P. 136:	path

/tcb/enhanced jigsaw (style, no value)

This is an abbreviation for setting skin=enhanced jigsaw.

```
\begin{tcbraster}[enhanced jigsaw,raster equal height,raster columns=4,
    colback=LightGreen,colframe=DarkGreen,colbacktitle=LimeGreen!75!DarkGreen,
    opacityframe=0.5,opacityback=0.5,opacitybacktitle=0.5,
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
  \begin{tcolorbox}
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

N 2017-07-01 /tcb/enhanced standard jigsaw (style, no value)

For unbreakable boxes, this is identical to using /tcb/enhanced jigsaw. But, for breakable boxes, the *break sequence* is identical to the standard jigsaw → P. 205 skin, see Section 17.8 from page 377.

/tcb/skin=enhancedfirst jigsaw (skin)

This is the jigsaw variant of skin enhancedfirst → P. 210. It differs by its frame engine, see Section 10.11 on page 201.

Environment and engines for the skin 'enhancedfirst jigsaw'

/tcb/graphical environment → P. 135:	tikzpicture
/tcb/frame engine → P. 135:	pathfirstjigsaw
/tcb/interior titled engine → P. 135:	pathfirst
/tcb/interior engine → P. 136:	pathfirst
/tcb/segmentation engine → P. 136:	path
/tcb/title engine → P. 136:	pathfirst

```
\begin{tcbraster}[skin=enhancedfirst jigsaw,raster equal height,raster columns=4,
    colback=LightGreen,colframe=DarkGreen,colbacktitle=LimeGreen!75!DarkGreen,
    opacityframe=0.5,opacityback=0.5,opacitybacktitle=0.5,
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
  \begin{tcolorbox}
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

/tcb/skin=enhancedmiddle jigsaw (skin)

This is the jigsaw variant of skin enhancedmiddle → P. 211. It differs by its frame engine, see Section 10.11 on page 201.

Environment and engines for the skin 'enhancedmiddle jigsaw'

/tcb/graphical environment → P. 135:	tikzpicture
/tcb/frame engine → P. 135:	pathmiddlejigsaw
/tcb/interior titled engine → P. 135:	pathmiddle
/tcb/interior engine → P. 136:	pathmiddle
/tcb/segmentation engine → P. 136:	path
/tcb/title engine → P. 136:	pathmiddle

```
\begin{tcbraster}[skin=enhancedmiddle jigsaw,raster equal height,raster columns=4,
    colback=LightGreen,colframe=DarkGreen,colbacktitle=LimeGreen!75!DarkGreen,
    opacityframe=0.5,opacityback=0.5,opacitybacktitle=0.5,
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
  \begin{tcolorbox}
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

/tcb/marker (style, no value)

This styles relies on the skin enhancedmiddle jigsaw. It is intended to be used as an optical marker like a highlighter pen.

```
\begin{tcolorbox}[marker]
\lipsum[2]
\end{tcolorbox}
```

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

This examples demonstrates the creation of several *text marker* environments based on `enhancedmiddle` → P. 211.

```
\tcbset{textmarker/.style={%
    skin=enhancedmiddle jigsaw,breakable,parbox=false,
    boxrule=0mm,leftrule=5mm,rightrule=5mm,boxsep=0mm,arc=0mm,outer arc=0mm,
    left=3mm,right=3mm,top=1mm,bottom=1mm,toptitle=1mm,bottomtitle=1mm,oversize}}

\newtcolorbox{yellow}{textmarker,colback=yellow!5!white,colframe=yellow}
\newtcolorbox{orange}{textmarker,colback=DarkOrange!5!white,
                      colframe=DarkOrange!75!yellow}
\newtcolorbox{red}{textmarker,colback=red!5!white,colframe=red}
\newtcolorbox{blue}{textmarker,colback=DeepSkyBlue!5!white,colframe=DeepSkyBlue}
\newtcolorbox{green}{textmarker,colback=Chartreuse!5!white,colframe=Chartreuse}
\newtcolorbox{rainbow}{textmarker,interior hidden,
  frame style={top color=blue,bottom color=red,middle color=green}}

\begin{yellow}
  \lipsum[1-3]
\end{yellow}

\begin{orange}
  \lipsum[4]
\end{orange}

\begin{red}
  \lipsum[5]
\end{red}

\begin{green}
  \lipsum[6]
\end{green}

\begin{blue}
  \lipsum[7]
\end{blue}

\begin{rainbow}
  \lipsum[8]
\end{rainbow}
```

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique,

libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

Fusce mauris. Vestibulum luctus nibh at lectus. Sed bibendum, nulla a faucibus semper, leo velit ultricies tellus, ac venenatis arcu wisi vel nisl. Vestibulum diam. Aliquam pellentesque, augue quis sagittis posuere, turpis lacus congue quam, in hendrerit risus eros eget felis. Maecenas eget erat in sapien mattis porttitor. Vestibulum porttitor. Nulla facilisi. Sed a turpis eu lacus commodo facilisis. Morbi fringilla, wisi in dignissim interdum, justo lectus sagittis dui, et vehicula libero dui cursus dui. Mauris tempor ligula sed lacus. Duis cursus enim ut augue. Cras ac magna. Cras nulla. Nulla egestas. Curabitur a leo. Quisque egestas wisi eget nunc. Nam feugiat lacus vel est. Curabitur consectetuer.

Suspendisse vel felis. Ut lorem lorem, interdum eu, tincidunt sit amet, laoreet vitae, arcu. Aenean faucibus pede eu ante. Praesent enim elit, rutrum at, molestie non, nonummy vel, nisl. Ut lectus eros, malesuada sit amet, fermentum eu, sodales cursus, magna. Donec eu purus. Quisque vehicula, urna sed ultricies auctor, pede lorem egestas dui, et convallis elit erat sed nulla. Donec luctus. Curabitur et nunc. Aliquam dolor odio, commodo pretium, ultricies non, pharetra in, velit. Integer arcu est, nonummy in, fermentum faucibus, egestas vel, odio.

Sed commodo posuere pede. Mauris ut est. Ut quis purus. Sed ac odio. Sed vehicula hendrerit sem. Duis non odio. Morbi ut dui. Sed accumsan risus eget odio. In hac habitasse platea dictumst. Pellentesque non elit. Fusce sed justo eu urna porta tincidunt. Mauris felis odio, sollicitudin sed, volutpat a, ornare ac, erat. Morbi quis dolor. Donec pellentesque, erat ac sagittis semper, nunc dui lobortis purus, quis congue purus metus ultricies tellus. Proin et quam. Class aptent taciti sociosqu ad litora torquent per conubia nostra, per inceptos hymenaeos. Praesent sapien turpis, fermentum vel, eleifend faucibus, vehicula eu, lacus.

Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Donec odio elit, dictum in, hendrerit sit amet, egestas sed, leo. Praesent feugiat sapien aliquet odio. Integer vitae justo. Aliquam vestibulum fringilla lorem. Sed neque lectus, consectetuer at, consectetuer sed, eleifend ac, lectus. Nulla facilisi. Pellentesque eget lectus. Proin eu metus. Sed porttitor. In hac habitasse platea dictumst. Suspendisse eu lectus. Ut mi mi, lacinia sit amet, placerat et, mollis vitae, dui. Sed ante tellus, tristique ut, iaculis eu, malesuada ac, dui. Mauris nibh leo, facilisis non, adipiscing quis, ultrices a, dui.

/tcb/skin=enhancedlast jigsaw (skin)

This is the jigsaw variant of skin enhancedlast → P. 212. It differs by its frame engine, see Section 10.11 on page 201.

Environment and engines for the skin 'enhancedlast'

/tcb/graphical environment → P. 135:	tikzpicture
/tcb/frame engine → P. 135:	pathlastjigsaw
/tcb/interior titled engine → P. 135:	pathlast
/tcb/interior engine → P. 136:	pathlast
/tcb/segmentation engine → P. 136:	path
/tcb/title engine → P. 136:	pathlast

```
\begin{tcbraster}[skin=enhancedlast jigsaw,raster equal height,raster columns=4,
    colback=LightGreen,colframe=DarkGreen,colbacktitle=LimeGreen!75!DarkGreen,
    opacityframe=0.5,opacityback=0.5,opacitybacktitle=0.5,
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
  \begin{tcolorbox}
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

10.15 Skin Family 'bicolor'

/tcb/skin=bicolor (skin)

This skin is quite similar to the standard → P. 204 and enhanced → P. 206 skin. But instead of a segmentation line, the optional lower part of the box is filled with a different color or drawn with a different style.

Environment and engines for the skin 'bicolor'

/tcb/graphical environment → P. 135:	tikzpicture
/tcb/frame engine → P. 135:	path
/tcb/interior titled engine → P. 135:	*special*
/tcb/interior engine → P. 136:	*special*
/tcb/segmentation engine → P. 136:	*special*
/tcb/title engine → P. 136:	path

- The most basic usage of this skin is to set the background color of the lower part by /tcb/colbacklower → P. 220 and all other options like for the standard → P. 204 skin.

```
\begin{tcolorbox}[skin=bicolor,title=The title,
    colframe=FireBrick!75!black,colback=Salmon!50!white,colbacklower=Salmon]
  The upper part.
  \tcblower
  The lower part.
\end{tcolorbox}
```

- The more advanced usage of this skin is to apply the /tcb/frame style → P. 148 and the /tcb/interior style → P. 149 like for the enhanced → P. 206 skin. Also, the /tcb/segmentation style → P. 151 can be used, but it is applied to the whole lower part.

```
\begin{tcolorbox}[skin=bicolor,title=The title,
    frame style={top color=FireBrick,
                 bottom color=FireBrick!15!white,draw=black},
    interior style={left color=Salmon,right color=Salmon!50!white},
    segmentation style={right color=Salmon,left color=Salmon!50!white}]
  The upper part.
  \tcblower
  The lower part.
\end{tcolorbox}
```

/tcb/bicolor (style, no value)

This is an abbreviation for setting skin=bicolor.

```
\begin{tcbraster}[bicolor,raster equal height,raster columns=4,
    colback=LightGreen,colframe=DarkGreen,colbacklower=LimeGreen!75!LightGreen,
    colbacktitle=LimeGreen!75!DarkGreen,
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
  \begin{tcolorbox}
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
\end{tcbraster}
```



/tcb/colbacklower=⟨*color*⟩ (no default, initially `black!15!white`)

Sets the background ⟨*color*⟩ of the lower part. It depends on the skin, if this value is used.

```
\tcbset{gitexample/.style={listing and comment,comment={#1},
  skin=bicolor,boxrule=1mm,fonttitle=\bfseries,coltitle=black,
  frame style={draw=black,left color=Gold,right color=Goldenrod!50!Gold},
  colback=black,colbacklower=Goldenrod!75!Gold,
  colupper=white,collower=black,
  listing options={language={bash},aboveskip=0pt,belowskip=0pt,nolol,
  basicstyle=\ttfamily\bfseries,extendedchars=true}}}

\begin{tcblisting}{title={Snapshot of the staging area},
  gitexample={The option '-a' automatically stages all tracked and modified
              files before the commit.\par
              This can be combined with the message option '-m'
              as seen in the third line.}}
git commit
git commit -a
git commit -am 'changes to my example'
\end{tcblisting}
```



/tcb/skin=bicolorfirst (skin)

This is a flavor of bicolor → P. 219 which is used as a *first* part in a break sequence for bicolor → P. 219. Nevertheless, this skin can be applied independently.

Environment and engines for the skin 'bicolorfirst'

/tcb/graphical environment → P. 135:	tikzpicture
/tcb/frame engine → P. 135:	pathfirst
/tcb/interior titled engine → P. 135:	*special*
/tcb/interior engine → P. 136:	*special*
/tcb/segmentation engine → P. 136:	*special*
/tcb/title engine → P. 136:	pathfirst

```
\begin{tcbraster}[skin=bicolorfirst,raster equal height,raster columns=4,
    colback=LightGreen,colframe=DarkGreen,colbacklower=LimeGreen!75!LightGreen,
    colbacktitle=LimeGreen!75!DarkGreen,
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
  \begin{tcolorbox}
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
\end{tcbraster}
```



/tcb/skin=bicolormiddle (skin)

This is a flavor of bicolor → P. 219 which is used as a *middle* part in a break sequence for bicolor → P. 219. Nevertheless, this skin can be applied independently.

Environment and engines for the skin 'bicolormiddle'

/tcb/graphical environment → P. 135:	tikzpicture
/tcb/frame engine → P. 135:	pathmiddle
/tcb/interior titled engine → P. 135:	*special*
/tcb/interior engine → P. 136:	*special*
/tcb/segmentation engine → P. 136:	*special*
/tcb/title engine → P. 136:	pathmiddle

```
\begin{tcbraster}[skin=bicolormiddle,raster equal height,raster columns=4,
    colback=LightGreen,colframe=DarkGreen,colbacklower=LimeGreen!75!LightGreen,
    colbacktitle=LimeGreen!75!DarkGreen,
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
  \begin{tcolorbox}
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

/tcb/skin=bicolorlast (skin)

This is a flavor of bicolor → P. 219 which is used as a *last* part in a break sequence for bicolor → P. 219. Nevertheless, this skin can be applied independently.

Environment and engines for the skin 'bicolorlast'

/tcb/graphical environment → P. 135:	tikzpicture
/tcb/frame engine → P. 135:	pathlast
/tcb/interior titled engine → P. 135:	*special*
/tcb/interior engine → P. 136:	*special*
/tcb/segmentation engine → P. 136:	*special*
/tcb/title engine → P. 136:	pathlast

```
\begin{tcbraster}[skin=bicolorlast,raster equal height,raster columns=4,
    colback=LightGreen,colframe=DarkGreen,colbacklower=LimeGreen!75!LightGreen,
    colbacktitle=LimeGreen!75!DarkGreen,
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
  \begin{tcolorbox}
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
\end{tcbraster}
```



10.16 Skin Family 'tile'

N 2016-02-25 **/tcb/skin=tile** (skin)

This skin is a variant of skin bicolor → P. 219. Especially, the optional lower part of the box is colored by /tcb/colbacklower → P. 220. The main difference to bicolor → P. 219 is that tile has no frame.

Environment and engines for the skin 'tile'

/tcb/graphical environment → P. 135:	tikzpicture
/tcb/frame engine → P. 135:	empty
/tcb/interior titled engine → P. 135:	*special*
/tcb/interior engine → P. 136:	*special*
/tcb/segmentation engine → P. 136:	*special*
/tcb/title engine → P. 136:	path

N 2016-02-25 **/tcb/tile** (style, no value)

This is an abbreviation for setting skin=tile.

It also changes the geometry and some style options.

```
\begin{tcbraster}[tile,raster equal height,raster columns=4,
    colback=LightGreen,colframe=DarkGreen,colbacklower=LimeGreen!75!LightGreen,
    colbacktitle=LimeGreen!75!DarkGreen,
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
  \begin{tcolorbox}
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

N 2016-02-25 **/tcb/skin=tilefirst** (skin)

This is a flavor of tile → P. 224 which is used as a *first* part in a break sequence for tile → P. 224. Nevertheless, this skin can be applied independently.

Environment and engines for the skin 'tilefirst'

/tcb/graphical environment → P. 135:	tikzpicture
/tcb/frame engine → P. 135:	empty
/tcb/interior titled engine → P. 135:	*special*
/tcb/interior engine → P. 136:	*special*
/tcb/segmentation engine → P. 136:	*special*
/tcb/title engine → P. 136:	pathfirst

```
\begin{tcbraster}[skin=tilefirst,raster equal height,raster columns=4,
    colback=LightGreen,colframe=DarkGreen,colbacklower=LimeGreen!75!LightGreen,
    colbacktitle=LimeGreen!75!DarkGreen,
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm,boxrule=0pt]
  \begin{tcolorbox}
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
\end{tcbraster}
```



N 2016-02-25 **/tcb/skin=tilemiddle** (skin)

This is a flavor of tile[→ P. 224] which is used as a *middle* part in a break sequence for tile[→ P. 224]. Nevertheless, this skin can be applied independently.

Environment and engines for the skin 'tilemiddle'

/tcb/graphical environment[→ P. 135]:	tikzpicture
/tcb/frame engine[→ P. 135]:	empty
/tcb/interior titled engine[→ P. 135]:	*special*
/tcb/interior engine[→ P. 136]:	*special*
/tcb/segmentation engine[→ P. 136]:	*special*
/tcb/title engine[→ P. 136]:	pathmiddle

```
\begin{tcbraster}[skin=tilemiddle,raster equal height,raster columns=4,
    colback=LightGreen,colframe=DarkGreen,colbacklower=LimeGreen!75!LightGreen,
    colbacktitle=LimeGreen!75!DarkGreen,
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm,boxrule=0pt]
  \begin{tcolorbox}
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

N 2016-02-25 **/tcb/skin=tilelast** (skin)

This is a flavor of tile →P. 224 which is used as a *last* part in a break sequence for tile →P. 224. Nevertheless, this skin can be applied independently.

Environment and engines for the skin 'tilelast'

/tcb/graphical environment →P. 135:	tikzpicture
/tcb/frame engine →P. 135:	empty
/tcb/interior titled engine →P. 135:	*special*
/tcb/interior engine →P. 136:	*special*
/tcb/segmentation engine →P. 136:	*special*
/tcb/title engine →P. 136:	pathlast

```
\begin{tcbraster}[skin=tilelast,raster equal height,raster columns=4,
    colback=LightGreen,colframe=DarkGreen,colbacklower=LimeGreen!75!LightGreen,
    colbacktitle=LimeGreen!75!DarkGreen,
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm,boxrule=0pt]
  \begin{tcolorbox}
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

10.17 Skin Family 'beamer'

/tcb/skin=beamer (skin)

This skin resembles boxes known from the beamer class and therefore is called 'beamer'. It uses the normal colors from the core package but shades them a little bit. To use this skin, the tikz library shadings has to be included in the preamble by:

```
\usetikzlibrary{shadings}
```

Environment and engines for the skin 'beamer'

/tcb/graphical environment → P. 135:	tikzpicture
/tcb/frame engine → P. 135:	path
/tcb/interior titled engine → P. 135:	*special*
/tcb/interior engine → P. 136:	*special*
/tcb/segmentation engine → P. 136:	*special*
/tcb/title engine → P. 136:	path

/tcb/beamer (style, no value)

This is an abbreviation for setting skin=beamer.

! It also changes the geometry and some style options.

```
\begin{tcbraster}[beamer,raster equal height,raster columns=4,
    colback=LightGreen,colframe=DarkGreen,
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
  \begin{tcolorbox}
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

```
\begin{tcolorbox}[beamer,colback=Salmon!50!white,colframe=FireBrick!75!black,
  adjusted title=A colored box with the 'beamer' skin]
This box looks like a box provided by the \texttt{beamer} class.
\end{tcolorbox}
```

A colored box with the 'beamer' skin

This box looks like a box provided by the `beamer` class.

```
\begin{tcolorbox}[beamer,colframe=blue,colback=black,
  watermark graphics=lichtspiel.jpg,
  coltext=white,watermark opacity=0.75,watermark stretch=1.0,
  title=Beamer Box with background picture]
\lipsum[1]
\end{tcolorbox}
```

Beamer Box with background picture

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

```
\newtcolorbox{myblock}[2][]{%
  beamer,breakable,colback=LightBlue,colframe=DarkBlue,#1,title=#2}%

\begin{myblock}{Beamerish \texttt{block}: \texttt{myblock}}
\lipsum[1]
\end{myblock}
```

Beamerish `block`: `myblock`

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

/tcb/skin=beamerfirst (skin)

This is a flavor of beamer → P. 228 which is used as a *first* part in a break sequence for beamer → P. 228. Nevertheless, this skin can be applied independently.

Environment and engines for the skin 'beamerfirst'

/tcb/graphical environment → P. 135:	tikzpicture
/tcb/frame engine → P. 135:	pathfirst
/tcb/interior titled engine → P. 135:	*special*
/tcb/interior engine → P. 136:	*special*
/tcb/segmentation engine → P. 136:	*special*
/tcb/title engine → P. 136:	pathfirst

```
\begin{tcbraster}[beamer,skin=beamerfirst,raster equal height,raster columns=4,
    colback=LightGreen,colframe=DarkGreen,
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
  \begin{tcolorbox}
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

/tcb/skin=beamermiddle (skin)

This is a flavor of beamer → P. 228 which is used as a *middle* part in a break sequence for beamer → P. 228. Nevertheless, this skin can be applied independently.

Environment and engines for the skin 'beamermiddle'

/tcb/graphical environment → P. 135:	tikzpicture
/tcb/frame engine → P. 135:	pathmiddle
/tcb/interior titled engine → P. 135:	*special*
/tcb/interior engine → P. 136:	*special*
/tcb/segmentation engine → P. 136:	*special*
/tcb/title engine → P. 136:	pathmiddle

```
\begin{tcbraster}[beamer,skin=beamermiddle,raster equal height,raster columns=4,
    colback=LightGreen,colframe=DarkGreen,
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
  \begin{tcolorbox}
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

/tcb/skin=beamerlast (skin)

This is a flavor of beamer → P. 228 which is used as a *last* part in a break sequence for beamer → P. 228. Nevertheless, this skin can be applied independently.

Environment and engines for the skin 'beamerlast'

/tcb/graphical environment → P. 135:	tikzpicture
/tcb/frame engine → P. 135:	pathlast
/tcb/interior titled engine → P. 135:	*special*
/tcb/interior engine → P. 136:	*special*
/tcb/segmentation engine → P. 136:	*special*
/tcb/title engine → P. 136:	pathlast

```
\begin{tcbraster}[beamer,skin=beamerlast,raster equal height,raster columns=4,
    colback=LightGreen,colframe=DarkGreen,
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
  \begin{tcolorbox}
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

10.18 Skin Family 'widget'

/tcb/skin=widget (skin)

This skin uses the normal colors from the core package but shades them a little bit. To use this skin, the `tikz` library `shadings` has to be included in the preamble by:

```
\usetikzlibrary{shadings}
```

The appearance of the skin can be controlled by /tcb/frame style → P. 148, /tcb/interior style → P. 149, and /tcb/segmentation style → P. 151, if needed.

Environment and engines for the skin 'widget'

/tcb/graphical environment → P. 135:	tikzpicture
/tcb/frame engine → P. 135:	path
/tcb/interior titled engine → P. 135:	path
/tcb/interior engine → P. 136:	path
/tcb/segmentation engine → P. 136:	*special*
/tcb/title engine → P. 136:	*special*

/tcb/widget (style, no value)

This is an abbreviation for setting `skin=widget`.

! It also changes the geometry and some style options.

```
\begin{tcbraster}[widget,raster equal height,raster columns=4,
    colback=LightGreen,colframe=DarkGreen,
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
  \begin{tcolorbox}
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

```
\begin{tcolorbox}[widget,colback=Salmon!50!white,colframe=FireBrick!75!black,
  adjusted title=A colored box with the 'widget' skin]
This is my content.
\end{tcolorbox}
```

A colored box with the 'widget' skin

This is my content.

/tcb/skin=widgetfirst (skin)

This is a flavor of widget → P. 233 which is used as a *first* part in a break sequence for widget → P. 233. Nevertheless, this skin can be applied independently.

Environment and engines for the skin 'widgetfirst'

/tcb/graphical environment → P. 135:	tikzpicture
/tcb/frame engine → P. 135:	pathfirst
/tcb/interior titled engine → P. 135:	pathfirst
/tcb/interior engine → P. 136:	pathfirst
/tcb/segmentation engine → P. 136:	*special*
/tcb/title engine → P. 136:	*special*

```
\begin{tcbraster}[widget,skin=widgetfirst,raster equal height,raster columns=4,
    colback=LightGreen,colframe=DarkGreen,
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
  \begin{tcolorbox}
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

/tcb/skin=widgetmiddle (skin)

This is a flavor of widget → P. 233 which is used as a *middle* part in a break sequence for widget → P. 233. Nevertheless, this skin can be applied independently.

Environment and engines for the skin 'widgetmiddle'

/tcb/graphical environment → P. 135:	tikzpicture
/tcb/frame engine → P. 135:	pathmiddle
/tcb/interior titled engine → P. 135:	pathmiddle
/tcb/interior engine → P. 136:	pathmiddle
/tcb/segmentation engine → P. 136:	*special*
/tcb/title engine → P. 136:	*special*

```
\begin{tcbraster}[widget,skin=widgetmiddle,raster equal height,raster columns=4,
    colback=LightGreen,colframe=DarkGreen,
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
  \begin{tcolorbox}
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

/tcb/skin=widgetlast (skin)

This is a flavor of widget → P. 233 which is used as a *last* part in a break sequence for widget → P. 233. Nevertheless, this skin can be applied independently.

Environment and engines for the skin 'widgetlast'

/tcb/graphical environment → P. 135:	tikzpicture
/tcb/frame engine → P. 135:	pathlast
/tcb/interior titled engine → P. 135:	pathlast
/tcb/interior engine → P. 136:	pathlast
/tcb/segmentation engine → P. 136:	*special*
/tcb/title engine → P. 136:	*special*

```
\begin{tcbraster}[widget,skin=widgetlast,raster equal height,raster columns=4,
    colback=LightGreen,colframe=DarkGreen,
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
  \begin{tcolorbox}
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

10.19 Skin Family 'empty'

/tcb/skin=empty (skin)

This skin sets all engines to `empty`, i. e. nothing is drawn at all. Therefore, this skin is a good starting point to create a complete new style by yourself.

Environment and engines for the skin 'empty'

/tcb/graphical environment → P. 135:	tikzpicture
/tcb/frame engine → P. 135:	empty
/tcb/interior titled engine → P. 135:	empty
/tcb/interior engine → P. 136:	empty
/tcb/segmentation engine → P. 136:	empty
/tcb/title engine → P. 136:	empty

/tcb/empty (style, no value)

This is an abbreviation for setting `skin=empty`.

```
\begin{tcbraster}[empty,raster equal height,raster columns=4,
    coltitle=Navy,borderline={2pt}{0pt}{black!10!white},
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
  \begin{tcolorbox}
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

/tcb/blanker (style, initially unset)

This style relies on the skin empty → P. 237. All engines are set to empty and all margins are set to 0pt. In contrast to /tcb/blank → P. 208, the graphical paths are not constructed with exception of the geometry nodes.

```
\begin{tcolorbox}[blanker,watermark text=A blank box]
\lipsum[1]
\end{tcolorbox}
```

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

A blank box

```
% \tcbuselibrary{fitting}
\newtcboxfit{\mybox}[1]{blanker,width=4cm,height=7cm,top=4pt,
  watermark text=#1}

\begin{tabular}{|c|c|c|}\hline
A & B & C\\\hline
\mybox{A}{\lipsum[1]} & \mybox{B}{\lipsum[2]} & \mybox{C}{\lipsum[3]}\\\hline
\end{tabular}
```

A	B	C
Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.	Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.	Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

A blank box

/tcb/blankest (style, initially unset)

This style extends /tcb/blanker → P. 238. All engines are set to empty and all margins are set to 0pt. In contrast to /tcb/blanker → P. 238, also title, shadow, underlay, overlay, finish and borderline are removed.

```
% \tcbuselibrary{raster}
\begin{tcbraster}[raster columns=3,raster equal height,
    title=Box \thetcbrasternum,
    enhanced,size=small,colframe=red!50!black,colback=red!10!white,
    coltitle=yellow!85!black,
    drop fuzzy shadow,watermark text={Box \thetcbrasternum},
    borderline={.25mm}{-0.5mm}{green!40!black},
    finish={\begin{tcbclipframe}\draw[blue,opacity=0.1,line width=1cm]
      (frame.south west) -- (frame.north east);\end{tcbclipframe}},
    ]
  \begin{tcolorbox}\lipsum[4]\end{tcolorbox}
  \begin{tcolorbox}[blanker]\lipsum[4]\end{tcolorbox}
  \begin{tcolorbox}[blankest]\lipsum[4]\end{tcolorbox}
\end{tcbraster}
```

Box 1

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

Box 2

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

/tcb/skin=emptyfirst (skin)

This is a flavor of empty → P. 237 which is used as a *first* part in a break sequence for empty → P. 237. Nevertheless, this skin can be applied independently.

Environment and engines for the skin 'emptyfirst'

/tcb/graphical environment → P. 135:	tikzpicture
/tcb/frame engine → P. 135:	empty
/tcb/interior titled engine → P. 135:	empty
/tcb/interior engine → P. 136:	empty
/tcb/segmentation engine → P. 136:	empty
/tcb/title engine → P. 136:	empty

```
\begin{tcbraster}[empty,skin=emptyfirst,raster equal height,raster columns=4,
    coltitle=Navy,borderline={2pt}{0pt}{black!10!white},
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
  \begin{tcolorbox}
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

/tcb/skin=emptymiddle (skin)

This is a flavor of empty → P. 237 which is used as a *middle* part in a break sequence for empty → P. 237. Nevertheless, this skin can be applied independently.

Environment and engines for the skin 'emptymiddle'

/tcb/graphical environment → P. 135:	tikzpicture
/tcb/frame engine → P. 135:	empty
/tcb/interior titled engine → P. 135:	empty
/tcb/interior engine → P. 136:	empty
/tcb/segmentation engine → P. 136:	empty
/tcb/title engine → P. 136:	empty

```
\begin{tcbraster}[empty,skin=emptymiddle,raster equal height,raster columns=4,
    coltitle=Navy,borderline={2pt}{0pt}{black!10!white},
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
  \begin{tcolorbox}
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

/tcb/skin=emptylast (skin)

This is a flavor of empty → P. 237 which is used as a *last* part in a break sequence for empty → P. 237. Nevertheless, this skin can be applied independently.

Environment and engines for the skin 'emptylast'

/tcb/graphical environment → P. 135:	tikzpicture
/tcb/frame engine → P. 135:	empty
/tcb/interior titled engine → P. 135:	empty
/tcb/interior engine → P. 136:	empty
/tcb/segmentation engine → P. 136:	empty
/tcb/title engine → P. 136:	empty

```
\begin{tcbraster}[empty,skin=emptylast,raster equal height,raster columns=4,
    coltitle=Navy,borderline={2pt}{0pt}{black!10!white},
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
  \begin{tcolorbox}
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

This example demonstrates a breakable customized box. Here, we define an environment `freebox`. The first application of `freebox` produces an unbroken `tcolorbox`. The box is drawn by the code given by `/tcb/frame code` → P. 138 and `/tcb/interior code` → P. 139. The second application of `freebox` is broken into several parts which are drawn by the codes given by `/tcb/skin first is subskin of` → P. 141, `/tcb/skin middle is subskin of` → P. 141, and `/tcb/skin last is subskin of` → P. 141.

```
% Preamble:
%\usepackage{tikz,lipsum}
%\tcbuselibrary{skins,breakable}
\tikzset{coltria/.style={fill=red!15!white}}

\newtcolorbox{freebox}[1][]{empty,breakable,leftrule=5mm,left=2mm,
  frame style={fill,top color=red!75!black,bottom color=red!75!black,middle color=red},
  colback=yellow!50!white,
  watermark color=red!50!yellow!75!white,
  watermark text on=unbroken is unbroken box,
  watermark text on=first is first part,
  watermark text on=middle is middle part,
  watermark text on=last is last part,
  % code for unbroken boxes:
  frame code={\path[tcb fill frame] (frame.south west)--(frame.north west)
    --([xshift=-5mm]frame.north east)--([yshift=-5mm]frame.north east)
    --([yshift=5mm]frame.south east)--([xshift=-5mm]frame.south east)--cycle; },
  interior code={\path[tcb fill interior] (interior.south west)--(interior.north west)
    --([xshift=-4.8mm]interior.north east)--([yshift=-4.8mm]interior.north east)
    --([yshift=4.8mm]interior.south east)--([xshift=-4.8mm]interior.south east)
    --cycle; },
  % code for the first part of a break sequence:
  skin first is subskin of={emptyfirst}{%
    frame code={\path[tcb fill frame] (frame.south west)--(frame.north west)
      --([xshift=-5mm]frame.north east)--([yshift=-5mm]frame.north east)
      --(frame.south east)--cycle;
      \path[coltria] ([xshift=2.5mm,yshift=1mm]frame.south west) -- +(120:2mm)
      -- +(60:2mm)-- cycle; },
    interior code={\path[tcb fill interior] (interior.south west|-frame.south)
      --(interior.north west)--([xshift=-4.8mm]interior.north east)
      --([yshift=-4.8mm]interior.north east)--(interior.south east|-frame.south)
      --cycle; },
  },%
  % code for the middle part of a break sequence:
  skin middle is subskin of={emptymiddle}{%
    frame code={\path[tcb fill frame] (frame.south west)--(frame.north west)
      --(frame.north east)--(frame.south east)--cycle;
      \path[coltria] ([xshift=2.5mm,yshift=-1mm]frame.north west) -- +(240:2mm)
        -- +(300:2mm) -- cycle;
      \path[coltria] ([xshift=2.5mm,yshift=1mm]frame.south west) -- +(120:2mm)
        -- +(60:2mm) -- cycle;
      },
    interior code={\path[tcb fill interior] (interior.south west|-frame.south)
      --(interior.north west|-frame.north)--(interior.north east|-frame.north)
      --(interior.south east|-frame.south)--cycle; },
    },
  % code for the last part of a break sequence:
  skin last is subskin of={emptylast}{%
    frame code={\path[tcb fill frame] (frame.south west)--(frame.north west)
      --(frame.north east)--([yshift=5mm]frame.south east)
      --([xshift=-5mm]frame.south east)--cycle;
      \path[coltria] ([xshift=2.5mm,yshift=-1mm]frame.north west) -- +(240:2mm)
      -- +(300:2mm) -- cycle;
      },
    interior code={\path[tcb fill interior] (interior.south west)
```

```
      --(interior.north west|-frame.north)--(interior.north east|-frame.north)
      --([yshift=4.8mm]interior.south east)--([xshift=-4.8mm]interior.south east)
      --cycle; },
    },
  #1}

\begin{freebox}
\lipsum[1]
\end{freebox}

\begin{freebox}
\lipsum[1-12]
\end{freebox}
```

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

unbroken box

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

first part

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim.

Vestibulum pellentesque felis eu massa.
Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.
Fusce mauris. Vestibulum luctus nibh at lectus. Sed bibendum, nulla a faucibus semper, leo velit ultricies tellus, ac venenatis arcu wisi vel nisl. Vestibulum diam. Aliquam pellentesque, augue quis sagittis posuere, turpis lacus congue quam, in hendrerit risus eros eget felis. Maecenas eget erat in sapien mattis porttitor. Vestibulum porttitor. Nulla facilisi. Sed a turpis eu lacus commodo facilisis. Morbi fringilla, wisi in dignissim interdum, justo lectus sagittis dui, et vehicula libero dui cursus dui. Mauris tempor ligula sed lacus. Duis cursus enim ut augue. Cras ac magna. Cras nulla. Nulla egestas. Curabitur a leo. Quisque egestas wisi eget nunc. Nam feugiat lacus vel est. Curabitur consectetuer.
Suspendisse vel felis. Ut lorem lorem, interdum eu, tincidunt sit amet, laoreet vitae, arcu. Aenean faucibus pede eu ante. Praesent enim elit, rutrum at, molestie non, nonummy vel, nisl. Ut lectus eros, malesuada sit amet, fermentum eu, sodales cursus, magna. Donec eu purus. Quisque vehicula, urna sed ultricies auctor, pede lorem egestas dui, et convallis elit erat sed nulla. Donec luctus. Curabitur et nunc. Aliquam dolor odio, commodo pretium, ultricies non, pharetra in, velit. Integer arcu est, nonummy in, fermentum faucibus, egestas vel, odio.
Sed commodo posuere pede. Mauris ut est. Ut quis purus. Sed ac odio. Sed vehicula hendrerit sem. Duis non odio. Morbi ut dui. Sed accumsan risus eget odio. In hac habitasse platea dictumst. Pellentesque non elit. Fusce sed justo eu urna porta tincidunt. Mauris felis odio, sollicitudin sed, volutpat a, ornare ac, erat. Morbi quis dolor. Donec pellentesque, erat ac sagittis semper, nunc dui lobortis purus, quis congue purus metus ultricies tellus. Proin et quam. Class aptent taciti sociosqu ad litora torquent per conubia nostra, per inceptos hymenaeos. Praesent sapien turpis, fermentum vel, eleifend faucibus, vehicula eu, lacus.
Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Donec odio elit, dictum in, hendrerit sit amet, egestas sed, leo. Praesent feugiat sapien aliquet odio. Integer vitae justo. Aliquam vestibulum fringilla lorem. Sed neque lectus, consectetuer at, consectetuer sed, eleifend ac, lectus. Nulla facilisi. Pellentesque eget lectus. Proin eu metus. Sed porttitor. In hac habitasse platea dictumst. Suspendisse eu lectus. Ut mi mi, lacinia sit amet, placerat et, mollis vitae, dui. Sed ante tellus, tristique ut, iaculis eu, malesuada ac, dui. Mauris nibh leo, facilisis non, adipiscing quis, ultrices a, dui.
Morbi luctus, wisi viverra faucibus pretium, nibh est placerat odio, nec commodo wisi enim eget quam. Quisque libero justo, consectetuer a, feugiat vitae, porttitor eu, libero. Suspendisse sed mauris vitae elit sollicitudin malesuada. Maecenas ultricies eros sit amet ante. Ut venenatis velit. Maecenas sed mi eget dui varius euismod. Phasellus aliquet volutpat odio. Vestibulum ante ipsum primis in faucibus orci luctus et ultrices posuere cubilia Curae; Pellentesque sit amet pede ac sem eleifend consectetuer. Nullam elementum, urna vel imperdiet sodales, elit ipsum pharetra ligula, ac pretium ante justo a nulla. Curabitur tristique arcu eu metus. Vestibulum lectus. Proin mauris. Proin eu nunc eu urna hendrerit faucibus. Aliquam auctor, pede consequat laoreet varius, eros tellus scelerisque quam, pellentesque hendrerit ipsum dolor sed augue. Nulla nec lacus. Suspendisse vitae elit. Aliquam arcu neque, ornare in, ullamcorper quis, commodo eu, libero. Fusce sagittis erat at erat tristique mollis. Maecenas sapien libero, molestie et,

middle part

lobortis in, sodales eget, dui. Morbi ultrices rutrum lorem. Nam elementum ullamcorper leo. Morbi dui. Aliquam sagittis. Nunc placerat. Pellentesque tristique sodales est. Maecenas imperdiet lacinia velit. Cras non urna. Morbi eros pede, suscipit ac, varius vel, egestas non, eros. Praesent malesuada, diam id pretium elementum, eros sem dictum tortor, vel consectetuer odio sem sed wisi.

Sed feugiat. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Ut pellentesque augue sed urna. Vestibulum diam eros, fringilla et, consectetuer eu, nonummy id, sapien. Nullam at lectus. In sagittis ultrices mauris. Curabitur malesuada erat sit amet massa. Fusce blandit. Aliquam erat volutpat. Aliquam euismod. Aenean vel lectus. Nunc imperdiet justo nec dolor.

last part

Etiam euismod. Fusce facilisis lacinia dui. Suspendisse potenti. In mi erat, cursus id, nonummy sed, ullamcorper eget, sapien. Praesent pretium, magna in eleifend egestas, pede pede pretium lorem, quis consectetuer tortor sapien facilisis magna. Mauris quis magna varius nulla scelerisque imperdiet. Aliquam non quam. Aliquam porttitor quam a lacus. Praesent vel arcu ut tortor cursus volutpat. In vitae pede quis diam bibendum placerat. Fusce elementum convallis neque. Sed dolor orci, scelerisque ac, dapibus nec, ultricies ut, mi. Duis nec dui quis leo sagittis commodo.

10.20 Skin 'spartan'

/tcb/skin=spartan (skin)

This skin is quite ... spartan. It supports no rounded corners, no overlays, no shadows, no borderlines, and no finishes. The only exception are underlays. One cannot do very fancy things with this skin, but it compiles very fast. Therefore, the `spartan` skin is used for the draft mode, see Section 10.12 on page 203. Nevertheless, it can be used as a normal skin.

Environment and engines for the skin 'spartan'

/tcb/graphical environment → P. 135:	tikzpicture
/tcb/frame engine → P. 135:	spartan
/tcb/interior titled engine → P. 135:	spartan
/tcb/interior engine → P. 136:	spartan
/tcb/segmentation engine → P. 136:	spartan
/tcb/title engine → P. 136:	spartan

/tcb/spartan (style, no value)

This is an abbreviation for setting `skin=spartan`.

```
\begin{tcbraster}[spartan,raster equal height,raster columns=4,
    colback=LightGreen,colframe=DarkGreen,colbacktitle=LimeGreen!75!DarkGreen,
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
  \begin{tcolorbox}
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

10.21 Skin 'draft'

/tcb/skin=draft (skin)

This skin is intended to be used while drafting new geometric settings for a `tcolorbox`.

Environment and engines for the skin 'draft'

/tcb/graphical environment → P. 135:	`tikzpicture`
/tcb/frame engine → P. 135:	*special*
/tcb/interior titled engine → P. 135:	*special*
/tcb/interior engine → P. 136:	*special*
/tcb/segmentation engine → P. 136:	`path`
/tcb/title engine → P. 136:	`path`

/tcb/draft (style, no value)

This is an abbreviation for setting `skin=draft`.

```
\begin{tcbraster}[draft,raster equal height,raster columns=4,
    colback=LightGreen,colframe=DarkGreen,colbacktitle=LimeGreen!75!DarkGreen,
    left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
  \begin{tcolorbox}
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
  \end{tcolorbox}
  \begin{tcolorbox}[adjusted title=My title]
    This is my content.
    \tcblower
    More content.
  \end{tcolorbox}
\end{tcbraster}
```



```
\vspace*{3mm}
\begin{tcolorbox}[draft,title=A colored box with the 'draft' skin]
\lipsum[1-3]
\tcblower
\lipsum[4-6]
\end{tcolorbox}
```

frame: w=423.94617pt, h=506.20157pt

A colored box with the 'draft' skin title: w=392.64822pt, h=6.2pt

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

upper: w=392.64822pt, h=249.95pt

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula. Fusce mauris. Vestibulum luctus nibh at lectus. Sed bibendum, nulla a faucibus semper, leo velit ultricies tellus, ac venenatis arcu wisi vel nisl. Vestibulum diam. Aliquam pellentesque, augue quis sagittis posuere, turpis lacus congue quam, in hendrerit risus eros eget felis. Maecenas eget erat in sapien mattis porttitor. Vestibulum porttitor. Nulla facilisi. Sed a turpis eu lacus commodo facilisis. Morbi fringilla, wisi in dignissim interdum, justo lectus sagittis dui, et vehicula libero dui cursus dui. Mauris tempor ligula sed lacus. Duis cursus enim ut augue. Cras ac magna. Cras nulla. Nulla egestas. Curabitur a leo. Quisque egestas wisi eget nunc. Nam feugiat lacus vel est. Curabitur consectetuer.

lower: w=392.64822pt, h=205.95pt

Suspendisse vel felis. Ut lorem lorem, interdum eu, tincidunt sit amet, laoreet vitae, arcu. Aenean faucibus pede eu ante. Praesent enim elit, rutrum at, molestie non, nonummy vel, nisl. Ut lectus eros, malesuada sit amet, fermentum eu, sodales cursus, magna. Donec eu purus. Quisque vehicula, urna sed ultricies auctor, pede lorem egestas dui, et convallis elit erat sed nulla. Donec luctus. Curabitur et nunc. Aliquam dolor odio, commodo pretium, ultricies non, pharetra in, velit. Integer arcu est, nonummy in, fermentum faucibus, egestas vel, odio.

interior: w=421.10092pt, h=490.04318pt

10.22 Skin Family 'freelance'


This skin family 'freelance' is deprecated with `tcolorbox` 3.00. It is not longer needed, because `/tcb/frame code` → P. 138, `/tcb/interior code` → P. 139, `/tcb/interior titled code` → P. 138, and `/tcb/title code` → P. 140 can be applied to every skin now. In this sense, everything has become *freelance* now.
For users of `/tcb/freelance`: Old code should continue to work. There may be exceptions for breakable freelance boxes under certain circumstances. For new code, use `/tcb/empty` → P. 237 or `/tcb/enhanced` → P. 206 where you would have used `/tcb/freelance` before.

`/tcb/skin=freelance` (skin)

This skin gives full freedom for the appearance of the `tcolorbox`. All drawing engines are set to type `freelance`; they use the `tikz` package and compute the `/tcb/geometry nodes` → P. 137.

Environment and engines for the skin 'freelance'

`/tcb/graphical environment` → P. 135:	`tikzpicture`
`/tcb/frame engine` → P. 135:	`freelance`
`/tcb/interior titled engine` → P. 135:	`freelance`
`/tcb/interior engine` → P. 136:	`freelance`
`/tcb/segmentation engine` → P. 136:	`freelance`
`/tcb/title engine` → P. 136:	`freelance`

`/tcb/freelance` (style, no value)

This is an abbreviation for setting `skin=freelance`.

`/tcb/skin=freelancefirst` (skin)

This skin equals `freelance` with exception of the break sequence, see Section 17.8 on page 377.

`/tcb/skin=freelancemiddle` (skin)

This skin equals `freelance` with exception of the break sequence, see Section 17.8 on page 377.

`/tcb/skin=freelancelast` (skin)

This skin equals `freelance` with exception of the break sequence, see Section 17.8 on page 377.

`/tcb/extend freelance=`⟨*options*⟩ (no default, initially empty)

The ⟨*options*⟩ are added to the skin definition of `freelance`.

`/tcb/extend freelancefirst=`⟨*options*⟩ (no default, initially empty)

The ⟨*options*⟩ are added to the skin definition of `freelancefirst` which is used as first part of the break sequence of `freelance`. See `/tcb/skin first is subskin of` → P. 141 for a substitute of this key.

`/tcb/extend freelancemiddle=`⟨*options*⟩ (no default, initially empty)

The ⟨*options*⟩ are added to the skin definition of `freelancemiddle` which is used as middle part of the break sequence of `freelance`. See `/tcb/skin middle is subskin of` → P. 141 for a substitute of this key.

`/tcb/extend freelancelast=`⟨*options*⟩ (no default, initially empty)

The ⟨*options*⟩ are added to the skin definition of `freelancelast` which is used as last part of the break sequence of `freelance`. See `/tcb/skin last is subskin of` → P. 141 for a substitute of this key.

11 Inclusion of Boxed Image Files

The LIB skins library adds some commands to conveniently include boxed image files. For the following macros and options, the LIB skins library has to be loaded by a package option or inside the preamble by:

```
\tcbuselibrary{skins}
```

See Section 10 on page 148 for the documentation of all other options of the LIB skins library.

11.1 Macros

N 2014-11-14
U 2016-07-13

`\tcbincludegraphics[`⟨*options*⟩`]{`⟨*file name*⟩`}`

In principle, this macro includes an image file denoted by ⟨*file name*⟩ using the standard `\includegraphics` and puts it into a `tcolorbox`→P. 12. The ⟨*options*⟩ are `tcolorbox` keys to set up the colored box. Use `/tcb/graphics options`→P. 254 to specify options for the underlying `\includegraphics`. Some `tcolorbox` option keys are automatically set, namely `/tcb/enhanced`→P. 206 and options to center the image inside the box.

The sizing of the included image is done depending on the following:

- If a `/tcb/width`→P. 34 is specified, but no fixed `/tcb/height`→P. 53, the image is sized to fill the inner width of the box. The height of the box adapts to the image.
- If a fixed `/tcb/height`→P. 53 is specified, the image is sized to fill the fixed inner area of the box.
- If the `/tcb/capture`→P. 94 mode `/tcb/hbox`→P. 94 is specified, the image is sized according to given `\includegraphics` options only. The box adapts to the image.

```
% \tcbuselibrary{raster}
\begin{tcbraster}[raster columns=3,raster force size=false,size=fbox,
    colframe=red!50!black,colback=red!20!black,
    fonttitle=\bfseries,center title,drop fuzzy shadow]
  \tcbincludegraphics[title=Normal]{goldshade.png}
  \tcbincludegraphics[title=Fixed height,height=3cm]{goldshade.png}
  \tcbincludegraphics[title=hbox mode,hbox,graphics options={width=3cm}]
    {goldshade.png}
\end{tcbraster}
```



The auxiliary macro **\imagename** may be used inside \tcbincludegraphics → P. 251 to display the name of the file. **\imagename** is already partially detokenized and is allowed to contain special characters like the underscore. Note that an appropriate font is required to display such characters.

```
% \tcbuselibrary{raster}
\begin{tcbraster}[size=fbox,
    colframe=red!50!black,colback=red!20!black,
    fonttitle=\bfseries\ttfamily,center title,drop fuzzy shadow]
  \tcbincludegraphics[title=\imagename]{goldshade.png}
  \tcbincludegraphics[finish={
    \node[fill=white,fill opacity=0.5,text opacity=1]
    at (frame.center) {\bfseries\ttfamily\imagename};}]{blueshade.png}
\end{tcbraster}
```

N 2014-11-14 **\tcbincludepdf**[⟨*options*⟩]{⟨*file name*⟩}

This is a generalized version of \tcbincludegraphics → P. 251 which allows to include a complete PDF file denoted by ⟨*file name*⟩. Every page is boxed into an own tcolorbox → P. 12 customized by the given ⟨*options*⟩. It is reasonable to put such a series of boxes inside a tcbraster → P. 279 for alignment.

Use /tcb/graphics pages → P. 254 to use a selection of pages instead of using the whole file.

The auxiliary macro **\imagepage** may be used inside \tcbincludepdf to display the current page number.

```
% \tcbuselibrary{raster}
\begin{tcbraster}[raster columns=3,colframe=blue,colback=white,
  colbacktitle=blue!50!white,fonttitle=\small\bfseries\ttfamily,
  left=0pt,right=0pt,top=0pt,bottom=0pt,boxsep=0pt,boxrule=0.6pt,
  toptitle=1mm,bottomtitle=1mm,drop lifted shadow,center title,
  graphics pages={1,...,6},title={\imagename\ [\imagepage]}]
\tcbincludepdf{tcolorbox-example.pdf}
\end{tcbraster}
```

tcolorbox-example.pdf [1]

tcolorbox-example.pdf [2]



tcolorbox-example.pdf [3]



tcolorbox-example.pdf [4]



tcolorbox-example.pdf [5]



tcolorbox-example.pdf [6]



11.2 Option Keys

N 2014-11-14
U 2018-03-18

/tcb/graphics options=⟨*options*⟩ (no default, initially empty)

Used for \tcbincludegraphics → P. 251 and \tcbincludepdf → P. 253 to specify \includegraphics ⟨*options*⟩.

```
% \tcbuselibrary{raster}
\begin{tcbraster}[raster columns=3,size=fbox,raster equal height,
    colframe=red!50!black,colback=red!20!black,drop fuzzy shadow]
  \tcbincludegraphics{goldshade.png}
  \newcommand{\myangle}{angle=20}%
  \tcbincludegraphics[graphics options=\myangle]{goldshade.png}
  \tcbincludegraphics[graphics options={viewport=0cm 0cm 8cm 4cm,clip}]
    {goldshade.png}
\end{tcbraster}
```



N 2014-11-14

/tcb/graphics directory=⟨*directory*⟩ (no default, initially empty)

Used for \tcbincludegraphics → P. 251 and \tcbincludepdf → P. 253 to specify a file system ⟨*directory*⟩ where the image files are located.

```
\tcbset{
  graphics directory={.},
  graphics directory={examples},
  graphics directory={../../pictures},
}
```

The \graphicspath macro from the graphics package is superior to this option. /tcb/graphics directory may be used especially for \tcbincludepdf → P. 253.

N 2014-11-14

/tcb/graphics pages=⟨*selection*⟩ (no default, initially 1,...,\pdfpages)

Used for \tcbincludepdf → P. 253 to specify a ⟨*selection*⟩ of pages to be included. The largest page number is accessible by \pdfpages. The ⟨*selection*⟩ has to be given using the \foreach syntax of Ti*k*Z.

```
\tcbset{
  graphics pages={1,3,7},
  graphics pages={1,...,10},
  graphics pages={1,3,...,18},
  graphics pages={100,...,\pdfpages},
}
```

N 2018-03-21 **/tcb/graphics orientation=**⟨*orientation*⟩ (no default, initially **as-is**)

Used for \tcbincludegraphics → P. 251 and \tcbincludepdf → P. 253 to guarantee a certain ⟨*orientation*⟩ of the included image. After all other options for the image are processed, the result is possibly rotated to be in landscape or portrait mode.

Feasible values for ⟨*orientation*⟩ are:

- **as-is**: no rotation of the processed image.
- **landscape**: the processed image is possibly rotated by 90 degrees to ensure that the final width is not smaller than the final height.
- **landscape***: the processed image is possibly rotated by -90 degrees to ensure that the final width is not smaller than the final height.
- **portrait**: the processed image is possibly rotated by 90 degrees to ensure that the final height is not smaller than the final width.
- **portrait***: the processed image is possibly rotated by -90 degrees to ensure that the final height is not smaller than the final width.

```
% \tcbuselibrary{raster}
\begin{tcbraster}[raster columns=6,size=fbox,raster equal height,
    colframe=red!50!black,colback=red!20!black,drop fuzzy shadow]
  \tcbincludegraphics{Basilica_5.png}
  \tcbincludegraphics[graphics orientation=landscape]{Basilica_5.png}
  \tcbincludegraphics[graphics orientation=portrait]{Basilica_5.png}
  \tcbincludegraphics[graphics orientation=portrait*]{Basilica_5.png}
  \tcbincludegraphics[graphics options={viewport=0cm 0cm 2cm 3cm,clip}]
    {goldshade.png}
  \tcbincludegraphics[graphics options={viewport=0cm 0cm 2cm 3cm,clip},
    graphics orientation=landscape]{goldshade.png}
\end{tcbraster}
```



12 TikZ Image and Picture Fill Extensions; Auxiliary Macros

The LIB skins library adds some image and picture fill options to the vast option set of TikZ [22]. These options can be used in any `tikzpicture`. For the following options, the LIB skins library has to be loaded by a package option or inside the preamble by:

```
\tcbuselibrary{skins}
```

See Section 10 on page 148 for the documentation of all other options of the LIB skins library.

12.1 Fill Plain

`/tikz/fill plain image=`⟨*file name*⟩ (no default, initially unset)

Fills the current path with an external image referenced by ⟨*file name*⟩. The image is put in the center of the path, but it is not resized to fit into the path area.

```
\begin{tikzpicture}
\path[draw,fill plain image=goldshade.png]
  (2.75,-0.75) -- (3,0) -- (2.75,0.75)
  \foreach \w in {45,90,...,315}
    { -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```



`/tikz/fill plain image*=`⟨*file name*⟩ (no default, initially unset)

Fills the current path with an external image referenced by ⟨*file name*⟩. The image is put in the center of the path, but it is not resized to fit into the path area. The ⟨*graphics options*⟩ are given to the underlying `\includegraphics` command.

```
\begin{tikzpicture}
\path[draw,fill plain ❩
      ❨image*={width=2.5cm}{goldshade.png}]
  (2.75,-0.75) -- (3,0) -- (2.75,0.75)
  \foreach \w in {45,90,...,315}
    { -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```



`/tikz/fill plain picture=`⟨*graphical code*⟩ (no default, initially unset)

Fills the current path with the given ⟨*graphical code*⟩. The result is put in the center of the path, but it is not resized to fit into the path area. Note that this is almost identical to the standard `path picture` option.

```
\begin{tikzpicture}
\path[draw,fill plain picture={%
  \draw[red!50!yellow,line width=2mm]
    (0,0) circle (1cm);
  \draw[red,line width=5mm] (-1,-1) -- (1,1);
  \draw[red,line width=5mm] (-1,1) -- (1,-1);
  }]
  (2.75,-0.75) -- (3,0) -- (2.75,0.75)
  \foreach \w in {45,90,...,315}
    { -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```



12.2 Fill Stretch

/tikz/fill stretch image=⟨*file name*⟩ (no default, initially unset)

Fills the current path with an external image referenced by ⟨*file name*⟩. The image is stretched to fill the path area.

```
\begin{tikzpicture}
\path[fill stretch image=goldshade.png]
  (2.75,-0.75) -- (3,0) -- (2.75,0.75)
  \foreach \w in {45,90,...,315}
    { -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```



/tikz/fill stretch image*={⟨*graphics options*⟩}{⟨*file name*⟩} (no default, initially unset)

Fills the current path with an external image referenced by ⟨*file name*⟩. The ⟨*graphics options*⟩ are given to the underlying **\includegraphics** command. The image is stretched to fill the path area.

```
\begin{tikzpicture}
\path[fill stretch image*=
  {angle=90,origin=c}{goldshade.png}]
  (2.75,-0.75) -- (3,0) -- (2.75,0.75)
  \foreach \w in {45,90,...,315}
    { -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```



/tikz/fill stretch picture=⟨*graphical code*⟩ (no default, initially unset)

Fills the current path with the given ⟨*graphical code*⟩. The result is stretched to fill the path area.

```
\begin{tikzpicture}
\path[draw,fill stretch picture={%
  \draw[red!50!yellow,line width=2mm]
    (0,0) circle (1cm);
  \draw[red,line width=5mm] (-1,-1) -- (1,1);
  \draw[red,line width=5mm] (-1,1) -- (1,-1);
  }]
  (2.75,-0.75) -- (3,0) -- (2.75,0.75)
  \foreach \w in {45,90,...,315}
    { -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```



12.3 Fill Overzoom

/tikz/fill overzoom image=⟨*file name*⟩ (no default, initially unset)

Fills the current path with an external image referenced by ⟨*file name*⟩. The image is zoomed such that the path area fills the image.

```
\begin{tikzpicture}
\path[fill overzoom image=goldshade.png]
  (2.75,-0.75) -- (3,0) -- (2.75,0.75)
  \foreach \w in {45,90,...,315}
    { -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```



/tikz/fill overzoom image*={⟨*graphics options*⟩}{⟨*file name*⟩} (no default, initially unset)

Fills the current path with an external image referenced by ⟨*file name*⟩. The ⟨*graphics options*⟩ are given to the underlying **\includegraphics** command. The image is zoomed such that the path area fills the image.

```
\begin{tikzpicture}
\path[fill overzoom image*=
  {angle=90,origin=c}{goldshade.png}]
  (2.75,-0.75) -- (3,0) -- (2.75,0.75)
  \foreach \w in {45,90,...,315}
    { -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```



/tikz/fill overzoom picture=⟨*graphical code*⟩ (no default, initially unset)

Fills the current path with the given ⟨*graphical code*⟩. The result is zoomed such that the path area fills the image.

```
\begin{tikzpicture}
\path[draw,fill overzoom picture={%
  \draw[red!50!yellow,line width=2mm]
    (0,0) circle (1cm);
  \draw[red,line width=5mm] (-1,-1) -- (1,1);
  \draw[red,line width=5mm] (-1,1) -- (1,-1);
  }]
  (2.75,-0.75) -- (3,0) -- (2.75,0.75)
  \foreach \w in {45,90,...,315}
    { -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```



12.4 Fill Zoom

`/tikz/fill zoom image=`⟨*file name*⟩ (no default, initially unset)

Fills the current path with an external image referenced by ⟨*file name*⟩. The image is zoomed such that it fits inside the path area. Typically, some parts of the path area will stay unfilled.

```
\begin{tikzpicture}
\path[draw,fill zoom image=goldshade.png]
  (2.75,-0.75) -- (3,0) -- (2.75,0.75)
  \foreach \w in {45,90,...,315}
    { -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```



`/tikz/fill zoom image*={`⟨*graphics options*⟩`}{`⟨*file name*⟩`}` (no default, initially unset)

Fills the current path with an external image referenced by ⟨*file name*⟩. The ⟨*graphics options*⟩ are given to the underlying `\includegraphics` command. The image is zoomed such that it fits inside the path area. Typically, some parts of the path area will stay unfilled.

```
\begin{tikzpicture}
\path[draw,fill zoom image*=
  {angle=90,origin=c}{goldshade.png}]
  (2.75,-0.75) -- (3,0) -- (2.75,0.75)
  \foreach \w in {45,90,...,315}
    { -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```



`/tikz/fill zoom picture=`⟨*graphical code*⟩ (no default, initially unset)

Fills the current path with the given ⟨*graphical code*⟩. The result is zoomed such that it fits inside the path area. Typically, some parts of the path area will stay unfilled.

```
\begin{tikzpicture}
\path[draw,fill zoom picture={%
  \draw[red!50!yellow,line width=2mm]
    (0,0) circle (1cm);
  \draw[red,line width=5mm] (-1,-1) -- (1,1);
  \draw[red,line width=5mm] (-1,1) -- (1,-1);
  }]
  (2.75,-0.75) -- (3,0) -- (2.75,0.75)
  \foreach \w in {45,90,...,315}
    { -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```



12.5 Fill Shrink

`/tikz/fill shrink image`=⟨*file name*⟩ (no default, initially unset)

Fills the current path with an external image referenced by ⟨*file name*⟩. The image is zoomed such that it fits inside the path area, but it never gets enlarged. Typically, some parts of the path area will stay unfilled.

```
\begin{tikzpicture}
\path[draw,fill shrink image=goldshade.png]
  (2.75,-0.75) -- (3,0) -- (2.75,0.75)
  \foreach \w in {45,90,...,315}
    { -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```



`/tikz/fill shrink image*`=⟨*file name*⟩ (no default, initially unset)

Fills the current path with an external image referenced by ⟨*file name*⟩. The ⟨*graphics options*⟩ are given to the underlying `\includegraphics` command. The image is zoomed such that it fits inside the path area, but it never gets enlarged. Typically, some parts of the path area will stay unfilled.

```
\begin{tikzpicture}
\path[draw,fill shrink ⤸
      ⤹image*={width=1.5cm}{goldshade.png}]
  (2.75,-0.75) -- (3,0) -- (2.75,0.75)
  \foreach \w in {45,90,...,315}
    { -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```



`/tikz/fill shrink picture`=⟨*graphical code*⟩ (no default, initially unset)

Fills the current path with the given ⟨*graphical code*⟩. The result is zoomed such that it fits inside the path area, but it never gets enlarged. Typically, some parts of the path area will stay unfilled.

```
\begin{tikzpicture}
\path[draw,fill shrink picture={%
  \draw[red!50!yellow,line width=2mm]
    (0,0) circle (1cm);
  \draw[red,line width=5mm] (-1,-1) -- (1,1);
  \draw[red,line width=5mm] (-1,1) -- (1,-1);
  }]
  (2.75,-0.75) -- (3,0) -- (2.75,0.75)
  \foreach \w in {45,90,...,315}
    { -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```



12.6 Fill Tile

`/tikz/fill tile image=`⟨*file name*⟩ (no default, initially unset)

Fills the current path with a tile pattern using an external image referenced by ⟨*file name*⟩.

```
\begin{tikzpicture}
\path[fill tile image=pink_marble.png]
  (2.75,-0.75) -- (3,0) -- (2.75,0.75)
  \foreach \w in {45,90,...,315}
    { -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```

`/tikz/fill tile image*={`⟨*graphics options*⟩`}{`⟨*file name*⟩`}` (no default, initially unset)

Fills the current path with a tile pattern using an external image referenced by ⟨*file name*⟩. The ⟨*graphics options*⟩ are given to the underlying `\includegraphics` command.

```
\begin{tikzpicture}
\path[fill tile image*={width=1cm}{pink_marble.png}]
  (2.75,-0.75) -- (3,0) -- (2.75,0.75)
  \foreach \w in {45,90,...,315}
    { -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```



`/tikz/fill tile picture=`⟨*graphical code*⟩ (no default, initially unset)

Fills the current path with a tile pattern using the given ⟨*graphical code*⟩.

```
\begin{tikzpicture}
\path[draw,fill tile picture={%
  \draw[red!50!yellow,line width=2mm]
    (0,0) circle (1cm);
  \draw[red,line width=5mm] (-1,-1) -- (1,1);
  \draw[red,line width=5mm] (-1,1) -- (1,-1);
  }]
  (2.75,-0.75) -- (3,0) -- (2.75,0.75)
  \foreach \w in {45,90,...,315}
    { -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```



`/tikz/fill tile picture*={`⟨*fraction*⟩`}{`⟨*graphical code*⟩`}` (no default, initially unset)

Fills the current path with a tile pattern using the given ⟨*graphical code*⟩. The graphic is resized by ⟨*fraction*⟩.

```
\begin{tikzpicture}
\path[draw,fill tile picture*={0.25}{%
  \draw[red!50!yellow,line width=2mm]
    (0,0) circle (1cm);
  \draw[red,line width=5mm] (-1,-1) -- (1,1);
  \draw[red,line width=5mm] (-1,1) -- (1,-1);
  }]
  (2.75,-0.75) -- (3,0) -- (2.75,0.75)
  \foreach \w in {45,90,...,315}
    { -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```



12.7 Filling Options

`/tikz/fill image opacity=`⟨*fraction*⟩ (no default, initially `1.0`)

Sets the fill opacity for the image or picture fill options to the given ⟨*fraction*⟩.

```
\begin{tikzpicture}
\path[fill stretch image=goldshade.png] (0,0) circle (1cm);
\path[fill=red,fill stretch image=goldshade.png,fill image opacity=0.75]
  (2,0) circle (1cm);
\path[fill=red,fill stretch image=goldshade.png,fill image opacity=0.5]
  (4,0) circle (1cm);
\path[fill=red,fill stretch image=goldshade.png,fill image opacity=0.25]
  (6,0) circle (1cm);
\path[fill=red] (8,0) circle (1cm);
\end{tikzpicture}
```



`/tikz/fill image scale=`⟨*fraction*⟩ (no default, initially `1.0`)

Stretches, zooms, overzooms or shrinks the image or picture to the given ⟨*fraction*⟩ of the width and height of the current path.

```
\begin{tikzpicture}
\path[draw,fill zoom image=goldshade.png]
  (0,0) rectangle +(2,2);

\path[draw,fill zoom image=goldshade.png,fill image scale=0.75]
  (3,0) rectangle +(2,2);

\path[draw,fill zoom image=goldshade.png,fill image scale=1.5]
  (6,0) rectangle +(2,2);
\end{tikzpicture}
```

U 2018-03-18 `/tikz/fill image options=`⟨*graphics options*⟩ (no default, initially empty)

The ⟨*graphics options*⟩ are given to the underlying `\includegraphics` command for the image fill options. This can be just together with `/tikz/fill stretch image` → P. 257, `/tikz/fill overzoom image` → P. 258, `/tikz/fill zoom image` → P. 259, and `/tikz/fill tile image` → P. 261.

```
\begin{tikzpicture}
\path[fill image options={width=1cm},
  fill tile image=pink_marble.png]
  (2.75,-0.75) -- (3,0) -- (2.75,0.75)
  \foreach \w in {45,90,...,315}
    { -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```



Image blending example

```
\begin{tikzpicture}[every node/.style=
  {circle,minimum width=2cm}]
\node[fill stretch image=blueshade.png]
  (A) at (120:3cm) {A};
\node[fill stretch image=goldshade.png]
  (B) at (60:3cm) {B};
\node[
  preaction={fill stretch image=blueshade.png},
  fill stretch image=goldshade.png,
  fill image opacity=0.5] (C) {C};
\path (A) -- node{$+$} (B);
\draw[->,very thick] (A)--(C);
\draw[->,very thick] (B)--(C);
\end{tikzpicture}
```



12.8 Straightening of the Arcs

! This patch is considered as an experimental feature. It changes some of the original Ti*k*Z code. This change may break with future updates of Ti*k*Z.

N 2014-05-05 **\tcbpatcharcangular**

The Ti*k*Z package provides a nice `rounded corners` option to replace all corners by little arcs. `\tcbpatcharcangular` is a patch which straightens the arcs. To say it more prosaic, the little arcs are replaced by little straight lines.

```
\begin{tikzpicture}
  \draw[thick,rounded corners=8pt]
    (0,0) -- (0,2) -- (1,3.25) -- (2,2) -- (2,0)
     -- (0,2) -- (2,2) -- (0,0) -- (2,0);
  \tcbpatcharcangular
  \draw[thick,rounded corners=8pt,xshift=2.5cm]
    (0,0) -- (0,2) -- (1,3.25) -- (2,2) -- (2,0)
     -- (0,2) -- (2,2) -- (0,0) -- (2,0);
\end{tikzpicture}
```



N 2014-05-05 **\tcbpatcharcround**

This macro reverts `\tcbpatcharcangular`, i.e., the patch from `\tcbpatcharcangular` is replaced by the original code.

12.9 Extracting Node Dimensions

The following auxiliary macros are defined by the LIB skins library. They allow to determine the width and height of an arbitrary TikZ node. To be more specific, they determine the east-to-west and the north-to-south dimensions which may be not the maximal dimensions for a non-rectangular node. Note that the following dimensions are measured exactly including the line width of the border line. If a new rectangle or node with the same dimensions and a border is to be drawn, this border width has to be substracted.

N 2014-09-19 `\tcbsettowidthofnode{⟨register⟩}{⟨node⟩}`

Sets the east-to-west dimension of the given ⟨*node*⟩ to the TEX ⟨*register*⟩.

N 2014-09-19 `\tcbsetmacrotowidthofnode{⟨macro⟩}{⟨node⟩}`

Defines ⟨*macro*⟩ as the east-to-west dimension of the given ⟨*node*⟩.

N 2014-09-19 `\tcbsettoheightofnode{⟨register⟩}{⟨node⟩}`

Sets the north-to-south dimension of the given ⟨*node*⟩ to the TEX ⟨*register*⟩.

N 2014-09-19 `\tcbsetmacrotoheightofnode{⟨macro⟩}{⟨node⟩}`

Defines ⟨*macro*⟩ as the north-to-south dimension of the given ⟨*node*⟩.

```
\begin{tikzpicture}
  \node[align=center,draw=red,fill=yellow] (A) {This is my\\example node};
  \tcbsetmacrotowidthofnode\mywidth{A}
  \tcbsetmacrotoheightofnode\myheight{A}
  \path[fill=blue!25!white]           %  rectangle widthout border
    ([xshift=2mm]A.south east)
    rectangle node{Copy} +(\mywidth,\myheight);
  \node[draw=blue,fill=blue!25!white, % standard border width 0.4pt
    minimum width=\mywidth-0.4pt,     % minus width of border
    minimum height=\myheight-0.4pt    % minus height of border
    ]
    at ([xshift=5cm]A) {Copy 2};
\end{tikzpicture}
```

12.10 Hyper Nodes

The following auxiliary macro is defined by the LIB skins library.

N 2016-02-03 `\tcbhypernode{⟨macro⟩}{⟨node⟩}`

Applies a hyperlink creating ⟨*macro*⟩ from the package `hyperref` [15] to an existing `tikz` ⟨*node*⟩. `\tcbhypernode` can only be used inside a `tikzpicture` environment. The last argument of the ⟨*macro*⟩ is to be omitted and should stand for an object (text) which is to be made a hyperlink. For example, use `\hyperref[name]` instead of `\hyperref[name]{text}`.

```
% \usepackage{hyperref}
\begin{tikzpicture}
  \node[align=center,draw=red,fill=red!5] (mybutton)
    {Click me to jump to Section~\ref*{sec:tikzimagefilling}};
  \tcbhypernode{\hyperref[sec:tikzimagefilling]}{mybutton}
\end{tikzpicture}
```



13 Library LIB vignette

The library is loaded by a package option or inside the preamble by:

```
\tcbuselibrary{vignette}
```

This also loads the LIB skins library, see Section 10 on page 148, and the `fadings` library of `tikz` [22].

13.1 Vignette Drawing

N 2016-04-22 `\tcbvignette{⟨options⟩}`

In this context, a *vignette* is a four part rectangular frame. It is constructed as several Ti*k*Z paths and, therefore, can only be used inside a `tikzpicture` environment or inside `tcolorbox` → P. 12 options.

The ⟨*options*⟩ control position, size and style settings of the vignette. Theses options have the common key path `/tcb/vig/` and are described in the following.

The next examples show direct `\tcbvignette` usage without a `tcolorbox` → P. 12.

```
\begin{tikzpicture}
  \tcbvignette{}
\end{tikzpicture}
```

```
\begin{tikzpicture}
  \node[draw,fill=blue!15!white] (A) {Test};
  \tcbvignette{outside node=A,raised color=blue}
\end{tikzpicture}
```

```
\begin{tikzpicture}
  \node[draw,fill=blue!15!white] (A) {Another Test};
  \tcbvignette{size=3mm,outside node=A,
    north style=red,east style=yellow,
    south style=blue,west style=green}
\end{tikzpicture}
```

```
\begin{tikzpicture}
  \node[inner sep=3mm,fill=red!75] (A) {Test};
  \tcbvignette{over node=A,fade in}
\end{tikzpicture}
```

`\tcbvignette` can be used directly inside appropriate options keys for `tcolorbox` → P. 12. Note that options like `/tcb/underlay` → P. 195 need `/tcb/enhanced` → P. 206 or similar settings.

```
\begin{tcolorbox}[enhanced,size=small,sharp corners,
  colback=green!10,colframe=green!50!black,
  boxrule=1mm,titlerule=0mm,
  title=My title,center title,fonttitle=\bfseries,
  underlay={\tcbvignette{size=1mm,inside node=frame,
      raised color=green!50!black}}]
    This is a tcolorbox.
\end{tcolorbox}
```



Mostly, convenient short cuts like `/tcb/underlay vignette` → P. 272 can be used to add a *vignette* to a `tcolorbox` → P. 12. Here, `\tcbvignette` → P. 265 is used internally.

```
\begin{tcolorbox}[enhanced,size=small,sharp corners,
  colback=green!10,colframe=green!50!black,
  boxrule=1mm,titlerule=0mm,
  title=My title,center title,fonttitle=\bfseries,
  underlay vignette]
    This is a tcolorbox.
\end{tcolorbox}
```



13.2 Generic Geometry Settings

N 2016-04-22 **`/tcb/vig/xmin`**=⟨*length*⟩ (no default, initially `0pt`)

Sets the lower horizontal limit of a `\tcbvignette` → P. 265.

N 2016-04-22 **`/tcb/vig/xmax`**=⟨*length*⟩ (no default, initially `1cm`)

Sets the upper horizontal limit of a `\tcbvignette` → P. 265.

N 2016-04-22 **`/tcb/vig/ymin`**=⟨*length*⟩ (no default, initially `0pt`)

Sets the lower vertical limit of a `\tcbvignette` → P. 265.

N 2016-04-22 **`/tcb/vig/ymax`**=⟨*length*⟩ (no default, initially `1cm`)

Sets the upper vertical limit of a `\tcbvignette` → P. 265.

```
\begin{tikzpicture}
  \fill [black!20] (0,0) rectangle (3,2);
  \path [pattern=checkerboard,pattern color=black!30]
    (0,0) rectangle (3,2);
  \tcbvignette{xmin=1cm,xmax=2.5cm,ymin=0.5cm,ymax=1.75cm}
\end{tikzpicture}
```



N 2016-04-22 **`/tcb/vig/lower left corner`**=⟨*coordinates*⟩ (style, initially `0,0`)

Sets the lower left corner of a `\tcbvignette` → P. 265. This style sets `/tcb/vig/xmin` and `/tcb/vig/ymin`.

N 2016-04-22 **`/tcb/vig/upper right corner`**=⟨*coordinates*⟩ (style, initially `1,1`)

Sets the upper right corner of a `\tcbvignette` → P. 265. This style sets `/tcb/vig/xmax` and `/tcb/vig/ymax`.

```
\begin{tikzpicture}
  \fill [black!20] (0,0) rectangle (3,2);
  \path [pattern=checkerboard,pattern color=black!30]
    (0,0) rectangle (3,2);
  \tcbvignette{lower left corner={1,0.5},
               upper right corner={2.5,1.75}}
\end{tikzpicture}
```



N 2016-04-22 **/tcb/vig/inside node=⟨*name*⟩** (style, initally unset)

Places the \tcbvignette → P. 265 inside the node with the given ⟨*name*⟩. The outer limits of the *vignette* are adapted to the node geometry.

```
\begin{tikzpicture}
  \node[minimum width=2cm,minimum height=1cm] (A) {Node A};
  \tcbvignette{inside node=A}
  \draw[very thick] (A.south west) rectangle (A.north east);
\end{tikzpicture}
```



N 2016-04-22 **/tcb/vig/outside node=⟨*name*⟩** (style, initally unset)

Places the \tcbvignette → P. 265 outside the node with the given ⟨*name*⟩. The inner limits of the *vignette* are adapted to the node geometry.

```
\begin{tikzpicture}
  \node[minimum width=2cm,minimum height=1cm] (A) {Node A};
  \tcbvignette{outside node=A}
  \draw[very thick] (A.south west) rectangle (A.north east);
\end{tikzpicture}
```



N 2016-04-22 **/tcb/vig/over node=⟨*name*⟩** (style, initally unset)

Places the \tcbvignette → P. 265 over the node with the given ⟨*name*⟩. The outer limits of the *vignette* are adapted to the node geometry, but are shifted to the outside by /tcb/vig/over node offset.

```
\begin{tikzpicture}
  \node[minimum width=2cm,minimum height=1cm] (A) {Node A};
  \tcbvignette{over node offset=1mm,over node=A}
  \draw[very thick] (A.south west) rectangle (A.north east);
\end{tikzpicture}
```



N 2016-04-22 **/tcb/vig/over node offset=⟨*length*⟩** (no default, initially 0.1mm)

Determines the shift value for /tcb/vig/over node. Note that /tcb/vig/over node offset has to be set *before* /tcb/vig/over node is used.

N 2016-04-22 **/tcb/vig/north size=⟨*length*⟩** (no default, initially 2mm)

Sets the thickness of the north *vignette* part.

```
\begin{tikzpicture}
  \tcbvignette{north size=4mm}
\end{tikzpicture}
```

N 2016-04-22 **/tcb/vig/south size=⟨*length*⟩** (no default, initially 2mm)

Sets the thickness of the south *vignette* part.

```
\begin{tikzpicture}
  \tcbvignette{south size=4mm}
\end{tikzpicture}
```

N 2016-04-22 **/tcb/vig/east size=⟨*length*⟩** (no default, initially 2mm)

Sets the thickness of the east *vignette* part.

```
\begin{tikzpicture}
  \tcbvignette{east size=4mm}
\end{tikzpicture}
```

N 2016-04-22 **/tcb/vig/west size**=⟨*length*⟩ (no default, initially 2mm)

Sets the thickness of the west *vignette* part.

```
\begin{tikzpicture}
  \tcbvignette{west size=4mm}
\end{tikzpicture}
```

N 2016-04-22 **/tcb/vig/vertical size**=⟨*length*⟩ (style, initially 2mm)

Sets /tcb/vig/north size → P. 267 and /tcb/vig/south size → P. 267, to the given ⟨*length*⟩.

```
\begin{tikzpicture}
  \tcbvignette{vertical size=4mm}
\end{tikzpicture}
```

N 2016-04-22 **/tcb/vig/horizontal size**=⟨*length*⟩ (style, initially 2mm)

Sets /tcb/vig/east size → P. 267 and /tcb/vig/west size, to the given ⟨*length*⟩.

```
\begin{tikzpicture}
  \tcbvignette{horizontal size=4mm}
\end{tikzpicture}
```

N 2016-04-22 **/tcb/vig/size**=⟨*length*⟩ (style, initially 2mm)

Sets /tcb/vig/north size → P. 267, /tcb/vig/south size → P. 267, /tcb/vig/east size → P. 267, and /tcb/vig/west size to the given ⟨*length*⟩.

```
\begin{tikzpicture}
  \tcbvignette{size=4mm}
\end{tikzpicture}
```

! /tcb/vig/north size → P. 267, /tcb/vig/south size → P. 267, etc. have to be set *before* /tcb/vig/outside node → P. 267 is used.

13.3 Generic Color and Style Settings

N 2016-04-22 **/tcb/vig/north style**={⟨*style*⟩} (no default, initially red!50!white)

Sets TikZ ⟨*style*⟩ options for the north *vignette* part.

```
\begin{tikzpicture}
  \tcbvignette{north style=blue}
\end{tikzpicture}
```

N 2016-04-22 **/tcb/vig/south style**={⟨*style*⟩} (no default, initially red!50!black)

Sets TikZ ⟨*style*⟩ options for the south *vignette* part.

```
\begin{tikzpicture}
  \tcbvignette{south style={draw=blue,fill=yellow}}
\end{tikzpicture}
```

N 2016-04-22 **/tcb/vig/east style=**{⟨*style*⟩} (no default, initially `red!75!black`)

Sets TikZ ⟨*style*⟩ options for the east *vignette* part.

```
\begin{tikzpicture}
  \tcbvignette{east style={left color=yellow!75!black,
    right color=blue!75!black}}
\end{tikzpicture}
```

N 2016-04-22 **/tcb/vig/west style=**{⟨*style*⟩} (no default, initially `red!75!white`)

Sets TikZ ⟨*style*⟩ options for the west *vignette* part.

```
\begin{tikzpicture}
  \tcbvignette{west style={preaction={fill=black!20},
    pattern=checkerboard,
    pattern color=black!30}}
\end{tikzpicture}
```

N 2016-05-24 **/tcb/vig/scope=**{⟨*style*⟩} (no default, initially empty)

The four *vignette* parts are drawn inside a TikZ `scope` environment which takes the given ⟨*style*⟩ as option.

```
\begin{tikzpicture}
  \tcbvignette{scope={transparency group,opacity=0.25}}
\end{tikzpicture}
```


N 2016-04-22 **/tcb/vig/raised color=**⟨*color*⟩ (no default)

Creates a raised frame impression by setting the four style options /tcb/vig/north style → P. 268, /tcb/vig/south style → P. 268, /tcb/vig/east style, and /tcb/vig/west style to darkened and lightened variations of the given ⟨*color*⟩.

```
\begin{tikzpicture}
  \tcbvignette{raised color=blue}
\end{tikzpicture}
```

N 2016-04-22 **/tcb/vig/lowered color=**⟨*color*⟩ (no default)

Creates a lowered frame impression by setting the four style options /tcb/vig/north style → P. 268, /tcb/vig/south style → P. 268, /tcb/vig/east style, and /tcb/vig/west style to darkened and lightened variations of the given ⟨*color*⟩.

```
\begin{tikzpicture}
  \tcbvignette{lowered color=green!75!black}
\end{tikzpicture}
```

N 2016-04-22 **/tcb/vig/color from=**⟨*inner*⟩ **to** ⟨*outer*⟩ (no default)

Sets the four style options /tcb/vig/north style → P. 268, /tcb/vig/south style → P. 268, /tcb/vig/east style, and /tcb/vig/west style such that the color shades from the ⟨*inner*⟩ color to the ⟨*outer*⟩ color.

```
\begin{tikzpicture}
  \tcbvignette{color from=red to blue!50}
\end{tikzpicture}
```

N 2016-04-22 **/tcb/vig/base color=**⟨*color*⟩ (no default)

Sets the base color for /tcb/vig/raised color, /tcb/vig/lowered color, /tcb/finish fading vignette → P. 275. Typically, this value has not to be set directly.

N 2016-04-22 `/tcb/vig/draw method=direct|clipped` (no default, initially `direct`)

Especially, if shadings or fadings are used, the drawn *vignette* graphs are displayed sometimes not as perfect as expected. Glitches and imperfections are very dependent on the previewer software. The `/tcb/vig/draw method` intends to give a choice of alternative drawing methods.

- `direct`: The *vignette* parts are drawn/filled by using a single Ti*k*Z graph. This is the preferred (and default) method for solid color graphs.
- `clipped`: The *vignette* parts are drawn somewhat oversized and are clipped to the intended region. In combination with shadings and fadings this seems to give a better/different optical result (depends on the previewer).

```
\begin{tikzpicture}
  \tcbvignette{color from=red to yellow}
\end{tikzpicture}
```

```
\begin{tikzpicture}
  \tcbvignette{color from=red to yellow,draw method=clipped}
\end{tikzpicture}
```

This option is a stopgap and may be changed or preferably removed in future.

13.4 Generic Fading Settings

The `fadings` library of `tikz` [22] is loaded automatically by the LIB vignette library. Amongst others, the fadings `west`, `east`, `north`, and `south` are defined inside the `fadings` library.

The LIB vignette library adds some more fadings called `semi west`, `semi east`, `semi north`, and `semi south`. These fadings are much *weaker* than the normal fadings.

```
\begin{tikzpicture}
  \fill [black!20] (0,0) rectangle (1,1);
  \path [pattern=checkerboard,pattern color=black!30]
    (0,0) rectangle (1,1);
  \fill [path fading=semi west,blue] (0,0) rectangle (1,1);
\end{tikzpicture}
```

Comparison of the Fadings

`west`	`east`
`north`	`south`
`semi west`	`semi east`
`semi north`	`semi south`

N 2016-04-22 **/tcb/vig/fade in={⟨style⟩}** (style, default **white**)

Sets the four style options /tcb/vig/north style →P. 268, /tcb/vig/south style →P. 268, /tcb/vig/east style →P. 269, and /tcb/vig/west style →P. 269 such that the paths fade from outside to inside.

```
\begin{tikzpicture}
  \fill [black!20] (-0.5,-0.5) rectangle (1.5,1.5);
  \path [pattern=checkerboard,pattern color=black!30]
    (-0.5,-0.5) rectangle (1.5,1.5);
  \tcbvignette{fade in=blue}
\end{tikzpicture}
```



N 2016-04-22 **/tcb/vig/fade out={⟨style⟩}** (style, default **white**)

Sets the four style options /tcb/vig/north style →P. 268, /tcb/vig/south style →P. 268, /tcb/vig/east style →P. 269, and /tcb/vig/west style →P. 269 such that the paths fade from inside to outside.

```
\begin{tikzpicture}
  \fill [black!20] (-0.5,-0.5) rectangle (1.5,1.5);
  \path [pattern=checkerboard,pattern color=black!30]
    (-0.5,-0.5) rectangle (1.5,1.5);
  \tcbvignette{fade out=blue}
\end{tikzpicture}
```



N 2016-04-22 **/tcb/vig/semi fade in={⟨style⟩}** (style, default **white**)

Sets the four style options /tcb/vig/north style →P. 268, /tcb/vig/south style →P. 268, /tcb/vig/east style →P. 269, and /tcb/vig/west style →P. 269 such that the paths fade weak from outside to inside.

```
\begin{tikzpicture}
  \fill [black!20] (-0.5,-0.5) rectangle (1.5,1.5);
  \path [pattern=checkerboard,pattern color=black!30]
    (-0.5,-0.5) rectangle (1.5,1.5);
  \tcbvignette{semi fade in=blue}
\end{tikzpicture}
```



N 2016-04-22 **/tcb/vig/semi fade out={⟨style⟩}** (style, default **white**)

Sets the four style options /tcb/vig/north style →P. 268, /tcb/vig/south style →P. 268, /tcb/vig/east style →P. 269, and /tcb/vig/west style →P. 269 such that the paths fade weak from inside to outside.

```
\begin{tikzpicture}
  \fill [black!20] (-0.5,-0.5) rectangle (1.5,1.5);
  \path [pattern=checkerboard,pattern color=black!30]
    (-0.5,-0.5) rectangle (1.5,1.5);
  \tcbvignette{semi fade out=blue}
\end{tikzpicture}
```



13.5 Vignette as Underlay

N 2016-04-22 **/tcb/underlay vignette={⟨*options*⟩}** (style, no default)

This puts a \tcbvignette → P. 265 with the given ⟨*options*⟩ as /tcb/underlay → P. 195 to a tcolorbox → P. 12. The dimensions of the *vignette* are matched to the dimensions of the tcolorbox → P. 12. For example, /tcb/leftrule → P. 35 is used as /tcb/vig/west size → P. 268. Also, /tcb/colframe → P. 27 is used as /tcb/vig/raised color → P. 269.
For a /tcb/breakable → P. 365 tcolorbox, the *vignette* is also been broken. Alternatively, \tcbvignette → P. 265 could be used directly inside an /tcb/underlay → P. 195 with appropriate settings.

```
\begin{tcolorbox}[enhanced,size=small,sharp corners,
  colback=green!10,colframe=green!50!black,
  boxrule=2mm,titlerule=0mm,
  title=My title,center title,fonttitle=\bfseries,
  underlay vignette]
    This is a tcolorbox.
\end{tcolorbox}
```

My title
This is a tcolorbox.

```
\begin{tcolorbox}[enhanced,size=small,arc=0pt,
  colback=blue!10,colframe=blue,boxrule=2mm,
  underlay vignette={size=1.5mm}]
    This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

```
\begin{tcolorbox}[enhanced,size=small,sharp corners,
  colframe=red,interior hidden,boxrule=2mm,
  colupper=white,center upper,fontupper=\bfseries,
  underlay vignette]
    This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

```
\begin{tcolorbox}[enhanced,size=small,sharp corners,
  colback=red!50!yellow,frame hidden,boxrule=2mm,
  underlay vignette={color from=red!50!yellow to white,
     draw method=clipped,size=2.1mm}]
    This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

```
\tcbox[enhanced,sharp corners,colback=red!10,colframe=red]
  {Test}

\tcbox[enhanced,sharp corners,colback=red!10,colframe=red,
  underlay vignette]{Test}
```

Test

Test

N 2016-04-22 **/tcb/underlay raised shading vignette={⟨*options*⟩}** (style, no default)

This is a special style derived from /tcb/underlay vignette → P. 272, where the frame color is shaded to create a soft raised frame impression.

```
\begin{tcolorbox}[enhanced,sharp corners,
  colback=green!10,
  colframe=green!50!black,
  size=small,boxrule=2mm,titlerule=0mm,
  title=My title,center title,fonttitle=\bfseries,
  underlay raised shading vignette]
    This is a tcolorbox.
\end{tcolorbox}
```



N 2016-04-22 **/tcb/underlay raised fading vignette={⟨*options*⟩}** (style, no default)

This style gives a similar effect as /tcb/underlay raised shading vignette, but a path fading is used here. Different optical impression are very previewer-dependent.

```
\begin{tcolorbox}[enhanced,sharp corners,
  colback=green!10,
  colframe=green!50!black,
  size=small,boxrule=2mm,titlerule=0mm,
  title=My title,center title,fonttitle=\bfseries,
  underlay raised fading vignette]
    This is a tcolorbox.
\end{tcolorbox}
```



N 2016-04-22 **/tcb/underlay shade in vignette={⟨*options*⟩}** (style, no default)

This is a special style derived from /tcb/underlay vignette → P. 272, where the frame color is shaded into the interior color.

```
\begin{tcolorbox}[enhanced,sharp corners,frame hidden,
  colback=green!10,
  colframe=green!50!black,
  size=small,boxrule=2mm,titlerule=0mm,
  underlay shade in vignette]
    This is a tcolorbox.
\end{tcolorbox}
```



13.6 Vignette as Finish

N 2016-04-22 **/tcb/finish vignette={⟨*options*⟩}** (style, no default)

This puts a \tcbvignette → P. 265 with the given ⟨*options*⟩ as /tcb/finish → P. 197 to a tcolorbox → P. 12. The default style settings create a raised frame impression by drawing black and white color parts with reduced opacity.

```
\begin{tcolorbox}[enhanced,size=small,
  colback=green!10,colframe=green!50!black,
  boxrule=0.5mm,titlerule=0mm,
  title=My title,center title,fonttitle=\bfseries,
  finish vignette={size=1mm}]
    This is a tcolorbox.
\end{tcolorbox}
```

My title
This is a tcolorbox.

```
\tcbincludegraphics[blankest,width=3cm,
  finish vignette={size=3mm}]{pink_marble.png}
```



N 2016-04-22 **/tcb/finish raised fading vignette={⟨*options*⟩}** (style, no default)

This puts a \tcbvignette → P. 265 with the given ⟨*options*⟩ as /tcb/finish → P. 197 to a tcolorbox → P. 12. The default style settings create a soft raised frame impression by drawing fading black and white color parts.

```
\begin{tcolorbox}[enhanced,size=small,
  colback=green!10,colframe=green!50!black,
  boxrule=0.5mm,titlerule=0mm,
  title=My title,center title,fonttitle=\bfseries,
  finish raised fading vignette={size=1mm}]
    This is a tcolorbox.
\end{tcolorbox}
```

My title
This is a tcolorbox.

```
\tcbincludegraphics[blankest,width=3cm,
  finish raised fading vignette={size=3mm}]{pink_marble.png}
```

N 2016-04-22 **/tcb/finish fading vignette={⟨*options*⟩}** (style, no default)

This puts a \tcbvignette → P. 265 with the given ⟨*options*⟩ as /tcb/finish → P. 197 to a tcolorbox → P. 12. The default style settings fade the box into white from inside to outside. Note that /tcb/vig/over node → P. 267 is used here. /tcb/vig/over node offset → P. 267 can be adapted to overlap the box more or less. The fade color can be set using /tcb/vig/base color → P. 269.

```
\begin{tcolorbox}[enhanced,size=small,
  colback=green!10,colframe=green!50!black,
  boxrule=0.5mm,titlerule=0mm,
  title=My title,center title,fonttitle=\bfseries,
  finish fading vignette={size=2mm}]
    This is a tcolorbox.
\end{tcolorbox}
```

My title

This is a tcolorbox.

```
\tcbincludegraphics[blankest,width=3cm,
  finish fading vignette={size=3mm}]{pink_marble.png}
```

```
\begin{tcolorbox}[colback=blue!50!black,size=small,
  title=Example]
\tcbincludegraphics[blankest,
  finish fading vignette={base color=blue!50!black,size=3mm,
    over node offset=0.2mm}]{pink_marble.png}
\end{tcolorbox}
```

Example



```
\begin{tcbitemize}[raster columns=3,bicolor,
  raster equal height,sharp corners,boxrule=2mm,
  colframe=red,colback=yellow!5,colbacklower=yellow!25!red!20]
\tcbitem A
\tcbitem[underlay vignette] B
\tcbitem[underlay={\tcbvignette{inside node=interior,
  lowered color=red,size=1mm}}] C
\tcbitem[underlay vignette,
  underlay={\tcbvignette{inside node=interior,
  lowered color=red,size=1mm}}] D
\tcbitem[boxrule=3mm,underlay vignette={size=2mm},
  underlay={\tcbvignette{inside node=interior,
  lowered color=red,size=1mm}}] E
\tcbitem[underlay raised shading vignette] F
\tcbitem[underlay raised shading vignette,
  underlay={\tcbvignette{inside node=interior,
  lowered color=red,size=1mm}}] G
\tcbitem[title=H1,underlay={\tcbvignette{inside node=interior,
  lowered color=red,size=1mm}},finish vignette] H2
\tcbitem[boxrule=0.25mm,colback=red!30,finish vignette] I1 \tcblower I2
\tcbitem[tile,colback=red!30,finish raised fading vignette] J1 \tcblower J2
\tcbitem[boxrule=1mm,underlay={\tcbvignette{inside node=interior,
  raised color=red,size=1mm}}] K
\tcbitem[boxrule=1mm,title=L1,underlay={\tcbvignette{inside node=title,
  lowered color=red,size=0.5mm}}] L2
\end{tcbitemize}
```



14 Library raster

The library is loaded by a package option or inside the preamble by:

```
\tcbuselibrary{raster}
```

14.1 Concept of Rasters

A *raster* is used to align several colored boxes in a regular way. It can be seen as a far related counterpart to the `matrix` construct of Ti*k*Z, but it differs in many aspects.

In principle, `tcolorbox`es are arranged in rows and columns when put inside a `tcbraster` → P. 279 environment. The boxes are fluently added to the raster like adding text to a paragraph. Especially, line/row breaks are done automatically and one cannot end a line/row ahead of schedule. Further, a *raster* is not restricted to a single page but may break into an arbitrary series of pages.



```
\begin{tcbraster}[raster columns=3,raster rows=3,raster height=\linewidth,
  enhanced,size=small,sharp corners,arc=8mm,colframe=red!50!black,
  colback=yellow!10!white,watermark overzoom=1.0,fit algorithm=hybrid* ]
  \begin{tcolorbox}[rounded corners=northwest,boxrule=0pt,
    watermark graphics=lichtspiel.jpg]\end{tcolorbox}
  \tcboxfit{\lipsum[1]}
  \begin{tcolorbox}[rounded corners=northeast,boxrule=0pt,
    watermark graphics=goldshade.png]\end{tcolorbox}
  \tcboxfit{\lipsum[2]}
  \begin{tcolorbox}[valign=center,halign=center]Nine Boxes.\end{tcolorbox}
  \tcboxfit{\lipsum[3]}
  \begin{tcolorbox}[rounded corners=southwest,boxrule=0pt,
    watermark graphics=goldshade.png]\end{tcolorbox}
  \tcboxfit{\lipsum[4]}
  \begin{tcolorbox}[rounded corners=southeast,boxrule=0pt,
    watermark graphics=lichtspiel.jpg]\end{tcolorbox}
\end{tcbraster}
```

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nine Boxes.

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

14.2 Macros of the Library

N 2014-11-10
U 2017-02-01

```
\begin{tcbraster}[⟨options⟩]
  ⟨environment content⟩
\end{tcbraster}
```

A raster arranges enclosed boxes in a regular way, mainly into rows and columns. The ⟨*options*⟩ are used to control the raster parameters and to set the properties for the enclosed boxes.

- The *raster* is only allowed to contain a series of `tcolorbox` → P. 12 environments or derived constructs. With some small restrictions, boxes created with `\tcboxfit` → P. 410 can also be added. Boxes created with `\tcbox` → P. 14 are not reasonable here, but may be used to a certain degree.
- Do not add anything else between the boxes inside the raster with exception of white-space. Especially, do not use `\\` or `\par` to end a row; row breaks are done automatically.
- The boxes inside a raster are numbered automatically. `\thetcbrasternum` may be used inside a box to access this number.

```
\begin{tcbraster}[raster columns=3, raster equal height,
  size=small,colframe=red!50!black,colback=red!10!white,colbacktitle=red!50!white,
  title={Box \# \thetcbrasternum}]
  \begin{tcolorbox}First box\end{tcolorbox}
  \begin{tcolorbox}Second box\end{tcolorbox}
  \begin{tcolorbox}This is a box\\with a second line\end{tcolorbox}
  \begin{tcolorbox}Another box\end{tcolorbox}
  \begin{tcolorbox}A box again\end{tcolorbox}
\end{tcbraster}
```

Box # 1
First box

Box # 2
Second box

Box # 3
This is a box
with a second line

Box # 4
Another box

Box # 5
A box again

```
\begin{tcbraster}[raster columns=2, raster equal height=rows,
  size=small,colframe=red!50!black,colback=red!10!white,colbacktitle=red!50!white,
  title={Box \# \thetcbrasternum}]
  \begin{tcolorbox}First box\end{tcolorbox}
  \begin{tcolorbox}Second box\end{tcolorbox}
  \begin{tcolorbox}This is a box\\with a second line\end{tcolorbox}
  \begin{tcolorbox}Another box\end{tcolorbox}
  \begin{tcolorbox}A box again\end{tcolorbox}
\end{tcbraster}
```

Box # 1
First box

Box # 2
Second box

Box # 3
This is a box
with a second line

Box # 4
Another box

Box # 5
A box again

N 2014-11-10 `\begin{tcbitemize}[⟨options⟩]`
⟨*environment content*⟩
`\end{tcbitemize}`

This is a special case of a `tcbraster` → P. 279 with the given ⟨*options*⟩.

- Here, the enclosed boxes are created using `\tcbitem`.
- There has to be at least one `\tcbitem`.
- One cannot use anything else than `\tcbitem` to add something to the *raster*.

This leads to a very compact syntax.

```
\begin{tcbitemize}[raster columns=2, raster equal height=rows,
  size=small,colframe=red!50!black,colback=red!10!white,colbacktitle=red!50!white,
  title={Box \# \thetcbrasternum}]
  \tcbitem First box
  \tcbitem Second box
  \tcbitem This is a box\\with a second line
  \tcbitem[colback=yellow,colbacktitle=yellow!50!black] Another box
  \tcbitem A box again
\end{tcbitemize}
```



! `tcbitemize` has more restrictions than `tcbraster` → P. 279. Especially, the `/tcb/capture` → P. 94 mode has to be `minipage`. For example, `/tcb/fit` → P. 412 cannot be used safely. If `/tcb/fit` → P. 412 should be used, turn over to `tcbraster` → P. 279.

N 2014-11-10 `\tcbitem[⟨options⟩]`

Used inside `tcbitemize` to create a new `tcolorbox` → P. 12 with the given ⟨*options*⟩.

N 2016-02-19

```
\begin{tcboxedraster}[⟨raster options⟩]{⟨box options⟩}
  ⟨environment content⟩
\end{tcboxedraster}
```

This is a convenience environment which combines a `tcolorbox` → P. 12 with an embedded `tcbraster` → P. 279. The ⟨*box options*⟩ are given to the outer `tcolorbox` → P. 12, while the ⟨*raster options*⟩ are given to the embedded `tcbraster` → P. 279. This environment is especially useful for rasters inside rasters.

```
\begin{tcboxedraster}[raster columns=3, raster equal height,
  size=small,colframe=red!50!black,colback=red!10!white,colbacktitle=red!50!white,
  title={Box \# \thetcbrasternum}]
  {colback=yellow!10,fonttitle=\bfseries,title=Boxed Raster}
  \begin{tcolorbox}First box\end{tcolorbox}
  \begin{tcolorbox}Second box\end{tcolorbox}
  \begin{tcolorbox}This is a box\\with a second line\end{tcolorbox}
  \begin{tcolorbox}Another box\end{tcolorbox}
  \begin{tcolorbox}A box again\end{tcolorbox}
\end{tcboxedraster}
```

Boxed Raster

Box # 1	Box # 2	Box # 3
First box	Second box	This is a box with a second line
Box # 4	**Box # 5**	
Another box	A box again	

```
% \tcbuselibrary{skins}
\begin{tcbraster}[raster columns=2, raster equal height,
  raster every box/.style={size=small,colframe=red!50!black,colback=red!10!white,
    valign=center,halign=center}]
  \begin{tcolorbox}One\end{tcolorbox}
  \begin{tcolorbox}Two\end{tcolorbox}
    \begin{tcboxedraster}{blankest}
      \begin{tcolorbox}Three\end{tcolorbox}
      \begin{tcolorbox}Four\end{tcolorbox}
      \begin{tcolorbox}Five\end{tcolorbox}
      \begin{tcolorbox}Six\end{tcolorbox}
    \end{tcboxedraster}
    \begin{tcolorbox}Seven\end{tcolorbox}
\end{tcbraster}
```

One	Two
Three / Four / Five / Six	Seven

N 2016-04-27

```
\begin{tcboxeditemize}[⟨raster options⟩]{⟨box options⟩}
  ⟨environment content⟩
\end{tcboxeditemize}
```

This is a convenience environment which combines a `tcolorbox` → P. 12 with an embedded `tcbitemize` → P. 280. The ⟨*box options*⟩ are given to the outer `tcolorbox` → P. 12, while the ⟨*raster options*⟩ are given to the embedded `tcbitemize` → P. 280. This environment is especially useful for rasters inside rasters.

```
\begin{tcboxeditemize}[raster columns=3, raster equal height,
  size=small,colframe=red!50!black,colback=red!10!white,colbacktitle=red!50!white,
  title={Box \# \thetcbrasternum}]
  {colback=yellow!10,fonttitle=\bfseries,title=Boxed Itemize}
  \tcbitem First box
  \tcbitem Second box
  \tcbitem This is a box\\with a second line
  \tcbitem Another box
  \tcbitem A box again
\end{tcboxeditemize}
```

Boxed Itemize

- Box # 1: First box
- Box # 2: Second box
- Box # 3: This is a box with a second line
- Box # 4: Another box
- Box # 5: A box again

14.3 Option Keys of the Library

N 2014-11-10 **/tcb/raster columns**=⟨*number*⟩ (no default, initially 2)

Sets the ⟨*number*⟩ of columns for a *raster*.

```
\begin{tcbitemize}[raster columns=3,
  size=small,colframe=red!50!black,colback=red!10!white]
  \tcbitem One
  \tcbitem Two
  \tcbitem Three
  \tcbitem Four
\end{tcbitemize}
\begin{tcbitemize}[raster columns=4,
  size=small,colframe=blue!50!black,colback=blue!10!white]
  \tcbitem One
  \tcbitem Two
  \tcbitem Three
  \tcbitem Four
\end{tcbitemize}
```



N 2014-11-10 **/tcb/raster rows**=⟨*number*⟩ (no default, initially 2)

Sets the ⟨*number*⟩ of rows for a *raster*. Note that this is only relevant in connection with setting **/tcb/raster height** →P. 284 to a value greater than `0pt`. Then, it defines the number of rows *per* given height.

N 2014-11-10 **/tcb/raster width**=⟨*length*⟩ (no default, initially `\linewidth`)

Sets the total raster width to the given ⟨*length*⟩. **/tcb/raster left skip** →P. 285 and **/tcb/raster right skip** →P. 285 are part of the total width.

```
\begin{tcbitemize}[raster width=\linewidth/2,
  size=small,colframe=red!50!black,colback=red!10!white]
  \tcbitem One
  \tcbitem Two
  \tcbitem Three
  \tcbitem Four
\end{tcbitemize}
```



N 2014-11-10 **/tcb/raster height=⟨*length*⟩** (no default, initially 0pt)

Sets the raster height *per* /tcb/raster rows → P. 283 to the given ⟨*length*⟩. This forces an appropriate height for the enclosed boxes. /tcb/raster before skip and /tcb/raster after skip are not part of this calculation. If the ⟨*length*⟩ is set to 0pt, this feature is deactivated.

```
\begin{tcbitemize}[raster height=4cm, raster rows=2,
  size=small,colframe=red!50!black,colback=red!10!white]
  \tcbitem One
  \tcbitem Two
  \tcbitem[enhanced,
    finish={\draw[blue,very thick,<->] (frame.south)
      -- node[right,pos=.75]{4cm} +(0,4); }]
    Three
  \tcbitem Four
  \tcbitem Five
\end{tcbitemize}
```



N 2014-11-10
U 2014-12-16 **/tcb/raster before skip=⟨*glue*⟩** (no default, initially 2mm)

Space of the given ⟨*glue*⟩ is inserted vertically before the *raster*. This space is discardable.

N 2014-11-10
U 2014-12-16 **/tcb/raster after skip=⟨*glue*⟩** (no default, initially 2mm)

Space of the given ⟨*glue*⟩ is inserted vertically after the *raster*. This space is discardable.

N 2015-01-08 **/tcb/raster equal skip=⟨*length*⟩** (style, no default)

Shortcut to set /tcb/raster before skip, /tcb/raster after skip, /tcb/raster column skip → P. 285, and /tcb/raster row skip → P. 285 to the same ⟨*length*⟩ value.

```
\begin{tcbitemize}[raster equal skip=4mm,
  size=small,colframe=red!50!black,colback=red!10!white]
  \tcbitem One
  \tcbitem Two
  \tcbitem Three
  \tcbitem Four
\end{tcbitemize}
```



N 2014-11-10 **/tcb/raster left skip=⟨*length*⟩** (no default, initially 0pt)

Space of the given ⟨*length*⟩ is inserted horizontally left of the *raster*.

```
\begin{tcbitemize}[raster left skip=2cm,
  size=small,colframe=red!50!black,colback=red!10!white]
  \tcbitem One
  \tcbitem Two
  \tcbitem Three
  \tcbitem Four
\end{tcbitemize}
```

One | Two

Three | Four

N 2014-11-10 **/tcb/raster right skip=⟨*length*⟩** (no default, initially 0pt)

Space of the given ⟨*length*⟩ is inserted horizontally right of the *raster*.

```
\begin{tcbitemize}[raster right skip=2cm,
  size=small,colframe=red!50!black,colback=red!10!white]
  \tcbitem One
  \tcbitem Two
  \tcbitem Three
  \tcbitem Four
\end{tcbitemize}
```

One | Two

Three | Four

N 2014-11-10 **/tcb/raster column skip=⟨*length*⟩** (no default, initially 2mm)

Space of the given ⟨*length*⟩ is inserted horizontally between the columns.

```
\begin{tcbitemize}[raster column skip=2cm,
  size=small,colframe=red!50!black,colback=red!10!white]
  \tcbitem One
  \tcbitem Two
  \tcbitem Three
  \tcbitem Four
\end{tcbitemize}
```

One | Two

Three | Four

N 2014-11-10 **/tcb/raster row skip=⟨*length*⟩** (no default, initially 2mm)

Space of the given ⟨*length*⟩ is inserted vertically between the rows.

```
\begin{tcbitemize}[raster row skip=0pt,
  size=small,colframe=red!50!black,colback=red!10!white]
  \tcbitem One
  \tcbitem Two
  \tcbitem Three
  \tcbitem Four
\end{tcbitemize}
```

One | Two

Three | Four

N 2014-11-10 **/tcb/raster halign=**⟨*alignment*⟩ (no default, initially **left**)

Defines the horizontal alignment for the boxes of the rows of a *raster*, if these rows are not completely filled (mainly: the last one).
Feasible values for ⟨*alignment*⟩ are:

- **left**: align to the left side,
- **center**: align to the center,
- **right**: align to the right side.

```
\begin{tcbitemize}[raster halign=center,
  size=small,colframe=red!50!black,colback=red!10!white]
  \tcbitem One
  \tcbitem Two
  \tcbitem Three
\end{tcbitemize}
```

N 2014-11-10 **/tcb/raster valign=**⟨*alignment*⟩ (no default, initially **center**)

Defines the vertical alignment for the boxes of a row, if the boxes do not have equal height. This sets the **/tcb/box align** → P. 79 option.
Feasible values for ⟨*alignment*⟩ are:

- **top**: align to the top side,
- **center**: align to the center,
- **bottom**: align to the bottom side.

```
\begin{tcbitemize}[raster valign=top, raster columns=3,
  size=small,colframe=red!50!black,colback=red!10!white]
  \tcbitem \Huge One
  \tcbitem \Large Two
  \tcbitem Three
\end{tcbitemize}
\begin{tcbitemize}[raster valign=center, raster columns=3,
  size=small,colframe=blue!50!black,colback=blue!10!white]
  \tcbitem \Huge One
  \tcbitem \Large Two
  \tcbitem Three
\end{tcbitemize}
\begin{tcbitemize}[raster valign=bottom, raster columns=3,
  size=small,colframe=green!50!black,colback=green!10!white]
  \tcbitem \Huge One
  \tcbitem \Large Two
  \tcbitem Three
\end{tcbitemize}
```

N 2014-11-10
U 2017-02-28

/tcb/raster equal height=⟨*type*⟩ (default **all**, initially **none**)

Puts the enclosed boxes into a common /tcb/equal height group → P. 61. The ⟨*id*⟩ of the equal height group is chosen automatically, but it may be set manually by /tcb/raster equal height group. Also see /tcb/minimum for current equal height group → P. 62. Feasible values for ⟨*type*⟩ are:

- **none**: no equal height setting,
- **rows**: all boxes in a row are set to equal height,
- **all**: all boxes in the raster are set to equal height.

Note that you have to compile twice to see changes.

```
\begin{tcbitemize}[raster equal height=rows,
  size=small,colframe=red!50!black,colback=red!10!white]
  \tcbitem One
  \tcbitem \Huge Two
  \tcbitem Three
  \tcbitem Four
\end{tcbitemize}
```

One

Two

Three

Four

```
\begin{tcbitemize}[raster equal height,
  size=small,colframe=red!50!black,colback=red!10!white]
  \tcbitem One
  \tcbitem \Huge Two
  \tcbitem Three
  \tcbitem Four
\end{tcbitemize}
```

One

Two

Three

Four

N 2014-11-10

/tcb/raster equal height group=⟨*id*⟩ (no default)

Overwrites the automatically chosen id with the given ⟨*id*⟩. If this is used to share a common height between the *raster* and another raster or box, the /tcb/raster equal height option should be set to **all**.

```
\tcbset{size=small,colframe=red!50!black,colback=red!10!white}
\begin{tcolorbox}[equal height group=raster-manual-id]
  A single box
\end{tcolorbox}
\begin{tcbitemize}[raster equal height,raster equal height group=raster-manual-id]
  \tcbitem One
  \tcbitem \Huge Two
\end{tcbitemize}
```

A single box

One

Two

N 2014-11-10 **/tcb/raster force size=true|false** (default **true**, initially **true**)

Enforces the raster size computations onto the enclosed boxes. If set to **false**, individual settings can be used (for the better or worse).

```
\begin{tcbitemize}[raster force size=false, raster halign=center,
  size=small,colframe=red!50!black,colback=red!10!white]
  \tcbitem One
  \tcbitem Two
  \tcbitem[add to width=-3cm] Three
  \tcbitem[add to width=-3cm] Four
  \tcbitem[add to width=-3cm] Five
  \tcbitem[add to width=3cm] Six
\end{tcbitemize}
```



N 2014-11-10 **/tcb/raster reset** (no value)

Sets all raster settings back to their default values. Note that /tcb/reset → P. 105 does not execute this option. Style settings like /tcb/raster odd column etc. are not touched by /tcb/raster reset.

14.4 Adding Styles for Specific Boxes

The following styles can be defined to address certain boxes inside a *raster*. Note that such style definitions are not removed by /tcb/reset → P. 105 or /tcb/raster reset. The style definitions are used in the order given below.

N 2014-11-24 **/tcb/raster every box** (style)

This style is used for every box.

N 2014-11-10 **/tcb/raster odd column** (style)

This style is used for every box in an odd column.

```
\begin{tcbitemize}[size=small,colframe=red!50!black,colback=red!10!white,
  raster odd column/.style={colframe=blue!50!black,colback=blue!10!white}]
  \tcbitem One
  \tcbitem Two
  \tcbitem Three
  \tcbitem Four
\end{tcbitemize}
```



N 2014-11-10 **/tcb/raster even column** (style)

This style is used for every box in an even column.

N 2014-11-10 **/tcb/raster column n** (style)

This style is used for every box in the **n**-th column. **n** has to be replaced by a number.

N 2014-11-10 **/tcb/raster odd row** (style)

This style is used for every box in an odd row.

N 2014-11-10 **/tcb/raster even row** (style)

This style is used for every box in an even row.

N 2014-11-10 **/tcb/raster row m** (style)

This style is used for every box in the m-th row. m has to be replaced by a number.

```
\begin{tcbitemize}[size=small,colframe=red!50!black,colback=red!10!white,
  raster row 2/.style={colframe=blue!50!black,colback=blue!10!white}]
  \tcbitem One
  \tcbitem Two
  \tcbitem Three
  \tcbitem Four
\end{tcbitemize}
```

One | Two

Three | Four

N 2014-11-10 **/tcb/raster odd number** (style)

This style is used for every box with an odd number.

N 2014-11-10 **/tcb/raster even number** (style)

This style is used for every box with an even number.

```
\begin{tcbitemize}[size=small,colframe=red!50!black,colback=red!10!white,
  raster columns=3,
  raster even number/.style={colframe=blue!50!black,colback=blue!10!white}]
  \tcbitem One
  \tcbitem Two
  \tcbitem Three
  \tcbitem Four
  \tcbitem Five
  \tcbitem Six
\end{tcbitemize}
```

One | Two | Three

Four | Five | Six

N 2014-11-10 **/tcb/raster row m column n** (style)

This style is used for the box in the m-th row and n-th column. m and n have to be replaced by numbers.

N 2014-11-10 **/tcb/raster number n** (style)

This style is used for the box with number n. n has to be replaced by a number.

```
\begin{tcbitemize}[size=small,colframe=red!50!black,colback=red!10!white,
  raster number 4/.style={colframe=blue!50!black,colback=blue!10!white}]
  \tcbitem One
  \tcbitem Two
  \tcbitem Three
  \tcbitem Four
\end{tcbitemize}
```

One | Two

Three | Four

14.5 Combining Columns or Rows

N 2016-02-19 **/tcb/raster multicolumn=**⟨*number*⟩ (no default, initially unset)

This option has to be set inside the option list of a tcolorbox → P. 12 inside a tcbraster → P. 279 or inside \tcbitem → P. 280 inside tcbitemize → P. 280. It merges the given ⟨*number*⟩ of boxes into one single box on the same line. The resulting box gets the **\thetcbrasternum** of the first box. If there are not enough boxes available on the current line, this option is ignored and a warning is given.

```
\begin{tcbitemize}[raster equal height=rows,raster columns=3,
  title=\thetcbrasternum,colframe=red!50!black,colback=red!10!white]
\tcbitem[colframe=blue!50!black,colback=blue!10!white,raster multicolumn=1]
  multicolumn=1
\tcbitem
\tcbitem
\tcbitem[colframe=blue!50!black,colback=blue!10!white,raster multicolumn=2]
  multicolumn=2
\tcbitem
\tcbitem[colframe=blue!50!black,colback=blue!10!white,raster multicolumn=3]
  multicolumn=3
\tcbitem
\tcbitem[colframe=blue!50!black,colback=blue!10!white,raster multicolumn=2]
  multicolumn=2
\end{tcbitemize}
```

1
multicolumn=1

2

3

4
multicolumn=2

6

7
multicolumn=3

10

11
multicolumn=2

N 2016-02-19 **/tcb/raster multirow=**⟨*number*⟩ (no default, initially unset)

This option has to be set inside the option list of a tcolorbox → P. 12 inside a tcbraster → P. 279 or inside \tcbitem → P. 280 inside tcbitemize → P. 280. This option not really merges boxes, but simply sizes the current box to fit the space of ⟨*number*⟩ rows.

! /tcb/raster multirow needs /tcb/raster height → P. 284 to be set. How to achieve a similar result for boxes without fixed /tcb/raster height → P. 284 is shown afterwards.

```
\begin{tcbitemize}[raster rows=3,raster columns=3,raster height=6cm,
  raster every box/.style={colframe=red!50!black,colback=red!10!white}]
\tcbitem
\tcbitem
\tcbitem
\tcbitem[colframe=blue!50!black,colback=blue!10!white,raster multirow=2]
  multirow=2
\tcbitem[raster multicolumn=2,raster multirow=2,blankest]
  \begin{tcbitemize}[raster rows=2,raster columns=2,raster height=\tcbtextheight]
  \tcbitem
  \tcbitem
  \tcbitem
  \tcbitem
  \end{tcbitemize}
\end{tcbitemize}
```



For rasters without fixed /tcb/raster height → P. 284, /tcb/raster multirow → P. 291 cannot be used. Note that \tcbtextheight → P. 147 also cannot be used like in the previous example.
But, with combination of /tcb/raster equal height → P. 287 and /tcb/space to → P. 59, a similar effect can be created:

```
\begin{tcbitemize}[raster columns=3,raster equal height=rows,
  raster every box/.style={colframe=red!50!black,colback=red!10!white}]
\tcbitem
\tcbitem
\tcbitem
\tcbitem[colframe=blue!50!black,colback=blue!10!white]
 \lipsum[2]
\tcbitem[raster multicolumn=2,blankest,space to=\myspace]
  \begin{tcbitemize}[raster columns=2]
  \tcbitem This is a box of the inner raster.
  \tcbitem
  \tcbitem[height=\myspace]
  \tcbitem[height=\myspace]
  \end{tcbitemize}
\end{tcbitemize}
```

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

This is a box of the inner raster.

14.6 Rasters inside Rasters

A *raster* inside a *raster* cannot be used directly, because a *raster* can only contain a *tcolorbox* or something derived from a *tcolorbox*. So, a *raster* can be put inside a *tcolorbox* inside a *raster*.

Some examples for such constructions can be found at `tcboxedraster` → P. 281, `/tcb/raster multicolumn` → P. 290, `/tcb/raster multirow` → P. 291.

14.6.1 Raster Setup

The intermediating `tcolorbox` → P. 12 can be made invisible by using `/tcb/blankest` → P. 239.

```
\begin{tcbraster}[raster equal height=rows,
  raster every box/.style={colframe=red!50!black,colback=red!10!white}]
  \begin{tcolorbox}[blankest]
    \begin{tcbraster}[raster columns=1]
      \begin{tcolorbox}One\end{tcolorbox}
      \begin{tcolorbox}Two\end{tcolorbox}
    \end{tcbraster}
  \end{tcolorbox}
  \begin{tcolorbox}raster+tcolorbox+raster\end{tcolorbox}
\end{tcbraster}
```

One

Two

raster+tcolorbox+raster

```
\begin{tcbraster}[raster equal height=rows,
  raster every box/.style={colframe=red!50!black,colback=red!10!white}]
  \begin{tcboxedraster}[raster columns=1]{blankest}
    \begin{tcolorbox}One\end{tcolorbox}
    \begin{tcolorbox}Two\end{tcolorbox}
  \end{tcboxedraster}
  \begin{tcolorbox}raster+tcboxedraster\end{tcolorbox}
\end{tcbraster}
```

One

Two

raster+tcboxedraster

```
\begin{tcbitemize}[raster equal height=rows,
  raster every box/.style={colframe=red!50!black,colback=red!10!white}]
  \tcbitem[blankest]
    \begin{tcbitemize}[raster columns=1]
      \tcbitem One
      \tcbitem Two
    \end{tcbitemize}
  \tcbitem tcbitemize+tcbitem+tcbitemize
\end{tcbitemize}
```

One

Two

tcbitemize+tcbitem+tcbitemize

14.6.2 Placing Spaces

If the heights of boxes inside staggered rasters should be matched, the space has to be distributed accordingly.

- For fixed height boxes/rasters using `/tcb/raster height` → P. 284, the height of boxes is available by `\tcbtextheight` → P. 147. This can be used to size deeper layered boxes/rasters.
- For boxes/rasters layed out using `/tcb/raster equal height` → P. 287, space can be distributed by `/tcb/space to` → P. 59. It can take several compilations until all spaces are distributed correctly.

```
\begin{tcbitemize}[raster rows=2,raster height=6cm,
  raster every box/.style={colframe=red!50!black,colback=red!10!white}]
  \tcbitem[blankest]
    \begin{tcbitemize}[raster columns=1,raster rows=2,raster height=\tcbtextheight]
      \tcbitem One
      \tcbitem Two
    \end{tcbitemize}
  \tcbitem This is a fixed height box.
  \tcbitem Three
  \tcbitem Four
\end{tcbitemize}
```

One

Two

This is a fixed height box.

Three

Four

```
\begin{tcbitemize}[raster columns=4,raster rows=4,raster height=0.8\linewidth,
  raster every box/.style={size=small,beamer,
    colframe=blue!75!yellow,colback=red!75!yellow!20,
    center title,title=Box}]
  \tcbitem One
  \tcbitem Two
  \tcbitem Three
  \tcbitem Four
  \tcbitem[raster multirow=2,blankest]
    \begin{tcbitemize}[raster columns=1,raster rows=2,raster height=\tcbtextheight]
      \tcbitem Twelve
      \tcbitem Eleven
    \end{tcbitemize}
  \tcbitem[raster multirow=2,raster multicolumn=2,
      colframe=red!75!yellow,colback=blue!75!yellow!20]
    This is an example with fixed height boxes.
  \tcbitem[raster multirow=2,blankest]
    \begin{tcbitemize}[raster columns=1,raster rows=2,raster height=\tcbtextheight]
      \tcbitem Five
      \tcbitem Six
    \end{tcbitemize}
  \tcbitem Ten
  \tcbitem Nine
  \tcbitem Eight
  \tcbitem Seven
\end{tcbitemize}
```



```
\begin{tcbitemize}[raster equal height=rows,
  raster every box/.style={colframe=red!50!black,colback=red!10!white}]
  \tcbitem[blankest,space to=\myspace]
    \begin{tcbitemize}[raster columns=1]
      \tcbitem One
      \tcbitem[add to natural height=\myspace]
        This box will adapt its height.
    \end{tcbitemize}
  \tcbitem This is a flexible height box.
  \tcbitem \lipsum[4]
  \tcbitem[blankest,space to=\myspace]
    \begin{tcbitemize}[raster columns=1]
      \tcbitem One
      \tcbitem[add to natural height=\myspace]
        This box will adapt its height.
    \end{tcbitemize}
\end{tcbitemize}
```

One

This box will adapt its height.

This is a flexible height box.

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

One

This box will adapt its height.

```
\begin{tcbitemize}[raster equal height=rows,
  raster every box/.style={colframe=red!50!black,colback=red!10!white}]
  \tcbitem[blankest,space to=\myspace]
    \begin{tcbitemize}[raster columns=1]
      \tcbitem One
      \tcbitem[add to natural height=\myspace]
        This box will adapt its height.
      \tcbitem \lipsum[4]
    \end{tcbitemize}
  \tcbitem[blankest,space to=\myspace]
    \begin{tcbitemize}[raster columns=1]
      \tcbitem[blankest]\includegraphics[width=\linewidth]{goldshade.png}
      \tcbitem[add to natural height=\myspace]
        This box will adapt its height.
    \end{tcbitemize}
\end{tcbitemize}
```

One

This box will adapt its height.

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

This box will adapt its height.

15 Libraries LIB listings, LIB listingsutf8, and LIB minted

15.1 Loading the Libraries

In contrast to other `tcolorbox` libraries, the libraries LIB listings, LIB listingsutf8, and LIB minted are concurrent in the sense that they all do the same thing, i. e. displaying listings with or without typesetting the listing in LaTeX parallel. The difference is the underlying LaTeX package which does the core job for displaying a listing. So, typically, you need just *one* of these libraries. If you do not have a clue, which one of them you should use, you should take LIB listingsutf8.

> ! The order in which the libraries are included influences the default settings and the `/tcb/reset` → P. 105 behavior. The settings of a later loaded library overwrite the settings of a previous loaded library. A library is never loaded twice.

15.1.1 Loading LIB listings

This library uses the package `listings` [6] to typeset listings. It is loaded by a package option or inside the preamble by:

```
\tcbuselibrary{listings}
```

This also loads the package `listings` [6].

The `/tcb/listing engine` → P. 310 is set to `listings` by the library. To reactivate this setting, if overwritten by other libraries, use

```
\tcbset{listing engine=listings}
```

15.1.2 Loading LIB listingsutf8

> ! This library is not needed (and troublesome) when using XeLaTeX.

To extend `listings` for UTF-8 encoded sources, you can use the support from the package `listingsutf8` [10] by loading the library variant LIB listingsutf8.

```
\tcbuselibrary{listingsutf8}
\tcbset{listing utf8=latin1}% optional; 'latin1' is the default.
```

This also loads the library LIB listings and the packages `listings` [6] and `listingsutf8` [10].

The `/tcb/listing engine` → P. 310 is set to `listings` by the library. To reactivate this setting, if overwritten by other libraries, use

```
\tcbset{listing engine=listings}
```

15.1.3 Loading LIB minted

This library uses the package `minted` [12] to typeset listings. It is loaded by a package option or inside the preamble by:

```
\tcbuselibrary{minted}
```

This also loads the package `minted` [12].

> **!** The `minted` package uses the external tool `Pygments` [14] to apply syntax highlighting. It has to be installed and set up, before the library can be used, see [12] and [14]. The `tcolorbox` library LIB minted does not work, if the package `minted` [12] does not work.

The `/tcb/listing engine` → P. 310 is set to `minted` by the library. To reactivate this setting, if overwritten by other libraries, use

```
\tcbset{listing engine=minted}
```

15.2 Common Macros of the Libraries

`\begin{tcblisting}{`⟨*options*⟩`}`
⟨*environment content*⟩
`\end{tcblisting}`

Creates a colored box based on a `tcolorbox` → P. 12. Controlled by the given ⟨*options*⟩, the environment content is typeset normally and/or as a listing. Furthermore, the ⟨*options*⟩ control appearance and functions of the `tcolorbox`. By default, the listing is interpreted as a LaTeX listing.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black}
This is a \LaTeX\ example which displays the text as source code
and in compiled form.
\end{tcblisting}
```

```
This is a \LaTeX\ example which displays the text as source code
and in compiled form.
```

This is a LaTeX example which displays the text as source code and in compiled form.

```
% \tcbuselibrary{listings} /or/ \tcbuselibrary{listingsutf8}
\begin{tcblisting}{colback=yellow!5,colframe=yellow!50!black,listing only,
    title=This is source code in another language (XML), fonttitle=\bfseries,
  listing options={language=XML,columns=fullflexible,keywordstyle=\color{red}}}
<?xml version="1.0"?>
<project name="Package tcolorbox" default="documentation" basedir=".">
  <description>
    Apache Ant build file (http://ant.apache.org/)
  </description>
</project>
\end{tcblisting}
```

This is source code in another language (XML)

```
<?xml version="1.0"?>
<project name="Package␣tcolorbox" default="documentation" basedir=".">
  <description>
    Apache Ant build file (http://ant.apache.org/)
  </description>
</project>
```

```
% \tcbuselibrary{minted}
\begin{tcblisting}{colback=yellow!5,colframe=yellow!50!black,listing only,
    title=This is source code in another language (XML), fonttitle=\bfseries,
  listing engine=minted,minted language=xml}
<?xml version="1.0"?>
<project name="Package tcolorbox" default="documentation" basedir=".">
  <description>
    Apache Ant build file (http://ant.apache.org/)
  </description>
</project>
\end{tcblisting}
```

This is source code in another language (XML)

```
<?xml version="1.0"?>
<project name="Package tcolorbox" default="documentation" basedir=".">
  <description>
    Apache Ant build file (http://ant.apache.org/)
  </description>
</project>
```

```
% This box is as wide as needed (listing only !!)
% \tcbuselibrary{skins}
\begin{tcblisting}{colback=green!5!white,colframe=green!50!black,listing only,
  hbox,enhanced,drop fuzzy shadow,before=\begin{center},after=\end{center}}
\begin{tikzpicture}
\fill[red] (0,0) rectangle (1,1);
\end{tikzpicture}
\end{tcblisting}
```

```
\begin{tikzpicture}
\fill[red] (0,0) rectangle (1,1);
\end{tikzpicture}
```

\begin{tcboutputlisting}
⟨*environment content*⟩
\end{tcboutputlisting}

Saves the environment content to a file which is named by the key value of `listing file`. Later, this file can be loaded by `\tcbinputlisting` or `\tcbuselistingtext` or `\tcbuselistinglisting`.

```
\begin{tcboutputlisting}
This \textbf{text} is written to a standardized file for later usage.
\end{tcboutputlisting}
```

\tcbinputlisting{⟨*options*⟩}

Creates a colored boxed based on a `tcolorbox`. The text content is read from a file named by the key value of `listing file`. Apart from that, the function is equal to that of `tcblisting` → P. 299.

```
\tcbinputlisting{colback=red!5!white,colframe=red!75!black,text only}
\tcbinputlisting{colback=green!5,colframe=green!75!black,listing only}
```

```
\begin{tikzpicture}
\fill[red] (0,0) rectangle (1,1);
\end{tikzpicture}
```

\tcbuselistingtext

Loads text from a file named by the key value of `listing file`.

```
\tcbuselistingtext
```

\tcbuselistinglisting

Typesets text as listing from a file named by the key value of `listing file`.

```
\tcbuselistinglisting
```

```
\begin{tikzpicture}
\fill[red] (0,0) rectangle (1,1);
\end{tikzpicture}
```

\tcbusetemplisting

Typesets text as listing from a temporary file which was written by `tcbwritetemp` → P. 126.

See Section 22.4 on page 441 and Section 22.5 on page 443 for more elaborate methods to create new environments and commands.

If a new sort of `tcblisting` environments should be created with one optional argument only, one is highly recommended to use `\DeclareTCBListing` → P. 441 or `\NewTCBListing` → P. 441 instead of `\newtcblisting` to avoid content scanning problems.

`\newtcblisting[⟨init options⟩]{⟨name⟩}[⟨number⟩][⟨default⟩]{⟨options⟩}`

Creates a new environment ⟨*name*⟩ based on `tcblisting` → P. 299. Basically, `\newtcblisting` operates like `\newenvironment`. This means, the new environment ⟨*name*⟩ optionally takes ⟨*number*⟩ arguments, where ⟨*default*⟩ is the default value for the optional first argument. The ⟨*options*⟩ are given to the underlying `tcblisting`. Note that `/tcb/savedelimiter` → P. 26 is set to the given ⟨*name*⟩ automatically. The ⟨*init options*⟩ allow setting up automatic numbering, see Section 5 from page 108.

```
\newtcblisting{mybox}{%
  colback=red!5!white,
  colframe=red!75!black}

\begin{mybox}
This is my \LaTeX\ box.
\end{mybox}
```

This is my \LaTeX\ box.

This is my LaTeX box.

```
\newtcblisting{mybox}[1]{%
  colback=red!5!white,
  colframe=red!75!black,
  fonttitle=\bfseries,
  title=#1}

\begin{mybox}{Listing Box}
This is my \LaTeX\ box.
\end{mybox}
```

Listing Box

This is my \LaTeX\ box.

This is my LaTeX box.

```
\newtcblisting{mybox}[2][]{%
  colback=red!5!white,
  colframe=red!75!black,
  fonttitle=\bfseries,
  title=#2,#1}

\begin{mybox}[listing only]
  {Listing Box}
This is my \LaTeX\ box.
\end{mybox}
\bigskip

\begin{mybox}[listing side text]
  {Listing Box}
This is my
\LaTeX\ box.
\end{mybox}
```

Listing Box

This is my \LaTeX\ box.

Listing Box

This is my \LaTeX\ box.

This is my LaTeX box.

Definition in the preamble:

```
\newtcblisting[auto counter]{mycbox}[1]{%
  colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
  title=Listing \thetcbcounter: #1}
```

```
\begin{mycbox}{Listing Box}
This is my \LaTeX\ box.
\end{mycbox}
```

Listing 1: Listing Box

This is my \LaTeX\ box.

This is my LaTeX box.

`\renewtcblisting`[⟨*init options*⟩]{⟨*name*⟩}[⟨*number*⟩][⟨*default*⟩]{⟨*options*⟩}

Operates like `\newtcblisting` → P. 302, but based on `\renewenvironment` instead of `\newenvironment`. An existing environment is redefined.

`\newtcbinputlisting`[⟨*init options*⟩]{\⟨*name*⟩}[⟨*number*⟩][⟨*default*⟩]{⟨*options*⟩}

Creates a new macro \⟨*name*⟩ based on `\tcbinputlisting` → P. 301. Basically, `\newtcbinputlisting` operates like `\newcommand`. The new macro \⟨*name*⟩ optionally takes ⟨*number*⟩ arguments, where ⟨*default*⟩ is the default value for the optional first argument. The ⟨*options*⟩ are given to the underlying `tcbinputlisting`. The ⟨*init options*⟩ allow setting up automatic numbering, see Section 5 from page 108.

```
\newtcbinputlisting[use counter from=mycbox]{\mylisting}[2][]{%
  listing file={#2},
  title=Listing (\thetcbcounter) of \texttt{#2},
  colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
  listing only,breakable,#1}

\mylisting[before upper=\textit{This is the included file content:}]
          {\jobname.tcbtemp}
```

Listing (2) of `tcolorbox.tcbtemp`

This is the included file content:

```
\newtcbinputlisting[use counter from=mycbox]{\mylisting}[2][]{%
  listing file={#2},
  title=Listing (\thetcbcounter) of \texttt{#2},
  colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
  listing only,breakable,#1}

\mylisting[before upper=\textit{This is the included file content:}]
          {\jobname.tcbtemp}
```

```
\newtcbinputlisting[use counter from=mycbox]{\mylisting}[2][]{%
  listing engine=minted,minted language=latex,minted style=colorful,
  listing file={#2},
  title=Listing (\thetcbcounter) of \texttt{#2},
  colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
  listing only,breakable,#1}

\mylisting[before upper=\textit{This is the included file content:}]
          {\jobname.tcbtemp}
```

Listing (3) of `tcolorbox.tcbtemp`

This is the included file content:

```
\newtcbinputlisting[use counter from=mycbox]{\mylisting}[2][]{%
  listing engine=minted,minted language=latex,minted style=colorful,
  listing file={#2},
  title=Listing (\thetcbcounter) of \texttt{#2},
  colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
  listing only,breakable,#1}

\mylisting[before upper=\textit{This is the included file content:}]
          {\jobname.tcbtemp}
```

`\renewtcbinputlisting`[⟨*init options*⟩]{\⟨*name*⟩}[⟨*number*⟩][⟨*default*⟩]{⟨*options*⟩}

Operates like `\newtcbinputlisting`, but based on `\renewcommand` instead of `\newcommand`. An existing macro is redefined.

15.3 Option Keys of the LIB listings Library

/tcb/listing options=⟨*key list*⟩ (no default, initially `style=tcblatex`)

Sets the options from the package `listings` [6] which are used during typesetting of the listing. For LaTeX listings, there is a predefined `listings` style named `tcblatex` which can be used.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!25,left=6mm,
listing options={style=tcblatex,numbers=left,numberstyle=\tiny\color{red!75!black}}}
This is a \LaTeX\ example which displays the text as source code
and in compiled form. Additionally, we use line numbers here.
\end{tcblisting}
```

```
1 This is a \LaTeX\ example which displays the text as source code
2 and in compiled form. Additionally, we use line numbers here.
```

This is a LaTeX example which displays the text as source code and in compiled form. Additionally, we use line numbers here.

/tcb/no listing options (no value, initially unset)

Abbreviation for `listing options={}`. This removes all options for the `listings` package. This includes the `tcblisting` standard style `tcblatex` and the encoding presets. Use this option, if you want to set the `listings` options outside of `tcblisting`, e. g. globally in the preamble.

```
\begin{tcblisting}{no listing options}
All \textit{listings} options removed.
\end{tcblisting}
```

```
All \textit{listings} options removed.
```

All *listings* options removed.

/tcb/listing style=⟨*style*⟩ (no default, initially `tcblatex`)

Abbreviation for `listing options={style=...}`. This key sets a ⟨*style*⟩ for the `listings` package, see [6]. For LaTeX, there is a predefined style named `tcblatex`.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,
listing style=tcblatex}
Here, we use the predefined style.
\end{tcblisting}
```

```
Here, we use the predefined style.
```

Here, we use the predefined style.

`/tcb/listing inputencoding=`⟨*encoding*⟩ (no default, initially `\inputencodingname`)

Sets the input encoding value for the predefined listing style `tcblatex` and `tcbdocumentation` from the library LIB documentation. The initial value is derived from the package `inputenc` if used.

`/tcb/listing remove caption=true|false` (default `true`, initially `true`)

If set to `true`, some part of the caption building code of the `listings` package is silenced to prevent some unwanted interaction with the `hyperref` package resulting in additional vertical space. If set to `false`, the `listings` package code is kept unchanged. Note that listings outside `tcblisting` → P. 299 and `\tcbinputlisting` → P. 301 are always processed normally. Typically, a user is not expected to use this key at all.

`/tcb/every listing line=`⟨*text*⟩ (no default, initially unset/empty)

Inserts some ⟨*text*⟩ to the begin of every line of a listing. Note that this a hack of the `listings` package code. This may become unusable or superfluous in the future.

```
\newtcblisting{commandshell}{colback=black,colupper=white,colframe=yellow!75!black,
  listing only,listing options={style=tcblatex,language=sh},
  every listing line={\textcolor{red}{\small\ttfamily\bfseries root \$> }}}

\begin{commandshell}
ls -al
cd /usr/lib
\end{commandshell}
```

```
root $> ls -al
root $> cd /usr/lib
```

`/tcb/every listing line*=`⟨*text*⟩ (no default, initially unset/empty)

Identical to `/tcb/every listing line` plus additional enlargement of `/tcb/rightupper` → P. 41 by the width of ⟨*text*⟩. Therefore, this option has to be used after the geometry settings are done. This option is intended to be used in conjunction with `/tcb/hbox` → P. 94.

```
\newtcblisting{commandshell}{colback=black,colupper=white,colframe=yellow!75!black,
  listing only,listing options={style=tcblatex,language=sh},hbox,
  every listing line*={\textcolor{red}{\small\ttfamily\bfseries root \$> }}}

\begin{commandshell}
ls -al
cd /usr/lib
\end{commandshell}
```

```
root $> ls -al
root $> cd /usr/lib
```

See further options in Section 15.6 on page 310.

! For an combined example of using `\lstinline` inside a `tcolorbox`, see `\DeclareTotalTCBox` → P. 439.

15.4 Option Keys of the LIB listingsutf8 Library

> ! The LIB listingsutf8 library is not needed (and troublesome) when using XeLaTeX.

The LIB listingsutf8 library is an extension of the LIB listings library, so all options from Section 15.3 on page 305 are applicable.

`/tcb/listing utf8=`⟨*one-byte-encoding*⟩ (style, no default, initially `latin1`)
Abbreviation for using `/tcb/listing inputencoding` → P. 306 together with UTF-8 support from the package `listingsutf8` [10]. This option is available only for the library variant LIB listingsutf8. The ⟨*one-byte-encoding*⟩ is one of the applicable encodings from [10], e. g. `latin1`.

See further options in Section 15.6 on page 310.

15.5 Option Keys of the LIB minted Library

/tcb/minted language=⟨*programming language*⟩ (no default, initially `latex`)

Sets a ⟨*programming language*⟩ known to `Pygments` [14].

```
\begin{tcblisting}{listing engine=minted,minted style=trac,
  minted language=java,
  colback=red!5!white,colframe=red!75!black,listing only}
    public class HelloWorld {
      // A 'Hello World' in Java
      public static void main(String[] args) {
        System.out.println("Hello World!");
      }
    }
\end{tcblisting}
```

```
public class HelloWorld {
  // A 'Hello World' in Java
  public static void main(String[] args) {
    System.out.println("Hello World!");
  }
}
```

U 2017-07-05 **/tcb/minted options=**⟨*key list*⟩ (no default, initially `tabsize=2,fontsize=\small, breaklines,autogobble`)

Sets the options from the package `minted` [12] which are used during typesetting of the listing.

```
% \tcbuselibrary{skins}
\newtcblisting{myjava}{listing engine=minted,
  minted style=colorful,
  minted language=java,
  minted options={fontsize=\small,breaklines,autogobble,linenos,numbersep=3mm},
  colback=blue!5!white,colframe=blue!75!black,listing only,
  left=5mm,enhanced,
  overlay={\begin{tcbclipinterior}\fill[red!20!blue!20!white] (frame.south west)
    rectangle ([xshift=5mm]frame.north west);\end{tcbclipinterior}}}

\begin{myjava}
  public class HelloWorld {
    // A 'Hello World' in Java
    public static void main(String[] args) {
      System.out.println("Hello World!");
    }
  }
\end{myjava}
```

```
1 public class HelloWorld {
2   // A 'Hello World' in Java
3   public static void main(String[] args) {
4     System.out.println("Hello World!");
5   }
6 }
```

`/tcb/minted style=`⟨*style*⟩ (no default, initially unset)

Sets a ⟨*style*⟩ known to `Pygments` [14]. This is independent from `/tcb/minted options` → P. 308. Note that styles are always applied globally; all following examples will be set in the given ⟨*style*⟩ until a new style is set. Also note that setting `\usemintedstyle{`⟨*style*⟩`}` only once per document is more economic, if all styles in a document are the same. For examples of different styles, see `/tcb/minted language` → P. 308 and `/tcb/minted options` → P. 308.

See further options in Section 15.6 on the following page.

15.6 Common Option Keys of all Libraries

For the ⟨*options*⟩ in `tcblisting` → P. 299 respectively `\tcbinputlisting` → P. 301 the following `pgf` keys can be applied. The key tree path `/tcb/` is not to be used inside these macros.

`/tcb/listing engine=`⟨*engine*⟩ (no default)

Sets the ⟨*engine*⟩ which typesets the listings. Feasible values are

- **`listings`**, if library LIB listings or LIB listingsutf8 is loaded.
- **`minted`**, if library LIB minted is loaded.

`/tcb/listing file=`⟨*file name*⟩ (no default, initially `\jobname.listing`)

Sets the ⟨*file name*⟩ of the file which is used to save listings.

`/tcb/listing and text` (no value, initially set)

Typesets the environment content as listing in the upper part and as compiled text in the lower part.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,listing and text}
This is a \LaTeX\ example.
\end{tcblisting}
```

This is a \LaTeX\ example.

This is a LaTeX example.

`/tcb/text and listing` (no value)

Typesets the environment content as compiled text in the upper part and as listing in the lower part.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,text and listing}
This is a \LaTeX\ example.
\end{tcblisting}
```

This is a LaTeX example.

This is a \LaTeX\ example.

`/tcb/listing only` (no value)

Typesets the environment content as listing.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,listing only}
This is a \LaTeX\ example.
\end{tcblisting}
```

This is a \LaTeX\ example.

/tcb/text only (no value)

Typesets the environment content as compiled text.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,text only}
This is a \LaTeX\ example.
\end{tcblisting}
```

This is a LaTeX example.

/tcb/comment=⟨*text*⟩ (no default, initially empty)

Records a comment with ⟨*text*⟩ as content. The comment is displayed e. g. in conjunction with /tcb/listing and comment → P. 314 and /tcb/comment and listing → P. 314.

```
\begin{tcblisting}{comment={This comment is really only a comment},
  colback=red!5!white,colframe=red!75!black}
This is a \textbf{tcolorbox}.
\end{tcblisting}
```

This is a \textbf{tcolorbox}.

This is a **tcolorbox**.

N 2014-11-17 **/tcb/comment only** (no value)

Typesets the environment content with the comment text.

```
\begin{tcblisting}{comment only,
  comment={This is a comment.},
  colback=red!5!white,colframe=red!75!black}
This is a \textbf{tcolorbox}.
\end{tcblisting}
```

This is a comment.

/tcb/image comment={⟨*options*⟩}{⟨*filename*⟩} (style, no default, initially unset)

Uses an image denoted by ⟨*filename*⟩ as *comment* for the listing. The image is included by the standard **\includegraphics** macro with given ⟨*options*⟩.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,listing side comment,
  image comment={width=2.5cm}{example-image-a.pdf},center lower}
This is a \LaTeX\ example.
\end{tcblisting}
```

This is a \LaTeX\ example.



N 2014-11-14 **/tcb/tcbimage comment=⟨*filename*⟩** (style, no default, initially unset)

Uses an image denoted by ⟨*filename*⟩ as *comment* for the listing. The image is included by the \tcbincludegraphics → P. 251 macro. The inclusion can be customized by /tcb/comment style → P. 314.

! The library LIB skins is needed to apply this option.

```
% \tcbuselibrary{skins}
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,listing side comment,
  righthand width=3cm,lower separated=false,
  tcbimage comment={example-image-a.pdf},
  comment style={size=fbox,colframe=blue,colback=blue!50,sharp corners,
    drop fuzzy shadow}}
This is a \LaTeX\ example.
\end{tcblisting}
```

```
This is a \LaTeX\ example.
```



N 2014-11-14 **/tcb/pdf comment=⟨*filename*⟩** (style, default listing file, initially unset)

Uses a PDF file denoted by ⟨*filename*⟩ as *comment* for the listing. The image is included by \tcbincludepdf → P. 253 inside a tcbraster → P. 279. The inclusion can be customized by /tcb/comment style → P. 314.

! The libraries LIB skins and LIB raster are needed to apply this option.

```
% \tcbuselibrary{skins,raster}
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,listing and comment,
  righthand width=3cm,lower separated=false,middle=1mm,
  pdf comment={tcolorbox-example.pdf},
  comment style={raster columns=3,graphics pages={1,2,3},
    colframe=blue,drop fuzzy shadow}}
This is a \LaTeX\ example.
\end{tcblisting}
```

This is a \LaTeX\ example.



N 2014-11-14 **/tcb/pdf extension=⟨*extension*⟩** (no default, initially pdf)

Sets the PDF file name extension for /tcb/pdf comment → P. 312 to ⟨*extension*⟩. Note that ⟨*extension*⟩ always overwrites any actual extension given inside /tcb/pdf comment → P. 312.

N 2014-11-14 **/tcb/comment style=⟨*options*⟩** (no default, initially empty)

Sets the ⟨*options*⟩ for /tcb/tcbimage comment → P. 312 and /tcb/pdf comment → P. 312. These are tcolorbox options to customize the colored box drawn around the image(s), also image options encapsulated by /tcb/graphics options → P. 254, and tcbraster → P. 279 options for /tcb/pdf comment → P. 312.

/tcb/listing and comment (no value)

Typesets the environment content as listing in the upper part and a given comment in the lower part.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,listing and comment,
  comment={This is my comment. It may contain line breaks.\par
    It can even use the environment content
    \flqq\ignorespaces\tcbuselistingtext\unskip\frqq}}
This is a \LaTeX\ example.
\end{tcblisting}
```

This is a \LaTeX\ example.

This is my comment. It may contain line breaks.
It can even use the environment content «This is a LaTeX example.»

/tcb/comment and listing (no value)

Typesets a given comment in the upper part and the environment content as listing in the lower part.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,comment and listing,
comment={This is my comment.}}
This is a \LaTeX\ example.
\end{tcblisting}
```

This is my comment.

This is a \LaTeX\ example.

/tcb/listing side text (style, no value)

Typesets the environment content side by side as listing in the left (upper) part and as compiled text in the right (lower) part. This is a shortcut for setting /tcb/listing and text→ P. 310 and /tcb/sidebyside→ P. 116.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,listing side text}
This is a \LaTeX\ example.
\end{tcblisting}
```

```
This is a \LaTeX\ example.
```

This is a LaTeX example.

Note that **sidebyside=false** has to be added, if the setting of /tcb/listing side text is to be annihilated.

/tcb/text side listing (style, no value)

Typesets the environment content side by side as compiled text in the left (upper) part and as listing in the right (lower) part. This is a shortcut for setting /tcb/text and listing→ P. 310 and /tcb/sidebyside→ P. 116.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,text side listing}
This is a \LaTeX\ example.
\end{tcblisting}
```

This is a LaTeX example.

```
This is a \LaTeX\ example.
```

/tcb/listing outside text (no value)

Typesets the environment content side by side as listing in a **tcolorbox** and as compiled text outside the box in the right part of the page. Nevertheless, the outside text is treated as *lower* part of the **tcolorbox** and can be formatted with all lower part options. The space partitioning is done with the side by side options from Section 6 on page 116.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,listing outside text}
This is a \LaTeX\ example.
\end{tcblisting}
```

```
This is a \LaTeX\ example.
```

This is a LaTeX example.

/tcb/text outside listing (no value)

Typesets the environment content side by side as listing in a **tcolorbox** and as compiled text outside the box in the left part of the page. Nevertheless, the outside text is treated as *lower* part of the **tcolorbox** and can be formatted with all lower part options. The space partitioning is done with the side by side options from Section 6 on page 116.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,text outside listing}
This is a \LaTeX\ example.
\end{tcblisting}
```

This is a LaTeX example.

```
This is a \LaTeX\ example.
```

/tcb/listing side comment (style, no value)

Typesets the environment content side by side as listing in the left (upper) part and a given comment in the right (lower) part. This is a shortcut for setting /tcb/listing and comment → P. 314 and /tcb/sidebyside → P. 116.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,listing side comment,
  righthand width=1.5cm,image comment={width=1.5cm}{example-image-a.pdf}}
This is a \LaTeX\ example.
\end{tcblisting}
```

This is a \LaTeX\ example.

/tcb/comment side listing (style, no value)

Typesets the environment content side by side with a given comment in the left (upper) part and as listing in the right (lower) part. This is a shortcut for setting /tcb/comment and listing → P. 314 and /tcb/sidebyside → P. 116.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,comment side listing,
  lefthand width=1.5cm,image comment={width=1.5cm}{example-image-a.pdf}}
This is a \LaTeX\ example.
\end{tcblisting}
```

This is a \LaTeX\ example.

/tcb/listing outside comment (no value)

Typesets the environment content side by side as listing in a tcolorbox and a given comment outside the box in the right part of the page. Nevertheless, the outside text is treated as *lower* part of the tcolorbox and can be formatted with all lower part options. The space partitioning is done with the side by side options from Section 6 on page 116.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,listing outside comment,
  righthand width=1.5cm,image comment={width=1.5cm}{example-image-a.pdf}}
This is a \LaTeX\ example.
\end{tcblisting}
```

This is a \LaTeX\ example.

/tcb/comment outside listing (no value)

Typesets the environment content side by side as listing in a tcolorbox and a given comment outside the box in the left part of the page. Nevertheless, the outside text is treated as *lower* part of the tcolorbox and can be formatted with all lower part options. The space partitioning is done with the side by side options from Section 6 on page 116.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,comment outside listing,
  lefthand width=1.5cm,image comment={width=1.5cm}{example-image-a.pdf}}
This is a \LaTeX\ example.
\end{tcblisting}
```

This is a \LaTeX\ example.

/tcb/listing above text (no value)

Typesets the environment content as listing in a tcolorbox and as compiled text outside and below the box. The outside text is treated as *lower* part of the tcolorbox and can be formatted with all lower part options. The distance between box and text is controlled by /tcb/middle → P. 43.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,listing above text}
This is a \LaTeX\ example.
\end{tcblisting}
```

```
This is a \LaTeX\ example.
```

This is a LaTeX example.

N 2014-11-07 /tcb/listing above* text (no value)

Widely equal to /tcb/listing above text, but the outside text is not formatted with the lower part options. Also, it is not put into a minipage and it may span several pages. The distance between box and text is controlled by /tcb/after → P. 78.

/tcb/text above listing (no value)

Typesets the environment content as listing in a tcolorbox and as compiled text outside and above the box. The outside text is treated as *lower* part of the tcolorbox and can be formatted with all lower part options. The distance between box and text is controlled by /tcb/middle → P. 43.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,text above listing}
This is a \LaTeX\ example.
\end{tcblisting}
```

This is a LaTeX example.

```
This is a \LaTeX\ example.
```

N 2014-11-07 /tcb/text above* listing (no value)

Widely equal to /tcb/text above listing, but the outside text is not formatted with the lower part options. Also, it is not put into a minipage and it may span several pages. The distance between box and text is controlled by /tcb/before → P. 78.

/tcb/listing above comment (no value)

Typesets the environment content as listing in a tcolorbox and a given comment outside and below the box. The outside text is treated as *lower* part of the tcolorbox and can be formatted with all lower part options. The distance between box and comment is controlled by /tcb/middle → P. 43.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,listing above comment,
  center lower,image comment={width=3cm}{example-image-a.pdf}}
This is a \LaTeX\ example.
\end{tcblisting}
```

This is a \LaTeX\ example.



N 2014-11-07 /tcb/listing above* comment (no value)

Widely equal to /tcb/listing above comment, but the outside comment is not formatted with the lower part options. Also, it is not put into a minipage and it may span several pages. The distance between box and comment is controlled by /tcb/after → P. 78.

/tcb/comment above listing (no value)

Typesets the environment content as listing in a tcolorbox and a given comment outside and above the box. The outside text is treated as *lower* part of the tcolorbox and can be formatted with all lower part options. The distance between box and comment is controlled by /tcb/middle → P. 43.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,comment above listing,
  center lower,image comment={width=3cm}{example-image-a.pdf}}
This is a \LaTeX\ example.
\end{tcblisting}
```



This is a \LaTeX\ example.

N 2014-11-07 /tcb/comment above* listing (no value)

Widely equal to /tcb/comment above listing, but the outside comment is not formatted with the lower part options. Also, it is not put into a minipage and it may span several pages. The distance between box and comment is controlled by /tcb/before → P. 78.

15.7 Option Keys for Processing and Full Document Examples

A complete LaTeX document including `\documentclass`, `\begin{document}` and `\end{document}` cannot be processed directly by `tcolorbox`. It always has to be compiled separately. There are two methods supported by the package to process and display such a full document example:

- Prepare and compile the example document independent from your main document. The source file and the resulting PDF file can be included into the main document afterwards. This is the most economic way since the example document can be left untouched after the example is complete.
- The other possibility is to compile the example on the fly while the main document is compiled. This way has some charm, because the example can be edited inside the main document. But be aware that the compilation of the example is issued on every run of the main document. Also, there are fewer degrees of freedom how the example is compiled.

For both methods, the resulting example PDF file can be included as a `/tcb/pdf comment` → P. 312.

The following example shows how to apply the first method. There already is a file `tcolorbox-example.tex` and a PDF file `tcolorbox-example.pdf`. Both of them are input partly by the following:

```
% \tcbuselibrary{breakable,skins,raster}
\tcbinputlisting{
  enhanced jigsaw,breakable,pad at break*=2mm,height fixed for=first and middle,
  lower separated=false,
  leftlower=0pt,rightlower=0pt,middle=0pt,
  colframe=red!50!black,colback=yellow!10!white,
  listing and comment,
  listing file={tcolorbox-example},
  listing options=
    {style=tcblatex,texcsstyle=*\color{red!70!black},firstline=20,lastline=85},
  after upper={\par\bigskip\texttt{\ldots}\par},
  pdf comment,
  comment style={drop lifted shadow,graphics pages={1,...,4}},
}
```

```
\documentclass{article}
\usepackage{tikz,lipsum,lmodern}
\usepackage[most]{tcolorbox}

\begin{document}

%-------------------------------------------------------------
\section{Colored boxes}

\begin{tcolorbox}[colback=red!5!white,colframe=red!75!black]
  My box.
\end{tcolorbox}

\begin{tcolorbox}[colback=blue!5!white,colframe=blue!75!black,title=My title]
  My box with my title.
\end{tcolorbox}

\begin{tcolorbox}[colback=green!5!white,colframe=green!75!black]
  Upper part of my box.
  \tcblower
```

```
  Lower part of my box.
\end{tcolorbox}

\begin{tcolorbox}[colback=yellow!5!white,colframe=yellow!50!black,
  colbacktitle=yellow!75!black,title=My title]
  I can do this also with a title.
  \tcblower
  Lower part of my box.
\end{tcolorbox}

\begin{tcolorbox}[colback=yellow!10!white,colframe=red!75!black,lowerbox=invisible,
  savelowerto=\jobname_ex.tex]
  Now, we play hide and seek. Where is the lower part?
  \tcblower
  I'm invisible until you find me.
\end{tcolorbox}

\begin{tcolorbox}[colback=yellow!10!white,colframe=red!75!black,title=Here I am]
  \input{\jobname_ex.tex}
\end{tcolorbox}


\begin{tcolorbox}[enhanced,sharp corners=uphill,
    colback=blue!50!white,colframe=blue!25!black,coltext=yellow,
    fontupper=\Large\bfseries,arc=6mm,boxrule=2mm,boxsep=5mm,
    borderline={0.3mm}{0.3mm}{white}]
  Funny settings.
\end{tcolorbox}


\begin{tcolorbox}[enhanced,frame style image=blueshade.png,
  opacityback=0.75,opacitybacktitle=0.25,
  colback=blue!5!white,colframe=blue!75!black,
  title=My title]
  This box is filled with an external image.\par
  Title and interior are made partly transparent to show the image.
\end{tcolorbox}


\begin{tcolorbox}[enhanced,attach boxed title to top
    center={yshift=-3mm,yshifttext=-1mm},
  colback=blue!5!white,colframe=blue!75!black,colbacktitle=red!80!black,
  title=My title,fonttitle=\bfseries,
  boxed title style={size=small,colframe=red!50!black} ]
  This box uses a \textit{boxed title}. The box of the title can
  be formatted independently from the main box.
\end{tcolorbox}

...
```

1 Colored boxes

My box.

My title

My box with my title.

Upper part of my box.

Lower part of my box.

My title

I can do this also with a title.

Lower part of my box.

Now, we play hide and seek. Where is the lower part?

Here I am

I'm invisible until you find me.

Funny settings.

My title

This box is filled with an external image.
Title and interior are made partly transparent to show the image.

My title

This box uses a *boxed title*. The box of the title can be formatted independently from the main box.

2 LaTeX-Examples

```
This is a \LaTeX\ example:
\begin{equation}
\sum\limits_{i=1}^n i = \frac{n(n+1)}{2}.
\end{equation}
```

This is a LaTeX example:

$$\sum_{i=1}^{n} i = \frac{n(n+1)}{2}. \tag{1}$$

Side by side

```
This is a \LaTeX\ example:
\begin{equation}
\sum\limits_{i=1}^n i =
    \frac{n(n+1)}{2}.
\end{equation}
```

This is a LaTeX example:

$$\sum_{i=1}^{n} i = \frac{n(n+1)}{2}. \tag{2}$$

3 Theorems

Theorem 3.1: Summation of Numbers

For all natural number n it holds:

$$\sum_{i=1}^{n} i = \frac{n(n+1)}{2}. \tag{3}$$

We have given Theorem 3.1 on page 2.

3.2 Theorem (Summation of Numbers): *For all natural number n it holds:*

$$\sum_{i=1}^{n} i = \frac{n(n+1)}{2}. \tag{4}$$

4 Watermarks

Box with a watermark picture

Here, you see my nice box, with a picture as a watermark. This picture is automatically resized to fit the dimensions of my box. Instead of a picure, some text could be used or arbitrary graphical code. See the documentation for more options.

5 Boxes in boxes

Box

Box inside box

Box inside box inside box

And now for something completely different: Boxes!

This | is | another | box.

6 Breakable Boxes

Breakable box

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.
Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.
Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.
Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.
Fusce mauris. Vestibulum luctus nibh at lectus. Sed bibendum, nulla a faucibus semper, leo velit ultricies tellus, ac venenatis arcu wisi vel nisl. Vestibulum diam. Aliquam pellentesque, augue quis sagittis posuere, turpis lacus congue quam, in hendrerit risus eros eget felis. Maecenas eget erat in sapien mattis porttitor. Vestibulum porttitor. Nulla facilisi. Sed a turpis eu lacus commodo facilisis. Morbi fringilla, wisi in dignissim interdum, justo lectus sagittis dui, et vehicula libero dui cursus dui. Mauris tempor ligula sed lacus. Duis cursus enim ut augue. Cras ac magna. Cras nulla. Nulla egestas. Curabitur a leo. Quisque egestas wisi eget nunc. Nam feugiat lacus vel est. Curabitur consectetuer.
Suspendisse vel felis. Ut lorem lorem, interdum eu, tincidunt sit amet, laoreet vitae, arcu. Aenean faucibus pede eu ante. Praesent enim elit, rutrum at, molestie non, nonummy vel, nisl. Ut lectus eros, malesuada sit amet, fermentum eu, sodales cursus, magna. Donec eu purus. Quisque vehicula, urna sed ultricies auctor, pede lorem egestas dui, et convallis elit erat sed nulla. Donec luctus. Curabitur et nunc. Aliquam dolor odio, commodo pretium, ultricies non, pharetra in, velit. Integer arcu est, nonummy in, fermentum faucibus, egestas vel, odio.
Sed commodo posuere pede. Mauris ut est. Ut quis purus. Sed ac odio. Sed vehicula hendrerit sem. Duis non odio. Morbi ut dui. Sed accumsan risus eget odio. In hac habitasse platea dictumst. Pellentesque non elit.

N 2014-11-14 **/tcb/no process** (no default)

Removes all processing commands if set before.

N 2014-11-14 **/tcb/process code=**⟨*code*⟩ (no default, initially empty)

Adds ⟨*code*⟩ which is executed during \tcbinputlisting → P. 301 and tcblisting → P. 299. At the time of executing the given ⟨*code*⟩, the listing is already written to /tcb/listing file → P. 310, but the colored box is not constructed yet. Its intended use is to process the listing somehow before displaying. The processing result can be used inside a /tcb/comment → P. 311. Several /tcb/process code options can be given which are processed in the given order. Typically, ⟨*code*⟩ is added by using the following styles /tcb/run system command, /tcb/run pdflatex, etc.

! To use the further options, the compiler has to be called with the -shell-escape permission to authorize potentially dangerous system calls. Be warned that this is a security risk. Anyway, it's more economic to compile examples independent from the main document and to include them as shown in the previous pages.

N 2014-11-14 **/tcb/run system command=**⟨*system command*⟩ (style, no default, initially unset)

Runs a ⟨*system command*⟩, if the document is compiled with the -shell-escape permission. The current listing file can be accessed as \filename@area\filename@base\filename@ext. This ⟨*system command*⟩ is added to /tcb/process code.

N 2014-11-14
U 2016-05-27 **/tcb/compilable listing** (style, no default)

Sets /tcb/listing file → P. 310 to \jobname-listing-⟨*counter*⟩.

! The default /tcb/listing file → P. 310 setting cannot be used to compile a listing, since the base name equals the \jobname and the included PDF files should be unique. Therefore, to use /tcb/run pdflatex etc., the /tcb/listing file → P. 310 has to be set to a unique value. One may use /tcb/compilable listing for this purpose.

N 2014-11-14 **/tcb/run pdflatex=**⟨*arguments*⟩ (style, no default, initially unset)

Issues a pdflatex compilation of the listing with the given ⟨*arguments*⟩.

- The main document has to be compiled with the -shell-escape permission.
- The /tcb/listing file → P. 310 has to be unique for the listing.
- If the listing has to be compiled twice, add run pdflatex two times to the option list.

```
\begin{tcblisting}{enhanced jigsaw,lower separated=false,
  leftlower=0pt,rightlower=0pt,
  colframe=red!50!black,colback=yellow!10!white,
  listing options={style=tcblatex,texcsstyle=*\color{red!70!black}},
  listing and comment,
  pdf comment,freeze pdf,
  compilable listing,
  run pdflatex
}
\documentclass{beamer}
\usetheme{Warsaw}
\begin{document}
\begin{frame}{Beamer example}
  \begin{block}{Hello World}
    \begin{itemize}[<+->]
      \item One
      \item Two
    \end{itemize}
  \end{block}

  \begin{alertblock}{Integral}
    \begin{equation}
```

```
      \visible<3->{\int\limits_1^x \frac{1}{t}~dt}
      \visible<4->{ = \ln(x).}
    \end{equation}
  \end{alertblock}
\end{frame}
\end{document}
\end{tcblisting}
```

```
\documentclass{beamer}
\usetheme{Warsaw}
\begin{document}
\begin{frame}{Beamer example}
  \begin{block}{Hello World}
    \begin{itemize}[<+->]
      \item One
      \item Two
    \end{itemize}
  \end{block}

  \begin{alertblock}{Integral}
    \begin{equation}
      \visible<3->{\int\limits_1^x \frac{1}{t}~dt}
      \visible<4->{ = \ln(x).}
    \end{equation}
  \end{alertblock}
\end{frame}
\end{document}
```









N 2014-11-14 **/tcb/run xelatex=⟨*arguments*⟩** (style, no default, initially unset)

Issues a `xelatex` compilation of the listing with the given ⟨*arguments*⟩.

N 2014-11-14 **/tcb/run lualatex=⟨*arguments*⟩** (style, no default, initially unset)

Issues a `lualatex` compilation of the listing with the given ⟨*arguments*⟩.

N 2014-11-14 **/tcb/run makeindex=⟨*arguments*⟩** (style, no default, initially unset)

Issues a `makeindex` compilation of the listing with the given ⟨*arguments*⟩.

N 2014-11-14 **/tcb/run bibtex=⟨*arguments*⟩** (style, no default, initially unset)

Issues a `bibtex` compilation of the listing with the given ⟨*arguments*⟩.

N 2014-11-14 **/tcb/run biber=⟨*arguments*⟩** (style, no default, initially unset)

Issues a `biber` compilation of the listing with the given ⟨*arguments*⟩.

N 2014-11-14 **/tcb/run arara=⟨*arguments*⟩** (style, no default, initially unset)

Issues an `arara` compilation of the listing with the given ⟨*arguments*⟩.

N 2014-11-14 **/tcb/run latex=⟨*arguments*⟩** (style, no default, initially unset)

Issues a `latex` compilation of the listing with the given ⟨*arguments*⟩.

N 2014-11-14 **/tcb/run dvips=⟨*arguments*⟩** (style, no default, initially unset)

Issues a `dvips` compilation of the listing with the given ⟨*arguments*⟩.

N 2014-11-14 **/tcb/run ps2pdf=⟨*arguments*⟩** (style, no default, initially unset)

Issues a `ps2pdf` compilation of the listing with the given ⟨*arguments*⟩.

```
\begin{tcblisting}{enhanced jigsaw,
  title={PSTricks with pdflatex},fonttitle=\bfseries,
  colframe=red!50!black,colback=yellow!10!white,
  listing options={style=tcblatex,texcsstyle=*\color{red!70!black}},
  lower separated=false,middle=0pt,
  listing side comment,righthand width=4cm,
  compilable listing,
  run latex,run dvips,run ps2pdf,
  pdf comment,freeze pdf,
  comment style={raster columns=1,
    graphics options={viewport=0.5in 7.7in 3.5in 10.5in,clip}},
}
\documentclass{article}
\usepackage{pstricks,multido}
\begin{document}
\psset{unit=3}%
\multido{\nHue=0.01+0.01}{100}{%
\definecolor{MyColor}{hsb}{\nHue,1,1}%
\pscircle[linewidth=0.01,linecolor=MyColor]{\nHue}}
\end{document}
\end{tcblisting}
```

PSTricks with pdflatex

```
\documentclass{article}
\usepackage{pstricks,multido}
\begin{document}
\psset{unit=3}%
\multido{\nHue=0.01+0.01}{100}{%
\definecolor{MyColor}{hsb}{\nHue,1,1}%
\pscircle[linewidth=0.01,linecolor=MyColor]{\nHue}}
\end{document}
```



For most applications, you will like to add `/tcb/freeze pdf` as option, since the included `pdf` file is only refreshed, if the source for this file has changed.

N 2016-07-14 **`/tcb/freeze file`**=⟨*file*⟩ (no default, initially unset)

Observes some ⟨*file*⟩, usually the final file produced by `/tcb/process code` → P. 322, `/tcb/run system command` → P. 322, `/tcb/run pdflatex` → P. 322, etc. If the MD5 checksum of the current `/tcb/listing file` → P. 310 is unchanged and ⟨*file*⟩ exists, the processing is skipped and the ⟨*file*⟩ is kept (frozen). Typically, the style `/tcb/freeze pdf` can be used for convenience.

N 2016-07-14 **`/tcb/freeze none`** (no default, initially set)

Freeze no file and always execute the given process commands.

N 2016-07-14 **`/tcb/freeze extension`**=⟨*text*⟩ (style, no default)

Calls `/tcb/freeze file` with the current `/tcb/listing file` → P. 310 stripped with its extension plus ⟨*text*⟩ as new extension.

```
...
listing file=myfile.tex,
freeze extension=-modified.pdf,    % ->   myfile-modified.pdf   is observed
...
```

N 2016-07-14 **`/tcb/freeze pdf`** (no value)

Calls `/tcb/freeze file` with the current `/tcb/listing file` → P. 310 stripped with its extension plus `.pdf` as new extension.

N 2016-07-14 **`/tcb/freeze png`** (no value)

Calls `/tcb/freeze file` with the current `/tcb/listing file` → P. 310 stripped with its extension plus `.png` as new extension. See the examples for `/tcb/run pdflatex` → P. 322 and `/tcb/run ps2pdf` → P. 324.

N 2016-07-14 **`/tcb/freeze jpg`** (no value)

Calls `/tcb/freeze file` with the current `/tcb/listing file` → P. 310 stripped with its extension plus `.jpg` as new extension.

15.8 Creation of LaTeX Tutorials

The following source code gives a guideline for the creation of LaTeX tutorials. In the next section, a framework for LaTeX exercises is described. All examples shall be numbered optionally.

Firstly, some additional `tcb` keys are defined for the appearance. For the examples, three environments `texexp`, `texexptitled`, and `texexptitledspec` are defined with automatic numbering.

- `texexp` is used for untitled examles,
- `texexptitled` is used for titled examles,
- `texexptitledspec` is used for titled examles with special treatment.

Definition in the preamble:

```
\tcbset{
  texexp/.style={colframe=red!50!yellow!50!black, colback=red!50!yellow!5!white,
      coltitle=red!50!yellow!3!white,
      fonttitle=\small\sffamily\bfseries, fontupper=\small, fontlower=\small},
  example/.style 2 args={texexp,
      title={Example \thetcbcounter: #1},label={#2}},
}


\newtcblisting{texexp}[1]{texexp,#1}
\newtcblisting[auto counter,number within=section]{texexptitled}[3][]{%
  example={#2}{#3},#1}
\newtcolorbox[use counter from=texexptitled]{texexptitledspec}[3][]{%
  example={#2}{#3},#1}
```

```
\begin{tcblisting}{texexp}
This is a \LaTeX\ example which displays the text as source code
and in compiled form.
\end{tcblisting}
```

```
This is a \LaTeX\ example which displays the text as source code
and in compiled form.
```

This is a LaTeX example which displays the text as source code and in compiled form.

```
\begin{texexptitled}{First example with a title line}{firstExample}
Here, we use Example \ref{firstExample} with a title line.
\end{texexptitled}
```

Example 15.1: First example with a title line

```
Here, we use Example \ref{firstExample} with a title line.
```

Here, we use Example 15.1 with a title line.

```
\begin{texexp}{}
This is a \LaTeX\ example which displays the text as source code
and in compiled form.
\end{texexp}
```

```
This is a \LaTeX\ example which displays the text as source code
and in compiled form.
```

This is a LaTeX example which displays the text as source code and in compiled form.

```
\begin{texexp}{text and listing}
This is a \LaTeX\ example which displays the text as source code
and in compiled form.
\end{texexp}
```

This is a LaTeX example which displays the text as source code and in compiled form.

```
This is a \LaTeX\ example which displays the text as source code
and in compiled form.
```

```
\begin{texexp}{listing only}
This is a \LaTeX\ example which displays the text as source code only.
\end{texexp}
```

```
This is a \LaTeX\ example which displays the text as source code only.
```

```
\begin{texexp}{text only}
This is a \LaTeX\ example which displays the text in compiled form only.
\end{texexp}
```

This is a LaTeX example which displays the text in compiled form only.

```
\begin{texexptitled}{An Example with a Heading}{heading1}
This is a \LaTeX\ example with a numbered heading line
which can be referred to.
\end{texexptitled}
Here, we see Example \ref{heading1}.
```

Example 15.2: An Example with a Heading

```
This is a \LaTeX\ example with a numbered heading line
which can be referred to.
```

This is a LaTeX example with a numbered heading line which can be referred to.

Here, we see Example 15.2.

```
\begin{texexptitled}[listing only]{Another Example with a Heading}{heading2}
The keys can be used in combination. Here, an example with a heading line
and source code only is given.
\end{texexptitled}
Here, we see Example \ref{heading2}.
```

Example 15.3: Another Example with a Heading

The keys can be used in combination. Here, an example with a heading line and source code only is given.

Here, we see Example 15.3.

```
\begin{texexptitled}[float]{A floating Example with a Heading}{heading3}
This is another \LaTeX\ example with numbered heading line.
But now, the box is a floating object.
\end{texexptitled}
```

Example 15.4: A floating Example with a Heading

This is another **\LaTeX** example with numbered heading line.
But now, the box is a floating object.

This is another LaTeX example with numbered heading line. But now, the box is a floating object.

```
The floating box of the last example is seen as Example \ref{heading3}
on page \pageref{heading3}.
```

The floating box of the last example is seen as Example 15.4 on page 328.

```
\begin{texexptitledspec}{Special application}{texexpbox1}
\begin{lstlisting}[style=tcblatex]
Some \LaTeX\ source code.
\end{lstlisting}
\tcblower
For special cases, the environment |texexptitledspec| with style
|example| can be used directly. As one can see, the upper and the lower
part of the box can be used uncoupled also.
\end{texexptitledspec}
```

Example 15.5: Special application

Some **\LaTeX** source code.

For special cases, the environment **texexptitledspec** with style **example** can be used directly. As one can see, the upper and the lower part of the box can be used uncoupled also.

The following series of examples demonstrate the application of tcolorbox → P. 12 options for diversification.

```
\begin{texexptitled}{How to use options (1):\par The basic example}{options1}
\begin{tikzpicture}
\path[fill=yellow!50!white] (0,0) circle (11mm);
\path[fill=white] (0,0) circle (9mm);
\foreach \w/\c in {90/red,210/green,330/blue}
{\path[shading=ball,ball color=\c] (\w:1cm) circle (7mm);}
\end{tikzpicture}
\end{texexptitled}
```

Example 15.6: How to use options (1): The basic example

```
\begin{tikzpicture}
\path[fill=yellow!50!white] (0,0) circle (11mm);
\path[fill=white] (0,0) circle (9mm);
\foreach \w/\c in {90/red,210/green,330/blue}
{\path[shading=ball,ball color=\c] (\w:1cm) circle (7mm);}
\end{tikzpicture}
```



```
\begin{texexptitled}[center lower,enhanced,segmentation hidden,middle=0mm]
  {How to use options (2):\par The text output is centered and the
    segmentation line has vanished.}{options2}
\begin{tikzpicture}
\path[fill=yellow!50!white] (0,0) circle (11mm);
\path[fill=white] (0,0) circle (9mm);
\foreach \w/\c in {90/red,210/green,330/blue}
{\path[shading=ball,ball color=\c] (\w:1cm) circle (7mm);}
\end{tikzpicture}
\end{texexptitled}
```

Example 15.7: How to use options (2): The text output is centered and the segmentation line has vanished.

```
\begin{tikzpicture}
\path[fill=yellow!50!white] (0,0) circle (11mm);
\path[fill=white] (0,0) circle (9mm);
\foreach \w/\c in {90/red,210/green,330/blue}
{\path[shading=ball,ball color=\c] (\w:1cm) circle (7mm);}
\end{tikzpicture}
```



```
\begin{texexptitled}[tikz lower,bicolor,colbacklower=white]
  {How to use options (3):\par Here, the |tikzpicture| is totally hidden.
    The |bicolor| skin highlights the output.}{options3}
\path[fill=yellow!50!white] (0,0) circle (11mm);
\path[fill=white] (0,0) circle (9mm);
\foreach \w/\c in {90/red,210/green,330/blue}
{\path[shading=ball,ball color=\c] (\w:1cm) circle (7mm);}
\end{texexptitled}
```

Example 15.8: How to use options (3):
Here, the `tikzpicture` is totally hidden. The `bicolor` skin highlights the output.

```
\path[fill=yellow!50!white] (0,0) circle (11mm);
\path[fill=white] (0,0) circle (9mm);
\foreach \w/\c in {90/red,210/green,330/blue}
{\path[shading=ball,ball color=\c] (\w:1cm) circle (7mm);}
```



```
\begin{texexptitled}[center lower,listing side text,righthand width=3.5cm,
  bicolor,colbacklower=white]
  {How to use options (4):\par The |bicolor| skin also works with side
   by side mode}{options4}
\begin{tikzpicture}
\path[fill=yellow!50!white] (0,0) circle (11mm);
\path[fill=white] (0,0) circle (9mm);
\foreach \w/\c in {90/red,210/green,330/blue}
{\path[shading=ball,ball color=\c]
    (\w:1cm) circle (7mm);}
\end{tikzpicture}
\end{texexptitled}
```

Example 15.9: How to use options (4):
The `bicolor` skin also works with side by side mode

```
\begin{tikzpicture}
\path[fill=yellow!50!white] (0,0) circle (11mm);
\path[fill=white] (0,0) circle (9mm);
\foreach \w/\c in {90/red,210/green,330/blue}
{\path[shading=ball,ball color=\c]
    (\w:1cm) circle (7mm);}
\end{tikzpicture}
```



```
\begin{texexptitled}[center lower,listing outside text,righthand width=3.5cm]
  {How to use options (5):\par Putting our picture outside is just
    a matter of one word.}{options5}
\begin{tikzpicture}
\path[fill=yellow!50!white] (0,0) circle (11mm);
\path[fill=white] (0,0) circle (9mm);
\foreach \w/\c in {90/red,210/green,330/blue}
{\path[shading=ball,ball color=\c]
    (\w:1cm) circle (7mm);}
\end{tikzpicture}
\end{texexptitled}
```

Example 15.10: How to use options (5): Putting our picture outside is just a matter of one word.

```
\begin{tikzpicture}
\path[fill=yellow!50!white] (0,0) circle (11mm);
\path[fill=white] (0,0) circle (9mm);
\foreach \w/\c in {90/red,210/green,330/blue}
{\path[shading=ball,ball color=\c]
    (\w:1cm) circle (7mm);}
\end{tikzpicture}
```



```
\begin{texexptitled}[center lower,text above listing]
  {How to use options (6):\par The picture may also be put above
    the listing box.}{options6}
\begin{tikzpicture}
\path[fill=yellow!50!white] (0,0) circle (11mm);
\path[fill=white] (0,0) circle (9mm);
\foreach \w/\c in {90/red,210/green,330/blue}
{\path[shading=ball,ball color=\c]
    (\w:1cm) circle (7mm);}
\end{tikzpicture}
\end{texexptitled}
```



Example 15.11: How to use options (6): The picture may also be put above the listing box.

```
\begin{tikzpicture}
\path[fill=yellow!50!white] (0,0) circle (11mm);
\path[fill=white] (0,0) circle (9mm);
\foreach \w/\c in {90/red,210/green,330/blue}
{\path[shading=ball,ball color=\c]
    (\w:1cm) circle (7mm);}
\end{tikzpicture}
```

```
\begin{texexptitled}[beamer,center lower,text outside listing,lefthand width=3.5cm]
  {How to use options (7):\par Our style is easily transformed into
    a beamerish one.}{options7}
\begin{tikzpicture}
\path[fill=yellow!50!white] (0,0) circle (11mm);
\path[fill=white] (0,0) circle (9mm);
\foreach \w/\c in {90/red,210/green,330/blue}
{\path[shading=ball,ball color=\c]
    (\w:1cm) circle (7mm);}
\end{tikzpicture}
\end{texexptitled}
```



Example 15.12: How to use options (7):
Our style is easily transformed into a beamerish one.

```
\begin{tikzpicture}
\path[fill=yellow!50!white] (0,0) circle (11mm);
\path[fill=white] (0,0) circle (9mm);
\foreach \w/\c in {90/red,210/green,330/blue}
{\path[shading=ball,ball color=\c]
    (\w:1cm) circle (7mm);}
\end{tikzpicture}
```

15.9 Creation of LaTeX Exercises

In the following, a guideline is given for the creation of LaTeX exercises with solutions. These solutions are saved to disk for application at a place of choice. Therefore, all used exercises are logged to a file `\jobname.records` for automatic processing. The solution contents themselves are saved to a subdirectory named `solutions`. Also see Section 8 on page 128.

- Before the first exercise is given, `\tcbstartrecording` → P. 128 has to be called to start recording.
- The solution is given as content of a `tcboutputlisting` → P. 301 environment. Note, that you can use this content also inside the exercise with `\tcbuselistingtext` → P. 301 in compiled form.
- After the last exercise is given (and before using the solutions), `\tcbstoprecording` → P. 128 has to be called to stop recording.
- The solutions are loaded by `\tcbinputrecords` → P. 128.

Inside the exercise text, there may be text parts which are needed as LaTeX source code and as compiled text as well. These parts can be saved by `tcbwritetemp` → P. 126 and used in compiled form by `\tcbusetemp` → P. 126 or as source code by `\tcbusetemplisting` → P. 301.

At first, we generate some a common style for the exercises and the solutions. Further, since exercises and solutions should be numbered, we force to use a label ⟨*marker*⟩. Automatically, the label `exe:`⟨*marker*⟩ is used to mark the exercise and the label `sol:`⟨*marker*⟩ is used to mark the solution.

```
\tcbset{texercisestyle/.style={arc=0.5mm, colframe=blue!25!yellow!90!white,
  colback=blue!25!yellow!5!white, coltitle=blue!25!yellow!40!black,
  fonttitle=\small\sffamily\bfseries, fontupper=\small, fontlower=\small,
  listing options={style=tcblatex,texcsstyle=*\color{red!40!black}},
}}
```

With these preparations, the kernel environment `texercise` for our exercises is created quickly:

Definition in the preamble:

```
\newtcolorbox[auto counter,number within=section,list inside=exam]{texercise}[2][]{%
  texercisestyle,
  listing file={solutions/texercise\thetcbcounter.tex},
  label={exe:#2},
  record={\string\processsol{solutions/texercise\thetcbcounter.tex}{#2}},
  title={Exercise \thetcbcounter\hfill\mdseries Solution on page \pageref{sol:#2}},
  list text={Exercise with solution on page \pageref{sol:#2}},#1}
```

The following examples demonstrate the application.

```
\tcbstartrecording
```

```
\begin{texercise}{tabular_example}
\textit{Create the following table:}\par\smallskip%
\begin{tcboutputlisting}
\begin{tabular}{|p{3cm}|p{3cm}|p{3cm}|p{3cm}|}\hline
\multicolumn{4}{|c|}{\bfseries\itshape Das alte Italien}\\\hline
\multicolumn{2}{|c|}{\bfseries Antike} &
\multicolumn{2}{c|}{\bfseries Mittelalter}\\\hline
\multicolumn{1}{|c|}{\itshape Republik}&
\multicolumn{1}{c|}{\itshape Kaiserreich}&
\multicolumn{1}{c|}{\itshape Franken}&
\multicolumn{1}{c|}{\itshape Teilstaaten}\\\hline
In den Zeiten der r\"{o}mischen Republik standen dem Staat jeweils zwei
Konsuln vor, deren Machtbefugnisse identisch waren. &
Das r\"{o}mische Kaiserreich wurde von einem Alleinherrscher, dem Kaiser,
regiert.
& In der V\"{o}lkerwanderungszeit \"{u}bernahmen die Goten und sp\"{a}ter die
Franken die Vorherrschaft.
& Im sp\"{a}teren Mittelalter regierten F\"{u}rsten einen Fleckenteppich
von Einzelstaaten.\\\hline
\end{tabular}
\end{tcboutputlisting}
\tcbuselistingtext%
\end{texercise}
```

Exercise 15.1 Solution on page 337

Create the following table:

Das alte Italien			
Antike		**Mittelalter**	
Republik	*Kaiserreich*	*Franken*	*Teilstaaten*
In den Zeiten der römischen Republik standen dem Staat jeweils zwei Konsuln vor, deren Machtbefugnisse identisch waren.	Das römische Kaiserreich wurde von einem Alleinherrscher, dem Kaiser, regiert.	In der Völkerwanderungszeit übernahmen die Goten und später die Franken die Vorherrschaft.	Im späteren Mittelalter regierten Fürsten einen Fleckenteppich von Einzelstaaten.

```
\begin{texercise}{macro_oneparam}
\begin{tcboutputlisting}
\newcommand{\headingline}[1]{%
  \begin{center}\Large\bfseries #1\end{center}}
\end{tcboutputlisting}
\tcbuselistingtext%

Create a new macro \verb+\headingline+ which produces the
following output:\par\smallskip
\begin{tcbwritetemp}
\headingline{Very important heading}
\end{tcbwritetemp}
\tcbusetemplisting\tcbusetemp%
\end{texercise}
```

Exercise 15.2 Solution on page 337

Create a new macro `\headingline` which produces the following output:

```
\headingline{Very important heading}
```

Very important heading

```
\begin{texercise}{macro_twoparam}
\begin{tcboutputlisting}
\newcommand{\minitable}[2]{%
  \begin{center}\begin{tabular}{p{10cm}}\hline%
  \multicolumn{1}{c}{\bfseries#1}\\\hline%
  #2\\\hline%
  \end{tabular}\end{center}}
\end{tcboutputlisting}
\tcbuselistingtext%
Create a new macro \verb+\minitable+ which produces the
following output:\par\smallskip
\begin{tcbwritetemp}
\minitable{My heading}{In this tiny tabular, there is only a heading
  and some text below which has a width of ten centimeters.}
\end{tcbwritetemp}
\tcbusetemplisting\par\smallskip\tcbusetemp%
\end{texercise}
```

Exercise 15.3 Solution on page 337

Create a new macro `\minitable` which produces the following output:

```
\minitable{My heading}{In this tiny tabular, there is only a heading
  and some text below which has a width of ten centimeters.}
```

My heading
In this tiny tabular, there is only a heading and some text below which has a width of ten centimeters.

```
\begin{texercise}{macro_threeparam}
\begin{tcboutputlisting}
\newcommand{\synop}[3]{%
  \begin{tabular}{@{}p{(\linewidth-\tabcolsep*2-\arrayrulewidth)/2}|%
    p{(\linewidth-\tabcolsep*2-\arrayrulewidth)/2}@{}}\hline
  \multicolumn{2}{c}{\bfseries #1}\\\hline
  \multicolumn{1}{c|}{\itshape English}&
  \multicolumn{1}{c}{\itshape German}\\\hline
  #2 & #3
  \end{tabular}}
\end{tcboutputlisting}
\tcbuselistingtext%
Create a new macro \verb+\synop+ which typesets a synoptic text according
to the following example. Base your macro on a tabular which takes the
total line width.\par\smallskip
\begin{tcbwritetemp}
\synop{Neil Armstrong}%
{That's one small step for a man, one giant leap for mankind.}%
{Das ist ein kleiner Schritt f\"{u}r einen Mann,
   ein riesiger Sprung f\"{u}r die Menschheit.}
\end{tcbwritetemp}
\tcbusetemplisting\par\smallskip\tcbusetemp%
\end{texercise}
```

Exercise 15.4 Solution on page 338

Create a new macro `\synop` which typesets a synoptic text according to the following example. Base your macro on a tabular which takes the total line width.

```
\synop{Neil Armstrong}%
{That's one small step for a man, one giant leap for mankind.}%
{Das ist ein kleiner Schritt f\"{u}r einen Mann,
   ein riesiger Sprung f\"{u}r die Menschheit.}
```

Neil Armstrong	
English	*German*
That's one small step for a man, one giant leap for mankind.	Das ist ein kleiner Schritt für einen Mann, ein riesiger Sprung für die Menschheit.

```
\tcbstoprecording
```

Now, we give a list of all exercises with:

```
\tcblistof[\subsection]{exam}{List of Exercises%
  \label{listofexercises}}
```

15.10 List of Exercises

15.1 Exercise with solution on page 337 334
15.2 Exercise with solution on page 337 335
15.3 Exercise with solution on page 337 335
15.4 Exercise with solution on page 338 336

15.11 Solutions for the given LaTeX Exercises

For all solutions, a macro `\processsol` was written to the file `\jobname.records`. Now, we need a definition for this macro to use the solutions.

```
% \usepackage{hyperref} % for phantomlabel
\newtcbinputlisting{\processsol}[2]{%
  texercisestyle,
  listing only,
  listing file={#1},
  phantomlabel={sol:#2},%
  title={Solution for Exercise \ref{exe:#2} on page \pageref{exe:#2}},
}
```

The loading of all solutions is done by:

```
\tcbinputrecords
```

With this, we get:

Solution for Exercise 15.1 on page 334

```
\begin{tabular}{|p{3cm}|p{3cm}|p{3cm}|p{3cm}|}\hline
\multicolumn{4}{|c|}{\bfseries\itshape Das alte Italien}\\\hline
\multicolumn{2}{|c|}{\bfseries Antike} &
\multicolumn{2}{c|}{\bfseries Mittelalter}\\\hline
\multicolumn{1}{|c|}{\itshape Republik}&
\multicolumn{1}{c|}{\itshape Kaiserreich}&
\multicolumn{1}{c|}{\itshape Franken}&
\multicolumn{1}{c|}{\itshape Teilstaaten}\\\hline
In den Zeiten der r\"{o}mischen Republik standen dem Staat jeweils zwei
Konsuln vor, deren Machtbefugnisse identisch waren. &
Das r\"{o}mische Kaiserreich wurde von einem Alleinherrscher, dem Kaiser,
regiert.
& In der V\"{o}lkerwanderungszeit \"{u}bernahmen die Goten und sp\"{a}ter die
Franken die Vorherrschaft.
& Im sp\"{a}teren Mittelalter regierten F\"{u}rsten einen Fleckenteppich
von Einzelstaaten.\\\hline
\end{tabular}
```

Solution for Exercise 15.2 on page 335

```
\newcommand{\headingline}[1]{%
  \begin{center}\Large\bfseries #1\end{center}}
```

Solution for Exercise 15.3 on page 335

```
\newcommand{\minitable}[2]{%
  \begin{center}\begin{tabular}{p{10cm}}\hline%
  \multicolumn{1}{c}{\bfseries#1}\\\hline%
  #2\\\hline%
  \end{tabular}\end{center}}
```

Solution for Exercise 15.4 on page 336

```
\newcommand{\synop}[3]{%
  \begin{tabular}{@{}p{(\linewidth-\tabcolsep*2-\arrayrulewidth)/2}|%
    p{(\linewidth-\tabcolsep*2-\arrayrulewidth)/2}@{}}\hline
  \multicolumn{2}{c}{\bfseries #1}\\\hline
  \multicolumn{1}{c|}{\itshape English}&
  \multicolumn{1}{c}{\itshape German}\\\hline
  #2 & #3
  \end{tabular}}
```

16 Library LIB theorems

The library is loaded by a package option or inside the preamble by:

```
\tcbuselibrary{theorems}
```

This also loads the package `amsmath`.

16.1 Macros of the Library

U 2016-06-22 `\newtcbtheorem[⟨init options⟩]{⟨name⟩}{⟨display name⟩}{⟨options⟩}{⟨prefix⟩}`

Creates new environments ⟨*name*⟩ and ⟨*name*⟩`*` based on `tcolorbox` to frame a (mathematical) theorem. The ⟨*display name*⟩ is used in the title line with a number, e. g. «Theorem 5.1». The ⟨*options*⟩ are given to the underlying `tcolorbox` to control the appearance. The ⟨*init options*⟩ allow setting up automatic numbering, see Section 5 on page 108. The new environment ⟨*name*⟩ takes one optional and two mandatory parameters. The optional parameter supplements the options and should be used only in rare cases. The first mandatory parameter is the title text for the theorem and is also set as `/tcb/nameref` → P. 99 identifier. The second mandatory parameter is a ⟨*marker*⟩. The theorem is automatically labeled with ⟨*prefix*⟩⟨*separator*⟩⟨*marker*⟩ where ⟨*separator*⟩ is predefined as ':', see `/tcb/label separator` → P. 346.

The new environment ⟨*name*⟩`*` takes one optional and one mandatory parameter and represents an unnumbered variant of the environment ⟨*name*⟩. This variant is not labeled and not listed in lists of theorems.

Definition in the preamble:

```
\newtcbtheorem[number within=section]{mytheo}{My Theorem}%
  {colback=green!5,colframe=green!35!black,fonttitle=\bfseries}{th}
```

```
% usage of '\nameref' needs 'nameref' or 'hyperref' to be loaded
\begin{mytheo}{This is my title}{theoexample}
  This is the text of the theorem. The counter is automatically assigned and,
  in this example, prefixed with the section number. This theorem is numbered with
  \ref{th:theoexample}, it is given on page~\pageref{th:theoexample},
  and it is titled \flqq\nameref{th:theoexample}\frqq.
\end{mytheo}
```

My Theorem 16.1: This is my title

This is the text of the theorem. The counter is automatically assigned and, in this example, prefixed with the section number. This theorem is numbered with 16.1, it is given on page 339, and it is titled «This is my title».

```
\begin{mytheo}[label=myownlabel]{This is my title}{}
  The label parameter can be left empty without \LaTeX\ error.
  Or you may use an own label to reference Theorem \ref{myownlabel}.
\end{mytheo}
```

My Theorem 16.2: This is my title

The label parameter can be left empty without LaTeX error. Or you may use an own label to reference Theorem 16.2.

```
\begin{mytheo}{}{}
  The title can also be left empty without problem. Note that the ':'
  vanished magically.
\end{mytheo}
```

My Theorem 16.3

The title can also be left empty without problem. Note that the ':' vanished magically.

```
\begin{mytheo*}{Unnumbered Theorem}
  This theorem is not numbered.
\end{mytheo*}
```

My Theorem: Unnumbered Theorem

This theorem is not numbered.

```
\begin{mytheo*}{}
  This theorem has no number and no title.
\end{mytheo*}
```

My Theorem

This theorem has no number and no title.

! To switch off the `nameref` feature permanently, add `nameref/.style={}` inside the ⟨*options*⟩ list.

`\renewtcbtheorem[`⟨*init options*⟩`]{`⟨*name*⟩`}{`⟨*display name*⟩`}{`⟨*options*⟩`}{`⟨*prefix*⟩`}`

Operates like `\newtcbtheorem` → P. 339, but based on `\renewenvironment` instead of `\newenvironment`. An existing environment is redefined.

`\tcbmaketheorem{`⟨*name*⟩`}{`⟨*display name*⟩`}{`⟨*options*⟩`}{`⟨*counter*⟩`}{`⟨*prefix*⟩`}`

! `\newtcbtheorem` → P. 339 supersedes this macro.

Creates a new environment ⟨*name*⟩ based on `tcolorbox` to frame a (mathematical) theorem. The ⟨*display name*⟩ is used in the title line with a number, e. g. «Theorem 5.1». The ⟨*options*⟩ are given to the underlying `tcolorbox` to control the appearance. The ⟨*counter*⟩ is used for automatic numbering. The new environment ⟨*name*⟩ takes one optional and two mandatory parameters. The optional parameter supplements the options and should be used only in rare cases. The first mandatory parameter is the title text for the theorem and the second mandatory parameter is a ⟨*marker*⟩. The theorem is automatically labeled with ⟨*prefix*⟩⟨*separator*⟩⟨*marker*⟩ where ⟨*separator*⟩ is predefined as ':', see `/tcb/label separator` → P. 346.

deprecated

`\tcboxmath[⟨options⟩]{⟨mathematical box content⟩}`

Creates a `tcolorbox` → P. 12 which is fitted to the width of the given ⟨*mathematical box content*⟩. This box is intended to be applied as part of a larger formula and may be used as replacement for the `\boxed` macro of `amsmath`.

```
\begin{equation}
\tcbset{fonttitle=\scriptsize}
\tcboxmath[colback=LightBlue!25!white,colframe=blue]{ a^2 = 16 }
\quad \Rightarrow \quad
\tcboxmath[colback=Salmon!25!white,colframe=red,title=Implication]%
  { a = 4 ~\vee~ a=-4. }
\end{equation}
```

$$a^2 = 16 \quad \Rightarrow \quad \text{Implication: } a = 4 \ \vee \ a = -4. \tag{3}$$

`\tcbhighmath[⟨options⟩]{⟨mathematical box content⟩}`

This is a special case of the `\tcboxmath` macro which uses the style `/tcb/highlight math` → P. 349. It is intended to provide context sensitive highlighting of formula parts. The color settings via `/tcb/highlight math style` → P. 349 may be different inside theorems or other colored areas and outside.

```
\tcbset{myformula/.style={colback=yellow!10!white,colframe=red!50!black,
  every box/.style={highlight math style={colback=LightBlue!50!white,colframe=Navy}}
  }}

\begin{align}
  \tcbhighmath{\sum\limits_{n=1}^{\infty} \frac{1}{n}} &= \infty.\\
  \int x^2 ~\text{d}x                                  &= \frac13 x^3 + c.
\end{align}

\begin{tcolorbox}[ams align,myformula]
  \tcbhighmath{\sum\limits_{n=1}^{\infty} \frac{1}{n}} &= \infty.\\
  \int x^2 ~\text{d}x                                  &= \frac13 x^3 + c.
\end{align}
\end{tcolorbox}
```

$$\sum_{n=1}^{\infty} \frac{1}{n} = \infty. \tag{4}$$

$$\int x^2 \, \mathrm{d}x = \frac{1}{3}x^3 + c. \tag{5}$$

$$\sum_{n=1}^{\infty} \frac{1}{n} = \infty. \tag{6}$$

$$\int x^2 \, \mathrm{d}x = \frac{1}{3}x^3 + c. \tag{7}$$

\tcbhighmath → P. 341 can be used in symbiosis with the empheq package which allows to specify own boxing commands to mark multiline formulas.

```
% \usepackage{empheq}
\begin{empheq}[box=\tcbhighmath]{align}
a&=\sin(z)\\
E&=mc^2 + \int_a^b x\, dx
\end{empheq}

\tcbset{highlight math style={enhanced,
  colframe=red!60!black,colback=yellow!50!white,arc=4pt,boxrule=1pt,
  drop fuzzy shadow}}

\begin{empheq}[box=\tcbhighmath]{align}
a&=\sin(z)\\
E&=mc^2 + \int_a^b x\, dx
\end{empheq}
```

$$a = \sin(z) \tag{8}$$
$$E = mc^2 + \int_a^b x\,dx \tag{9}$$

$$a = \sin(z) \tag{10}$$
$$E = mc^2 + \int_a^b x\,dx \tag{11}$$

Besides \tcbhighmath → P. 341, one can easily define an independent new box based on \tcbox → P. 14 which acts like \tcbhighmath → P. 341:

```
% \usepackage{empheq}
\newtcbox{\otherbox}[1][]{nobeforeafter,math upper,tcbox raise base,
  enhanced,frame hidden,boxrule=0pt,interior style={top color=green!10!white,
  bottom color=green!10!white,middle color=green!50!yellow},
  fuzzy halo=1pt with green,#1}

\begin{empheq}[box=\otherbox]{align}
a&=\sin(z)\\
E&=mc^2 + \int_a^b x\, dx
\end{empheq}

\begin{equation}
\tcbhighmath{E} = \otherbox{mc^2}
\end{equation}
```

$$a = \sin(z) \tag{12}$$
$$E = mc^2 + \int_a^b x\,dx \tag{13}$$

$$E = mc^2 \tag{14}$$

16.2 Option Keys of the Library

/tcb/separator sign=⟨*sign*⟩ (no default, initially :)

The given ⟨*sign*⟩ is used inside the title text of a theorem as separater between display name combined with number and the specific title text. It is omitted, if there is no specific title text.

```
% \usepackage{amssymb}
\newtcbtheorem[use counter from=mytheo]{sometheorem}{Theorem}%
  {colback=white,colframe=red!50!black,fonttitle=\bfseries,
   separator sign={\ $\blacktriangleright$}}{theo}
\begin{sometheorem}{My example}{}
My theorem text.
\end{sometheorem}
```

Theorem 16.4 ▶ My example

My theorem text.

/tcb/separator sign colon (style, no value, initially set)

Sets /tcb/separator sign to the default colon : sign.

/tcb/separator sign dash (style, no value)

Sets /tcb/separator sign to an en-dash sign.

```
\newtcbtheorem[use counter from=mytheo]{sometheorem}{Theorem}%
  {colback=white,colframe=red!50!black,fonttitle=\bfseries,
   separator sign dash}{theo}
\begin{sometheorem}{My example}{}
My theorem text.
\end{sometheorem}
```

Theorem 16.5 – My example

My theorem text.

/tcb/separator sign none (style, no value)

Sets /tcb/separator sign to empty.

```
\newtcbtheorem[use counter from=mytheo]{sometheorem}{Theorem}%
  {colback=white,colframe=red!50!black,fonttitle=\bfseries,
   separator sign none}{theo}
\begin{sometheorem}{My example}{}
My theorem text.
\end{sometheorem}
```

Theorem 16.6 My example

My theorem text.

`/tcb/description delimiters={⟨left⟩}{⟨right⟩}` (no default, initially empty)

The given ⟨*left*⟩ and ⟨*right*⟩ delimiter signs are used to frame the descriptive title text of a theorem.

```
\newtcbtheorem[use counter from=mytheo]{sometheorem}{Theorem}%
  {colback=white,colframe=red!50!black,fonttitle=\bfseries,
   description delimiters={\flqq}{\frqq}}{theo}
\begin{sometheorem}{My example}{}
My theorem text.
\end{sometheorem}
```

Theorem 16.7: «My example»

My theorem text.

`/tcb/description delimiters parenthesis` (style, no value)

Sets `/tcb/description delimiters` to (and).

```
\newtcbtheorem[use counter from=mytheo]{sometheorem}{Theorem}%
  {colback=white,colframe=red!50!black,fonttitle=\bfseries,
   description delimiters parenthesis}{theo}
\begin{sometheorem}{My example}{}
My theorem text.
\end{sometheorem}
```

Theorem 16.8: (My example)

My theorem text.

`/tcb/description delimiters none` (style, no value, initially set)

Sets `/tcb/description delimiters` to the default empty texts.

`/tcb/description color=`⟨*color*⟩ (default empty, initially empty)

Sets the ⟨*color*⟩ of the descriptive title text deviating from `/tcb/coltitle` → P. 28. The color is reset to `/tcb/coltitle` → P. 28, if `description color` is used without value.

```
\newtcbtheorem[use counter from=mytheo]{sometheorem}{Theorem}%
  {colback=white,colframe=red!50!black,fonttitle=\bfseries,
   description color=red!25!yellow}{theo}
\begin{sometheorem}{My example}{}
My theorem text.
\end{sometheorem}
```

Theorem 16.9: My example

My theorem text.

`/tcb/description font=`⟨*text*⟩ (default empty, initially empty)

Sets ⟨*text*⟩ (e. g. font settings) before the descriptive title text deviating from `/tcb/fonttitle` → P. 29. The ⟨*text*⟩ is removed, if `description font` is used without value.

```
\newtcbtheorem[use counter from=mytheo]{sometheorem}{Theorem}%
  {colback=white,colframe=red!50!black,fonttitle=\bfseries,
   description delimiters={\glqq}{\grqq},
   description font=\mdseries\itshape}{theo}
\begin{sometheorem}{My example}{}
My theorem text.
\end{sometheorem}
```

Theorem 16.10: *„My example“*

My theorem text.

`/tcb/description formatter=`⟨*macro*⟩ (default empty, initially empty)

Sets ⟨*macro*⟩ as formatter for the descriptive title text. The ⟨*macro*⟩ has to take one mandatory argument (the description text).

Note that `/tcb/description delimiters` → P. 344, `/tcb/description color` → P. 344, and `/tcb/description font` are ignored, if this option is used.

If `description formatter` is used without value, the formatter is reset to its standard behavior.

```
\newtcbox{\formbox}{enhanced,frame empty,size=minimal,boxsep=2pt,arc=1pt,
  on line,interior style image=goldshade.png}

\newtcbtheorem[use counter from=mytheo]{sometheorem}{Theorem}%
  {colback=white,colframe=red!50!black,fonttitle=\bfseries,
   description formatter=\formbox}{theo}
\begin{sometheorem}{My example}{}
My theorem text.
\end{sometheorem}
```

Theorem 16.11: My example

My theorem text.

`/tcb/terminator sign=`⟨*sign*⟩ (no default, initially empty)

The given ⟨*sign*⟩ is used as terminator at the end of the title text of a theorem.

```
\newtcbtheorem[use counter from=mytheo]{sometheorem}{Theorem}%
  {colback=white,colframe=red!50!black,fonttitle=\bfseries,
   terminator sign={.}}{theo}
\begin{sometheorem}{My example}{}
My theorem text.
\end{sometheorem}
```

Theorem 16.12: My example.

My theorem text.

/tcb/terminator sign colon (style, no value, initially set)

Sets /tcb/terminator sign → P. 345 to the colon : sign.

```
\newtcbtheorem[use counter from=mytheo]{sometheorem}{Theorem}%
  {colback=white,colframe=red!50!black,fonttitle=\bfseries,
   separator sign dash,terminator sign colon}{theo}
\begin{sometheorem}{My example}{}
My theorem text.
\end{sometheorem}
```

Theorem 16.13 – My example:

My theorem text.

/tcb/terminator sign dash (style, no value)

Sets /tcb/terminator sign → P. 345 to an en-dash sign.

```
\newtcbtheorem[use counter from=mytheo]{sometheorem}{Theorem}%
  {colback=white,colframe=red!50!black,fonttitle=\bfseries,
   terminator sign dash}{theo}
\begin{sometheorem}{My example}{}
My theorem text.
\end{sometheorem}
```

Theorem 16.14: My example –

My theorem text.

/tcb/terminator sign none (style, no value)

Sets /tcb/terminator sign → P. 345 to the default empty text.

N 2016-04-19 **/tcb/label separator=⟨*separator*⟩** (no default, initially :)

The given ⟨*separator*⟩ is used for labels created with environments which are defined themselves by \newtcbtheorem → P. 339. This ⟨*separator*⟩ is put between ⟨*prefix*⟩ (defined by \newtcbtheorem → P. 339) and ⟨*marker*⟩ (defined by an actual theorem environment).

```
\newtcbtheorem[use counter from=mytheo]{sometheorem}{Theorem}%
  {colback=white,colframe=red!50!black,fonttitle=\bfseries,
   label separator=*}{theo}
\begin{sometheorem}{My example}{myex}
My theorem text.
\end{sometheorem}
See Example~\ref{theo*myex}.
```

Theorem 16.15: My example

My theorem text.

See Example 16.15.

N 2018-01-12 **/tcb/theorem full label supplement**={⟨*style*⟩} (no default, initially empty)

The given ⟨*style*⟩ is used in connection with labels created with environments which are defined themselves by \newtcbtheorem → P. 339. This ⟨*style*⟩ uses one argument which is automatically set to the full label marker of the environment, i.e. a text consisting of ⟨*prefix*⟩ (defined by \newtcbtheorem → P. 339), /tcb/label separator → P. 346, and ⟨*marker*⟩ (defined by an actual theorem environment).

```
% The following adds a hyper target to all environments
% created with \newtcbtheorem
\tcbset{theorem full label supplement={hypertarget={#1}}}

\newtcbtheorem[use counter from=mytheo]{sometheorem}{Theorem}%
   {colback=white,colframe=red!50!black,fonttitle=\bfseries}{theo}
\begin{sometheorem}{My example}{myex2}
My theorem text.
\end{sometheorem}
This automated \hyperlink{theo:myex2}{hyper target can be linked to with a
 hyper link}.
```

Theorem 16.16: My example

My theorem text.

This automated hyper target can be linked to with a hyper link.

A second usage of /tcb/theorem full label supplement overwrites the first setting.

N 2018-01-12 **/tcb/theorem label supplement**={⟨*style*⟩} (no default, initially empty)

The given ⟨*style*⟩ is used in connection with labels created with environments which are defined themselves by \newtcbtheorem → P. 339. This ⟨*style*⟩ uses one argument which is automatically set to the label ⟨*marker*⟩ defined by an actual theorem environment.

A second usage of /tcb/theorem label supplement overwrites the first setting, but /tcb/theorem full label supplement and /tcb/theorem label supplement can be used independently.

```
% 'marginnote' has to be loaded
\newtcbtheorem[use counter from=mytheo]{sometheorem}{Theorem}%
   {colback=white,colframe=red!50!black,fonttitle=\bfseries,
    theorem label supplement={hypertarget={XYZ-##1}},
    theorem full label supplement={code={\marginnote{##1}}}
   }{theo}
\begin{sometheorem}{My example}{myex3}
My theorem text.
\end{sometheorem}
This automated \hyperlink{XYZ-myex3}{hyper target can be linked to with a
 hyper link}.
```

theo:myex3

Theorem 16.17: My example

My theorem text.

This automated hyper target can be linked to with a hyper link.

/tcb/theorem name and number (style, no value, initially set)

Prints theorem name followed by theorem number inside the title.

```
\newtcbtheorem[use counter from=mytheo]{sometheorem}{Theorem}%
  {colback=white,colframe=red!50!black,fonttitle=\bfseries,
   theorem name and number}{theo}
\begin{sometheorem}{My example}{}
My theorem text.
\end{sometheorem}
```

Theorem 16.18: My example

My theorem text.

/tcb/theorem number and name (style, no value)

Prints theorem number followed by theorem name inside the title.

```
\newtcbtheorem[use counter from=mytheo]{sometheorem}{Theorem}%
  {colback=white,colframe=red!50!black,fonttitle=\bfseries,
   theorem number and name}{theo}
\begin{sometheorem}{My example}{}
My theorem text.
\end{sometheorem}
```

16.19 Theorem: My example

My theorem text.

/tcb/theorem name (style, no value)

Prints theorem name without number inside the title.

```
\newtcbtheorem[use counter from=mytheo]{sometheorem}{Theorem}%
  {colback=white,colframe=red!50!black,fonttitle=\bfseries,
   theorem name,enhanced,watermark text={\thetcbcounter}}{theo}
\begin{sometheorem}{My example}{}
My theorem text.
\end{sometheorem}
```

Theorem: My example

My theorem text. 16.20

/tcb/theorem={⟨*display name*⟩}{⟨*counter*⟩}{⟨*title*⟩}{⟨*marker*⟩} (no default)

This key is internally used by \tcbmaketheorem → P. 340, but can be used directly in a tcolorbox for a more flexible approach. The ⟨*display name*⟩ is used together with the increased ⟨*counter*⟩ value and the ⟨*title*⟩ for the title line of the box. Additionally, a \label with the given ⟨*marker*⟩ is created.

```
% \newcounter{texercise}%  preamble
\begin{tcolorbox}[colback=green!10,colframe=green!50!black,arc=4mm,
                  theorem={Test}{texercise}{Direct usage}{myMarker}]
Here, we see the test \ref{myMarker}.
\end{tcolorbox}
```

Test 1: Direct usage

Here, we see the test 1.

For a common appearance inside the document, the key theorem should not be used directly as in the example above, but as part of a new environment created by hand or using \tcbmaketheorem → P. 340 or using its successor \newtcbtheorem → P. 339.

/tcb/highlight math (style, no value)

Predefined style which is used for \tcbhighmath → P. 341. It can be changed comfortable with /tcb/highlight math style.

/tcb/highlight math style=⟨*style definition*⟩ (style, no default)

Changes the definition for /tcb/highlight math to the given ⟨*style definition*⟩. See \tcbhighmath → P. 341 for another example.

```
% \tcbuselibrary{skins}
\tcbset{highlight math style={enhanced,%<-- needed for the 'remember' options
  colframe=red,colback=red!10!white,boxsep=0pt}}
\begin{align*}
\tcbhighmath[remember as=fx]{f(x)}
     &= \int\limits_{1}^{x} \frac{1}{t^2}~dt
      = \left[ -\frac{1}{t} \right]_{1}^{x}\\
     &= -\frac{1}{x} + \frac{1}{1}\\
     &=
\tcbhighmath[remember,overlay={%
    \draw[blue,very thick,->] (fx.south) to[bend right] ([yshift=2mm]frame.west);}]
  {1-\frac{1}{x}.}
\end{align*}
```

$$f(x) = \int_1^x \frac{1}{t^2}\,dt = \left[-\frac{1}{t}\right]_1^x$$
$$= -\frac{1}{x} + \frac{1}{1}$$
$$= 1 - \frac{1}{x}.$$

`/tcb/math upper` (style, no value)

Sets the upper part to mathematical mode with font `\displaystyle`.

`/tcb/math lower` (style, no value)

Sets the lower part to mathematical mode with font `\displaystyle`.

`/tcb/math` (style, no value)

Sets the upper part *and* lower part to mathematical mode with font `\displaystyle`.

```
\begin{tcolorbox}[math,colback=yellow!10!white,colframe=red!50!black]
  \sum\limits_{n=1}^{\infty} \frac{1}{n} = \infty.
\end{tcolorbox}
```

$$\sum_{n=1}^{\infty} \frac{1}{n} = \infty.$$

! The following styles are only tested to work with the original `amsmath` environments. If e.g. the `equation` environment is redefined as `gather`, then `/tcb/ams equation` should / could not be used. Obviously, you are encouraged to use `/tcb/ams gather` → P. 352 in this case.

U 2014-10-30 `/tcb/ams equation upper` (style, no value)

Adds an `amsmath` `equation` environment to the start and end of the upper part.

U 2014-10-30 `/tcb/ams equation lower` (style, no value)

Adds an `amsmath` `equation` environment to the start and end of the lower part.

U 2014-10-30 `/tcb/ams equation` (style, no value)

Adds an `amsmath` `equation` environment to the start and end of the upper *and* lower part.

```
\begin{tcolorbox}[ams equation,colback=yellow!10!white,colframe=red!50!black]
  \sum\limits_{n=1}^{\infty} \frac{1}{n} = \infty.
\end{tcolorbox}
```

$$\sum_{n=1}^{\infty} \frac{1}{n} = \infty. \tag{15}$$

U 2014-10-30 `/tcb/ams equation* upper` (style, no value)

Adds an `amsmath` `equation*` environment to the start and end of the upper part.

U 2014-10-30 `/tcb/ams equation* lower` (style, no value)

Adds an `amsmath` `equation*` environment to the start and end of the lower part.

U 2014-10-30 `/tcb/ams equation*` (style, no value)

Adds an `amsmath` `equation*` environment to the start and end of the upper *and* lower part.

```
\begin{tcolorbox}[ams equation*,colback=yellow!10!white,colframe=red!50!black]
  \sum\limits_{n=1}^{\infty} \frac{1}{n} = \infty.
\end{tcolorbox}
```

$$\sum_{n=1}^{\infty} \frac{1}{n} = \infty.$$

/tcb/ams align upper (style, no value)

Adds an `amsmath` `align` environment to the start and end of the upper part.

/tcb/ams align lower (style, no value)

Adds an `amsmath` `align` environment to the start and end of the lower part.

/tcb/ams align (style, no value)

Adds an `amsmath` `align` environment to the start and end of the upper *and* lower part.

```
\begin{tcolorbox}[ams align,colback=yellow!10!white,colframe=red!50!black]
  \sum\limits_{n=1}^{\infty} \frac{1}{n} &= \infty.\\
  \int x^2 ~\text{d}x                    &= \frac13 x^3 + c.
\end{tcolorbox}
```

$$\sum_{n=1}^{\infty} \frac{1}{n} = \infty. \tag{16}$$

$$\int x^2 \,\mathrm{d}x = \frac{1}{3}x^3 + c. \tag{17}$$

/tcb/ams align* upper (style, no value)

Adds an `amsmath` `align*` environment to the start and end of the upper part.

/tcb/ams align* lower (style, no value)

Adds an `amsmath` `align*` environment to the start and end of the lower part.

/tcb/ams align* (style, no value)

Adds an `amsmath` `align*` environment to the start and end of the upper *and* lower part.

```
\begin{tcolorbox}[ams align*,colback=yellow!10!white,colframe=red!50!black]
  \sum\limits_{n=1}^{\infty} \frac{1}{n} &= \infty.\\
  \int x^2 ~\text{d}x                    &= \frac13 x^3 + c.
\end{tcolorbox}
```

$$\sum_{n=1}^{\infty} \frac{1}{n} = \infty.$$

$$\int x^2 \,\mathrm{d}x = \frac{1}{3}x^3 + c.$$

/tcb/ams gather upper (style, no value)

Adds an amsmath gather environment to the start and end of the upper part.

/tcb/ams gather lower (style, no value)

Adds an amsmath gather environment to the start and end of the lower part.

/tcb/ams gather (style, no value)

Adds an amsmath gather environment to the start and end of the upper *and* lower part.

```
\begin{tcolorbox}[ams gather,colback=yellow!10!white,colframe=red!50!black]
  \sum\limits_{n=1}^{\infty} \frac{1}{n} = \infty.\\
  \int x^2 ~\text{d}x = \frac13 x^3 + c.
\end{tcolorbox}
```

$$\sum_{n=1}^{\infty} \frac{1}{n} = \infty. \tag{18}$$

$$\int x^2 \,\mathrm{d}x = \frac{1}{3}x^3 + c. \tag{19}$$

/tcb/ams gather* upper (style, no value)

Adds an amsmath gather* environment to the start and end of the upper part.

/tcb/ams gather* lower (style, no value)

Adds an amsmath gather* environment to the start and end of the lower part.

/tcb/ams gather* (style, no value)

Adds an amsmath gather* environment to the start and end of the upper *and* lower part.

```
\begin{tcolorbox}[ams gather*,colback=yellow!10!white,colframe=red!50!black]
  \sum\limits_{n=1}^{\infty} \frac{1}{n} = \infty.\\
  \int x^2 ~\text{d}x = \frac13 x^3 + c.
\end{tcolorbox}
```

$$\sum_{n=1}^{\infty} \frac{1}{n} = \infty.$$

$$\int x^2 \,\mathrm{d}x = \frac{1}{3}x^3 + c.$$

`/tcb/ams nodisplayskip upper` (style, no value)

Neutralizes the `\abovedisplayskip` of a following `align` or `gather` environment for the upper part. Note that the text content has to start with such a formula.

`/tcb/ams nodisplayskip lower` (style, no value)

Neutralizes the `\abovedisplayskip` of a following `align` or `gather` environment for the lower part. Note that the text content has to start with such a formula.

`/tcb/ams nodisplayskip` (style, no value)

Neutralizes the `\abovedisplayskip` of a following `align` or `gather` environment for the upper part *and* lower part. Note that the text content has to start with such a formula.

```
\begin{tcolorbox}[ams nodisplayskip,colback=yellow!10!white,colframe=red!50!black]
  \begin{gather}
  \sum\limits_{n=1}^{\infty} \frac{1}{n} = \infty.\\
  \int x^2 ~\text{d}x = \frac13 x^3 + c.
  \end{gather}
  And now for something completely different.
\end{tcolorbox}
```

$$\sum_{n=1}^{\infty} \frac{1}{n} = \infty. \tag{20}$$

$$\int x^2 \,\mathrm{d}x = \frac{1}{3}x^3 + c. \tag{21}$$

And now for something completely different.

New colored mathematical environments are easily created using `\newtcolorbox` → P. 15:

```
\newtcolorbox{mymath}{ams gather*,colback=yellow!10!white,colframe=red!50!black}

\begin{mymath}
  \sum\limits_{n=1}^{\infty} \frac{1}{n} = \infty.\\
  \int x^2 ~\text{d}x = \frac13 x^3 + c.
\end{mymath}
```

$$\sum_{n=1}^{\infty} \frac{1}{n} = \infty.$$

$$\int x^2 \,\mathrm{d}x = \frac{1}{3}x^3 + c.$$

! All described options like `/tcb/ams gather upper` → P. 352, `/tcb/ams gather lower` → P. 352, `/tcb/ams gather` → P. 352 are (partially) setting (overwritting) the keys `/tcb/before upper` → P. 65, `/tcb/after upper` → P. 65, `/tcb/before lower` → P. 66, `/tcb/after lower` → P. 66.
Therefore, e. g. `\tcbset{ams gather,before upper={\text{Pythagoras:}}}` produces an invalid result. For this case, you are invited to use
`\tcbset{ams gather,before upper app={\text{Pythagoras:}}}`,
see `/tcb/before upper app` → P. 423.

`/tcb/theorem style=`⟨*name*⟩ (no default, initially `standard`)

Applies a predefined style ⟨*name*⟩ to the theorem environment. Some of the feasible ⟨*name*⟩ values resemble style names from the packages `theorem` and `ntheorem` to give convenient access to known patterns.



The styles alter `/tcb/separator sign` → P. 343, `/tcb/description delimiters` → P. 344, `/tcb/terminator sign` → P. 345, and more. Therefore, one should apply such keys *after* a theorem style.

For the following examples, we use:

Definition in the preamble:

```
\newtcbtheorem[use counter from=mytheo]{theorem}{Theorem}{%
  fonttitle=\bfseries\upshape,fontupper=\itshape,
  colframe=green!50!black,colback=green!10!white,
  colbacktitle=green!20!white,coltitle=blue!75!black}{theo}
```

The predefined styles are:

- `standard`: This is the initial value.

```
\begin{theorem}[theorem style=standard]{standard}{}
This is my theorem. \begin{equation*} a^2 + b^2 = c^2. \end{equation*}
\end{theorem}
```

Theorem 16.21: standard

This is my theorem.

$$a^2 + b^2 = c^2.$$

- `change standard`

```
\begin{theorem}[theorem style=change standard]{change standard}{}
This is my theorem. \begin{equation*} a^2 + b^2 = c^2. \end{equation*}
\end{theorem}
```

16.22 Theorem: change standard

This is my theorem.

$$a^2 + b^2 = c^2.$$

- `plain`

```
\begin{theorem}[theorem style=plain]{plain}{}
This is my theorem. \begin{equation*} a^2 + b^2 = c^2. \end{equation*}
\end{theorem}
```

Theorem 16.23 (plain): *This is my theorem.*

$$a^2 + b^2 = c^2.$$

- break

```
\begin{theorem}[theorem style=break]{break}{}
This is my theorem. \begin{equation*} a^2 + b^2 = c^2. \end{equation*}
\end{theorem}
```

Theorem 16.24 (break):
This is my theorem.

$$a^2 + b^2 = c^2.$$

- plain apart

```
\begin{theorem}[theorem style=plain apart]{plain apart}{}
This is my theorem. \begin{equation*} a^2 + b^2 = c^2. \end{equation*}
\end{theorem}
```

Theorem 16.25 (plain apart)

This is my theorem.

$$a^2 + b^2 = c^2.$$

- change

```
\begin{theorem}[theorem style=change]{change}{}
This is my theorem. \begin{equation*} a^2 + b^2 = c^2. \end{equation*}
\end{theorem}
```

16.26 Theorem (change): *This is my theorem.*

$$a^2 + b^2 = c^2.$$

- change break

```
\begin{theorem}[theorem style=change break]{change break}{}
This is my theorem. \begin{equation*} a^2 + b^2 = c^2. \end{equation*}
\end{theorem}
```

16.27 Theorem (change break):
This is my theorem.

$$a^2 + b^2 = c^2.$$

- change apart

```
\begin{theorem}[theorem style=change apart]{change apart}{}
This is my theorem. \begin{equation*} a^2 + b^2 = c^2. \end{equation*}
\end{theorem}
```

16.28 Theorem (change apart)

This is my theorem.

$$a^2 + b^2 = c^2.$$

- margin

```
\begin{theorem}[theorem style=margin,left=10mm]{margin}{}
This is my theorem. \begin{equation*} a^2 + b^2 = c^2. \end{equation*}
\end{theorem}
\begin{theorem}[theorem style=margin,left=10mm,oversize]{margin}{}
This is my theorem. \begin{equation*} a^2 + b^2 = c^2. \end{equation*}
\end{theorem}
```

16.29 Theorem (margin): *This is my theorem.*

$$a^2 + b^2 = c^2.$$

16.30 Theorem (margin): *This is my theorem.*

$$a^2 + b^2 = c^2.$$

- margin break

```
\begin{theorem}[theorem style=margin break,left=10mm]{margin break}{}
This is my theorem. \begin{equation*} a^2 + b^2 = c^2. \end{equation*}
\end{theorem}
\begin{theorem}[theorem style=margin break,left=10mm,oversize]{margin break}{}
This is my theorem. \begin{equation*} a^2 + b^2 = c^2. \end{equation*}
\end{theorem}
```

16.31 Theorem (margin break):
This is my theorem.

$$a^2 + b^2 = c^2.$$

16.32 Theorem (margin break):
This is my theorem.

$$a^2 + b^2 = c^2.$$

- margin apart

```
\begin{theorem}[theorem style=margin apart,left=10mm]{margin apart}{}
This is my theorem. \begin{equation*} a^2 + b^2 = c^2. \end{equation*}
\end{theorem}
\begin{theorem}[theorem style=margin apart,left=10mm,oversize]{margin apart}{}
This is my theorem. \begin{equation*} a^2 + b^2 = c^2. \end{equation*}
\end{theorem}
```

16.33 Theorem (margin apart)

This is my theorem.

$$a^2 + b^2 = c^2.$$

16.34 Theorem (margin apart)

This is my theorem.

$$a^2 + b^2 = c^2.$$

16.3 Examples for Definitions and Theorems

In the following, the application of \tcbmaketheorem → P. 340 to highlight mathematical definitions, theorems, or the like is demonstrated.

At first, additional tcb keys are created for the appearance of the colored boxes. It is assumed that theorems and corollaries should be identically colored. All following environments are numbered with a common counter, but this can be changed easily. Here, the counter output is supplemented by the subsection number. Further, the cleveref package [5] is used for clever references.

Definition in the preamble:

```
% \usepackage{cleveref}
\tcbset{
  defstyle/.style={fonttitle=\bfseries\upshape, fontupper=\slshape,
              arc=0mm, colback=blue!5!white,colframe=blue!75!black},
  theostyle/.style={fonttitle=\bfseries\upshape, fontupper=\slshape,
               colback=red!10!white,colframe=red!75!black},
}
\newtcbtheorem[number within=subsection,crefname={definition}{definitions}]%
  {Definition}{Definition}{defstyle}{def}
\newtcbtheorem[use counter from=Definition,crefname={theorem}{theorems}]%
  {Theorem}{Theorem}{theostyle}{theo}
\newtcbtheorem[use counter from=Definition,crefname={corollary}{corollaries}]%
  {Corollary}{Corollary}{theostyle}{cor}
```

By \newtcbtheorem → P. 339, commonly numbered theorem environments are created now. defstyle and theostyle are used for the appearance.

Now, everything is prepared for the following examples.

```
The following theorem is numbered as \Cref{theo:diffbarstetig} and
referenced with the marker \texttt{theo:diffbarstetig}.\bigskip

\begin{Theorem}{Differenzierbarkeit bedingt Stetigkeit, wobei diese Benennung
  zu Testzwecken ungew\"{o}hnlich lang ist}{diffbarstetig}%
  Eine Funktion $f:I\to\mathbb{R}$ ist in $x_0\in I$ stetig, wenn $f$ in
  $x_0$ differenzierbar ist.
\end{Theorem}
```

The following theorem is numbered as Theorem 16.3.1 and referenced with the marker theo:diffbarstetig.

Theorem 16.3.1: Differenzierbarkeit bedingt Stetigkeit, wobei diese Benennung zu Testzwecken ungewöhnlich lang ist

Eine Funktion $f : I \to \mathbb{R}$ ist in $x_0 \in I$ stetig, wenn f in x_0 differenzierbar ist.

```
The following definition is numbered as \Cref{def:diffbarkeit} and
referenced with the marker \texttt{def:diffbarkeit}.\bigskip

\begin{Definition}{Differenzierbarkeit}{diffbarkeit}
  Eine Funktion $f:~I\to\mathbb{R}$ auf einem Intervall $I$ hei\ss{}t in
  $x_0\in I$ differenzierbar oder linear approximierbar,
  wenn der Grenzwert
  \begin{equation*}
  \lim\limits_{x\to x_0}\frac{f(x)-f(x_0)}{x-x_0}=
  \lim\limits_{h\to 0}\frac{f(x_0+h)-f(x_0)}{h}
  \end{equation*}
  existiert. Bei Existenz hei\ss{}t dieser Grenzwert Ableitung
  oder Differentialquotient von $f$ in $x_0$ und man
  schreibt f\"{u}r ihn
  \begin{equation*}
  f'(x_0)\quad\text{oder}\quad\frac{df}{dx}(x_0).
  \end{equation*}
\end{Definition}
```

The following definition is numbered as Definition 16.3.2 and referenced with the marker `def:diffbarkeit`.

Definition 16.3.2: Differenzierbarkeit

Eine Funktion $f: I \to \mathbb{R}$ *auf einem Intervall* I *heißt in* $x_0 \in I$ *differenzierbar oder linear approximierbar, wenn der Grenzwert*

$$\lim_{x\to x_0} \frac{f(x)-f(x_0)}{x-x_0} = \lim_{h\to 0} \frac{f(x_0+h)-f(x_0)}{h}$$

existiert. Bei Existenz heißt dieser Grenzwert Ableitung oder Differentialquotient von f *in* x_0 *und man schreibt für ihn*

$$f'(x_0) \quad \text{oder} \quad \frac{df}{dx}(x_0).$$

```
The following corollary is numbered as \Cref{cor:nullstellen} and
referenced with the marker \texttt{cor:nullstellen}.\bigskip

\begin{Corollary}{Nullstellenexistenz}{nullstellen}
  Ist $f:[a,b]\to\mathbb{R}$ stetig und haben $f(a)$ und $f(b)$ entgegengesetzte
  Vorzeichen, also $f(a)f(b)<0$, so besitzt $f$ eine Nullstelle $x_0\in]a,b[$,
  also $f(x_0)=0$.
\end{Corollary}
```

The following corollary is numbered as Corollary 16.3.3 and referenced with the marker `cor:nullstellen`.

Corollary 16.3.3: Nullstellenexistenz

Ist $f:[a,b]\to\mathbb{R}$ *stetig und haben* $f(a)$ *und* $f(b)$ *entgegengesetzte Vorzeichen, also* $f(a)f(b)<0$*, so besitzt* f *eine Nullstelle* $x_0 \in]a,b[$*, also* $f(x_0)=0$.

```
\begin{Theorem}[boxrule=2mm,toptitle=-1.5mm,bottomtitle=-1.5mm]{%
    Hinreichende Bedingung f\"{u}r Wendepunkte}{wendehinreichend}%
  $f$ sei eine auf einem Intervall $]a,b[$ dreimal stetig differenzierbare Funktion.
  Ist $f''(x_0)=0$ in $x_0\in]a,b[$ und $f'''(x_0)\ne 0$, so ist
  $(x_0,f(x_0))$ ein Wendepunkt von $f$.
\end{Theorem}
```

Theorem 16.3.4: Hinreichende Bedingung für Wendepunkte

f sei eine auf einem Intervall $]a,b[$ dreimal stetig differenzierbare Funktion. Ist $f''(x_0)=0$ in $x_0\in]a,b[$ und $f'''(x_0)\neq 0$, so ist $(x_0,f(x_0))$ ein Wendepunkt von f.

```
% \usepackage{varioref}
% \usepackage{cleveref}
% \tcbuselibrary{skins}
\newtcbtheorem[use counter from=Definition]{YetAnotherTheorem}{Theorem}%
  {theorem style=plain apart,label type=theorem,enhanced,frame hidden,
  boxrule=2mm,titlerule=0mm,toptitle=1mm,bottomtitle=1mm,
  fonttitle=\bfseries\large,fontupper=\normalsize,
  coltitle=green!35!black,colbacktitle=green!15!white,
  colback=green!50!yellow!15!white,borderline={1pt}{0pt}{green!25!blue},
  }{theo}

\begin{YetAnotherTheorem}{Mittelwertsatz f\"{u}r $n$ Variable}{meanvaluetheorem}%
  Es sei $n\in\mathbb{N}$, $D\subseteq\mathbb{R}^n$ eine offene Menge und
  $f\in C^{1}(D,\mathbb{R})$. Dann gibt es auf jeder Strecke
  $[x_0,x]\subset D$ einen Punkt $\xi\in[x_0,x]$, so dass gilt
  \begin{equation*}
  f(x)-f(x_0) = \operatorname{grad} f(\xi)^{\top}(x-x_0)
  \end{equation*}
\end{YetAnotherTheorem}

\medskip
Here, |cleveref| support is used to reference \Cref{theo:meanvaluetheorem}
on \Cpageref{theo:meanvaluetheorem}. This \namecref{theo:meanvaluetheorem}
can also be referenced by |\Vref| resulting in \Vref{theo:meanvaluetheorem}.
```

Theorem 16.3.5 (Mittelwertsatz für n Variable)

Es sei $n \in \mathbb{N}$, $D \subseteq \mathbb{R}^n$ eine offene Menge und $f \in C^1(D, \mathbb{R})$. Dann gibt es auf jeder Strecke $[x_0, x] \subset D$ einen Punkt $\xi \in [x_0, x]$, so dass gilt

$$f(x) - f(x_0) = \operatorname{grad} f(\xi)^\top (x - x_0)$$

Here, `cleveref` support is used to reference Theorem 16.3.5 on Page 359. This theorem can also be referenced by `\Vref` resulting in Theorem 16.3.5.

Note that `/tcb/label type` → P. 98 was used in the example above to feed `cleveref` [5] with the needed name information.

```
Here, using |\Vref| resulting in \Vref{theo:meanvaluetheorem} is more interesting\ldots
```

Here, using \Vref resulting in Theorem 16.3.5 on the preceding page is more interesting...

```
% \tcbuselibrary{skins}
\newtcbtheorem[use counter from=Definition]{YetAnotherTheorem}{Theorem}%
  {theorem style=change apart,enhanced,arc=0mm,outer arc=0mm,
  boxrule=0mm,toprule=1mm,bottomrule=1mm,left=1mm,right=1mm,
  titlerule=0mm,toptitle=0mm,bottomtitle=1mm,top=0mm,
  colframe=red!50!black,colback=red!5!white,coltitle=red!50!black,
  title style={top color=yellow!50!white,bottom color=red!5!white,
    middle color=yellow!50!white},
  fonttitle=\bfseries\sffamily\normalsize,fontupper=\normalsize\itshape,
  }{theo}

\begin{YetAnotherTheorem}{Mittelwertsatz f\"{u}r $n$ Variable}{mittelwertsatz_n2}%
  Es sei $n\in\mathbb{N}$, $D\subseteq\mathbb{R}^n$ eine offene Menge und
  $f\in C^{1}(D,\mathbb{R})$. Dann gibt es auf jeder Strecke
  $[x_0,x]\subset D$ einen Punkt $\xi\in[x_0,x]$, so dass gilt
  \begin{equation*}
  f(x)-f(x_0) = \operatorname{grad} f(\xi)^{\top}(x-x_0)
  \end{equation*}
\end{YetAnotherTheorem}
```

16.3.6 Theorem (Mittelwertsatz für n Variable)

Es sei $n \in \mathbb{N}$, $D \subseteq \mathbb{R}^n$ eine offene Menge und $f \in C^1(D, \mathbb{R})$. Dann gibt es auf jeder Strecke $[x_0, x] \subset D$ einen Punkt $\xi \in [x_0, x]$, so dass gilt

$$f(x) - f(x_0) = \operatorname{grad} f(\xi)^\top (x - x_0)$$

```
% \usepackage{varwidth}   \tcbuselibrary{skins}
\newtcbtheorem[use counter from=Definition]{YetAnotherTheorem}{Theorem}%
{enhanced,frame empty,interior empty,colframe=ForestGreen!50!white,
  coltitle=ForestGreen!50!black,fonttitle=\bfseries,colbacktitle=ForestGreen!15!white,
  borderline={0.5mm}{0mm}{ForestGreen!15!white},
  borderline={0.5mm}{0mm}{ForestGreen!50!white,dashed},
  attach boxed title to top center={yshift=-2mm},
  boxed title style={boxrule=0.4pt},varwidth boxed title}{theo}

\begin{YetAnotherTheorem}{Mittelwertsatz f\"{u}r $n$ Variable}{mittelwertsatz_n3}%
  Es sei $n\in\mathbb{N}$, $D\subseteq\mathbb{R}^n$ eine offene Menge und
  $f\in C^{1}(D,\mathbb{R})$. Dann gibt es auf jeder Strecke
  $[x_0,x]\subset D$ einen Punkt $\xi\in[x_0,x]$, so dass gilt
  \begin{equation*}
  f(x)-f(x_0) = \operatorname{grad} f(\xi)^{\top}(x-x_0)
  \end{equation*}
\end{YetAnotherTheorem}
```

Theorem 16.3.7: Mittelwertsatz für n Variable

Es sei $n \in \mathbb{N}$, $D \subseteq \mathbb{R}^n$ eine offene Menge und $f \in C^1(D, \mathbb{R})$. Dann gibt es auf jeder Strecke $[x_0, x] \subset D$ einen Punkt $\xi \in [x_0, x]$, so dass gilt

$$f(x) - f(x_0) = \operatorname{grad} f(\xi)^\top (x - x_0)$$

You need more attention for your theorems? Here, you are ...

```
% tcbuselibrary{skins}  % preamble
\begin{Theorem}[enhanced,
    fuzzy halo=3mm with yellow,
    fuzzy halo=2mm with red,
    fuzzy halo=1mm with yellow,
    watermark color=red!35!white,
    watermark text={Overacting\\Fundamental Theorem}]%
  {Fundamental Theorem of Theorems}{fundamental}%
  \lipsum[1-2]
\end{Theorem}
```

Theorem 16.3.8: Fundamental Theorem of Theorems

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.
Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Overacting
Fundamental Theorem

Let's try a more conservative approach:

```
% \tcbuselibrary{skins}
\newtcbtheorem[use counter from=Definition]{YetAnotherTheorem}{Theorem}%
  {theorem style=plain,enhanced,colframe=blue!50!black,colback=yellow!20!white,
   coltitle=red!50!black,fonttitle=\upshape\bfseries,fontupper=\itshape,
   drop fuzzy shadow=blue!50!black!50!white,boxrule=0.4pt}{theo}

\begin{YetAnotherTheorem}{Mittelwertsatz f\"{u}r $n$ Variable}{mittelwertsatz_n4}%
  Es sei $n\in\mathbb{N}$, $D\subseteq\mathbb{R}^n$ eine offene Menge und
  $f\in C^{1}(D,\mathbb{R})$. Dann gibt es auf jeder Strecke
  $[x_0,x]\subset D$ einen Punkt $\xi\in[x_0,x]$, so dass gilt
  \begin{equation*}
  f(x)-f(x_0) = \operatorname{grad} f(\xi)^{\top}(x-x_0)
  \end{equation*}
\end{YetAnotherTheorem}
```

Theorem 16.3.9 (Mittelwertsatz für n Variable): *Es sei $n \in \mathbb{N}$, $D \subseteq \mathbb{R}^n$ eine offene Menge und $f \in C^1(D, \mathbb{R})$. Dann gibt es auf jeder Strecke $[x_0, x] \subset D$ einen Punkt $\xi \in [x_0, x]$, so dass gilt*

$$f(x) - f(x_0) = \operatorname{grad} f(\xi)^\top (x - x_0)$$

16.4 Using other theorem environments with `tcolorbox`

Instead of creating theorem environments with the methods described before, environments from other packages can be boxed with a `tcolorbox`.

Environments may be created e.g. by methods from the `theorem` package or the `amsthm` package. `\tcolorboxenvironment` → P. 17 can be used to put a box around these environments.

Definition in the preamble:

```
\usepackage{amsthm}

\theoremstyle{plain}%    from 'amsthm'
\newtheorem{lem}{Lemma}% from 'amsthm'

\tcolorboxenvironment{lem}{
  enhanced jigsaw,colframe=cyan,interior hidden,
  breakable,before skip=10pt,after skip=10pt }

\tcolorboxenvironment{proof}{% 'proof' from 'amsthm'
  blanker,breakable,left=5mm,
  before skip=10pt,after skip=10pt,
  borderline west={1mm}{0pt}{red}}
```

```
\begin{lem}
  \lipsum[2]
\end{lem}

\lipsum[3]

\begin{proof}
  \lipsum*[4]
\end{proof}
```

Lemma 1. *Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.*

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

Proof. Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula. □

17 Library LIB breakable

The library is loaded by a package option or inside the preamble by:

```
\tcbuselibrary{breakable}
```

17.1 Technical Overview

The library LIB breakable supports the automatic breaking of a `tcolorbox`. This feature is enabled by `/tcb/breakable` → P. 365 and disabled by `/tcb/unbreakable` → P. 366.

If a `tcolorbox` is set to be `/tcb/breakable` → P. 365, then the following algorithm is executed:

1. The box content is read to a box register similar but not identical to the unbreakable case.
2. If the total box fits into the current page, it is shipped out visibly unbroken and the algorithm stops.

   Unbroken Box

   The box. unbroken

3. Otherwise, it is checked if at least `/tcb/lines before break` → P. 366 of the upper box can be placed on the current page. If not, a page break is inserted and the algorithm goes back to Step 2.
4. Now, the *break sequence* starts. The upper box part or the lower box part is split such that it fits into the current page. The fitting part is named *first part* of the *break sequence* and shipped out.

   Broken Box

   The box. first

5. If the remaining content of the total box fits into the current page, the algorithm continues with Step 7, else with Step 6.
6. The upper box part or the lower box part is split such that it fits into the current page. The fitting part is named *middle part* of the *break sequence* and shipped out. Then, the algorithm goes back to Step 5.

   The box. middle

7. The remaining part is named *last part* of the *break sequence* and shipped out. The algorithm stops.

   The box. last

The algorithm takes care that the optional segmentation line never appears at the end of a box. The optional lower box part is also checked to have at least `/tcb/lines before break` → P. 366.

In principle, all boxes of the *break sequence* share the same geometric parameters. The differences are:

- The given /tcb/before → P. 78 and /tcb/after → P. 78 values are used only before the *first* and after the *last* part of the *break sequence*.
- A special behavior between the parts of the *break sequence* can be given by /tcb/toprule at break → P. 369, /tcb/bottomrule at break → P. 369, /tcb/enlarge top at break by → P. 83, and /tcb/enlarge bottom at break by → P. 83.
- The /tcb/skin → P. 134 decides *how* the *first*, *middle*, and *last* part look like. Actually, every part type has its own skin given by the options /tcb/skin first → P. 134, /tcb/skin middle → P. 134, and /tcb/skin last → P. 134. Typically, these options are set automatically by the main skin, see Subsection 17.8 from page 377.

17.2 Limitations and Known Bugs

- The maximal total height of the upper and of the lower part of normal breakable tcolorboxes is about 65536pt (ca. 2300cm) apiece. If such a part gets longer, the output will get buggy without warning. For very oversized boxes which are longer than 65536pt, use the unlimited value for /tcb/breakable → P. 365. With the unlimited setting, the applied algorithm has (virtually) no height limit for boxes, but very likely the compiler memory will have to be increased for boxes longer than 300 pages (depending on compiler settings and box content). But it is recommended to use unlimited for critical large boxes only.
- You can nest an unbreakable tcolorbox inside another tcolorbox, even inside a breakable one. But you cannot not nest a breakable box inside a breakable box. The /tcb/breakable → P. 365 key for a nested box is ignored automatically[3], i. e. inner boxes are always unbreakable.

  After all, in the unlikely case you really want to have the nested box to be breakable, use /tcb/enforce breakable → P. 366 for the nested box[4]. **But, a breakable box inside a breakable box will usually give a mess.**
- If your text content contains some text color changing commands, your color will not survive the break to the next box. But, with the fontspec package and xelatex or lualatex, you can use \addfontfeatures{Color=mycolor} to add a font color which survives the break.

N 2014-10-30
- The perpage option of the footmisc package is deliberately deactivated inside a breakable box since all footnotes are placed at the end of the box (possibly far away from the reference point).

N 2016-02-15
- Making a box /tcb/breakable → P. 365 which actually is not broken creates a box which acts *almost* like an unbreakable box. Visual differences are kept as indiscernible as possible, but can appear with certain /tcb/before → P. 78 and /tcb/after → P. 78 settings, especially, if there is an automatic page break before the box.

N 2016-05-25
- LuaTEX version 0.95 changes the behaviour of the basic \vsplit (a bug?!) resulting in badly broken boxes. Thanks to Jeremy Engel, the LIB breakable library contains a patch for this which also loads the the ifluatex package.

[3] Until tcolorbox 3.04, the /tcb/breakable → P. 365 key was not ignored for nested boxes.
[4] /tcb/enforce breakable → P. 366 acts like /tcb/breakable → P. 365 until tcolorbox 3.04.

17.3 Main Option Keys

U 2017-02-01 `/tcb/breakable=true|false|unlimited` (default `true`, initially `false`)

Allows the `tcolorbox` to be breakable. If the box is larger than the available space at the current page, the box is automatically broken and continued to the next next page. All sorts of `tcolorbox` can be made breakable. It depends on the skin how the breaking looks like. If you do not know better, use `/tcb/enhanced` → P. 206 for breaking a box. The parts of the *break sequence* are numbered by the counter `tcbbreakpart`.

- `false`: Sets the `tcolorbox` to be unbreakable.
- `true`: Breaks the `tcolorbox` from one page to another. The maximal total height of the upper and of the lower part is about 65536pt (ca. 2300cm or ca. 90 pages) apiece.
- `unlimited`: Experimental code for unlimited total height of breakable boxes. For boxes longer than 300 pages (or even shorter ones) the compiler memory will have to be increased.

```
% \usepackage{lipsum}  % preamble
\tcbset{enhanced jigsaw,colback=red!5!white,colframe=red!75!black,
  watermark color=yellow!25!white,watermark text=\arabic{tcbbreakpart},
  fonttitle=\bfseries}

\begin{tcolorbox}[breakable,title=My breakable box]
\lipsum[1-6]
\end{tcolorbox}
```

My breakable box

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. In hac habitasse platea

dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.
Fusce mauris. Vestibulum luctus nibh at lectus. Sed bibendum, nulla a faucibus semper, leo velit ultricies tellus, ac venenatis arcu wisi vel nisl. Vestibulum diam. Aliquam pellentesque, augue quis sagittis posuere, turpis lacus congue quam, in hendrerit risus eros eget felis. Maecenas eget erat in sapien mattis porttitor. Vestibulum porttitor. Nulla facilisi. Sed a turpis eu lacus commodo facilisis. Morbi fringilla, wisi in dignissim interdum, justo lectus sagittis dui, et vehicula libero dui cursus dui. Mauris tempor ligula sed lacus. Duis cursus enim ut augue. Cras ac magna. Cras nulla. Nulla egestas. Curabitur a leo. Quisque egestas wisi eget nunc. Nam feugiat lacus vel est. Curabitur consectetuer.
Suspendisse vel felis. Ut lorem lorem, interdum eu, tincidunt sit amet, laoreet vitae, arcu. Aenean faucibus pede eu ante. Praesent enim elit, rutrum at, molestie non, nonummy vel, nisl. Ut lectus eros, malesuada sit amet, fermentum eu, sodales cursus, magna. Donec eu purus. Quisque vehicula, urna sed ultricies auctor, pede lorem egestas dui, et convallis elit erat sed nulla. Donec luctus. Curabitur et nunc. Aliquam dolor odio, commodo pretium, ultricies non, pharetra in, velit. Integer arcu est, nonummy in, fermentum faucibus, egestas vel, odio.

`/tcb/unbreakable` (no value, initially set)

Sets the `tcolorbox` to be unbreakable.

`/tcb/enforce breakable` (no value)

A `tcolorbox` inside a `tcolorbox` is automatically set to be unbreakable. Using `/tcb/breakable` → P. 365 on such an inner box has no effect. If one *really* wants the inner box to be breakable, use `/tcb/enforce breakable`. **This will usually give a mess of shattered boxes. You are advised to not use this option.**

Note that `/tcb/enforce breakable` has the functionality that `/tcb/breakable` → P. 365 had until package version 3.04 and exists for backward compatibility.

`/tcb/title after break=`⟨*text*⟩ (no default, initially empty)

The `/tcb/title` → P. 18 is used only for the *first* part of a *break sequence*. Use `title after break` to create a heading line with ⟨*text*⟩ as content for all following parts.

`/tcb/notitle after break` (no value, initially set)

Removes the title line or following parts in a *break sequence* if set before.

`/tcb/adjusted title after break=`⟨*text*⟩ (style, no default, initially unset)

Works like `/tcb/adjusted title` → P. 18 but applied to `/tcb/title after break`.

`/tcb/lines before break=`⟨*number*⟩ (no default, initially 2)

Assures that the given ⟨*number*⟩ of lines of the upper box part or the lower box part are placed before a break happens.

U 2017-07-05 **/tcb/break at=⟨*length*⟩/⟨*length*⟩/.../⟨*length*⟩** (no default, initially `0pt`)

Defines break points at the given ⟨*length*⟩ values. The first ⟨*length*⟩ defines the (maximal) height of the first partial box, the second ⟨*length*⟩ defines the (maximal) height of the second partial box, and so on. The last ⟨*length*⟩ value is applied to all following partial boxes if any.

- Setting a ⟨*length*⟩ to `0pt` means that the naturally available space is used for breaking.
- Setting a ⟨*length*⟩ to a negative value means that the sum of this negative value and the naturally available space is used for breaking (boxes will shrink in height). That that before version 4.10 negative values were treated like `0pt`.

```
% \usepackage{multicol,lipsum}
\begin{multicols}{3}\footnotesize
Breakable boxes inside a |multicols| environment need special attendance.
They are broken by default at |\textheight|.
The |break at| option can be used to insert better break points by hand.
\begin{tcolorbox}[enhanced jigsaw,size=small,vfill before first,
  colframe=red,colback=yellow!10!white,before title=\raggedright,
  title={Broken box inside a |multicols| environment},fonttitle=\bfseries,
  enforce breakable,% use only breakable in the real world!
  pad at break=1mm,break at=3cm/6.3cm ]
\lipsum[1]
\end{tcolorbox}
\refKey{/tcb/height fixed for} may also be considered for |multicols| environments.
\end{multicols}
```

Breakable boxes inside a `multicols` environment need special attendance. They are broken by default at `\textheight`. The `break at` option can be used to insert better break points by hand.

Broken box inside a `multicols` environment

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

`/tcb/height fixed for` → P. 370 may also be considered for `multicols` environments.

/tcb/enlargepage=⟨*length*⟩/⟨*length*⟩/.../⟨*length*⟩ (no default, initially `0pt`)

Inserts a `\enlargethispage{`⟨*length*⟩`}` to the pages of the break sequence, i. e. allows one to enlarge (or shrink) partial boxes. The first ⟨*length*⟩ is applied to the first partial box, the second ⟨*length*⟩ is applied to the second partial box, and so on. The last ⟨*length*⟩ value is applied to all following partial boxes if any. Note that floating boxes will not be enlarged.

```
\begin{tcolorbox}[breakable,enlargepage=0mm/\baselineskip/2\baselineskip/0mm,...
```

The example code enlarged the second partial box by one line, the third partial box by two lines, and all following parts are not enlarged.



If an automated page break occures before the first partial box, the page enlargement is applied to the page before the first partial box *and* again to the page of the first partial box. Insert a manual break to prevent this.
In general, `enlargepage` should be used at the final stage of a document for fine-tuning only.

`/tcb/enlargepage flexible=`⟨*length*⟩ (no default, initially `0pt`)

This allows an automated page enlargement for up to ⟨*length*⟩. The algorithm can use this to avoid breaking a box, if there is anough room after enlargement. Also, the *last* partial box of a break sequence may be enlarged to avoid further breaking.

Note that this potential enlargement is *additive* to settings of `/tcb/enlargepage` → P. 367. But `/tcb/enlargepage flexible` overwrites settings of `/tcb/pad before break*` → P. 369 or `/tcb/pad at break*` → P. 369.

```
% The following setting hinders orphan lines for the last partial box
\tcbset{enlargepage flexible=\baselineskip}
```

N 2014-12-15 `/tcb/compress page=`⟨*option*⟩ (default `all`, initially `baselineskip`)

This option controls the space management on the page which contains the unbroken box or the first part of a *break sequence*. Feasible ⟨*option*⟩ values are:

- `all` (default value): All shrinkable glue on the page is potentially used for the unbroken box or the first part of a *break sequence*. Thus, all vertical spaces on the page will potentially be reduced to their minimal values.
- `baselineskip` (initial value): Shrinkable glue up to one `\baselineskip` on the page is potentially used for the unbroken box or the first part of a *break sequence*.
- `none`: The break algorithm respects the target size of the given glue values on the page. This was the inital value before version `3.34`.

`/tcb/shrink break goal=`⟨*length*⟩ (no default, initially `0pt`)

This is an emergency parameter if the break algorithm produces unpleasant breaks. It shrinks the goal height of the current box part by ⟨*length*⟩ which may result in smaller boxes. Never use negative values. *Usually, this option will never be needed at all.*

17.4 Option Keys for the Break Appearance

/tcb/toprule at break=⟨*length*⟩ (no default, initially `0.5mm`)
Sets the line width of the top rule to ⟨*length*⟩ *if* the box is /tcb/breakable → P. 365. In this case, it is applied to *middle* and *last* parts in a break sequence. Note that /tcb/toprule → P. 35 overwrites this value if used afterwards.

/tcb/bottomrule at break=⟨*length*⟩ (no default, initially `0.5mm`)
Sets the line width of the bottom rule to ⟨*length*⟩ *if* the box is /tcb/breakable → P. 365. In this case, it is applied to *first* and *middle* parts in a break sequence. Note that /tcb/bottomrule → P. 35 overwrites this value if used afterwards.

/tcb/topsep at break=⟨*length*⟩ (no default, initially `0mm`)
Additional vertical space of ⟨*length*⟩ which is added at the top of *middle* and *last* parts in a break sequence. In general, it is not advisable to change this value if these parts start with a rule or a title.

/tcb/bottomsep at break=⟨*length*⟩ (no default, initially `0mm`)
Additional vertical space of ⟨*length*⟩ which is added at the bottom of *first* and *middle* parts in a break sequence. In general, it is not advisable to change this value if these parts end with a rule.

/tcb/pad before break=⟨*length*⟩ (style, no default, initially `3.5mm`)
Sets the total amount of vertical space after the text content and before the break point to ⟨*length*⟩. This style sets /tcb/toprule at break to `0pt` and changes /tcb/topsep at break as required. In general, it is not advisable to change this value if the *middle* and *last* parts in a break sequence start with a rule or a title.

/tcb/pad before break*=⟨*length*⟩ (style, no default)
Sets /tcb/pad before break to ⟨*length*⟩ and /tcb/enlargepage flexible → P. 368 to an appropriate value such that empty closing frames are avoided.

/tcb/pad after break=⟨*length*⟩ (style, no default, initially `3.5mm`)
Sets the total amount of vertical space after the break point and before the text content to ⟨*length*⟩. This style sets /tcb/bottomrule at break to `0pt` and changes /tcb/bottomsep at break as required. In general, it is not advisable to change this value if the *first* and *middle* parts in a break sequence end with a rule.

/tcb/pad at break=⟨*length*⟩ (style, no default, initially `3.5mm`)
Abbreviation for setting ⟨*length*⟩ to /tcb/pad before break and /tcb/pad after break.

/tcb/pad at break*=⟨*length*⟩ (style, no default)
Sets /tcb/pad at break to ⟨*length*⟩ and /tcb/enlargepage flexible → P. 368 to an appropriate value such that empty closing frames are avoided.

```
% \usepackage{lipsum}  % preamble
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[enhanced jigsaw,breakable,pad at break*=0mm,
  title={For this box, the pad space at the break point is set to 0mm}]
  \lipsum[1-2]
\end{tcolorbox}
```

For this box, the pad space at the break point is set to 0mm

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque.

Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.
Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

`/tcb/pad at break`→ P. 369 or `/tcb/pad at break*`→ P. 369 should be used as very last option in an option list, because they adapt other settings.

Also see `/tcb/enlarge top at break by`→ P. 83 and `/tcb/enlarge bottom at break by`→ P. 83.

`/tcb/height fixed for=`⟨*part*⟩ (no default, initially `none`)

When certain amount of space is available for a partial box of a break sequence, the partial box typically is smaller than this space (depending on the box content). For given ⟨*part*⟩(s), the height can be set to all available space.

- `none`: Every partial `tcolorbox` is set with its natural height.
- `first`: The *first* partial box is set to a height which matches the available space.
- `middle`: All *middle* partial boxes are set to a height which matches the available space.
- `last`: The *last* partial box is set to a height which matches the available space.
- `first and middle`: The *first* and all *middle* partial boxes are set to a height which matches the available space.
- `middle and last`: All *middle* partial boxes and the *last* partial box are set to a height which matches the available space.
- `all`: All partial boxes are set to a height which matches the available space.

If the box keeps unbroken, this option is not applied. See `/tcb/height`→ P. 53 for setting a fixed height for unbroken boxes. See `/tcb/height fill`→ P. 56 for giving unbroken boxes maximum height.

`/tcb/vfill before first=true|false` (default `true`, initially `false`)

Inserts a `\vfill` at the begin of the *first* partial box to move this partial box to the end of the current page. This may be used as an alternative to `/tcb/height fixed for=first` to get justified columns or pages. The `\vfill` is not inserted, if the box gets not actually broken.

N 2017-03-20 `/tcb/segmentation at break=true|false` (default `true`, initially `true`)

If a breakable box contains an *upper part* and a *lower part* and the break happens at the *segmentation* between both parts, then

- the segmenation line (or similar) is drawn as first element of the partial box containing the *lower part*, if `/tcb/segmentation at break` is set to be `true`.
- the segmenation line (or similar) is not drawn at all, if `/tcb/segmentation at break` is set to be `false`. This may be preferable for skins like `bicolor`→ P. 219, `tile`→ P. 224, or `beamer`→ P. 228.

17.5 Extra Options for Partial Boxes

N 2015-07-16 **/tcb/extras**={⟨*options*⟩} (no default, initially unset)

Adds `tcolorbox` ⟨*options*⟩ to every box of a *break sequence* after skin settings are done. This is quite late in box processing. Geometry and break settings should *not be used* here, because they will either be ignored or have unexpected negative results. But it is possible to change most colors, skin effects, shadows, borders, frame code, etc. Note that using `/tcb/extras` for every box is very seldom an advantage over setting the options directly. Usually, `/tcb/extras first`, `/tcb/extras middle`, etc. are sensible to apply.

N 2015-07-16 **/tcb/no extras** (style, no default, initially set)

Removes all extras if set before.

N 2015-07-16 **/tcb/extras broken**={⟨*options*⟩} (no default, initially unset)

If the box is set to be `/tcb/breakable` → P. 365 and *is* broken actually, then the ⟨*options*⟩ are added to every box of the *break sequence*. `/tcb/extras` overwrites this key.

N 2015-07-16 **/tcb/extras unbroken**={⟨*options*⟩} (no default, initially unset)

If the box is set to be `/tcb/breakable` → P. 365 but *is not* broken actually or if the box is set to be `/tcb/unbreakable` → P. 366, then the ⟨*options*⟩ are added to the box. `/tcb/extras` overwrites this key.

N 2015-07-16 **/tcb/no extras unbroken** (style, no default, initially set)

Removes the unbroken extras if set before.

N 2015-07-16 **/tcb/extras first**={⟨*options*⟩} (no default, initially unset)

If the box is set to be `/tcb/breakable` → P. 365 and *is* broken actually, then the ⟨*options*⟩ are added to the *first* box of the break sequence. `/tcb/extras` overwrites this key.

N 2015-07-16 **/tcb/no extras first** (style, no default, initially set)

Removes the first extras if set before.

N 2015-07-16 **/tcb/extras middle**={⟨*options*⟩} (no default, initially unset)

If the box is set to be `/tcb/breakable` → P. 365 and *is* broken actually, then the ⟨*options*⟩ are added to every *middle* box (if any) of the break sequence. `/tcb/extras` overwrites this key.

N 2015-07-16 **/tcb/no extras middle** (style, no default, initially set)

Removes the middle extras if set before.

N 2015-07-16 **/tcb/extras last**={⟨*options*⟩} (no default, initially unset)

If the box is set to be `/tcb/breakable` → P. 365 and *is* broken actually, then the ⟨*options*⟩ are added to the *last* box of the break sequence. `/tcb/extras` overwrites this key.

N 2015-07-16 **/tcb/no extras last** (style, no default, initially set)

Removes the last extras if set before.

N 2015-07-16 **/tcb/extras unbroken and first**={⟨*options*⟩} (no default, initially unset)

This is an abbreviation for setting `/tcb/extras unbroken` and `/tcb/extras first` together. `/tcb/extras` overwrites this key.

N 2015-07-16 **/tcb/extras middle and last**={⟨*options*⟩} (no default, initially unset)

This is an abbreviation for setting `/tcb/extras middle` and `/tcb/extras last` together. `/tcb/extras` overwrites this key.

N 2015-07-16 **/tcb/extras unbroken and last**={⟨*options*⟩} (no default, initially unset)

This is an abbreviation for setting `/tcb/extras unbroken` and `/tcb/extras last` together. `/tcb/extras` overwrites this key.

N 2015-07-16 **/tcb/extras first and middle**={⟨*options*⟩} (no default, initially unset)

This is an abbreviation for setting `/tcb/extras first` and `/tcb/extras middle` together. `/tcb/extras` overwrites this key.

```
% \usepackage{lipsum,multicol}
% \usetikzlibrary{decorations.pathmorphing}
% \tcbuselibrary{skins}
\newtcolorbox{mybox}[1][]{
  tile,
  colback=green!7,coltitle=blue!50!black,colbacktitle=blue!5,
  center title,
  toprule=1.25mm,bottomrule=1.25mm,
  extras unbroken and first={
    borderline north={0.25mm}{0.5mm}{blue,decoration={zigzag,amplitude=0.5mm},decorate}},
  extras unbroken and last={
    borderline south={0.25mm}{0.5mm}{blue,decoration={zigzag,amplitude=0.5mm},decorate}},
  #1
}

\begin{mybox}[title=My unbroken box]
\lipsum[1]
\end{mybox}

\begin{multicols}{3}
  \begin{mybox}[title=My broken box,
    enforce breakable,% use only breakable in the real world!
    break at=4.2cm,pad at break=2mm,
    height fixed for=first and middle,  ]
  \lipsum[2]
  \end{mybox}
\end{multicols}
```

My unbroken box

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

My broken box

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

17.6 Breakable boxes and the `multicol` package

With version 4.10, the algorithm for detecting the available height for a `tcolorbox` inside a `multicol` environment was improved with help of Frank Mittelbach. This change *may* impact existing user code which *may* have to be adapted.

Unbreakable `tcolorbox`es can be used without special care inside a `multicols` environment from the `multicol` package [9].
Since version 3.10, a breakable `tcolorbox` detects, if it is used inside a `multicols` environment. But choosing break points for a breakable box cannot be done by the balancing routine of `multicols`. By default, boxes will break at maximum column height. To get pleasant results, use the `/tcb/break at` → P. 367 and `/tcb/height fixed for` → P. 370 options.

```
% \usepackage{lipsum,multicol}  % preamble
\footnotesize
\begin{multicols}{2}
  \lipsum[1]
  \begin{tcolorbox}[enhanced jigsaw,breakable,size=title,
    colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
    title=My breakable box,pad at break=1mm, break at=-\baselineskip/0pt ]
  \lipsum[2-4]
  \end{tcolorbox}
  \lipsum[4]
\end{multicols}
```

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

My breakable box

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.
Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.
Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

This example is already set inside a `multicols` environment. This time, a *middle* part has full column height (here `\textheight`). `/tcb/height fixed for` → P. 370 is used to spread this box part over the full height to align with neighboring columns.

```
% \usepackage{lipsum,multicol}
\lipsum[1]
\begin{tcolorbox}[enhanced jigsaw,
  breakable,
  size=title,
  colback=red!5!white,
  colframe=red!75!black,
  fonttitle=\bfseries,
  title=My breakable box,
  pad at break=2mm,
  break at=-\baselineskip/0pt,
  height fixed for=middle ]
\lipsum[2-7]
\end{tcolorbox}
\lipsum[8]
```

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

My breakable box

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula. Fusce mauris. Vestibulum luctus nibh at lectus. Sed bibendum, nulla a faucibus semper, leo velit ultricies tellus, ac venenatis arcu wisi vel nisl. Vestibulum diam. Aliquam pellentesque, augue quis sagittis posuere, turpis lacus congue quam, in hendrerit risus eros eget felis. Maecenas eget erat in sapien mattis porttitor. Vestibulum porttitor. Nulla facilisi. Sed a turpis eu lacus commodo facilisis. Morbi fringilla, wisi in dignissim interdum, justo lectus sagittis dui, et vehicula libero dui cursus dui. Mauris tempor ligula sed lacus. Duis cursus enim ut augue. Cras ac magna. Cras nulla. Nulla egestas. Curabitur a leo. Quisque egestas wisi eget nunc. Nam feugiat lacus vel est. Curabitur consectetuer.

Suspendisse vel felis. Ut lorem lorem, interdum eu, tincidunt sit amet, laoreet vitae, arcu. Aenean faucibus pede eu ante. Praesent enim elit, rutrum at, molestie non, nonummy vel, nisl. Ut lectus eros, malesuada sit amet, fermentum eu, sodales cursus, magna. Donec eu purus. Quisque vehicula, urna sed ultricies auctor, pede lorem egestas dui, et convallis elit erat sed nulla. Donec luctus. Curabitur et nunc. Aliquam dolor odio, commodo pretium, ultricies non, pharetra in, velit. Integer arcu est, nonummy in, fermentum faucibus, egestas vel, odio.

Sed commodo posuere pede. Mauris ut est. Ut quis purus. Sed ac odio. Sed vehicula hendrerit sem. Duis non odio. Morbi ut dui. Sed accumsan risus eget odio. In hac habitasse platea dictumst. Pellentesque non elit. Fusce sed justo eu urna porta tincidunt. Mauris felis odio, sollicitudin sed, volutpat a, ornare ac, erat. Morbi

quis dolor. Donec pellentesque, erat ac sagittis semper, nunc dui lobortis purus, quis congue purus metus ultricies tellus. Proin et quam. Class aptent taciti sociosqu ad litora torquent per conubia nostra, per inceptos hymenaeos. Praesent sapien turpis, fermentum vel, eleifend faucibus, vehicula eu, lacus.

Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Donec odio elit, dictum in, hendrerit sit amet, egestas sed, leo. Praesent feugiat sapien aliquet odio. Integer vitae justo. Aliquam vestibulum fringilla lorem. Sed neque lectus, consectetuer at, consectetuer sed, eleifend ac, lectus. Nulla facilisi. Pellentesque eget lectus. Proin eu metus. Sed porttitor. In hac habitasse platea dictumst. Suspendisse eu lectus. Ut mi mi, lacinia sit amet, placerat et, mollis vitae, dui. Sed ante tellus, tristique ut, iaculis eu, malesuada ac, dui. Mauris nibh leo, facilisis non, adipiscing quis, ultrices a, dui.

The following example has a `\tcolorbox` which fills the `\multicols` environment completely. Here, `/tcb/height fixed for` → P. 370 is used to give all three columns the full height. Note that the appropriate `/tcb/break at` → P. 367 value is not computed automatically but set manually.

```
% \usepackage{lipsum,multicol}  % preamble
\small
\begin{multicols}{3}
  \begin{tcolorbox}[enhanced jigsaw,breakable,size=small,
    colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
    title=My breakable box,pad at break=2mm,drop fuzzy shadow,
    height fixed for=all, break at=11.4cm ]
  \lipsum[1-3]
  \end{tcolorbox}
\end{multicols}
```

My breakable box

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

17.7 Break Point Insertion

N 2017-07-05 **\tcbbreak**

A *breakable* box is not broken, if there is enough space on the current page or column. Therefore, typical penalty insertion with \break, \pagebreak, \columnbreak, ... *may* only work as expected, if the box is broken at least into two parts *without* inserting the penalties.

To *force* a page or column break, \tcbbreak starts a new paragraph and inserts an insane tall rule which causes a break and which is immediately discarded. You may ignore this technical information and just use it as you would use \pagebreak.

For an *unbreakable box*, \tcbbreak is identical to insert \par, i.e. it just starts a new paragraph.

Also see /tcb/break at → P. 367 for defining height dependend breaks.

```
% \usepackage{lipsum,multicol}  % preamble
\begin{multicols}{3}
  \begin{tcolorbox}[breakable,enhanced jigsaw,size=small,
    colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
    title=Break into parts
  ]
  First part\tcbbreak
  Second part\tcbbreak
  Third part
  \end{tcolorbox}
\end{multicols}

\begin{multicols}{3}
  \begin{tcolorbox}[enhanced jigsaw,size=small,
    colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
    title=You shall not break
  ]
  First part\tcbbreak
  Second part\tcbbreak
  Third part
  \end{tcolorbox}
\end{multicols}
```

Break into parts

First part

Second part

Third part

You shall not break

First part
Second part
Third part

17.8 Break Sequence for the Skins

The following diagrams document the *break sequence* for different skins. Depending on the main skin of a `tcolorbox`, the actual skins of the *break sequence* parts are displayed.




Unbroken Box
skin=enhanced
unbroken
Broken Boxes
skin=enhancedfirst
first
skin=enhancedmiddle
middle
skin=enhancedlast
last
Unbroken Box
skin=enhancedfirst
unbroken
Broken Boxes
skin=enhancedfirst
first
skin=enhancedmiddle
middle
skin=enhancedmiddle
last
Unbroken Box
skin=enhancedmiddle
unbroken
Broken Boxes
skin=enhancedmiddle
first
skin=enhancedmiddle
middle
skin=enhancedmiddle
last
Unbroken Box
skin=enhancedlast
unbroken
Broken Boxes
skin=enhancedmiddle
first
skin=enhancedmiddle
middle
skin=enhancedlast
last


Unbroken Box
skin=enhanced jigsaw
unbroken
Broken Boxes
skin=enhancedfirst jigsaw
skin=enhancedmiddle jigsaw
skin=enhancedlast jigsaw
Unbroken Box
skin=enhancedfirst jigsaw
unbroken
Broken Boxes
skin=enhancedfirst jigsaw
skin=enhancedmiddle jigsaw
skin=enhancedmiddle jigsaw
Unbroken Box
skin=enhancedmiddle jigsaw
unbroken
Broken Boxes
skin=enhancedmiddle jigsaw
skin=enhancedmiddle jigsaw
skin=enhancedmiddle jigsaw
Unbroken Box
skin=enhancedlast jigsaw
unbroken
Broken Boxes
skin=enhancedmiddle jigsaw
skin=enhancedmiddle jigsaw
skin=enhancedlast jigsaw

skin=empty
unbroken
skin=emptyfirst
first
skin=emptymiddle
middle
skin=emptylast
last
skin=emptyfirst
unbroken
skin=emptyfirst
first
skin=emptymiddle
middle
skin=emptymiddle
last
skin=emptymiddle
unbroken
skin=emptymiddle
first
skin=emptymiddle
middle
skin=emptymiddle
last
skin=emptylast
unbroken
skin=emptymiddle
first
skin=emptymiddle
middle
skin=emptylast
last


Unbroken Box
skin=bicolor
unbroken
Broken Boxes
skin=bicolorfirst
first
skin=bicolormiddle
middle
skin=bicolorlast
last
Unbroken Box
skin=bicolorfirst
unbroken
Broken Boxes
skin=bicolorfirst
first
skin=bicolormiddle
middle
skin=bicolormiddle
last
Unbroken Box
skin=bicolormiddle
unbroken
Broken Boxes
skin=bicolormiddle
first
skin=bicolormiddle
middle
skin=bicolormiddle
last
Unbroken Box
skin=bicolorlast
unbroken
Broken Boxes
skin=bicolormiddle
first
skin=bicolormiddle
middle
skin=bicolorlast
last


Unbroken Box
skin=tile
unbroken
Broken Boxes
skin=tilefirst
first
skin=tilemiddle
middle
skin=tilelast
last
Unbroken Box
skin=tilefirst
unbroken
Broken Boxes
skin=tilefirst
first
skin=tilemiddle
middle
skin=tilemiddle
last
Unbroken Box
skin=tilemiddle
unbroken
Broken Boxes
skin=tilemiddle
first
skin=tilemiddle
middle
skin=tilemiddle
last
Unbroken Box
skin=tilelast
unbroken
Broken Boxes
skin=tilemiddle
first
skin=tilemiddle
middle
skin=tilelast
last


Unbroken Box
skin=beamer
unbroken
Broken Boxes
skin=beamerfirst
skin=beamermiddle
skin=beamerlast
Unbroken Box
skin=beamerfirst
unbroken
Broken Boxes
skin=beamerfirst
skin=beamermiddle
skin=beamermiddle
Unbroken Box
skin=beamermiddle
unbroken
Broken Boxes
skin=beamermiddle
skin=beamermiddle
skin=beamermiddle
Unbroken Box
skin=beamerlast
unbroken
Broken Boxes
skin=beamermiddle
skin=beamermiddle
skin=beamerlast


Unbroken Box
skin=widget
unbroken
Broken Boxes
skin=widgetfirst
first
skin=widgetmiddle
middle
skin=widgetlast
last
Unbroken Box
skin=widgetfirst
unbroken
Broken Boxes
skin=widgetfirst
first
skin=widgetmiddle
middle
skin=widgetmiddle
last
Unbroken Box
skin=widgetmiddle
unbroken
Broken Boxes
skin=widgetmiddle
first
skin=widgetmiddle
middle
skin=widgetmiddle
last
Unbroken Box
skin=widgetlast
unbroken
Broken Boxes
skin=widgetmiddle
first
skin=widgetmiddle
middle
skin=widgetlast
last
frame: w=199.16928pt, h=108.12054pt
title: w=167.87134pt, h=7.65457pt
Unbroken Box
skin=draft
upper: w=167.87134pt, h=73.43599pt
interior: w=196.32404pt, h=90.50758pt
frame: w=199.16928pt, h=39.83368pt
title: w=167.87134pt, h=7.65457pt
Broken Boxes
upper: w=167.87134pt, h=5.14912pt
skin=draft
interior: w=196.32404pt, h=22.22072pt
frame: w=199.16928pt, h=28.45274pt
upper: w=167.87134pt, h=8.5359pt
skin=draft
interior: w=196.32404pt, h=25.6075pt
frame: w=199.16928pt, h=28.45274pt
upper: w=167.87134pt, h=8.5359pt
skin=draft
interior: w=196.32404pt, h=25.6075pt


Unbroken Box
skin=freelance
unbroken
Broken Boxes
skin=freelancefirst
first
skin=freelancemiddle
middle
skin=freelancelast
last
Unbroken Box
skin=freelancefirst
unbroken
Broken Boxes
skin=freelancefirst
first
skin=freelancemiddle
middle
skin=freelancemiddle
last
Unbroken Box
skin=freelancemiddle
unbroken
Broken Boxes
skin=freelancemiddle
first
skin=freelancemiddle
middle
skin=freelancemiddle
last
Unbroken Box
skin=freelancelast
unbroken
Broken Boxes
skin=freelancemiddle
first
skin=freelancemiddle
middle
skin=freelancelast
last

17.9 Break by Hand (Faked Break)

See Section 17.6 on page 373 for *real* column breaks.

Since the appearance of broken boxes is done by skins, it is quite easy to 'fake a break'. For this, you actually don't need the LIB breakable library at all.

```
\tcbset{enhanced,equal height group=fakedbreak,
  colback=LightGreen,colframe=DarkGreen,
  width=(\linewidth-6mm)/3,nobeforeafter,
  left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm}
%
\begin{tcolorbox}[title=My broken box,skin=enhancedfirst]
This is a box which breaks from one column to another
\end{tcolorbox}\hfill
\begin{tcolorbox}[skin=enhancedmiddle]
column. I am sorry to say that this is a trick.
Nevertheless, you may use this trick for your
\end{tcolorbox}\hfill
\begin{tcolorbox}[skin=enhancedlast]
own purposes.
\end{tcolorbox}
```

My broken box

This is a box which breaks from one column to another

column. I am sorry to say that this is a trick. Nevertheless, you may use this trick for your

own purposes.

18 Library magazine

The main purpose of this library is to store a `tcolorbox` into an array of box registers for later usage.

If the `tcolorbox` is not breakable, there is not much add-on compared to usual TEX/LATEX box storage and usage (and you do not really need this library for that use case). For a breakable `tcolorbox`, this library allows to capture all partial boxes into a sequence of registers. The partial boxes can be used anywhere in arbitrary order.

Example Article

This is an example for an article which starts right here and is continued to the following pages. The body text for the article is written inside a single `tcolorbox`. This box is split into parts using the tools from this section,

— continued on page 390 —

The name of this library indicates *magazine* in the sense of storage, but also in the sense of a journal where an article often is *continued on page x*. An example for this kind of application is given throughout this section starting on the right hand side. The creation of this library was motivated by Ulrike Fischer and Steven B. Segletes.

The library is loaded by a package option or inside the preamble by:

```
\tcbuselibrary{magazine}
```

This also loads the library breakable, see Section 17 on page 363.

! The box register operations of this library are global. TEX grouping will not clear the registers when leaving the current group. Also be aware that extensive use of large box arrays may eat up TEX's available memory and registers.

18.1 Creation and Resetting of Box Arrays

N 2015-07-13 `\newboxarray{`⟨*name*⟩`}`

This creates a new box array called ⟨*name*⟩. There already is a box array available with name `default` which can be used directly. Note that the creation is a global operation.

```
\newboxarray{myarray}
```

N 2015-07-13 `\boxarrayreset[`⟨*name*⟩`]`

Resets the size counter of a box array ⟨*name*⟩ to zero. If ⟨*name*⟩ is not provided, `default` is used as name. Use this or `/tcb/reset box array` before you apply `/tcb/store to box array` → P. 388. Otherwise, all boxes would be appended to the already existing boxes. This command does not clear box registers.

```
\boxarrayreset           % resets 'default'
\boxarrayreset{myarray}  % resets 'myarray'
```

N 2015-07-13 `/tcb/reset box array=`⟨*name*⟩ (default `default`, initially unset)

Resets the size counter of a box array ⟨*name*⟩ to zero. Use this or `\boxarrayreset` (which does the same) before you apply `/tcb/store to box array` → P. 388.

```
\tcbset{
  reset box array,          % resets 'default'
  reset box array=myarray, % resets 'myarray'
}
```

N 2015-07-13 `\boxarrayclear[⟨name⟩]`

Works like `\boxarrayreset` → P. 387 to reset the size counter of a box array ⟨*name*⟩ to zero. Additionally, all allocated box registers of the box array are cleared of their content. Note that the allocated box registers stay allocated. So, this may be useful to clear memory, but not to free registers for other applications. If `\consumeboxarray` → P. 391 or `\consumetcboxarray` → P. 391 was used to apply the stored boxes, there is no advantage in using `\boxarrayclear`.

```
\boxarrayclear            % clears 'default'
\boxarrayclear{myarray}   % clears 'myarray'
```

18.2 Storing Content

N 2015-07-13 `/tcb/store to box array=`⟨*name*⟩ (default `default`, initially unset)

Stores a `tcolorbox` or all parts of a break sequence of a `tcolorbox` into a box array ⟨*name*⟩. If no ⟨*name*⟩ is given, the already existing `default` box array is used. Otherwise, the box array has to be created beforehand with `\newboxarray` → P. 387. Note that the box has to be `/tcb/breakable` → P. 365, if the box shall break into several parts. Typically, manual break points are additionally defined by `/tcb/break at` → P. 367. Otherwise, the box parts will have a length of about `\textheight`. For most use cases, a `/tcb/reset box array` → P. 387 should be applied to reset the box array counter.

```
% \usepackage{lipsum}
\begin{tcolorbox}[enhanced jigsaw,size=fbox,width=4cm,
  colback=yellow!10,colframe=yellow!10!black,
  enforce breakable,% use only breakable in the real world!
  break at=7cm/4cm,
  height fixed for=all,
  watermark text=\arabic{tcbbreakpart},
  reset box array,
  store to box array
  ]
\lipsum[1]
\end{tcolorbox}

\useboxarray{1}\hfill
\begin{tabular}[b]{cc}
\multicolumn{2}{c}{\includegraphics[width=7cm]{Basilica_5.png}}\\
\useboxarray{2} & \useboxarray{3}
\end{tabular}
```

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhon-



cus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

If the first box part should fill the rest of the available space of the current page, you can use `\pagegoal-\pagetotal` minus some distance for the first element of `/tcb/break at` → P. 367. You may want to have some additional distance to the preceeding text.

```
% \usepackage{lipsum}
\begin{tcolorbox}[enhanced,breakable,
  reset box array,
  store to box array,
  break at=\pagegoal-\pagetotal-5mm/0pt,
  height fixed for=first and middle]
\lipsum[1-15]
\end{tcolorbox}%
%
\consumetcboxarray{1}{blanker,before=\par\vfill\noindent}
```

```
\begin{tcolorbox}[blanker,width=4cm,
  fontupper=\footnotesize,
  enforce breakable,% use only breakable in the real world!
  break at=4cm,
  height fixed for=all,
  watermark text=\arabic{tcbbreakpart},
  reset box array,
  store to box array
  ]
\includegraphics[width=\linewidth]{Basilica_5.png}\par
\lipsum[1-2]
\end{tcolorbox}

\begin{tcbitemize}[raster columns=3,raster equal height,
  size=small,halign=center,sharp corners,colback=blue!5]
\tcbitem\consumeboxarray{5}
\tcbitem\consumeboxarray{6}
\tcbitem\consumeboxarray{1}
\tcbitem\consumeboxarray{2}
\tcbitem\consumeboxarray{3}
\tcbitem\consumeboxarray{4}
\end{tcbitemize}
```

lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec

ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.



Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam

arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus

vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at,

mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum. Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor

N 2015-07-13 **/tcb/reset and store to box array=**⟨*name*⟩ (style, default **default**, initially unset)

Combination of /tcb/reset box array → P. 387 and /tcb/store to box array → P. 388.

N 2015-07-13 **/tcb/do not store to box array** (style, no default, initially set)

Disables the /tcb/store to box array → P. 388 option, if set before.

N 2015-07-13 **\begin{boxarraystore}**{⟨*name*⟩}
⟨*environment content*⟩
\end{boxarraystore}

Stores the environment content into a box array ⟨*name*⟩. This corresponds to the standard LaTeX environment **lrbox**, but the storage operation is global. As long as \boxarrayreset → P. 387 is not used, every new boxarraystore adds a further box to the array.

```
\boxarrayreset
\begin{boxarraystore}{default}\fbox{Mary}\end{boxarraystore}
\begin{boxarraystore}{default}\fbox{Had}\end{boxarraystore}
\begin{boxarraystore}{default}\fbox{a}\end{boxarraystore}
\begin{boxarraystore}{default}\fbox{Little}\end{boxarraystore}
\begin{boxarraystore}{default}\fbox{Lamb}\end{boxarraystore}
\useboxarray{5}\useboxarray{4}\useboxarray{3}\useboxarray{2}\useboxarray{1}\hfill
\useboxarray{1}\useboxarray{5}
```

Lamb Little a Had Mary Mary Lamb

18.3 Retrieving Content

N 2015-07-13 **\boxarraygetsize[**⟨*name*⟩**]{**⟨*macro*⟩**}**

Stores the current size of a box array ⟨*name*⟩ into a given ⟨*macro*⟩. If no ⟨*name*⟩ is given, the already existing **default** box array is used.

```
\boxarraygetsize{\mysize}
Current size of the default box array:
\mysize.
```

Current size of the default box array: 5.

— continued from page 387 —
namely /tcb/reset and store to box array → P. 390 with a new box array **myarticle** which was created by **\newboxarray{myarticle}**.
The resulting parts are distributed throughout this Section 18 on page 387 using \consumetcboxarray → P. 391 at
— continued on page 391 —

N 2015-07-13 **\useboxarray[**⟨*name*⟩**]{**⟨*index*⟩**}**

Typesets the box with the given ⟨*index*⟩ number from the box array ⟨*name*⟩. If no ⟨*name*⟩ is given, the already existing **default** box array is used. It is considered an error, if a not existing box array ⟨*name*⟩ is used. It is silently ignored, if the ⟨*index*⟩ is out of range. Note that \useboxarray corresponds to the standard **\usebox** macro, respectively, **\copy**.

```
\boxarraygetsize{\mysize}
\foreach \n in  {1,...,\mysize} { \useboxarray{\n} }
```

Mary Had a Little Lamb

N 2015-07-13 `\usetcboxarray[⟨name⟩]{⟨index⟩}{⟨options⟩}`

Typesets the box with the given ⟨*index*⟩ number from the box array ⟨*name*⟩ using `\useboxarray` → P. 390 as content of a `\tcbox` → P. 14. If no ⟨*name*⟩ is given, the already existing `default` box array is used. It is considered an error, if a not existing box array ⟨*name*⟩ is used. It is silently ignored, if the ⟨*index*⟩ is out of range. The `\tcbox` → P. 14 can be customized by `tcolorbox` ⟨*options*⟩.

```
\boxarraygetsize{\mysize}
\foreach \n in  {1,...,\mysize} { \usetcboxarray{\n}{on line,colframe=yellow,
  colback=yellow!10} }
```

Mary Had a Little Lamb

N 2015-07-13 `\consumeboxarray[⟨name⟩]{⟨index⟩}`

Typesets the box with the given ⟨*index*⟩ number from the box array ⟨*name*⟩. If no ⟨*name*⟩ is given, the already existing `default` box array is used. It is considered an error, if a not existing box array ⟨*name*⟩ is used. It is silently ignored, if the ⟨*index*⟩ is out of range. In contrast to `\useboxarray` → P. 390, `\consumeboxarray` corresponds to the standard `\box` macro, i.e. after typesetting the box register is cleared and cannot be used again.

```
\boxarraygetsize{\mysize}
First run: \foreach \n in  {1,...,\mysize} { \consumeboxarray{\n} }
\par
Second run: \foreach \n in  {1,...,\mysize} { \consumeboxarray{\n} }
```

First run: Mary Had a Little Lamb
Second run:

N 2015-07-13 `\consumetcboxarray[⟨name⟩]{⟨index⟩}{⟨options⟩}`

Typesets the box with the given ⟨*index*⟩ number from the box array ⟨*name*⟩ using `\consumeboxarray` as content of a `\tcbox` → P. 14. If no ⟨*name*⟩ is given, the already existing `default` box array is used. It is considered an error, if a not existing box array ⟨*name*⟩ is used. It is silently ignored, if the ⟨*index*⟩ is out of range. The `\tcbox` → P. 14 can be customized by `tcolorbox` ⟨*options*⟩. After typesetting the box register is cleared and cannot be used again.

— *continued from page 390* —
the appropriate places you see. The linking texts like *continued on page x* are created by `/tcb/finish` → P. 197 commands for the embedding `\tcbox` → P. 14. To label the box parts, `/tcb/phantomlabel` → P. 98 is used.
These quite small partial boxes are
— *continued on page 394* —

```
% \usepackage{lipsum}
\begin{tcolorbox}[enhanced jigsaw,size=fbox,width=6cm,
  colback=yellow!10,colframe=yellow!10!black,
  enforce breakable,% use only breakable in the real world!
  break at=5cm,
  watermark text=\arabic{tcbbreakpart},
  reset and store to box array
  ]
\lipsum[1]
\end{tcolorbox}

\consumeboxarray{2} \hfill \consumeboxarray{1} \hfill \consumeboxarray{1}
```

lus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tel-

N 2015-07-13 **\boxarraygetbox**[⟨*name*⟩]{⟨*macro*⟩}{⟨*index*⟩}

Assigns the box with the given ⟨*index*⟩ number from the box array ⟨*name*⟩ to a ⟨*macro*⟩. If no ⟨*name*⟩ is given, the already existing `default` box array is used. It is considered an error, if a not existing box array ⟨*name*⟩ is used. If the ⟨*index*⟩ is out of range, the ⟨*macro*⟩ will be undefined.

```
\tcbox[size=small,colframe=blue!20,colback=yellow!5,on line,
  reset and store to box array]{Test}

\boxarraygetsize{\mysize} Array size: \mysize

\boxarraygetbox{\mybox}{1}
Box width: \the\wd\mybox
\quad\usebox{\mybox}
```

Array size: 1
Box width: 30.35799pt Test

N 2017-06-27 **\ifboxarrayempty**[⟨*name*⟩]{⟨*index*⟩}{⟨*true*⟩}{⟨*false*⟩}

Tests the box with the given ⟨*index*⟩ number from the box array ⟨*name*⟩ for emptiness be empty and executes ⟨*true*⟩ if it is empty, and ⟨*false*⟩ otherwise. If no ⟨*name*⟩ is given, the already existing `default` box array is used. It is considered an error, if a not existing box array ⟨*name*⟩ is used.

```
\tcbox[size=small,colframe=blue!20,colback=yellow!5,on line,
  reset and store to box array]{Test}

\ifboxarrayempty{1}{no Box~1}{Box~1: \useboxarray{1}},
\ifboxarrayempty{2}{no Box~2}{Box~2: \useboxarray{2}}
```

Box 1: Test, no Box 2

18.4 Box Dimensions

N 2015-07-13 `\boxarraygetwidth[⟨name⟩]{⟨macro⟩}{⟨index⟩}`

Assigns the width of the box with the given ⟨*index*⟩ number from the box array ⟨*name*⟩ to a ⟨*macro*⟩. If no ⟨*name*⟩ is given, the already existing `default` box array is used. It is considered an error, if a not existing box array ⟨*name*⟩ is used. If the ⟨*index*⟩ is out of range, the ⟨*macro*⟩ will be set to `0pt`.

```
\tcbox[size=small,colframe=blue!20,colback=yellow!5,on line,
  reset and store to box array]{Test}

\begin{tabular}{ll}
\useboxarray{1} & width of box 1: \boxarraygetwidth{\mylen}{1} \mylen\\
\useboxarray{2} & width of box 2: \boxarraygetwidth{\mylen}{2} \mylen
\end{tabular}
```

Test width of box 1: 30.35799pt
width of box 2: 0pt

N 2015-07-13 `\boxarraygetheight[⟨name⟩]{⟨macro⟩}{⟨index⟩}`

Assigns the height of the box with the given ⟨*index*⟩ number from the box array ⟨*name*⟩ to a ⟨*macro*⟩. If no ⟨*name*⟩ is given, the already existing `default` box array is used. It is considered an error, if a not existing box array ⟨*name*⟩ is used. If the ⟨*index*⟩ is out of range, the ⟨*macro*⟩ will be set to `0pt`.

```
\tcbox[size=small,colframe=blue!20,colback=yellow!5,on line,
  reset and store to box array]{Test}

\begin{tabular}{ll}
\useboxarray{1} & height of box 1: \boxarraygetheight{\mylen}{1} \mylen\\
\useboxarray{2} & height of box 2: \boxarraygetheight{\mylen}{2} \mylen
\end{tabular}
```

Test height of box 1: 9.89883pt
height of box 2: 0pt

N 2015-07-13 `\boxarraygetdepth[⟨name⟩]{⟨macro⟩}{⟨index⟩}`

Assigns the depth of the box with the given ⟨*index*⟩ number from the box array ⟨*name*⟩ to a ⟨*macro*⟩. If no ⟨*name*⟩ is given, the already existing `default` box array is used. It is considered an error, if a not existing box array ⟨*name*⟩ is used. If the ⟨*index*⟩ is out of range, the ⟨*macro*⟩ will be set to `0pt`.

```
\tcbox[size=small,colframe=blue!20,colback=yellow!5,on line,
  reset and store to box array]{Test}

\begin{tabular}{ll}
\useboxarray{1} & depth of box 1: \boxarraygetdepth{\mylen}{1} \mylen\\
\useboxarray{2} & depth of box 2: \boxarraygetdepth{\mylen}{2} \mylen
\end{tabular}
```

Test depth of box 1: 3.69884pt
depth of box 2: 0pt

N 2015-07-13 `\boxarraygettotalheight[⟨name⟩]{⟨macro⟩}{⟨index⟩}`

Assigns the total height of the box with the given ⟨*index*⟩ number from the box array ⟨*name*⟩ to a ⟨*macro*⟩. If no ⟨*name*⟩ is given, the already existing `default` box array is used. It is considered an error, if a not existing box array ⟨*name*⟩ is used. If the ⟨*index*⟩ is out of range, the ⟨*macro*⟩ will be set to `0pt`.

— continued from page 391 —

for demonstration purposes. With the tools of this section, a magazine type document could be created, but this still needs a lot of manual control.

```
\boxarrayreset
\tcbox[size=small,colframe=blue!20,colback=yellow!5,on line,
  store to box array]{Test}

\begin{tabular}{ll}
\useboxarray{1} & total height of box 1: \boxarraygettotalheight{\mylen}{1} \mylen\\
\useboxarray{2} & total height of box 2: \boxarraygettotalheight{\mylen}{2} \mylen
\end{tabular}
```

Test total height of box 1: 13.59767pt
total height of box 2: 0pt

18.5 Leaflet Example

The following full application example can be used to create leaflets. Obviously, the code can be adapted and customized in many ways.

```
\documentclass[a4paper,landscape]{article}
\usepackage[noheadfoot,margin=0pt]{geometry}
\usepackage[skins,raster,magazine]{tcolorbox}
\usepackage{lipsum}

\newenvironment{leaflet}[1][]{%
  \begin{tcolorbox}[nobeforeafter,empty,colback=white,
    sharp corners,size=minimal,left=10mm,right=10mm,top=10mm,bottom=10mm,
    width=\textwidth/3,
    breakable,
    break at=\textheight,
    height fixed for=all,
    reset box array,
    store to box array,#1]}
  {\end{tcolorbox}%
    \begin{tcbitemize}[raster columns=3,raster equal skip=0pt,blankest]
      \tcbitem\consumeboxarray{5}
      \tcbitem\consumeboxarray{6}
      \tcbitem\consumeboxarray{1}
      \tcbitem\consumeboxarray{2}
      \tcbitem\consumeboxarray{3}
      \tcbitem\consumeboxarray{4}
    \end{tcbitemize}%
  }

\pagestyle{empty}
\begin{document}

\begin{leaflet}[underlay={\node[above=5mm,font=\footnotesize]
    at (frame.south) {- \arabic{tcbbreakpart} -};}]
  \includegraphics[width=\linewidth]{Basilica_5.png}
  \begin{center}
  \bfseries\LARGE Example
  \end{center}

  \section{Introduction}
  \lipsum[1]

  \section{Main Part A}
  \lipsum[2-8]

  \section{Main Part B}
  \lipsum[9-15]

  \section{Conclusion}
  \lipsum[16-18]
\end{leaflet}

\end{document}
```



Example

1 Introduction

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

2 Main Part A

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Ali-

cursus sodales, augue est scelerisque sapien, venenatis congue nulla arcu et pede. Ut suscipit enim vel sapien. Donec congue. Maecenas urna mi, suscipit in, placerat ut, vestibulum ut, massa. Fusce ultrices nulla et nisl.
Etiam ac leo a risus tristique nonummy. Donec dignissim tincidunt nulla. Vestibulum rhoncus molestie odio. Sed lobortis, justo et pretium lobortis, mauris turpis condimentum augue, nec ultricies nibh arcu pretium enim. Nunc purus neque, placerat id, imperdiet sed, pellentesque nec, nisl. Vestibulum imperdiet neque non sem accumsan laoreet. In hac habitasse platea dictumst. Etiam condimentum facilisis libero. Suspendisse in elit quis nisl aliquam dapibus. Pellentesque auctor sapien. Sed egestas sapien nec lectus. Pellentesque vel dui vel neque bibendum viverra. Aliquam porttitor nisl nec pede. Proin mattis libero vel turpis. Donec rutrum mauris et libero. Proin euismod porta felis. Nam lobortis, metus quis elementum commodo, nunc lectus elementum mauris, eget vulputate ligula tellus eu neque. Vivamus eu dolor.
Nulla in ipsum. Praesent eros nulla, congue vitae, euismod ut, commodo a, wisi. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Aenean nonummy magna non leo. Sed felis erat, ullamcorper in, dictum non, ultricies ut, lectus. Proin vel arcu a odio lobortis euismod. Vestibulum ante ipsum primis in faucibus orci luctus et ultrices posuere cubilia Curae; Proin ut est. Aliquam odio. Pellentesque massa turpis, cursus eu, euismod nec, tempor congue, nulla. Duis viverra gravida mauris. Cras tincidunt. Curabitur eros ligula, varius ut, pulvinar in, cursus faucibus, augue.

4 Conclusion

Nulla mattis luctus nulla. Duis commodo velit at leo. Aliquam vulputate magna et leo. Nam vestibulum ullamcorper leo. Vestibulum condimentum rutrum mauris. Donec id mauris. Morbi molestie justo et pede. Vivamus eget turpis sed nisl cursus tempor. Curabitur mollis sapien condimentum nunc. In wisi nisl, malesuada at, dignissim sit amet, lobortis in, odio. Aenean consequat arcu a ante. Pellentesque porta elit sit amet orci. Etiam at turpis nec elit ultricies imperdiet. Nulla facilisi. In hac habitasse platea dictumst. Suspendisse viverra aliquam risus. Nullam pede justo, molestie nonummy, scelerisque eu, facilisis vel, arcu.
Curabitur tellus magna, porttitor a, commodo a, commodo in, tortor. Donec interdum. Praesent scelerisque. Maecenas posuere sodales odio. Vivamus metus lacus, varius quis, imperdiet quis, rhoncus a, turpis. Etiam ligula arcu, elementum a, venenatis quis, sollicitudin sed, metus. Donec nunc pede, tincidunt in, venenatis vitae, faucibus vel, nibh. Pellentesque wisi. Nullam malesuada. Morbi ut tellus ut pede tincidunt porta. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Etiam congue neque id dolor.
Donec et nisl at wisi luctus bibendum. Nam interdum tellus ac libero. Sed sem justo, laoreet vitae, fringilla at, adipiscing ut, nibh. Maecenas non sem quis tortor eleifend fermentum. Etiam id tortor ac mauris porta vulputate. Integer porta neque vitae massa. Maecenas tempus libero a libero posuere dictum. Vestibulum ante ipsum primis in faucibus orci luctus et ultrices posuere cubilia Curae; Aenean quis mauris sed elit commodo placerat. Class aptent taciti sociosqu ad litora torquent per conubia nostra, per inceptos hymenaeos. Vivamus rhoncus tincidunt libero. Etiam elementum pretium justo. Vivamus est. Morbi a tellus eget pede tristique commodo. Nulla nisl. Vestibulum sed nisl eu sapien cursus rutrum.

quam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.
Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.
Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.
Fusce mauris. Vestibulum luctus nibh at lectus. Sed bibendum, nulla a faucibus semper, leo velit ultricies tellus, ac venenatis arcu wisi vel nisl. Vestibulum diam. Aliquam pellentesque, augue quis sagittis posuere, turpis lacus congue quam, in hendrerit risus eros eget felis. Maecenas eget erat in sapien mattis porttitor. Vestibulum porttitor. Nulla facilisi. Sed a turpis eu lacus commodo facilisis. Morbi fringilla, wisi in dignissim interdum, justo lectus sagittis dui, et vehicula libero dui cursus dui. Mauris tempor ligula sed lacus. Duis cursus enim ut augue. Cras ac magna. Cras nulla. Nulla egestas. Curabitur a leo. Quisque egestas wisi eget nunc. Nam feugiat lacus vel est. Curabitur consectetuer.
Suspendisse vel felis. Ut lorem lorem, interdum eu, tincidunt sit amet, laoreet vitae, arcu. Aenean faucibus pede eu ante. Praesent enim elit, rutrum at, molestie non, nonummy vel, nisl. Ut lectus eros, malesuada sit amet, fermentum eu, sodales cursus, magna. Donec eu purus. Quisque vehicula, urna sed ultricies auctor, pede lorem egestas dui, et convallis elit erat sed nulla. Donec luctus. Curabitur et nunc. Aliquam dolor odio, commodo pretium, ultricies non, pharetra in, velit. Integer arcu est, nonummy in, fermentum faucibus, egestas vel, odio. Sed commodo posuere pede. Mauris ut est. Ut quis purus. Sed ac odio. Sed vehicula hendrerit sem. Duis non odio. Morbi ut dui. Sed accumsan risus eget odio. In hac habitasse platea dictumst. Pellentesque non elit. Fusce sed justo eu urna porta tincidunt. Mauris felis odio, sollicitudin sed, volutpat a, ornare ac, erat. Morbi quis dolor. Donec pellentesque, erat ac sagittis semper, nunc dui lobortis purus, quis congue purus metus ultricies tellus. Proin et quam. Class aptent taciti sociosqu ad litora torquent per conubia nostra, per inceptos hymenaeos. Praesent sapien turpis, fermentum vel, eleifend faucibus, vehicula eu, lacus.
Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Donec odio elit, dictum in, hendrerit sit amet, egestas sed, leo. Praesent feugiat sapien aliquet odio. Integer vitae justo. Aliquam vestibulum fringilla lorem. Sed neque lectus, consectetuer at, consectetuer sed, eleifend ac, lectus. Nulla facilisi. Pellentesque eget lectus. Proin eu metus. Sed porttitor. In hac habitasse platea dictumst. Suspendisse eu lectus. Ut mi mi, lacinia sit amet, placerat et, mollis vitae, dui. Sed ante tellus, tristique ut, iaculis eu, malesuada ac, dui. Mauris nibh leo, facilisis non, adipiscing quis, ultrices a, dui.

3 Main Part B

Morbi luctus, wisi viverra faucibus pretium, nibh est placerat odio, nec commodo wisi enim eget quam. Quisque libero justo, consectetuer a, feugiat vitae, porttitor eu, libero. Suspendisse sed mauris vitae elit sollicitudin malesuada. Maecenas ultricies eros sit amet ante. Ut venenatis velit. Maecenas sed mi eget dui varius euismod. Phasellus aliquet volutpat odio. Vestibulum ante ipsum primis in faucibus orci luctus et ultrices posuere cubilia Curae; Pellentesque sit amet pede ac sem eleifend consectetuer. Nullam elementum, urna vel imperdiet sodales, elit ipsum pharetra ligula, ac pretium ante justo a nulla. Curabitur tristique arcu eu metus. Vestibulum lectus. Proin mauris. Proin eu nunc eu urna hendrerit faucibus. Aliquam auctor, pede consequat laoreet varius, eros tellus scelerisque quam, pellentesque hendrerit ipsum dolor sed augue. Nulla nec lacus.
Suspendisse vitae elit. Aliquam arcu neque, ornare in, ullamcorper quis, commodo eu, libero. Fusce sagittis erat at erat tristique mollis. Maecenas sapien libero, molestie et, lobortis in, sodales eget, dui. Morbi ultrices rutrum lorem. Nam elementum ullamcorper leo. Morbi dui. Aliquam sagittis. Nunc placerat. Pellentesque tristique sodales est. Maecenas imperdiet lacinia velit. Cras non urna. Morbi eros pede, suscipit ac, varius vel, egestas non, eros. Praesent malesuada, diam id pretium elementum, eros sem dictum tortor, vel consectetuer odio sem sed wisi.
Sed feugiat. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Ut pellentesque augue sed urna. Vestibulum diam eros, fringilla et, consectetuer eu, nonummy id, sapien. Nullam at lectus. In sagittis ultrices mauris. Curabitur malesuada erat sit amet massa. Fusce blandit. Aliquam erat volutpat. Aliquam euismod. Aenean vel lectus. Nunc imperdiet justo nec dolor.
Etiam euismod. Fusce facilisis lacinia dui. Suspendisse potenti. In mi erat, cursus id, nonummy sed, ullamcorper eget, sapien. Praesent pretium, magna in eleifend egestas, pede pede pretium lorem, quis consectetuer tortor sapien facilisis magna. Mauris quis magna varius nulla scelerisque imperdiet. Aliquam non quam. Aliquam porttitor quam a lacus. Praesent vel arcu ut tortor cursus volutpat. In vitae pede quis diam bibendum placerat. Fusce elementum convallis neque. Sed dolor orci, scelerisque ac, dapibus nec, ultricies ut, mi. Duis nec dui quis leo sagittis commodo.
Aliquam lectus. Vivamus leo. Quisque ornare tellus ullamcorper nulla. Mauris porttitor pharetra tortor. Sed fringilla justo sed mauris. Mauris tellus. Sed non leo. Nullam elementum, magna in

19 Library LIB poster

The main purpose of this library is to support creation of single page posters with `tcolorboxes`.

A `tcbposter` → P. 398 is a `tikzpicture` where `tcolorboxes` can be placed in a column oriented manner using `\posterbox` → P. 403 commands. This base concept is more or less copied from the great `baposter` package.

The LIB raster library, see Section 14 on page 277, can produce similar looking results and may be more appropriate depending on the actual project.

- The LIB raster library has a flow oriented concept, just like a convential text flow. The text flow (box flow) is a merely endless ribbon which gets broken into lines (and paragraphs) and the lines are broken into pages. LIB raster shapes the boxes to convenient sizes to fill lines and pages in a pleasant way.
- The LIB tcbposter library supports a quite free placement of boxes inside a page. Basically, boxes are placed like `nodes` are placed inside a `tikzpicture`. In contrast to LIB raster, this is a *single* page and not a flow of pages. The poster is divided into columns and rows. There is a more or less gentle force to use the columns (or spans of columns) for positioning and sizing while the row placement is completely optional.

The creation of this library was motivated by Ignasi.

! Inside a `tikzpicture` there should be no embedded `tikzpictures`. This rule is violated by the LIB poster library. Be aware that there may be some unwanted interactions between the main `tikzpicture` and the embedded ones inside the `tcolorboxes`.

The library is loaded by a package option or inside the preamble by:

```
\tcbuselibrary{poster}
```

This also loads the libraries LIB skins, see Section 10 on page 148, LIB breakable, see Section 17 on page 363, LIB magazine, see Section 18 on page 387, and LIB fitting, see Section 20 on page 410.

19.1 Overview

Click me to see the tutorial

You get the best overview of the LIB poster library and its facilities, if you look at the **Poster Tutorial** which is part of the `tcolorbox` documentation:
`tcolorbox-tutorial-poster.pdf`

19.2 Main Poster Environment

N 2017-07-03

```
\begin{tcbposter}[⟨options⟩]
  ⟨environment content⟩
\end{tcbposter}
```

This creates a `tikzpicture` environment with suitable additional settings defined by the given ⟨*options*⟩. Basically, `\posterbox` → P. 403 and `posterboxenv` → P. 403 are used to place `tcolorboxes` as nodes into the environment, but additional Ti*k*Z code can also be used. As ⟨*options*⟩ all `/tcb/posterset/` keys may be applied, namely:

- `/tcb/posterset/poster` → P. 400: poster settings like columns, rows, sizes...
- `/tcb/posterset/coverage` → P. 401 and `/tcb/posterset/no coverage` → P. 401: settings for a surrounding `tcolorbox` for background and margins.
- `/tcb/posterset/boxes` → P. 402: style of the `tcolorboxes` used for the poster.
- `/tcb/posterset/fontsize` → P. 402: scaling of used fonts.

```
\begin{tcbposter}[
  poster = {showframe,height=10cm,spacing=2mm},
  boxes  = {beamer,colframe=blue!50!black,colback=blue!50,colupper=yellow!50},
]
\posterbox{name=A,column=3,row=2}{My first box}
\posterbox[adjusted title=Second box]
          {name=B,column=2,span=2,below=A}{My second box}
\posterbox[adjusted title=Third box]
          {name=C,column=2,between=B and bottom}{My third box}
\end{tcbposter}
```



Inside tcbposter→ P. 398, there are several predefined Ti*k*Z nodes. These nodes share a common /tcb/poster/prefix→ P. 400 which is TCBPOSTER@ by default. This prefix is used to discriminate the poster nodes from local nodes of any embedded tikzpicture environment. You will never need this prefix using \posterbox→ P. 403 and its placement options, but if you want to refer to a predefined node using pure Ti*k*Z code. The predefined nodes (shown without prefix) are:

- poster: defines the bounding box of the poster (without the coverage).
- top: top position plus row spacing
- bottom: bottom position minus row spacing
- middle: vertical middle position
- col1, col2, ...: bounding box of column 1, column 2, ...
- row1, row2, ...: bounding box of row 1, row 2, ...

Further nodes are defined using the /tcb/posterloc/name→ P. 404 option.



There are several properties inside a tcbposter→ P. 398 which may be useful for advanced code (skip the following on first reading):

- \tcbposterwidth: Width of the poster (without margins).
- \tcbposterheight: Height of the poster (without margins).
- \tcbpostercolspacing: Column distance.
- \tcbposterrowspacing: Row distance.
- \tcbpostercolumns: Column quantity.
- \tcbposterrows: Row quantity.
- \tcbpostercolwidth: Width of a column.
- \tcbposterrowheight: Height of a row.

N 2017-07-03 \tcbposterset{⟨*options*⟩}

Sets options for every following tcbposter→ P. 398 inside the current TEX group. For example, the numbers for rows and columns may be defined for the whole document by this:

```
\tcbposterset{poster={columns=2,rows=3}}
```

See tcbposter→ P. 398 for all feasible options.

19.3 Poster Settings

N 2017-07-03 **/tcb/posterset/poster=**{⟨*option list*⟩} (style, no default)

This option can be applied inside `tcbposter` → P. 398 and `\tcbposterset` → P. 399 to set the given poster ⟨*option list*⟩, e.g.

```
\tcbposterset{poster={width=20cm,height=15cm}}
```

For the ⟨*option list*⟩, see the following keys.

N 2017-07-03 **/tcb/poster/columns=**⟨*number*⟩ (no default, initially `3`)

Sets the ⟨*number*⟩ of columns for a `tcbposter`.

```
\begin{tcbposter}[
  poster = {showframe,columns=5,rows=2,spacing=1mm,height=4cm},
]
\end{tcbposter}
```



N 2017-07-03 **/tcb/poster/rows=**⟨*number*⟩ (no default, initially `4`)

Sets the ⟨*number*⟩ of rows for a `tcbposter`.

N 2017-07-03 **/tcb/poster/colspacing=**⟨*length*⟩ (no default, initially `4mm`)

Sets ⟨*length*⟩ as distance between columns.

N 2017-07-03 **/tcb/poster/rowspacing=**⟨*length*⟩ (no default, initially `4mm`)

Sets ⟨*length*⟩ as distance between rows.

N 2017-07-03 **/tcb/poster/spacing=**⟨*length*⟩ (style, no default, initially `4mm`)

Sets ⟨*length*⟩ as distance between columns and rows.

N 2017-07-03 **/tcb/poster/showframe=true|false** (default `true`, initially `false`)

Displays a red auxiliary mesh as optical support during poster creation. Also, every `/tcb/posterloc/name` → P. 404 is displayed.

N 2017-07-03 **/tcb/poster/width=**⟨*length*⟩ (no default, initially `\linewidth`)

Sets ⟨*length*⟩ as width of the poster. For a typical poster, this has not to be set manually.

N 2017-07-03 **/tcb/poster/height=**⟨*length*⟩ (no default, initially unset)

Sets ⟨*length*⟩ as height of the poster. For a typical poster, this has not to be set manually, but is set automatically to an appropriate value.

N 2017-07-03 **/tcb/poster/prefix=**⟨*name*⟩ (no default, initially `TCBPOSTER@`)

⟨*name*⟩ is set as prefix for any Ti*k*Z node which is generated automatically by the LIB poster library. This encompasses predefined nodes like `top`, `bottom`, ..., and nodes defined by using `/tcb/posterloc/name` → P. 404. Also, see Section 19.2 on page 398. For a typical poster, this value can stay as it is.

19.4 Coverage

N 2017-07-03 `/tcb/posterset/coverage={`⟨*option list*⟩`}` (style, no default)

This option can be applied inside `tcbposter` → P. 398 and `\tcbposterset` → P. 399 and it adds an optional coverage for the poster which is a surrounding `tcolorbox` with the given ⟨*option list*⟩. Here, margins and background settings for the poster can be given. The *coverage* has several default `tcolorbox` settings suitable for the purpose:

```
enhanced, frame hidden, sharp corners, boxsep=0pt, boxrule=0pt,
top=4mm, bottom=4mm, left=4mm, right=4mm,
toptitle=2mm, bottomtitle=2mm, colback=white
```

The ⟨*option list*⟩ can contain any `tcolorbox` option.

```
\begin{tcbposter}[
  poster   = {showframe,spacing=1mm},
  coverage = {height=5cm,
              interior style={top color=yellow,bottom color=yellow!50!red},
              watermark text={My Poster},watermark color=white,
             },
]
\end{tcbposter}
```



- For a typical poster, the option `/tcb/spread` → P. 88 will use the whole page for the poster coverage.
- Poster margins can be adapted by `/tcb/left` → P. 39, `/tcb/right` → P. 40, `/tcb/top` → P. 42, `/tcb/bottom` → P. 43.
- Poster background can be changed by `/tcb/colback` → P. 27, `/tcb/interior style` → P. 149, `/tcb/interior style image` → P. 150, etc.

N 2017-07-03 `/tcb/posterset/no coverage` (style, no value, initially set)

Removes the surrounding `tcolorbox` completely.

19.5 Common Box Settings

N 2017-07-03 **/tcb/posterset/boxes**={⟨*option list*⟩} (style, no default)

This option can be applied inside tcbposter → P. 398 and \tcbposterset → P. 399 and it is used to set up the style of the tcolorboxes inside the poster. The ⟨*option list*⟩ can contain any tcolorbox option, but box size options are not assumed to be useful here, because the size will be determined by the placement options.

```
\begin{tcbposter}[
  poster   = {spacing=2mm,columns=3,rows=2},
  coverage = {height=5cm,
              interior style={top color=yellow,bottom color=yellow!50!red},
             },
  boxes    = {sharp corners=downhill,arc=3mm,boxrule=1mm,
              colback=white,colframe=cyan,
              title style={left color=black,right color=cyan},
              fonttitle=\bfseries\scshape}
]
  \posterbox[adjusted title=First]{column=1,row=1,span=2}{First box}
  \posterbox[adjusted title=Second]{column=1,row=2,span=2}{Second box}
  \posterbox[adjusted title=Third]{column=3,row=1,rowspan=2}{Third box}
\end{tcbposter}
```



19.6 Font Scaling

N 2017-07-03 **/tcb/posterset/fontsize**=⟨*length*⟩ (style, no default, initially unset)

This option can be applied inside tcbposter → P. 398 and \tcbposterset → P. 399. It uses /tcb/fit basedim → P. 413 and /tcb/fit fontsize macros → P. 414 to redefine \normalsize to ⟨*length*⟩ and all other standard font size macros like \small and \large accordingly. This needs a freely scalable font family like lmodern to work. If /tcb/posterset/fontsize is not applied, there standard font size macros are not changed in any way.

```
\begin{tcbposter}[
  poster   = {spacing=2mm,columns=3,rows=2},
  coverage = {height=5cm,
              interior style={top color=yellow,bottom color=yellow!50!red},
             },
  fontsize = 15pt,   % <--- \normalsize is now 15pt
]
...
```

19.7 Box Placement

N 2017-07-03 `\posterbox[`⟨*options*⟩`]{`⟨*placement*⟩`}{`⟨*box content*⟩`}`

Inside a `tcbposter` → P. 398 environment, this places a `tcolorbox` with additional `tcolorbox` ⟨*options*⟩ and the given ⟨*box content*⟩ at a place determined by ⟨*placement*⟩. All ⟨*placement*⟩ options are described in the following. Note that ⟨*box content*⟩ cannot contain *verbatim* material, see `posterboxenv`.

```
\begin{tcbposter}[
  poster = {showframe,height=4cm,spacing=2mm,rows=2},
  boxes  = {beamer,colframe=blue!50!black,colback=blue!50,colupper=yellow!50},
]
\posterbox[title=My title]{name=A,column=2,row=2}{My first box}
\end{tcbposter}
```



N 2017-07-03 `\begin{posterboxenv}[`⟨*options*⟩`]{`⟨*placement*⟩`}`
⟨*environment content*⟩
`\end{posterboxenv}`

This is the environment version of `\posterbox`, i.e. inside a `tcbposter` → P. 398 environment, this places a `tcolorbox` with additional `tcolorbox` ⟨*options*⟩ and the given ⟨*environment content*⟩ at a place determined by ⟨*placement*⟩. In contrast to `\posterbox`, the ⟨*environment content*⟩ is allowed to contain *verbatim* material. Note that the implementation of `\posterbox` is more efficient than the implementation of `posterboxenv`.

```
\begin{tcbposter}[
  poster = {showframe,height=4cm,spacing=2mm,rows=2},
  boxes  = {size=small,beamer,
            colframe=blue!50!black,colback=blue!50,colupper=yellow!50},
]
\begin{posterboxenv}[title=My title]{name=A,column=2,between=top and bottom}
  My first box.
  \begin{tcblisting}{size=small,colback=yellow!10}
My \textbf{first}
poster listing.
  \end{tcblisting}
\end{posterboxenv}
\end{tcbposter}
```



N 2017-07-03 **/tcb/posterloc/name=⟨*name*⟩** (no default, initially @)

Sets ⟨*name*⟩ as reference for the current \posterbox → P. 403 or posterboxenv → P. 403. A TikZ shape name is constructed automatically as combination of /tcb/poster/prefix → P. 400 and ⟨*name*⟩.

```
\begin{tcbposter}[
  poster = {showframe,height=2.5cm,spacing=2mm,rows=2},
  boxes  = {beamer,colframe=blue!50!black,colback=blue!50,colupper=yellow!50},
]
\posterbox{name=A,column=2,row=2}{My first box}
\node[below right=4mm,fill=yellow] (X) at (TCBPOSTER@poster.north west) {Example A};
\draw[blue,very thick,->] (X) |- (TCBPOSTER@A);
\end{tcbposter}
```



N 2017-07-03 **/tcb/posterloc/column=⟨*number*⟩** (no default, initially 1)

Places the box at the column denoted by ⟨*number*⟩. If /tcb/posterloc/span → P. 405 is not 1, the box is aligned to the left side of column ⟨*number*⟩.

```
\begin{tcbposter}[
  poster = {showframe,height=2.5cm,spacing=2mm,rows=2},
  boxes  = {beamer,colframe=blue!50!black,colback=blue!50,colupper=yellow!50},
]
\posterbox{row=1,column=2,span=2}{First box}
\posterbox{row=2,column=2,span=0.8}{Second box}
\end{tcbposter}
```



N 2017-07-03 **/tcb/posterloc/column*=⟨*number*⟩** (no default, initially unset)

Places the box at the column denoted by ⟨*number*⟩. If /tcb/posterloc/span → P. 405 is not 1, the box is aligned to the right side of column ⟨*number*⟩.

```
\begin{tcbposter}[
  poster = {showframe,height=2.5cm,spacing=2mm,rows=2},
  boxes  = {beamer,colframe=blue!50!black,colback=blue!50,colupper=yellow!50},
]
\posterbox{row=1,column*=2,span=2}{First box}
\posterbox{row=2,column*=2,span=0.8}{Second box}
\end{tcbposter}
```



N 2017-07-03 **/tcb/posterloc/span=⟨*number*⟩** (no default, initially 1)

Sets the width of the current box to span ⟨*number*⟩ columns. ⟨*number*⟩ is also allowed to be a real number like 0.5 or 1.7. See /tcb/posterloc/column → P. 404 and /tcb/posterloc/column* → P. 404 for examples.

N 2017-07-03 **/tcb/posterloc/row=⟨*number*⟩** (no default, initially unset)

If this option is applied, the box is placed at the row denoted by ⟨*number*⟩. Also, the height is set as fixed according to /tcb/posterloc/rowspan.

```
\begin{tcbposter}[
  poster = {showframe,height=2.5cm,spacing=2mm,rows=2},
  boxes  = {beamer,colframe=blue!50!black,colback=blue!50,colupper=yellow!50},
]
\posterbox{row=1,column=1}{First box}
\posterbox{row=1,column=2,rowspan=2}{Second box}
\posterbox[natural height]{row=1,column=3}{Third box}
\end{tcbposter}
```



N 2017-07-03 **/tcb/posterloc/rowspan=⟨*number*⟩** (no default, initially 1)

Sets the height of the current box to span ⟨*number*⟩ rows. ⟨*number*⟩ is also allowed to be a real number like 0.5 or 1.7.

```
\begin{tcbposter}[
  poster = {showframe,height=2.5cm,spacing=2mm,rows=2},
  boxes  = {beamer,colframe=blue!50!black,colback=blue!50,colupper=yellow!50},
]
\posterbox{row=1,column=1,rowspan=0.9}{First box}
\posterbox{row=1,column=2,rowspan=1.5}{Second box}
\posterbox{row=1,column=3,rowspan=2}{Third box}
\end{tcbposter}
```



N 2017-07-03 **/tcb/posterloc/fixed height** (no value, initially 0pt)

Sets the height of the current box span rows as denoted by /tcb/posterloc/rowspan. This can be used, if not /tcb/posterloc/row, but another height placement option is applied.

N 2017-07-03 **/tcb/posterloc/below=⟨*name*⟩** (no default, initially `top`)

The box is placed below another box with the given ⟨*name*⟩. Also, ⟨*name*⟩ can be a predefined node, see Section 19.2 on page 398.

```
\begin{tcbposter}[
  poster = {showframe,height=3cm,spacing=2mm,rows=2},
  boxes  = {beamer,colframe=blue!50!black,colback=blue!50,colupper=yellow!50},
]
\posterbox{name=A,column=1,below=top}{First box}
\posterbox{name=B,column=1,below=A}{Second box}
\posterbox{name=C,column=2,below=B}{Third box}
\posterbox{name=D,column=3,below=row1}{Fourth box}
\end{tcbposter}
```



N 2017-07-03 **/tcb/posterloc/above=⟨*name*⟩** (no default, initially unset)

The box is placed above another box with the given ⟨*name*⟩. Also, ⟨*name*⟩ can be a predefined node, see Section 19.2 on page 398.

```
\begin{tcbposter}[
  poster = {showframe,height=3cm,spacing=2mm,rows=2},
  boxes  = {beamer,colframe=blue!50!black,colback=blue!50,colupper=yellow!50},
]
\posterbox{name=A,column=1,above=bottom}{First box}
\posterbox{name=B,column=1,above=A}{Second box}
\posterbox{name=C,column=2,above=B}{Third box}
\posterbox{name=D,column=3,above=row2}{Fourth box}
\end{tcbposter}
```



N 2017-07-03 **/tcb/posterloc/at=⟨*name*⟩** (no default, initially unset)

The box is placed at the position with the given ⟨*name*⟩. This is quite likely a predefined node, see Section 19.2 on page 398.

```
\begin{tcbposter}[
  poster = {showframe,height=3cm,spacing=2mm,rows=2},
  boxes  = {beamer,colframe=blue!50!black,colback=blue!50,colupper=yellow!50},
]
\posterbox{name=A,column=1,at=middle}{First box}
\posterbox{name=B,column=2,at=row1}{Second box}
\end{tcbposter}
```



N 2017-07-03 **/tcb/posterloc/between=⟨*name1*⟩ and ⟨*name2*⟩** (no default, initially unset)

The box is placed below a box ⟨*name1*⟩ and above another box ⟨*name2*⟩. Also, ⟨*name1*⟩ and ⟨*name2*⟩ can be predefined nodes, see Section 19.2 on page 398.

```
\begin{tcbposter}[
  poster = {showframe,height=3cm,spacing=2mm,rows=2},
  boxes  = {beamer,colframe=blue!50!black,colback=blue!50,colupper=yellow!50},
]
\posterbox{name=A,column=1,below=top}{First box}
\posterbox{name=B,column=1,between=A and bottom}{Second box}
\posterbox{name=C,column=2,above=bottom}{Third box}
\posterbox{name=D,column=2,between=top and C,span=2}{Fourth box}
\posterbox{name=E,column=3,between=D and bottom}{Fifth box}
\end{tcbposter}
```



N 2017-07-03 **/tcb/posterloc/sequence**=⟨*sequence*⟩ (no default, initially unset)

The box is broken into partial boxes. These partial boxes are placed following the given ⟨*sequence*⟩ of placements. The feasible syntax for the ⟨*sequence*⟩ is:

⟨*column a*⟩ `between` ⟨*name a1*⟩ `and` ⟨*name a2*⟩ `then`
⟨*column b*⟩ `between` ⟨*name b1*⟩ `and` ⟨*name b2*⟩ `then`
⟨*column c*⟩ `between` ⟨*name c1*⟩ `and` ⟨*name c2*⟩ `then`...

Obviously, this places the first part box at ⟨*column a*⟩ between ⟨*name a2*⟩ and ⟨*name a2*⟩. The second box part is placed at ⟨*column b*⟩ between ⟨*name b2*⟩ and ⟨*name b2*⟩, and so on.

```
\begin{tcbposter}[
  poster = {showframe,height=6cm,spacing=2mm,rows=2},
  boxes  = {beamer,colframe=blue!50!black,colback=blue!50,colupper=yellow!50},
]
\posterbox[adjusted title=A]{name=A,column=1,below=top,span=2}{First box}
\posterbox{name=B,column=2,above=bottom,span=2}{Second box}
\posterbox[adjusted title=C,colframe=red!50!black,colback=red!50]{
  name=C, sequence=1 between A and bottom then
                  2 between A and B then
                  3 between top and B
  }{\lipsum[2]}
\end{tcbposter}
```



N 2017-07-03 **/tcb/placeholder** (style, no value)

If the box content of a /tcb/posterloc/sequence is too short to fill all reserved box parts, the empty boxes are drawn with the /tcb/placeholder style. This style can be redefined, e.g. to /tcb/blankest → P. 239, if nothing should be drawn for empty boxes.

```
\begin{tcbposter}[
  poster = {showframe,height=2.5cm,spacing=2mm,rows=2},
  boxes  = {beamer,colframe=blue!50!black,colback=blue!50,colupper=yellow!50},
]
\posterbox{name=A,column=1,below=top,span=2}{First box}
\posterbox[colframe=red!50!black,colback=red!50]{
  name=B, sequence=1 between A and bottom then
                  2 between A and bottom then
                  3 between top and bottom
  }{Second box followed by placeholder boxes}
\end{tcbposter}
```



N 2017-07-03 **/tcb/posterloc/xshift=⟨*length*⟩** (no default, initially 0pt)

Horizontal shift of a box by ⟨*length*⟩.

```
\begin{tcbposter}[
  poster = {showframe,height=3cm,spacing=2mm,rows=2},
  boxes  = {beamer,colframe=blue!50!black,colback=blue!50,colupper=yellow!50},
]
\posterbox{name=A,column=1,row=1,xshift=6mm}{First box}
\posterbox{name=B,column=2,row=2,xshift=-6mm}{Second box}
\end{tcbposter}
```



N 2017-07-03 **/tcb/posterloc/yshift=⟨*length*⟩** (no default, initially 0pt)

Vertical shift of a box by ⟨*length*⟩.

```
\begin{tcbposter}[
  poster = {showframe,height=3cm,spacing=2mm,rows=2},
  boxes  = {beamer,colframe=blue!50!black,colback=blue!50,colupper=yellow!50},
]
\posterbox{name=A,column=1,row=1,yshift=-4mm}{First box}
\posterbox{name=B,column=2,row=2,yshift=4mm}{Second box}
\end{tcbposter}
```



The library is loaded by a package option or inside the preamble by:

```
\tcbuselibrary{fitting}
```

20.1 Macros of the Library

`\tcboxfit[⟨options⟩]{⟨box content⟩}`

Creates a colored box where the given ⟨*box content*⟩ is fitted to the width and height of the box. A `tcboxfit` has to have a fixed height. If no fixed height is given, a square box is constructed. In principle, most ⟨*options*⟩ for a `tcolorbox` → P. 12 can be used for `\tcboxfit` with some restrictions. A `\tcboxfit` cannot have a lower part and cannot be broken.

```
% \usepackage{lipsum} \tcbuselibrary{raster}
\tcbset{colframe=blue!50!black,colback=red!10!white,
    boxsep=0pt,top=1mm,bottom=1mm,left=1mm,right=1mm,
    fit algorithm=hybrid*,raster equal skip=1mm}
\begin{tcbraster}[raster columns=3,raster valign=bottom]
  \tcboxfit[height=8cm]{\lipsum[1]}
  \tcboxfit[height=4cm]{\lipsum[1]}
  \tcboxfit[height=2cm]{\lipsum[1]}
\end{tcbraster}
\begin{tcbraster}[colback=green!10!white,boxsep=1mm]
  \tcboxfit[height=4cm]{\lipsum[2]}
  \tcboxfit[height=4cm,title=With a title]{\lipsum[2]}
\end{tcbraster}
```

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

With a title

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

See Section 22.6 on page 444 for more elaborate methods to create new commands.

\newtcboxfit[⟨*init options*⟩]{\⟨*name*⟩}[⟨*number*⟩][⟨*default*⟩]{⟨*options*⟩}

Creates a new macro \⟨*name*⟩ based on \tcboxfit→ P. 410. Basically, **\newtcboxfit** operates like **\newcommand**. The new macro \⟨*name*⟩ optionally takes ⟨*number*⟩+1 arguments, where ⟨*default*⟩ is the default value for the optional first argument. The ⟨*options*⟩ are given to the underlying **tcboxfit**. The ⟨*init options*⟩ allow setting up automatic numbering, see Section 5 from page 108.

```
\newtcboxfit{\mybox}{colback=red!5!white,
  colframe=red!75!black,width=4cm,
  height=1.5cm,halign=center}

\mybox{This is my own box.}\par
\mybox{This is my own box with more text
       to be written.}
```




```
% \usepackage{lipsum}
\newtcboxfit{\mybox}[2]{colback=red!5!white,
  colframe=red!75!black,fonttitle=\bfseries,
  boxsep=1mm,left=0mm,right=0mm,top=0mm,
  bottom=0mm,halign=center,valign=center,
  nobeforeafter,width=#1,height=#2}

\mybox{2.5cm}{1cm}{First box}%
\mybox{2.5cm}{1cm}{Second box with more text}\\
\mybox{5cm}{2cm}{Third box with text}\\
\mybox{5cm}{3cm}{\lipsum[1]}
```




```
% \usepackage{lipsum}
\newtcboxfit{\mybox}[2][]{colback=red!5!white,
  colframe=red!75!black,
  width=#2,height=#2/3*2,#1}

\mybox[colback=yellow]{5cm}%
  {\lipsum[2]}
```



\renewtcboxfit[⟨*init options*⟩]{\⟨*name*⟩}[⟨*number*⟩][⟨*default*⟩]{⟨*options*⟩}

Operates like \newtcboxfit, but based on **\renewcommand** instead of **\newcommand**. An existing macro is redefined.

\tcbfontsize{⟨*factor*⟩}

Selects a font size inside a tcolorbox which is scaled with the given ⟨*factor*⟩ relative to **\tcbfitdim**.

```
\tcbset{colback=red!5!white,colframe=red!75!black}
\begin{tcolorbox}[fit basedim=10pt]
  {\tcbfontsize{0.25} Very tiny,}\\
  {\tcbfontsize{0.5} Small,}\\
  {\tcbfontsize{1} Normal,}\\
  {\tcbfontsize{2} Large,}\\
  {\tcbfontsize{4} Huge.}
\end{tcolorbox}
```

20.2 Option Keys of the Library

The font size for the content of a box with fixed width and fixed height can be adjusted automatically. This is called the *fitbox capture mode*. Note that the fit control algorithm constructs a series of versions for the box and selects the 'best'. Therefore, the compilation time is quite longer than for a normal box. The algorithm will fail, if a different selected font size does not change the overall size of the box content. The `\tcboxfit` → P. 410 macro uses this algorithm by default.

> **!** The fit control keys are only applicable to unbreakable boxes without a lower part. The box content should not change counters.

`/tcb/fit` (style, initially unset)

Sets the `/tcb/capture` → P. 94 mode to `fitbox`, i. e. enables the font size adjustment algorithm. Thereby, a `tcolorbox` → P. 12 acts like `\tcboxfit` → P. 410 where the given ⟨*box content*⟩ is fitted to the width and height of the box. Therefore, the box has to have a fixed height. If no fixed height is given, a square box is constructed. The font dimension **`\tcbfitdim`** can also be used to adjust the margins of the box since a box with a tiny font may not need large margins. The number of constructed boxes is saved to the macro **`\tcbfitsteps`** for analysis.

```
% \usepackage{lipsum}
% \tcbuselibrary{skins}
\newtcolorbox{fitting}[2][]{fit,height=#2,boxsep=1pt,valign=center,opacityupper=0.5,
  top=0.4\tcbfitdim,bottom=0.4\tcbfitdim,left=0.75\tcbfitdim,right=0.75\tcbfitdim,
  enhanced,watermark text={\tcbfitsteps},colframe=blue!75!black,colback=white,#1}

\begin{fitting}{4cm}
\lipsum[1]
\end{fitting}

\begin{fitting}{2cm}
\lipsum[2]
\end{fitting}

\begin{fitting}{1cm}
\lipsum[3]
\end{fitting}
```

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

/tcb/fit to=⟨*width*⟩ and ⟨*height*⟩ (style, initially unset)

Shortcut for using /tcb/fit → P. 412 and setting the ⟨*width*⟩ and ⟨*height*⟩ values separately.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[fit to=3cm and 2cm]
  This box content is fitted to the given
  dimensions.
\end{tcolorbox}
```



/tcb/fit to height=⟨*height*⟩ (style, initially unset)

Shortcut for using /tcb/fit → P. 412 and setting the ⟨*height*⟩ value separately.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[fit to height=2cm]
  This box content is fitted to the given
  height.
\end{tcolorbox}
```



/tcb/fit basedim=⟨*length*⟩ (no default, initially 10pt)

Sets the starting font dimension for the font size adjustment algorithm to ⟨*length*⟩. The algorithm never enlarges this dimension.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[fit to=4cm and 2cm]
  Too few words for the box.
\end{tcolorbox}

\begin{tcolorbox}[fit to=4cm and 2cm,
  fit basedim=50pt]
  Enough words for the box.
\end{tcolorbox}
```



/tcb/fit skip=⟨*real value*⟩ (no default, initially 1.2)

Sets the skip value of the selected font to ⟨*real value*⟩ times \tcbfitdim.

```
% \usepackage{lipsum}
\tcbset{colback=red!5!white,
  colframe=red!75!black,left=1mm,
  right=1mm,boxsep=0mm}

\begin{tcolorbox}[fit to=5cm and 4cm,
  fit skip=1.0  ]
  \lipsum[1]
\end{tcolorbox}
```



/tcb/fit fontsize macros (style, initially unset)

Redefines the standard LaTeX font size macros `\tiny`, `\scriptsize`, `\footnotesize`, `\small`, `\normalsize`, `\large`, `\Large`, `\LARGE`, `\huge`, and `\Huge`, to set font sizes relative to the current `\tcbfitdim`. Note that the display skip values for mathematical formulas are respected by the redefined macros.

```
% \usepackage{lipsum}
\tcbset{colback=red!5!white,
  colframe=red!75!black,left=1mm,
  right=1mm,boxsep=0mm}

\begin{tcolorbox}[fit to height=4cm]
  {\Large\bfseries This text is
              not adapted:\par}
  \lipsum[2]
\end{tcolorbox}

\begin{tcolorbox}[fit to height=4cm,
  fit fontsize macros ]
  {\Large\bfseries This text is adapted:\par}
  \lipsum[2]
\end{tcolorbox}
```

This text is not adapted:

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

This text is adapted:

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

```
\tcbset{colback=red!5!white,
  colframe=red!75!black,left=1mm,
  right=1mm,boxsep=0mm}

\let\realHuge=\Huge

\begin{tcolorbox}[fit basedim=7pt,
  fontupper=\normalsize,
  fit fontsize macros]
The relative relative font size macros
are also usable without the
\textit{fit} algorithm.\par
{\Huge Adapted Huge} ---
{\realHuge Original Huge}
\end{tcolorbox}
```

The relative relative font size macros are also usable without the *fit* algorithm.

Adapted Huge — Original Huge

```
\tcbset{size=fbox,colback=red!5!white,
  colframe=red!75!black}

\tcboxfit[height=5cm,
  fit fontsize macros,
  fonttitle=\normalsize\bfseries,
  title=Adapted title]
{\lipsum[2]}
```

Adapted title

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

`/tcb/fit height plus=`⟨*dimension*⟩ (no default, initially `0pt`)

The box is allowed to enlarge the fixed height up to the given ⟨*dimension*⟩, before a font size fit is applied. An optional `/tcb/fit width plus` is tried after the height adaption.

```
% \usepackage{lipsum}
\tcbset{colback=red!5!white,colframe=red!75!black,left=1mm,top=1mm,bottom=1mm,
  right=1mm,boxsep=0mm,width=3cm,height=3cm,nobeforeafter}

\begin{tcolorbox}[fit]
This is a tcolorbox.
\end{tcolorbox}
\begin{tcolorbox}[fit,fit height plus=1cm]
This is a tcolorbox.
\end{tcolorbox}
\begin{tcolorbox}[fit]
\lipsum[2]
\end{tcolorbox}
\begin{tcolorbox}[fit,fit height plus=1cm]
\lipsum[2]
\end{tcolorbox}
```



`/tcb/fit width plus=`⟨*dimension*⟩ (no default, initially `0pt`)

The box is allowed to enlarge the fixed width up to the given ⟨*dimension*⟩, before a font size fit is applied. An optional `/tcb/fit height plus` is tried before the width adaption.

```
% \usepackage{lipsum}
\tcbset{colback=red!5!white,colframe=red!75!black,left=1mm,top=1mm,bottom=1mm,
  right=1mm,boxsep=0mm,width=3cm,height=3cm,nobeforeafter}

\begin{tcolorbox}[fit]
This is a tcolorbox.
\end{tcolorbox}
\begin{tcolorbox}[fit,fit width plus=1cm]
This is a tcolorbox.
\end{tcolorbox}
\begin{tcolorbox}[fit]
\lipsum[2]
\end{tcolorbox}
\begin{tcolorbox}[fit,fit width plus=1cm]
\lipsum[2]
\end{tcolorbox}
```



! Typically but not necessarily, the optional title of a `tcolorbox` is not part of the fit operation. If a `/tcb/fit width plus` is applied, the title is also adapted to the new width. If counters are increased inside the title text, they may be increased more than one time. To avoid this, you are encouraged to use `/tcb/phantom` → P. 98 or `/tcb/step and label` → P. 98 to set counters or use automatic numbering, see Subsection 5.1 from page 108.

`/tcb/fit width from=`⟨*min*⟩ `to` ⟨*max*⟩ (style, no default)

Sets the box width to ⟨*min*⟩ and allows the width to grow up to ⟨*max*⟩.

```
% \usepackage{lipsum}
\tcbset{colback=red!5!white,colframe=red!75!black,left=1mm,top=1mm,bottom=1mm,
  right=1mm,boxsep=0mm,height=4cm}

\begin{tcolorbox}[fit,width=\linewidth/2]
\lipsum[2]
\end{tcolorbox}\par
\begin{tcolorbox}[fit width from=\linewidth/2 to \linewidth]
\lipsum[2]
\end{tcolorbox}\par
```

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

`/tcb/fit height from=`⟨*min*⟩ `to` ⟨*max*⟩ (style, no default)

Sets the box height to ⟨*min*⟩ and allows the height to grow up to ⟨*max*⟩.

```
% \usepackage{lipsum}
\newtcolorbox{mybox}{colback=red!5!white,colframe=red!75!black,left=1mm,top=1mm,
  bottom=1mm,right=1mm,boxsep=0mm,width=4cm,nobeforeafter,
  fit height from=1cm to 8cm}

\begin{mybox}
This is a tcolorbox.
\end{mybox}
\begin{mybox}
This is a tcolorbox. This is a tcolorbox. This is a tcolorbox.
\end{mybox}
\begin{mybox}
\lipsum[2]
\end{mybox}
```



`/tcb/fit algorithm=`⟨*name*⟩ (no default, initially `fontsize`)

Sets the algorithm for the fitting process *after* optionally width and height are adapted. Feasible values for ⟨*name*⟩ are:

- `fontsize` (initial): The algorithm is a bisection method that adapts the font size until certain stop conditions are fulfilled. This is the most time-consuming method but it is robust and gives pleasant results.

  > ! The used font has to be freely scalable for this method! Other content than text is not scaled down. The aspect ratio is fully garanteed.

N 2014-10-29

- `fontsize*`: First, the `fontsize` algorithm is applied. If the font was scaled down and the resulting height is too small, the box is squeezed to fit the area.

  > ! The used font has to be freely scalable for this method! Other content than text may be slightly rescaled. The aspect ratio cannot be fully garanteed.

- `areasize`: The algorithm calculates the area size for the text without scaling the font. The text box is shaped for the needed aspect ratio in one or two steps. Finally, it is scaled down with a standard `\resizebox` macro.

  > ! The used font has not to be scalable. Every box content is scaled down. The aspect ratio cannot be fully garanteed.

N 2014-10-29

- `areasize*`: The `areasize` algorithm is applied, but if the content was scaled down and the resulting height is too small, the box is squeezed to fit the area.

  > ! The used font has not to be scalable. Every box content is scaled down. The aspect ratio cannot be fully garanteed.

- `hybrid`: First, this algorithm estimates the needed font size in one or two steps. Then an `areasize` fitting as above is a applied.

  > ! The used font has to be freely scalable for this method! Other content than text may be slightly rescaled. The aspect ratio cannot be fully garanteed.

N 2014-10-29

- `hybrid*`: First, this algorithm estimates the needed font size in one or two steps. Then an `areasize*` fitting as above is a applied.

  > ! The used font has to be freely scalable for this method! Other content than text may be slightly rescaled. The aspect ratio cannot be fully garanteed.

- `squeeze`: The text box is brutally scaled down to fit.

  > ! The aspect ratio is very likely to be horrible. You should not use this method for final documents.

```
% \usepackage{lipsum}
\newtcboxfit{mybox}[1]{colback=red!5!white,colframe=red!75!black,left=1mm,top=1mm,
  bottom=1mm,right=1mm,boxsep=0mm,width=3.5cm,height=7cm,nobeforeafter,
  before upper=\textcolor{blue}{\rule{5mm}{5mm}}\ ,
  enhanced,watermark text={\tcbfitsteps},
  fonttitle=\bfseries,adjusted title=#1,fit algorithm=#1}

\mybox{fontsize}{\lipsum[2]}\hfill
\mybox{hybrid}{\lipsum[2]}\hfill
\mybox{areasize}{\lipsum[2]}\hfill
\mybox{squeeze}{\lipsum[2]}

Quality \dotfill versus \dotfill Speed
```

fontsize

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

hybrid

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

areasize

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

squeeze

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Quality . . . . . versus . . . . . Speed

```
% \usepackage{lipsum}
\newtcboxfit{mybox}[2]{colback=red!5!white,colframe=red!75!black,left=1mm,top=1mm,
  size=tight,width=7.2cm,height=5cm,nobeforeafter,
  before upper=\textcolor{blue}{\rule{5mm}{5mm}}\ ,
  enhanced,fonttitle=\bfseries,adjusted title=#2,fit algorithm=#1}

\mybox{hybrid}{hybrid (possible gap at end)}{\lipsum[1]}\hfill
\mybox{hybrid*}{hybrid* (no gap but possibly squeezed)}{\lipsum[1]}
```

hybrid (possible gap at end)

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

hybrid* (no gap but possibly squeezed)

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

! The following options set control parameters for the fit algorithm. Mainly, they apply to the `fontsize` variant, see `/tcb/fit algorithm` → P. 418. The options should be seen as experimental and are likely to change in future versions, if necessary.

`/tcb/fit maxstep`=⟨*number*⟩ (no default, initially `20`)
Sets the maximal step size for the font size adjustment algorithm. In normal situations, the algorithm stops before reaching the intial value of 20 steps. If the box content does not shrink, this value prevents an endless loop.

`/tcb/fit maxfontdiff`=⟨*dimension*⟩ (no default, initially `0.1pt`)
The algorithm stops, if the font size is determined within a deviation of ⟨*dimension*⟩.

`/tcb/fit maxfontdiffgap`=⟨*dimension*⟩ (no default, initially `1pt`)
The algorithm stops, if the number of lines is determined and the font size is determined within a deviation of ⟨*dimension*⟩.

`/tcb/fit maxwidthdiff`=⟨*dimension*⟩ (no default, initially `1pt`)
The algorithm stops, if the (optionally) flexible box width is determined within a deviation of ⟨*dimension*⟩.

`/tcb/fit maxwidthdiffgap`=⟨*dimension*⟩ (no default, initially `10pt`)
The algorithm stops, if the number of lines is determined and the (optionally) flexible box width is determined within a deviation of ⟨*dimension*⟩.

`/tcb/fit warning`=⟨*value*⟩ (no default, initially `off`)
Typically, the fit control algorithm constructs several auxiliary boxes to determine the optimal one. If not switched off, the construction of the auxiliary boxes may produce many `hbox` warnings. This option key changes the `\hbadness` value.

- `off`: Most of `'Underfull \hbox'` and `'Overfull \hbox'` warnings are switched off (including the ones for the finally used box).
- `on`: All warnings for all auxiliary boxes are displayed.
- `final`: Only warnings for the finally used box are displayed. Note that an additional box has to be contructed for theses messages.

21 Library LIB hooks

The library is loaded by a package option or inside the preamble by:

```
\tcbuselibrary{hooks}
```

For the skin related options, the library LIB skins has to be loaded separately.

21.1 Concept of Hooks

A hook is a placeholder in some LaTeX code where additional code can be added. For example, the LaTeX macro `\AtBeginDocument` adds code to a hook which is placed at the beginning of every document.

Several option keys of `tcolorbox` allow providing some code which is added to specific places of a colored box. For example, `/tcb/before upper` → P. 65 places code before the content of the upper part. A following usage of this key overwrites any prior settings.

The library LIB hooks extends `/tcb/before upper` → P. 65 and several more existing keys to 'hookable' versions, e. g. `/tcb/before upper app` → P. 423 and `/tcb/before upper pre` → P. 423. The 'hookable' keys don't overwrite prior settings but either *app*end or *pre*pend the newly given code to the existing code.

The general naming convention (with some small exceptions) is:

- ⟨*option key*⟩ `app`: works like ⟨*option key*⟩ but *app*ends its code to the existing code.
- ⟨*option key*⟩ `pre`: works like ⟨*option key*⟩ but *pre*pends its code to the existing code.

If the original ⟨*option key*⟩ is used (again), all code will be overwritten. Therefore, the order of the option key usage is crucial.

```
% \usepackage{array,tabularx}
\newcolumntype{Y}{>{\raggedleft\arraybackslash}X}% see tabularx
\tcbset{enhanced,fonttitle=\bfseries\large,fontupper=\normalsize\sffamily,
  colback=yellow!10!white,colframe=red!50!black,colbacktitle=Salmon!30!white,
  coltitle=black,center title,
  tabularx={X||Y|Y|Y|Y||Y},% this sets 'before upper' and 'after upper'
  before upper app={Group & One & Two & Three & Four & Sum\\\hline\hline}  }

\begin{tcolorbox}[title=My table]
Red   & 1000.00 & 2000.00 &  3000.00 &  4000.00 & 10000.00\\\hline
Green & 2000.00 & 3000.00 &  4000.00 &  5000.00 & 14000.00\\\hline
Blue  & 3000.00 & 4000.00 &  5000.00 &  6000.00 & 18000.00\\\hline\hline
Sum   & 6000.00 & 9000.00 & 12000.00 & 15000.00 & 42000.00
\end{tcolorbox}
```

My table

Group	One	Two	Three	Four	Sum
Red	1000.00	2000.00	3000.00	4000.00	10000.00
Green	2000.00	3000.00	4000.00	5000.00	14000.00
Blue	3000.00	4000.00	5000.00	6000.00	18000.00
Sum	6000.00	9000.00	12000.00	15000.00	42000.00

21.2 Box Content Additions

The following option keys extend the options given in Subsection 4.11 from page 64.

/tcb/before title app=⟨*code*⟩ (no default)
Appends the given ⟨*code*⟩ to /tcb/before title → P. 64 *after* the color and font settings and *before* the content of the title.

/tcb/before title pre=⟨*code*⟩ (no default)
Prepends the given ⟨*code*⟩ to /tcb/before title → P. 64 *after* the color and font settings and *before* the content of the title.

/tcb/after title app=⟨*code*⟩ (no default)
Appends the given ⟨*code*⟩ to /tcb/after title → P. 64 *after* the content of the title.

/tcb/after title pre=⟨*code*⟩ (no default)
Prepends the given ⟨*code*⟩ to /tcb/after title → P. 64 *after* the content of the title.

/tcb/before upper app=⟨*code*⟩ (no default)
Appends the given ⟨*code*⟩ to /tcb/before upper → P. 65 *after* the color and font settings and *before* the content of the upper part.

/tcb/before upper pre=⟨*code*⟩ (no default)
Prepends the given ⟨*code*⟩ to /tcb/before upper → P. 65 *after* the color and font settings and *before* the content of the upper part.

/tcb/after upper app=⟨*code*⟩ (no default)
Appends the given ⟨*code*⟩ to /tcb/after upper → P. 65 *after* the content of the upper part.

/tcb/after upper pre=⟨*code*⟩ (no default)
Prepends the given ⟨*code*⟩ to /tcb/after upper → P. 65 *after* the content of the upper part.

```
% \tcbuselibrary{theorems}
\tcbset{ams align,%  this sets 'before upper' and 'after upper'
  colback=yellow!10!white,colframe=red!50!black,
  before upper app={\frac{2}{\sqrt{2}}&=\sqrt{2}.\\},
  after upper pre={\\\sin\left(\frac{\pi}{2}\right)&=1.},
}

\begin{tcolorbox}
  \sum\limits_{n=1}^{\infty} \frac{1}{n} &= \infty.\\
  \int x^2 ~\text{d}x &= \frac13 x^3 + c.
\end{tcolorbox}
```

$$\frac{2}{\sqrt{2}} = \sqrt{2}. \tag{22}$$

$$\sum_{n=1}^{\infty} \frac{1}{n} = \infty. \tag{23}$$

$$\int x^2 \, \mathrm{d}x = \frac{1}{3}x^3 + c. \tag{24}$$

$$\sin\left(\frac{\pi}{2}\right) = 1. \tag{25}$$

`/tcb/before lower app=`⟨*code*⟩ (no default)
Appends the given ⟨*code*⟩ to `/tcb/before lower` → P. 66 *after* the color and font settings and *before* the content of the lower part.

`/tcb/before lower pre=`⟨*code*⟩ (no default)
Prepends the given ⟨*code*⟩ to `/tcb/before lower` → P. 66 *after* the color and font settings and *before* the content of the lower part.

`/tcb/after lower app=`⟨*code*⟩ (no default)
Appends the given ⟨*code*⟩ to `/tcb/after lower` → P. 66 *after* the content of the lower part.

`/tcb/after lower pre=`⟨*code*⟩ (no default)
Prepends the given ⟨*code*⟩ to `/tcb/after lower` → P. 66 *after* the content of the lower part.

21.3 Embedding into the Surroundings

The following option keys extend the options given in Subsection 4.14 from page 78.



The 'hookable' versions are usable inside the document. In the preamble, they can only be used after explicit setting of `/tcb/before` → P. 78 and `/tcb/after` → P. 78 or by e. g. `/tcb/parskip` → P. 78.

`/tcb/before app=`⟨*code*⟩ (no default)
Appends the given ⟨*code*⟩ to `/tcb/before` → P. 78 before the colored box.

`/tcb/before pre=`⟨*code*⟩ (no default)
Prepends the given ⟨*code*⟩ to `/tcb/before` → P. 78 before the colored box.

`/tcb/after app=`⟨*code*⟩ (no default)
Appends the given ⟨*code*⟩ to `/tcb/after` → P. 78 after the colored box.

`/tcb/after pre=`⟨*code*⟩ (no default)
Prepends the given ⟨*code*⟩ to `/tcb/after` → P. 78 after the colored box.

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[title=My title,before app={The box follows:\\[4pt]},
  after app={This is the end.}]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

The box follows:

My title

This is a **tcolorbox**.

This is the end.

21.4 Overlays

The following option keys extend the options given in Subsection 4.12 from page 71.

/tcb/overlay app=⟨*graphical code*⟩ (no default)

Appends the given ⟨*graphical code*⟩ to /tcb/overlay→ P. 71.

```
% \usetikzlibrary{patterns} % preamble
% \tcbuselibrary{skins} % preamble
\tcbset{frogbox/.style={enhanced,colback=green!10,colframe=green!65!black,
  enlarge top by=5.5mm,
  overlay={\foreach \x in {2cm,3.5cm} {
    \begin{scope}[shift={([xshift=\x]frame.north west)}]
      \path[draw=green!65!black,fill=green!10,line width=1mm] (0,0) arc (0:180:5mm);
      \path[fill=black] (-0.2,0) arc (0:180:1mm);
    \end{scope}}}]}}
\tcbset{ribbon/.style={overlay app={%
  \path[fill=blue!75!white,draw=blue,double=white!85!blue,
    preaction={opacity=0.6,fill=blue!75!white},
    line width=0.1mm,double distance=0.2mm,
    pattern=fivepointed stars,pattern color=white!75!blue]
    ([xshift=-0.2mm,yshift=-1.02cm]frame.north east)
    -- ++(-1,1) -- ++(-0.5,0) -- ++(1.5,-1.5) -- cycle;}}}

\begin{tcolorbox}[frogbox,title=My title]
This is a \textbf{tcolorbox}.
\end{tcolorbox}

\begin{tcolorbox}[frogbox,ribbon,title=My title]
This is a \textbf{tcolorbox}.\par
Here, we apply a second overlay.
\end{tcolorbox}
```

/tcb/overlay pre=⟨*graphical code*⟩ (no default)

Prepends the given ⟨*graphical code*⟩ to /tcb/overlay→ P. 71.

/tcb/overlay unbroken app=⟨*graphical code*⟩ (no default)

Appends the given ⟨*graphical code*⟩ to /tcb/overlay unbroken→ P. 72.

/tcb/overlay unbroken pre=⟨*graphical code*⟩ (no default)

Prepends the given ⟨*graphical code*⟩ to /tcb/overlay unbroken→ P. 72.

/tcb/overlay first app=⟨*graphical code*⟩ (no default)

Appends the given ⟨*graphical code*⟩ to /tcb/overlay first→ P. 72.

/tcb/overlay first pre=⟨*graphical code*⟩ (no default)

Prepends the given ⟨*graphical code*⟩ to /tcb/overlay first→ P. 72.

`/tcb/overlay middle app`=⟨*graphical code*⟩ (no default)
Appends the given ⟨*graphical code*⟩ to `/tcb/overlay middle` → P. 72.

`/tcb/overlay middle pre`=⟨*graphical code*⟩ (no default)
Prepends the given ⟨*graphical code*⟩ to `/tcb/overlay middle` → P. 72.

`/tcb/overlay last app`=⟨*graphical code*⟩ (no default)
Appends the given ⟨*graphical code*⟩ to `/tcb/overlay last` → P. 72.

`/tcb/overlay last pre`=⟨*graphical code*⟩ (no default)
Prepends the given ⟨*graphical code*⟩ to `/tcb/overlay last` → P. 72.

`/tcb/overlay broken app`=⟨*graphical code*⟩ (no default)
Appends the given ⟨*graphical code*⟩ to `/tcb/overlay broken` → P. 72.

`/tcb/overlay broken pre`=⟨*graphical code*⟩ (no default)
Prepends the given ⟨*graphical code*⟩ to `/tcb/overlay broken` → P. 72.

`/tcb/overlay unbroken and first app`=⟨*graphical code*⟩ (no default)
Appends the given ⟨*graphical code*⟩ to `/tcb/overlay unbroken and first` → P. 72.

`/tcb/overlay unbroken and first pre`=⟨*graphical code*⟩ (no default)
Prepends the given ⟨*graphical code*⟩ to `/tcb/overlay unbroken and first` → P. 72.

`/tcb/overlay middle and last app`=⟨*graphical code*⟩ (no default)
Appends the given ⟨*graphical code*⟩ to `/tcb/overlay middle and last` → P. 72.

`/tcb/overlay middle and last pre`=⟨*graphical code*⟩ (no default)
Prepends the given ⟨*graphical code*⟩ to `/tcb/overlay middle and last` → P. 72.

`/tcb/overlay unbroken and last app`=⟨*graphical code*⟩ (no default)
Appends the given ⟨*graphical code*⟩ to `/tcb/overlay unbroken and last` → P. 72.

`/tcb/overlay unbroken and last pre`=⟨*graphical code*⟩ (no default)
Prepends the given ⟨*graphical code*⟩ to `/tcb/overlay unbroken and last` → P. 72.

N 2014-09-19 `/tcb/overlay first and middle app`=⟨*graphical code*⟩ (no default)
Appends the given ⟨*graphical code*⟩ to `/tcb/overlay first and middle` → P. 72.

N 2014-09-19 `/tcb/overlay first and middle pre`=⟨*graphical code*⟩ (no default)
Prepends the given ⟨*graphical code*⟩ to `/tcb/overlay first and middle` → P. 72.

21.5 Watermarks

The following option keys extend the options given in Subsection 10.3 from page 165.

> ! Watermarks are special overlays. The LIB hooks library allows the combination of several watermarks and overlays.

`/tcb/watermark text app=`⟨*text*⟩ (no default)

Appends a `/tcb/watermark text` → P. 165 to the colored box.

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[enhanced,title=My title,watermark graphics=Basilica_5.png,
  watermark opacity=0.25,
  watermark text app=Basilica,watermark color=Navy
  ]
\lipsum[1-2]
\tcblower
This example uses a public domain picture from\\
\url{http://commons.wikimedia.org/wiki/File:Basilica_5.png}
\end{tcolorbox}
```

My title

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

This example uses a public domain picture from
http://commons.wikimedia.org/wiki/File:Basilica_5.png

`/tcb/watermark text pre=`⟨*text*⟩ (no default)

Prepends a `/tcb/watermark text` → P. 165 to the colored box.

`/tcb/watermark text app on=`⟨*part*⟩ `is` ⟨*text*⟩ (no default)

Appends a `/tcb/watermark text on` → P. 165 the named ⟨*part*⟩ of a break sequence.

`/tcb/watermark text pre on=`⟨*part*⟩ `is` ⟨*text*⟩ (no default)

Prepends a `/tcb/watermark text on` → P. 165 the named ⟨*part*⟩ of a break sequence.

`/tcb/watermark graphics app=`⟨*file name*⟩ (no default)
Appends a `/tcb/watermark graphics` → P. 166 referenced by ⟨*file name*⟩ to the colored box.

`/tcb/watermark graphics pre=`⟨*file name*⟩ (no default)
Prepends a `/tcb/watermark graphics` → P. 166 referenced by ⟨*file name*⟩ to the colored box.

`/tcb/watermark graphics app on=`⟨*part*⟩ `is` ⟨*file name*⟩ (no default)
Appends a `/tcb/watermark graphics on` → P. 166 the named ⟨*part*⟩ of a break sequence. The picture is referenced by ⟨*file name*⟩.

`/tcb/watermark graphics pre on=`⟨*part*⟩ `is` ⟨*file name*⟩ (no default)
Prepends a `/tcb/watermark graphics on` → P. 166 the named ⟨*part*⟩ of a break sequence. The picture is referenced by ⟨*file name*⟩.

`/tcb/watermark tikz app=`⟨*graphical code*⟩ (no default)
Appends a `/tcb/watermark tikz` → P. 167 with the given `tikz` ⟨*graphical code*⟩ to the colored box.

`/tcb/watermark tikz pre=`⟨*graphical code*⟩ (no default)
Prepends a `/tcb/watermark tikz` → P. 167 with the given `tikz` ⟨*graphical code*⟩ to the colored box.

```
% \usepackage{tikz}
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
  watermark color=Navy,watermark opacity=0.25,
  smiley/.style={watermark tikz pre={%
    \path[fill=yellow,draw=yellow!75!red] (0,0) circle (1cm);
    \fill[red] (45:5mm) circle (1mm);
    \fill[red] (135:5mm) circle (1mm);
    \draw[line width=1mm,red] (215:5mm) arc (215:325:5mm);}}

\begin{tcolorbox}[enhanced,title=My title, watermark text=Watermark,
  smiley]
\lipsum[1-2]
\end{tcolorbox}
```

My title

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.
Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

`/tcb/watermark tikz app on=`⟨*part*⟩ `is` ⟨*graphical code*⟩ (no default)
Appends a `/tcb/watermark tikz on` → P. 167 the named ⟨*part*⟩ of a break sequence.

`/tcb/watermark tikz pre on=`⟨*part*⟩ `is` ⟨*graphical code*⟩ (no default)
Prepends a `/tcb/watermark tikz on` → P. 167 the named ⟨*part*⟩ of a break sequence.

21.6 Underlays

The following option keys extend the options given in Section 10.8 on page 195. There are no `app` type keys since underlays are stackable by default.

`/tcb/underlay pre`=⟨*graphical code*⟩ (no default)
Prepends the given ⟨*graphical code*⟩ to `/tcb/underlay` → P. 195.

`/tcb/underlay unbroken pre`=⟨*graphical code*⟩ (no default)
Prepends the given ⟨*graphical code*⟩ to `/tcb/underlay unbroken` → P. 196.

`/tcb/underlay first pre`=⟨*graphical code*⟩ (no default)
Prepends the given ⟨*graphical code*⟩ to `/tcb/underlay first` → P. 196.

`/tcb/underlay middle pre`=⟨*graphical code*⟩ (no default)
Prepends the given ⟨*graphical code*⟩ to `/tcb/underlay middle` → P. 196.

`/tcb/underlay last pre`=⟨*graphical code*⟩ (no default)
Prepends the given ⟨*graphical code*⟩ to `/tcb/underlay last` → P. 196.

`/tcb/underlay boxed title pre`=⟨*graphical code*⟩ (no default)
Prepends the given ⟨*graphical code*⟩ to `/tcb/underlay boxed title` → P. 196.

`/tcb/underlay broken pre`=⟨*graphical code*⟩ (no default)
Prepends the given ⟨*graphical code*⟩ to `/tcb/underlay broken` → P. 196.

`/tcb/underlay unbroken and first pre`=⟨*graphical code*⟩ (no default)
Prepends the given ⟨*graphical code*⟩ to `/tcb/underlay unbroken and first` → P. 196.

`/tcb/underlay middle and last pre`=⟨*graphical code*⟩ (no default)
Prepends the given ⟨*graphical code*⟩ to `/tcb/underlay middle and last` → P. 196.

`/tcb/underlay unbroken and last pre`=⟨*graphical code*⟩ (no default)
Prepends the given ⟨*graphical code*⟩ to `/tcb/underlay unbroken and last` → P. 196.

N 2014-09-19 `/tcb/underlay first and middle pre`=⟨*graphical code*⟩ (no default)
Prepends the given ⟨*graphical code*⟩ to `/tcb/underlay first and middle` → P. 196.

21.7 Finishes

The following option keys extend the options given in Section 10.9 on page 197. There are no `app` type keys since finishes are stackable by default.

`/tcb/finish pre=`⟨*graphical code*⟩ (no default)
Prepends the given ⟨*graphical code*⟩ to `/tcb/finish`→ P. 197.

`/tcb/finish unbroken pre=`⟨*graphical code*⟩ (no default)
Prepends the given ⟨*graphical code*⟩ to `/tcb/finish unbroken`→ P. 198.

`/tcb/finish first pre=`⟨*graphical code*⟩ (no default)
Prepends the given ⟨*graphical code*⟩ to `/tcb/finish first`→ P. 198.

`/tcb/finish middle pre=`⟨*graphical code*⟩ (no default)
Prepends the given ⟨*graphical code*⟩ to `/tcb/finish middle`→ P. 198.

`/tcb/finish last pre=`⟨*graphical code*⟩ (no default)
Prepends the given ⟨*graphical code*⟩ to `/tcb/finish last`→ P. 198.

`/tcb/finish broken pre=`⟨*graphical code*⟩ (no default)
Prepends the given ⟨*graphical code*⟩ to `/tcb/finish broken`→ P. 198.

`/tcb/finish unbroken and first pre=`⟨*graphical code*⟩ (no default)
Prepends the given ⟨*graphical code*⟩ to `/tcb/finish unbroken and first`→ P. 198.

`/tcb/finish middle and last pre=`⟨*graphical code*⟩ (no default)
Prepends the given ⟨*graphical code*⟩ to `/tcb/finish middle and last`→ P. 198.

`/tcb/finish unbroken and last pre=`⟨*graphical code*⟩ (no default)
Prepends the given ⟨*graphical code*⟩ to `/tcb/finish unbroken and last`→ P. 198.

N 2014-09-19 `/tcb/finish first and middle pre=`⟨*graphical code*⟩ (no default)
Prepends the given ⟨*graphical code*⟩ to `/tcb/finish first and middle`→ P. 198.

21.8 Skin Code

The following option keys extend the options given in Subsection 9.2 from page 138.

`/tcb/frame code app=`⟨*graphical code*⟩ (no default)
Appends the given ⟨*graphical code*⟩ to `/tcb/frame code`→ P. 138.

`/tcb/frame code pre=`⟨*graphical code*⟩ (no default)
Prepends the given ⟨*graphical code*⟩ to `/tcb/frame code`→ P. 138.

`/tcb/interior titled code app=`⟨*graphical code*⟩ (no default)
Appends the given ⟨*graphical code*⟩ to `/tcb/interior titled code`→ P. 138.

```
\begin{tcolorbox}[title=My title,enhanced,colframe=Navy,
  frame code app={\draw[yellow,line width=1cm] (
    frame.south west)--(frame.north east);},
  interior titled code app={\draw[red,line width=1cm]
    (frame.north west)--(frame.south east);},
  ]
\lipsum[1]
\end{tcolorbox}
```



/tcb/interior titled code pre=⟨*graphical code*⟩ (no default)
Prepends the given ⟨*graphical code*⟩ to /tcb/interior titled code → P. 138.

/tcb/interior code app=⟨*graphical code*⟩ (no default)
Appends the given ⟨*graphical code*⟩ to /tcb/interior code → P. 139.

/tcb/interior code pre=⟨*graphical code*⟩ (no default)
Prepends the given ⟨*graphical code*⟩ to /tcb/interior code → P. 139.

/tcb/segmentation code app=⟨*graphical code*⟩ (no default)
Appends the given ⟨*graphical code*⟩ to /tcb/segmentation code → P. 139.

/tcb/segmentation code pre=⟨*graphical code*⟩ (no default)
Prepends the given ⟨*graphical code*⟩ to /tcb/segmentation code → P. 139.

/tcb/title code app=⟨*graphical code*⟩ (no default)
Appends the given ⟨*graphical code*⟩ to /tcb/title code → P. 140.

/tcb/title code pre=⟨*graphical code*⟩ (no default)
Prepends the given ⟨*graphical code*⟩ to /tcb/title code → P. 140.

21.9 Extras

The following option keys extend the options given in Section 17.5 on page 371. There are no `app` type keys since extras are stackable by default.

N 2015-07-16 **`/tcb/extras pre={`**⟨*options*⟩**`}`** (no default)

Prepends the given ⟨*options*⟩ to `/tcb/extras`→ P. 371.

N 2015-07-16 **`/tcb/extras unbroken pre={`**⟨*options*⟩**`}`** (no default)

Prepends the given ⟨*options*⟩ to `/tcb/extras unbroken`→ P. 371.

N 2015-07-16 **`/tcb/extras first pre={`**⟨*options*⟩**`}`** (no default)

Prepends the given ⟨*options*⟩ to `/tcb/extras first`→ P. 371.

N 2015-07-16 **`/tcb/extras middle pre={`**⟨*options*⟩**`}`** (no default)

Prepends the given ⟨*options*⟩ to `/tcb/extras middle`→ P. 371.

N 2015-07-16 **`/tcb/extras last pre={`**⟨*options*⟩**`}`** (no default)

Prepends the given ⟨*options*⟩ to `/tcb/extras last`→ P. 371.

N 2015-07-16 **`/tcb/extras broken pre={`**⟨*options*⟩**`}`** (no default)

Prepends the given ⟨*options*⟩ to `/tcb/extras broken`→ P. 371.

N 2015-07-16 **`/tcb/extras unbroken and first pre={`**⟨*options*⟩**`}`** (no default)

Prepends the given ⟨*options*⟩ to `/tcb/extras unbroken and first`→ P. 371.

N 2015-07-16 **`/tcb/extras middle and last pre={`**⟨*options*⟩**`}`** (no default)

Prepends the given ⟨*options*⟩ to `/tcb/extras middle and last`→ P. 371.

N 2015-07-16 **`/tcb/extras unbroken and last pre={`**⟨*options*⟩**`}`** (no default)

Prepends the given ⟨*options*⟩ to `/tcb/extras unbroken and last`→ P. 371.

N 2015-07-16 **`/tcb/extras first and middle pre={`**⟨*options*⟩**`}`** (no default)

Prepends the given ⟨*options*⟩ to `/tcb/extras first and middle`→ P. 371.

22 Library xparse

The library is loaded by a package option or inside the preamble by:

```
\tcbuselibrary{xparse}
```

This also loads the package `xparse` [13].

The purpose of this library is to give comfortable access to the powerful document command production with `xparse` for `tcolorbox`. See the `xparse` package documentation [13] for details about the argument ⟨*specification*⟩ used in this section.

22.1 Option Keys

`/tcb/verbatim` (style, no value)

Sets options for a *verbatim* style `\tcbox` → P. 14. Since the indented boxes may contain only very few words, the dimensions are made smaller and `/tcb/nobeforeafter` → P. 78 and `/tcb/tcbox raise base` → P. 96 are set.

```
\DeclareTotalTCBox{\myverb}{ v }{verbatim,
  colframe=red!75!black,colupper=blue}{#1}

\myverb{\textbf} is a \myverb{\LaTeX} command.
```

\textbf is a \LaTeX command.

`/tcb/IfNoValueTF={`⟨*argument*⟩`}{`⟨*true options*⟩`}{`⟨*false options*⟩`}` (no default)

Wraps the `\IfNoValueTF` command of `xparse` for option setting. If the ⟨*argument*⟩ has no value, the ⟨*true options*⟩ are set. Otherwise, the ⟨*false options*⟩ are set.

```
\DeclareTColorBox{mybox}{ o }{colframe=red!75!black,
  IfNoValueTF={#1}{colback=red!5!white}{enhanced,interior style image=#1}}

\begin{mybox}
This is a tcolorbox.
\end{mybox}

\begin{mybox}[goldshade.png]
This is a tcolorbox.
\end{mybox}
```

This is a tcolorbox.

This is a tcolorbox.

/tcb/IfValueTF={⟨*argument*⟩}{⟨*true options*⟩}{⟨*false options*⟩} (no default)

Wraps the `\IfValueTF` command of `xparse` for option setting. If the ⟨*argument*⟩ has a value, the ⟨*true options*⟩ are set. Otherwise, the ⟨*false options*⟩ are set.

```
\DeclareTColorBox{mybox}{ o }{colframe=red!75!black,colback=red!5!white,
  IfValueTF={#1}{title={\flqq #1\frqq},fonttitle=\bfseries}{}}

\begin{mybox}
This is a tcolorbox.
\end{mybox}

\begin{mybox}[My title]
This is a tcolorbox.
\end{mybox}
```

This is a tcolorbox.

«My title»

This is a tcolorbox.

/tcb/IfBooleanTF={⟨*argument*⟩}{⟨*true options*⟩}{⟨*false options*⟩} (no default)

Wraps the `\IfBooleanTF` command of `xparse` for option setting. If the ⟨*argument*⟩ is `\BooleanTue`, the ⟨*true options*⟩ are set. If the ⟨*argument*⟩ is `\BooleanFalse`, the ⟨*false options*⟩ are set.

```
\DeclareTColorBox{mybox}{ s }{colframe=red!75!black,
  IfBooleanTF={#1}{colback=yellow!50!red}{colback=red!5!white}}

\begin{mybox}
This is a tcolorbox.
\end{mybox}

\begin{mybox}*
This is a tcolorbox.
\end{mybox}
```

This is a tcolorbox.

This is a tcolorbox.

22.2 Producing tcolorbox Environments and Commands

`\DeclareTColorBox[`⟨*init options*⟩`]{`⟨*name*⟩`}{`⟨*specification*⟩`}{`⟨*options*⟩`}`

Creates a new environment ⟨*name*⟩ based on `tcolorbox` → P. 12.

Basically, `\DeclareTColorBox` operates like `\DeclareDocumentEnvironment`. This means, the new environment ⟨*name*⟩ is constructed with the given argument ⟨*specification*⟩. The ⟨*options*⟩ are given to the underlying `tcolorbox` → P. 12.

Note that `/tcb/savedelimiter` → P. 26 is set to the given ⟨*name*⟩ automatically.

The ⟨*init options*⟩ allow setting up automatic numbering, see Section 5 from page 108.

The new environment is always created, irrespective of an already existing environment with the same name.

```
% counter from previous example
\DeclareTColorBox[use counter from=pabox]{mybox}{ O{red} m d"" O{} }
  {enhanced,colframe=#1!75!black,colback=#1!5!white,
   fonttitle=\bfseries,title={\thetcbcounter~#2},
   IfValueTF={#3}{watermark text={#3}}{},#4}

\begin{mybox}{My title}
This is a tcolorbox.
\end{mybox}

\begin{mybox}[blue]{My title}
This is a tcolorbox.
\end{mybox}

\begin{mybox}[green]{My title}"My Watermark"
This is a tcolorbox.
\end{mybox}

\begin{mybox}[yellow]{My title}[colbacktitle=yellow!50!white,coltitle=black]
This is a tcolorbox.
\end{mybox}

\begin{mybox}[purple]{My title}"All together"[coltitle=yellow]
This is a tcolorbox.
\end{mybox}
```

22.1 My title

This is a tcolorbox.

22.2 My title

This is a tcolorbox.

22.3 My title

This is a tcolorbox. My Watermark

22.4 My title

This is a tcolorbox.

22.5 My title

This is a tcolorbox. All together

`\NewTColorBox[`⟨*init options*⟩`]{`⟨*name*⟩`}{`⟨*specification*⟩`}{`⟨*options*⟩`}`

Operates like `\DeclareTColorBox` → P. 435, but based on `\NewDocumentEnvironment` instead of `\DeclareDocumentEnvironment`. An error is issued if ⟨*name*⟩ has already been defined.

`\RenewTColorBox[`⟨*init options*⟩`]{`⟨*name*⟩`}{`⟨*specification*⟩`}{`⟨*options*⟩`}`

Operates like `\DeclareTColorBox` → P. 435, but based on `\RenewDocumentEnvironment` instead of `\DeclareDocumentEnvironment`. An existing environment is redefined.

`\ProvideTColorBox[`⟨*init options*⟩`]{`⟨*name*⟩`}{`⟨*specification*⟩`}{`⟨*options*⟩`}`

Operates like `\DeclareTColorBox` → P. 435, but based on `\ProvideDocumentEnvironment` instead of `\DeclareDocumentEnvironment`. The environment ⟨*name*⟩ is only created if it is not already defined.

`\DeclareTotalTColorBox[`⟨*init options*⟩`]{\`⟨*name*⟩`}{`⟨*specification*⟩`}{`⟨*options*⟩`}{`⟨*content*⟩`}`

Creates a new command `\`⟨*name*⟩ based on `tcolorbox` → P. 12. In contrast to `\DeclareTColorBox` → P. 435, also the ⟨*content*⟩ of the `tcolorbox` is specified.

Basically, `\DeclareTotalTColorBox` operates like `\DeclareDocumentCommand`. This means, the new command `\`⟨*name*⟩ is constructed with the given argument ⟨*specification*⟩. The ⟨*options*⟩ are given to the underlying `tcolorbox` → P. 12 which is filled with the specified ⟨*content*⟩.

Note that `/tcb/savedelimiter` → P. 26 is set to the given ⟨*name*⟩ automatically.

The ⟨*init options*⟩ allow setting up automatic numbering, see Section 5 from page 108.

The new command is always created, irrespective of an already existing command with the same name.

```
\DeclareTotalTColorBox{\diabox}{ O{} v  m }
  { bicolor,nobeforeafter,equal height group=diabox,width=5.7cm,
    fonttitle=\bfseries\ttfamily,adjusted title={#2},center title,
    colframe=blue!20!black,leftupper=0mm,rightupper=0mm,colback=black!75!white,#1}
  { \tikz\path[fill zoom image={#2}] (0,0) rectangle (\linewidth,4cm);%
    \tcblower#3}

\diabox{blueshade.png}{Created with |GIMP|.\\\url{http://www.gimp.org}}
\diabox{goldshade.png}{Created with |GIMP|.\\\url{http://www.gimp.org}}
```

`\NewTotalTColorBox[`⟨*init options*⟩`]{\`⟨*name*⟩`}{`⟨*specification*⟩`}{`⟨*options*⟩`}{`⟨*content*⟩`}`

Operates like `\DeclareTotalTColorBox`, but based on `\NewDocumentCommand` instead of `\DeclareDocumentCommand`. An error is issued if `\`⟨*name*⟩ has already been defined.

`\RenewTotalTColorBox[`⟨*init options*⟩`]{\`⟨*name*⟩`}{`⟨*specification*⟩`}{`⟨*options*⟩`}{`⟨*content*⟩`}`

Operates like `\DeclareTotalTColorBox`, but based on `\RenewDocumentCommand` instead of `\DeclareDocumentCommand`. An existing command is redefined.

`\ProvideTotalTColorBox[`⟨*init options*⟩`]{\`⟨*name*⟩`}{`⟨*specification*⟩`}{`⟨*options*⟩`}{`⟨*content*⟩`}`

Operates like `\DeclareTotalTColorBox`, but based on `\ProvideDocumentCommand` instead of `\DeclareDocumentCommand`. The command `\`⟨*name*⟩ is only created if it is not already defined.

22.3 Producing tcbox Commands

`\DeclareTCBox[`⟨*init options*⟩`]{\`⟨*name*⟩`}{`⟨*specification*⟩`}{`⟨*options*⟩`}`

Creates a new command `\`⟨*name*⟩ based on `\tcbox` → P. 14. Basically, `\DeclareTCBox` operates like `\DeclareDocumentCommand`. This means, the new command `\`⟨*name*⟩ is constructed with the given argument ⟨*specification*⟩. The ⟨*options*⟩ are given to the underlying `\tcbox` → P. 14.

Note that `/tcb/savedelimiter` → P. 26 is set to the given ⟨*name*⟩ automatically.

The ⟨*init options*⟩ allow setting up automatic numbering, see Section 5 from page 108.

The new command is always created, irrespective of an already existing command with the same name.

```
% counter from previous example
\DeclareTCBox[use counter from=pabox]{\mybox}{ s m s }
{ nobeforeafter,colback=red!5!white,colframe=red!75!black,
  title={#2 (Box \thetcbcounter)},fonttitle=\bfseries,
  IfBooleanTF={#1}{enhanced,drop shadow}{},
  IfBooleanTF={#3}{colbacktitle=red!50!white}{}  }

\mybox{Bird}{This is my first box.}
  \hfill
\mybox*{Tree}{This is my second box.}
  \par\bigskip
\mybox{Bike}*{This is my third box.}
  \hfill
\mybox*{City}*{This is my fourth box.}
```

Bird (Box 22.6)
This is my first box.

Tree (Box 22.7)
This is my second box.

Bike (Box 22.8)
This is my third box.

City (Box 22.9)
This is my fourth box.

`\NewTCBox[`⟨*init options*⟩`]{\`⟨*name*⟩`}{`⟨*specification*⟩`}{`⟨*options*⟩`}`

Operates like `\DeclareTCBox`, but based on `\NewDocumentCommand` instead of `\DeclareDocumentCommand`. An error is issued if `\`⟨*name*⟩ has already been defined.

`\RenewTCBox[`⟨*init options*⟩`]{\`⟨*name*⟩`}{`⟨*specification*⟩`}{`⟨*options*⟩`}`

Operates like `\DeclareTCBox`, but based on `\RenewDocumentCommand` instead of `\DeclareDocumentCommand`. An existing command is redefined.

`\ProvideTCBox[`⟨*init options*⟩`]{\`⟨*name*⟩`}{`⟨*specification*⟩`}{`⟨*options*⟩`}`

Operates like `\DeclareTCBox`, but based on `\ProvideDocumentCommand` instead of `\DeclareDocumentCommand`. The command `\`⟨*name*⟩ is only created if it is not already defined.

`\DeclareTotalTCBox`[⟨*init options*⟩]{\⟨*name*⟩}{⟨*specification*⟩}{⟨*options*⟩}{⟨*content*⟩}

Creates a new command \⟨*name*⟩ based on `\tcbox` → P. 14. In contrast to `\DeclareTCBox` → P. 438, also the ⟨*content*⟩ of the `tcbox` is specified.

Basically, `\DeclareTotalTCBox` operates like `\DeclareDocumentCommand`. This means, the new command \⟨*name*⟩ is constructed with the given argument ⟨*specification*⟩. The ⟨*options*⟩ are given to the underlying `\tcbox` → P. 14 which is filled with the specified ⟨*content*⟩.

Note that `/tcb/savedelimiter` → P. 26 is set to the given ⟨*name*⟩ automatically.

The ⟨*init options*⟩ allow setting up automatic numbering, see Section 5 from page 108.

The new command is always created, irrespective of an already existing command with the same name.

```
\DeclareTotalTCBox{\myverb}{ O{red} v O{} }
{ fontupper=\ttfamily,nobeforeafter,tcbox raise base,arc=0pt,outer arc=0pt,
  top=0pt,bottom=0pt,left=0mm,right=0mm,
  leftrule=0pt,rightrule=0pt,toprule=0.3mm,bottomrule=0.3mm,boxsep=0.5mm,
  colback=#1!10!white,colframe=#1!50!black,#3}{#2}

To set a word \textbf{bold} in \myverb{\LaTeX}, use
\myverb[green]{\textbf{bold}}. Alternatively, write
\myverb[yellow]{{\bfseries bold}}.
In \myverb[blue]{\LaTeX}[enhanced,fuzzy halo], other font settings are
done in the same way, e.\,g. \myverb{\textit}, \myverb{\itshape}\\
or \myverb[brown]{\texttt}, \myverb[brown]{\ttfamily}.
```

To set a word **bold** in `\LaTeX`, use `\textbf{bold}`. Alternatively, write `{\bfseries bold}`. In `\LaTeX`, other font settings are done in the same way, e. g. `\textit`, `\itshape` or `\texttt`, `\ttfamily`.

The next example uses `\lstinline` from the `listings` package to typeset the verbatim content.

```
% \usepackage{listings} or \tcbuselibrary{listings}
\DeclareTotalTCBox{\commandbox}{ s v }
{verbatim,colupper=white,colback=black!75!white,colframe=black}
{\IfBooleanTF{#1}{\textcolor{red}{\ttfamily\bfseries > }}{}%
  \lstinline[language=command.com,keywordstyle=\color{blue!35!white}\bfseries]^#2^}

\commandbox*{cd "My Documents"} changes to directory \commandbox{My Documents}.

\commandbox*{dir /A} lists the directory content.

\commandbox*{copy example.txt d:\target} copies \commandbox{example.txt} to
  \commandbox{d:\target}.
```

`> cd "My␣Documents"` changes to directory `My Documents`.
`> dir /A` lists the directory content.
`> copy example.txt d:\target` copies `example.txt` to `d:\target`.

`\NewTotalTCBox`[⟨*init options*⟩]{\⟨*name*⟩}{⟨*specification*⟩}{⟨*options*⟩}{⟨*content*⟩}

Operates like `\DeclareTotalTCBox` → P. 439, but based on `\NewDocumentCommand` instead of `\DeclareDocumentCommand`. An error is issued if \⟨*name*⟩ has already been defined.

`\RenewTotalTCBox`[⟨*init options*⟩]{\⟨*name*⟩}{⟨*specification*⟩}{⟨*options*⟩}{⟨*content*⟩}

Operates like `\DeclareTotalTCBox` → P. 439, but based on `\RenewDocumentCommand` instead of `\DeclareDocumentCommand`. An existing command is redefined.

`\ProvideTotalTCBox`[⟨*init options*⟩]{\⟨*name*⟩}{⟨*specification*⟩}{⟨*options*⟩}{⟨*content*⟩}

Operates like `\DeclareTotalTCBox` → P. 439, but based on `\ProvideDocumentCommand` instead of `\DeclareDocumentCommand`. The command \⟨*name*⟩ is only created if it is not already defined.

`\tcboxverb`[⟨*options*⟩]{⟨*verbatim box content*⟩}

Creates a colored box based on `\tcbox` → P. 14 which is fitted to the width of the given ⟨*verbatim box content*⟩. The underlying `\tcbox` → P. 14 is styled with `/tcb/verbatim` → P. 433 plus the given ⟨*options*⟩. The difference to `\tcbox` → P. 14 is that the ⟨*verbatim box content*⟩ is interpreted *verbatim*. Therefore, `\tcboxverb` acts similar to `\verb`.

```
\tcboxverb{\LaTeX}, \tcboxverb[colback=blue!10!white,colupper=blue]{\LaTeX},
\tcboxverb[blank,fuzzy halo]{\LaTeX}, \tcboxverb[beamer]{\LaTeX},
\tcboxverb[enhanced,skin=enhancedmiddle jigsaw,colframe=red]{\LaTeX}.
```



22.4 Producing `tcblisting` Environments

Besides LIB xparse, the following commands also need the LIB listings library to be included.

`\DeclareTCBListing[`⟨*init options*⟩`]{`⟨*name*⟩`}{`⟨*specification*⟩`}{`⟨*options*⟩`}`

Creates a new environment ⟨*name*⟩ based on `tcblisting` → P. 299.

Basically, `\DeclareTCBListing` operates like `\DeclareDocumentEnvironment`. This means, the new environment ⟨*name*⟩ is constructed with the given argument ⟨*specification*⟩. The ⟨*options*⟩ are given to the underlying `tcblisting` → P. 299.

Note that `/tcb/savedelimiter` → P. 26 is set to the given ⟨*name*⟩ automatically.

The ⟨*init options*⟩ allow setting up automatic numbering, see Section 5 from page 108.

The new environment is always created, irrespective of an already existing environment with the same name.

```
\DeclareTCBListing{mybox}{ s O{} m }{%
  colback=red!5!white,
  colframe=red!75!black,
  fonttitle=\bfseries,
  IfBooleanTF={#1}
    {listing side text}
    {text side listing},
  title=#3,#2}

\begin{mybox}{Listing Box}
This is my
\LaTeX\ box.
\end{mybox}
\bigskip

\begin{mybox}*{Listing Box}
This is my
\LaTeX\ box.
\end{mybox}
\bigskip

\begin{mybox}[colback=yellow]
  {Listing Box}
This is my
\LaTeX\ box.
\end{mybox}
```

Listing Box

This is my LaTeX box.

This is my \LaTeX\ box.

Listing Box

This is my \LaTeX\ box.

This is my LaTeX box.

Listing Box

This is my LaTeX box.

This is my \LaTeX\ box.

`\NewTCBListing[`⟨*init options*⟩`]{`⟨*name*⟩`}{`⟨*specification*⟩`}{`⟨*options*⟩`}`

Operates like `\DeclareTCBListing`, but based on `\NewDocumentEnvironment` instead of `\DeclareDocumentEnvironment`. An error is issued if ⟨*name*⟩ has already been defined.

`\RenewTCBListing[`⟨*init options*⟩`]{`⟨*name*⟩`}{`⟨*specification*⟩`}{`⟨*options*⟩`}`

Operates like `\DeclareTCBListing`, but based on `\RenewDocumentEnvironment` instead of `\DeclareDocumentEnvironment`. An existing environment is redefined.

`\ProvideTCBListing[`⟨*init options*⟩`]{`⟨*name*⟩`}{`⟨*specification*⟩`}{`⟨*options*⟩`}`

Operates like `\DeclareTCBListing`, but based on `\ProvideDocumentEnvironment` instead of `\DeclareDocumentEnvironment`. The environment ⟨*name*⟩ is only created if it is not already defined.

Caveats of using an environment ending with an optional argument

```
\DeclareTCBListing{mybox}{ O{} }{listing only,#1}

\begin{mybox}[colframe=red]
\good
\end{mybox}

\begin{mybox}[colframe=red]\good\end{mybox}

\begin{mybox}
\good
\end{mybox}

\begin{mybox} \good\end{mybox}

\begin{mybox}\bad!\end{mybox}

\begin{mybox}
[\good]
\end{mybox}

\begin{mybox} [\good]\end{mybox}

\begin{mybox}[\bad!]\end{mybox}
```

22.5 Producing `tcbinputlisting` Commands

`\DeclareTCBInputListing[`⟨*init options*⟩`]{\`⟨*name*⟩`}{`⟨*specification*⟩`}{`⟨*options*⟩`}`

Creates a new command `\`⟨*name*⟩ based on `\tcbinputlisting` → P. 301. Basically, `\DeclareTCBInputListing` operates like `\DeclareDocumentCommand`. This means, the new command `\`⟨*name*⟩ is constructed with the given argument ⟨*specification*⟩. The ⟨*options*⟩ are given to the underlying `\tcbinputlisting` → P. 301.

The ⟨*init options*⟩ allow setting up automatic numbering, see Section 5 from page 108.

The new command is always created, irrespective of an already existing command with the same name.

```
% counter from previous example
\DeclareTCBInputListing[use counter from=pabox]{\mylisting}{ O{} O{red} m }{%
  listing file={#3},title=Listing~\thetcbcounter,
  colback=#2!5!white,colframe=#2!50!black,colbacktitle=#2!75!black,
  fonttitle=\bfseries,listing only,#1}

\mylisting[before upper=\textit{This is the included file content:}]
  [blue]{\jobname.tcbtemp}
```

Listing 22.10

This is the included file content:

```
% counter from previous example
\DeclareTCBInputListing[use counter from=pabox]{\mylisting}{ O{}
    O{red} m }{%
  listing file={#3},title=Listing~\thetcbcounter,
  colback=#2!5!white,colframe=#2!50!black,colbacktitle=#2!75!black,
  fonttitle=\bfseries,listing only,#1}

\mylisting[before upper=\textit{This is the included file content:}]
  [blue]{\jobname.tcbtemp}
```

`\NewTCBInputListing[`⟨*init options*⟩`]{\`⟨*name*⟩`}{`⟨*specification*⟩`}{`⟨*options*⟩`}`

Operates like `\DeclareTCBInputListing`, but based on `\NewDocumentCommand` instead of `\DeclareDocumentCommand`. An error is issued if `\`⟨*name*⟩ has already been defined.

`\RenewTCBInputListing[`⟨*init options*⟩`]{\`⟨*name*⟩`}{`⟨*specification*⟩`}{`⟨*options*⟩`}`

Operates like `\DeclareTCBInputListing`, but based on `\RenewDocumentCommand` instead of `\DeclareDocumentCommand`. An existing command is redefined.

`\ProvideTCBInputListing[`⟨*init options*⟩`]{\`⟨*name*⟩`}{`⟨*specification*⟩`}{`⟨*options*⟩`}`

Operates like `\DeclareTCBInputListing`, but based on `\ProvideDocumentCommand` instead of `\DeclareDocumentCommand`. The command `\`⟨*name*⟩ is only created if it is not already defined.

22.6 Producing `tboxfit` Commands

The following commands need the LIB fitting library to be included.

`\DeclareTCBoxFit`[⟨*init options*⟩]{\⟨*name*⟩}{⟨*specification*⟩}{⟨*options*⟩}

Creates a new command \⟨*name*⟩ based on `\tcboxfit` → P. 410. Basically, `\DeclareTCBoxFit` operates like `\DeclareDocumentCommand`. This means, the new command \⟨*name*⟩ is constructed with the given argument ⟨*specification*⟩. The ⟨*options*⟩ are given to the underlying `\tcboxfit` → P. 410.

Note that `/tcb/savedelimiter` → P. 26 is set to the given ⟨*name*⟩ automatically.

The ⟨*init options*⟩ allow setting up automatic numbering, see Section 5 from page 108.

The new command is always created, irrespective of an already existing command with the same name.

```
% \usepackage{lipsum}

\DeclareTCBoxFit{\mybox}{ O{} m o }
 {colback=red!5!white,
  colframe=red!75!black,
  width=#2,height=#2/3*2,
  IfValueTF={#3}{height=#3}{},
  #1}

\mybox[colback=yellow]{5cm}%
  {\lipsum[2]}

\mybox[colback=yellow]{5cm}[4cm]{\lipsum[2]}
```



`\NewTCBoxFit`[⟨*init options*⟩]{\⟨*name*⟩}{⟨*specification*⟩}{⟨*options*⟩}

Operates like `\DeclareTCBoxFit`, but based on `\NewDocumentCommand` instead of `\DeclareDocumentCommand`. An error is issued if \⟨*name*⟩ has already been defined.

`\RenewTCBoxFit`[⟨*init options*⟩]{\⟨*name*⟩}{⟨*specification*⟩}{⟨*options*⟩}

Operates like `\DeclareTCBoxFit`, but based on `\RenewDocumentCommand` instead of `\DeclareDocumentCommand`. An existing command is redefined.

`\ProvideTCBoxFit`[⟨*init options*⟩]{\⟨*name*⟩}{⟨*specification*⟩}{⟨*options*⟩}

Operates like `\DeclareTCBoxFit`, but based on `\ProvideDocumentCommand` instead of `\DeclareDocumentCommand`. The command \⟨*name*⟩ is only created if it is not already defined.

\DeclareTotalTCBoxFit[⟨*init options*⟩]{\⟨*name*⟩}{⟨*specification*⟩}{⟨*options*⟩}{⟨*content*⟩}

Creates a new command \⟨*name*⟩ based on `\tcboxfit`[→P. 410]. In contrast to `\DeclareTCBoxFit`[→P. 444], also the ⟨*content*⟩ of the `tcboxfit` is specified.

Basically, `\DeclareTotalTCBoxFit` operates like `\DeclareDocumentCommand`. This means, the new command \⟨*name*⟩ is constructed with the given argument ⟨*specification*⟩. The ⟨*options*⟩ are given to the underlying `\tcboxfit`[→P. 410] which is filled with the specified ⟨*content*⟩.

Note that `/tcb/savedelimiter`[→P. 26] is set to the given ⟨*name*⟩ automatically.

The ⟨*init options*⟩ allow setting up automatic numbering, see Section 5 from page 108.

The new command is always created, irrespective of an already existing command with the same name.

```
% \usepackage{lipsum}

\DeclareTotalTCBoxFit{\multibox}{ O{} m O{10} m }
 {nobeforeafter,colback=red!5!white,colframe=red!75!black,width=#2,height=#2/3*2,
  valign=center,#1}
 { \foreach \n in {1,...,#3} { #4} }

\multibox{5cm}{I shall not repeat.}
\multibox[colframe=blue!75!white]{5cm}[20]{I shall not repeat.}\\
\multibox[colback=yellow,height=5cm]{14cm}[100]{I shall not repeat.}
```

I shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat.

I shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat. I shall not repeat.

I shall not repeat. I shall not repeat.

\NewTotalTCBoxFit[⟨*init options*⟩]{\⟨*name*⟩}{⟨*specification*⟩}{⟨*options*⟩}{⟨*content*⟩}

Operates like `\DeclareTotalTCBoxFit`, but based on `\NewDocumentCommand` instead of `\DeclareDocumentCommand`. An error is issued if \⟨*name*⟩ has already been defined.

\RenewTotalTCBoxFit[⟨*init options*⟩]{\⟨*name*⟩}{⟨*specification*⟩}{⟨*options*⟩}{⟨*content*⟩}

Operates like `\DeclareTotalTCBoxFit`, but based on `\RenewDocumentCommand` instead of `\DeclareDocumentCommand`. An existing command is redefined.

\ProvideTotalTCBoxFit[⟨*init options*⟩]{\⟨*name*⟩}{⟨*specification*⟩}{⟨*options*⟩}{⟨*content*⟩}

Operates like `\DeclareTotalTCBoxFit`, but based on `\ProvideDocumentCommand` instead of `\DeclareDocumentCommand`. The command \⟨*name*⟩ is only created if it is not already defined.

23 Library LIB external

The library is loaded by a package option or inside the preamble by:

```
\tcbuselibrary{external}
```

The purpose of this library is to support externalization of document snippets like graphics or boxes which can be compiled stand-alone. These snippets are written to external files, compiled and the resulting pdf files are included to the main document as images. The whole procedure saves compilation time, if such a snippet is costly to compile but needs to compile just once or very seldom.

There are very good alternatives to this library. One should consider the `standalone` package or the Ti*k*Z externalization library instead. The LIB external library is something in between and can be seen as poor man variant of the Ti*k*Z externalization library.

The main differences between Ti*k*Z externalization and LIB external are:

- Ti*k*Z `external` compiles the whole original document in a sophisticated way while LIB external uses only the preamble or a part of the preamble of the original document.
- Ti*k*Z `external` can automatically externalize all `tikzpicture` environments while LIB external externalizes marked snippets only.
- Code snippets to be externalized by LIB external are not restricted to `tikzpicture` environments. But these snippets have to be stand-alone without dependencies to the rest of the document.

Why should somebody use LIB external instead of the more powerful Ti*k*Z `external`? One reason could be compilation speed, but the main reason for creating the library at all was that Ti*k*Z `external` tends to choke on complicated documents where the sophisticated mechanism stumbles. Since LIB external does not use the original document body for compilation, this cannot happen.

Source snippets are compiled, if their `md5` checksum has changed. They are not compiled automatically, if option settings are changed or anything outside the snippet is changed. Use `/tcb/external/force remake` → P. 447 to force compilation in this case or simply delete the externalized pdf oder md5 files.

To use the externalization options, the compiler has to be called with the `-shell-escape` permission to authorize potentially dangerous system calls. Be warned that this is a security risk.

23.1 Preparation of a Document for Externalization

The preamble of the main document has to contain the \tcbEXTERNALIZE command. Without this command, no externalization operation will be executed.

N 2015-03-11 **\tcbEXTERNALIZE**

It is mandatory for externalization that this command is used once in the preamble of the main document. Every setting *before* \tcbEXTERNALIZE will also be used for compiling an external snippet. Every setting *after* \tcbEXTERNALIZE will be ignored for compiling an external snippet. Place this command right before \begin{document}, if you are not absolutely sure about another place.
The main document has to look like the following:

```
\documentclass[a4paper]{book}%   for example
\usepackage{...}%                anything
% ...
% Tpyically, all or the very most settings for the document.

\tcbEXTERNALIZE% Typically, just before \begin{document}

% Additional settings which are ABSOLUTELY irrelevant for the
% stand-alone snippets.
%
\begin{document}
  % The document.
  % This also contains the marked snippets for externalization.
\end{document}
```

During compilation, a /tcb/external/runner file is dynamically created (several times). This is the actual main file for compiling an externalized snippet.

N 2015-03-11 **/tcb/external/runner=**⟨*file name*⟩ (no default, initially \jobname_run.tex)

Sets the ⟨*file name*⟩ for dynamically created runner file. This is the actual main file for a document snippet. Typically, the initial setting is not needed to be changed.

```
\tcbset{external/runner=myrunner.tex}
```

N 2015-03-11 **/tcb/external/prefix=**⟨*text*⟩ (no default, initially external/)

The ⟨*text*⟩ is prefixed to any /tcb/external/name → P. 449 for an externalization snippet. The initial setting implies saving all snippets into an external/ subdirectory. Depending on the operation system, the subdirectory may have to be created manually once.

```
% Use a 'real' prefix instead of writing into a subdirectory:
\tcbset{external/prefix=ext_}
```

N 2015-03-11 **/tcb/external/externalize=true|false** (default true, initially true)

If set to true, the marked snippets are compiled if necessary. If set to false, the marked snippets are not compiled but included as text. /tcb/external/externalize can only be used after \tcbEXTERNALIZE.

N 2015-03-11 **/tcb/external/force remake=true|false** (default true, initially false)

If set to true, the marked snippets are always compiled. If set to true, the marked snippets are compiled only if necessary. The necessity is given, if a compiled pdf file is missing or the md5 checksum of the source snippet has changed.

N 2015-03-11
U 2017-02-24 **/tcb/external/!** (style)

Shortcut for setting /tcb/external/force remake to true.

N 2015-06-12
U 2017-02-24 **/tcb/external/-** (style)

Shortcut for setting /tcb/external/externalize to false.

23.2 Marking Externalization Snippets

N 2015-03-11

```
\begin{tcbexternal}[⟨options⟩]{⟨name⟩}
  ⟨environment content⟩
\end{tcbexternal}
```

Marks the environment content as a snippet for externalization. Typically, the content is a `tikzpicture` or something similar. It is important to note that the snippet should not have any dependencies with the rest of the document, e.g. referencing counters or setting counters is not possible. The ⟨*name*⟩ is automatically prefixed with `/tcb/external/prefix`. In combination, this has to be a unique file name. It is advised to not use spaces or umlauts for the name. The ⟨*options*⟩ are keys from the `/tcb/external/` key tree.

```
\begin{tcbexternal}{example_tikzpicture}
  \begin{tikzpicture}
    \path[fill=yellow!50!white] (0,0) circle (11mm);
    \path[fill=white] (0,0) circle (9mm);
    \foreach \w/\c in {90/red,210/green,330/blue}
      {\path[shading=ball,ball color=\c] (\w:1cm) circle (7mm);}
  \end{tikzpicture}
\end{tcbexternal}
```



If a `tcolorbox` → P. 12 is externalized, one should use `/tcb/nobeforeafter` → P. 78 for the box. Indention and distances to the text before and after have to be given separately outside the `tcbexternal` environment.

```
\noindent%
\begin{tcbexternal}[minipage]{example_tcolorbox}
  \begin{tcolorbox}[nobeforeafter,enhanced,
      fonttitle=\bfseries,title=Externalized Box,
      colframe=red!50!black,drop fuzzy shadow,
      interior style={fill overzoom image=goldshade.png}]
    This complete tcolorbox is externalized. One cannot use numbered
    boxes here. Note the \texttt{minipage} option which tells the
    current line width to the external snippet.
  \end{tcolorbox}
\end{tcbexternal}
```

Externalized Box

This complete tcolorbox is externalized. One cannot use numbered boxes here. Note the `minipage` option which tells the current line width to the external snippet.

```
\begin{tcolorbox}[nobeforeafter,enhanced,
      fonttitle=\bfseries,title=Externalized Box,
      colframe=blue!50!black,
      interior style={fill overzoom image=blueshade.png}]
  \begin{tcbexternal}[minipage]{example_tcolorbox2}
    \color{white}%
    The interior of the tcolorbox is externalized.
    One can use numbered boxes without problems.
    Note that the text color has to be set for the text manually
    since it is converted into an image.
  \end{tcbexternal}
\end{tcolorbox}
```

Externalized Box

The interior of the tcolorbox is externalized. One can use numbered boxes without problems. Note that the text color has to be set for the text manually since it is converted into an image.

```
\begin{tcbexternal}[minipage]{example_tabularx}
  \newcolumntype{Y}{>{\raggedleft\arraybackslash}X}%
  \begin{tabularx}{\linewidth}{|l||Y|Y|Y|Y||Y|}\hline
    Group & One & Two & Three & Four & Sum\\\hline\hline
    Red & 1000.00 & 2000.00 & 3000.00 & 4000.00 & 10000.00\\\hline
    Green & 2000.00 & 3000.00 & 4000.00 & 5000.00 & 14000.00\\\hline
    Blue & 3000.00 & 4000.00 & 5000.00 & 6000.00 & 18000.00\\\hline\hline
    Sum & 6000.00 & 9000.00 & 12000.00 & 15000.00 & 42000.00\\\hline
  \end{tabularx}
\end{tcbexternal}
```

Group	One	Two	Three	Four	Sum
Red	1000.00	2000.00	3000.00	4000.00	10000.00
Green	2000.00	3000.00	4000.00	5000.00	14000.00
Blue	3000.00	4000.00	5000.00	6000.00	18000.00
Sum	6000.00	9000.00	12000.00	15000.00	42000.00

N 2015-03-11 `/tcb/external/name`=⟨*name*⟩ (no default, initially `unnamed`)

The ⟨*name*⟩ is automatically prefixed with `/tcb/external/prefix` → P. 447. In combination, this has to be a unique file name for externalization. Typically, this key is not used directly but is set indirectly as mandatory parameter, see `tcbexternal` → P. 448.

N 2015-03-11

```
\begin{extcolorbox}[⟨options⟩]{⟨name⟩}[⟨tcolorbox options⟩]
  ⟨environment content⟩
\end{extcolorbox}
```

This is an externalized version of `tcolorbox` → P. 12 created using `\newtcbexternalizetcolorbox` → P. 455:

```
\newtcbexternalizetcolorbox{extcolorbox}{tcolorbox}{}{}
```

⟨*options*⟩ and ⟨*name*⟩ are given to the underlying `tcbexternal` → P. 448 environment, while ⟨*tcolorbox options*⟩ are given to `tcolorbox` → P. 12.

! Note that you should not redefine `/tcb/before` → P. 78 and `/tcb/after` → P. 78 inside the ⟨*tcolorbox options*⟩, since the externalized version would not be identical to the non-externalized otherwise.

```
\begin{extcolorbox}[minipage]{example_extcolorbox}
  [ enhanced,colframe=red!50!black,colback=yellow!10,
    fonttitle=\bfseries,drop fuzzy shadow,
    title=My external box ]

  This box is completely externalized.

  \begin{tcolorbox}[colframe=blue,colback=blue!5,before skip=6pt]
  Inner box.
  \end{tcolorbox}
\end{extcolorbox}
```

My external box

This box is completely externalized.

Inner box.

!
- **Never** externalize numbered boxes.
- **Never** externalize boxes which contain references to other things, e.g. using `\ref` or `\cite`.
- **Never** externalize breakable boxes.

N 2015-03-11

```
\begin{extikzpicture}[⟨options⟩]{⟨name⟩}[⟨tikz options⟩]
  ⟨environment content⟩
\end{extikzpicture}
```

This is an externalized version of `tikzpicture` created using `\newtcbexternalizeenvironment` → P. 455:

```
\newtcbexternalizeenvironment{extikzpicture}{tikzpicture}{}{}{}
```

⟨*options*⟩ and ⟨*name*⟩ are given to the underlying `tcbexternal` → P. 448 environment, while ⟨*tikz options*⟩ are given to `tikzpicture`.

```
\begin{center}
\begin{extikzpicture}[
  preamble={\usepackage{pgfplots}},  % add package for external graph
  input source on error=false,       % do not load source on error
]{example_pgfplots}
  \pgfplotsset{width=12cm}
  \begin{axis}[3d box=background,grid=major,
    xlabel=$x$, ylabel=$y$, zlabel=$z$, view/h=40,
    mesh/interior colormap name=hot,
    colormap/blackwhite,
    z buffer=sort,domain=0:90,y domain=0:60,
    zmin=0,zmax=2,z post scale=1.2,
    ]
  \addplot3[surf,mesh/interior colormap name=blackwhite,
    colormap/hot,] ( {cos(x)},{sin(x)}, {2*sin(y)} );
  \addplot3[surf] ( {2*cos(x)*cos(y)},{2*sin(x)*cos(y)}, {2*sin(y)} );
  \end{axis}
\end{extikzpicture}
\end{center}
```



N 2015-03-11 **/tcb/externalize listing=⟨*name*⟩** (style, no default)

The text content of a tcblisting → P. 299 is externalized with the given ⟨*name*⟩. Note that the listing part is not externalized.

```
\begin{tcblisting}{externalize listing=example_listing,
  bicolor,colback=yellow!10,colframe=yellow!50!black,
  colbacklower=white,center lower}
\begin{tikzpicture}
  \path[fill=yellow!50!white] (0,0) circle (11mm);
  \path[fill=white] (0,0) circle (9mm);
  \foreach \w/\c in {90/red,210/green,330/blue}
    {\path[shading=ball,ball color=\c] (\w:1cm) circle (7mm);}
\end{tikzpicture}
\end{tcblisting}
```

```
\begin{tikzpicture}
  \path[fill=yellow!50!white] (0,0) circle (11mm);
  \path[fill=white] (0,0) circle (9mm);
  \foreach \w/\c in {90/red,210/green,330/blue}
    {\path[shading=ball,ball color=\c] (\w:1cm) circle (7mm);}
\end{tikzpicture}
```



N 2015-03-11 **/tcb/externalize listing!=⟨*name*⟩** (style, no default)

Combination of /tcb/externalize listing and /tcb/external/force remake → P. 447.

N 2015-03-11 **/tcb/externalize example=⟨*name*⟩** (style, no default)

The text content of a dispExample* → P. 463 is externalized with the given ⟨*name*⟩. Note that the listing part is not externalized.

```
\begin{dispExample*}{sidebyside,externalize example=example_example}
\tikz\path[shading=ball,
  ball color=red] circle (7mm);
\end{dispExample*}
```

```
\tikz\path[shading=ball,
  ball color=red] circle (7mm);
```

N 2015-03-11 **/tcb/externalize example!=⟨*name*⟩** (style, no default)

Combination of /tcb/externalize example and /tcb/external/force remake → P. 447.

23.3 Customization

N 2015-03-11 **/tcb/external/safety=⟨*length*⟩** (no default, initially 2mm)

The snippet box is surrounded with a safety border with a thickness of ⟨*length*⟩. This border is automatically trimmed during picture inclusion. The reason for this mechanism is to catch box content which extrudes over the bounding box. For example, shadows of a tcolorbox are painted outside the bounding box and would be lost otherwise.

N 2015-03-11 **/tcb/external/environment=⟨*env*⟩** (no default, initially unset)

Surrounds the exported snippet text with an environment ⟨*env*⟩ without parameters. Note that this option is ignored for /tcb/externalize listing → P. 452.

N 2015-05-05 **/tcb/external/environment with percent=true|false** (default true, initially true)

If set to true, the \begin and \end code of /tcb/external/environment is appended with a percent sign. For verbatim environments, this option typically has to be se to false.

N 2015-03-11 **/tcb/external/minipage=⟨*length*⟩** (default \linewidth, initially unset)

Surrounds the exported snippet text with a minipage. The optional ⟨*length*⟩ parameter sets the width of the minipage. Note that the default width is the current line width of the main document. See tcbexternal → P. 448 for examples. Note that this option is ignored for /tcb/externalize listing → P. 452.

N 2015-03-11 **/tcb/external/plain** (no value, initially set)

Removes any text which was set to surround the snippet. This removes the setting of /tcb/external/minipage, but is independent of /tcb/external/safety.

N 2015-03-11 **/tcb/external/compiler=⟨*text*⟩** (no default, initially pdflatex)

Sets the name of the compiler for the snippets. Note that this compiler has to support the \pdfmdfivesum primitive e.g. using the pdftexcmds package. This should work for xelatex and lualatex.

N 2015-03-11 **/tcb/external/runs=⟨*number*⟩** (no default, initially 1)

Sets the number of compiler runs for the snippet.

```
\begin{tcbexternal}[minipage,runs=2]{example_raster}
  \begin{tcbitemize}[raster equal height,
      size=small,colframe=red!50!black,colback=red!10!white]
    \tcbitem One
    \tcbitem \Huge Two
    \tcbitem Three
    \tcbitem Four
  \end{tcbitemize}
\end{tcbexternal}
```



N 2015-03-11 **/tcb/external/input source on error=true|false** (default true, initially true)

If set to true, the source code of the snippet is loaded instead of the failed pdf picture. Typically, this will lead to an error stop at the faulty place of the source and such helps detecting the cause. If the source input compiles without error, the document setup may be incorrect, see Section 23.1 on page 447. Maybe, the external/ subdirectory has to be created manually in this case, see /tcb/external/prefix → P. 447.
If the option is set to false, the compilation stops immediately on an error. The log file of the external snippet has to be consulted for error messages in this case.

N 2015-05-05 **/tcb/external/preclass=**⟨*code*⟩ (no default, initially unset)

The given ⟨*code*⟩ is added before the snippet document. Typically, this means before `\documentclass`. This is not used for compilation of the main document.

N 2015-05-05 **/tcb/external/PassOptionsToPackage={**⟨*options*⟩**}{**⟨*package*⟩**}** (no default, initially unset)

The given ⟨*options*⟩ are passed to the given ⟨*package*⟩ for the snippet document. This is a shortcut for using /tcb/external/preclass with `\PassOptionsToPackage`. This not used for compilation of the main document.

N 2015-05-05 **/tcb/external/PassOptionsToClass={**⟨*options*⟩**}{**⟨*class*⟩**}** (no default, initially unset)

The given ⟨*options*⟩ are passed to the given ⟨*class*⟩ for the snippet document. This is a shortcut for using /tcb/external/preclass with `\PassOptionsToClass`. This not used for compilation of the main document.

N 2015-05-05 **/tcb/external/clear preclass** (no value)

Removes all additional /tcb/external/preclass settings.

N 2015-03-11 **/tcb/external/preamble=**⟨*code*⟩ (no default, initially unset)

The given ⟨*code*⟩ is added to the preamble of the snippet document. This is not used for compilation of the main document.

N 2015-05-05 **/tcb/external/preamble tcbset=**⟨*options*⟩ (no default, initially unset)

The given ⟨*options*⟩ are added as parameter for `\tcbset` → P. 13 to the preamble of the snippet document. This are not used for compilation of the main document.

N 2015-03-16 **/tcb/external/clear preamble** (no value)

Removes all additional /tcb/external/preamble settings.

N 2015-03-11 **\tcbifexternal{**⟨*true*⟩**}{**⟨*false*⟩**}**

Expands to ⟨*true*⟩, if executed during snippet compilation, and to ⟨*false*⟩, if executed during main document compilation. This can be used *before* `\tcbEXTERNALIZE` → P. 447 to give different setting to snippet and main document.

```
\tcbifexternal{
  \usepackage{onlyforexternal}
}{
  \usepackage{onlyformain}
}
```

N 2015-03-11 `\newtcbexternalizeenvironment{⟨newenv⟩}{⟨env⟩}{⟨options⟩}{⟨begin⟩}{⟨end⟩}`

Creates a new environment ⟨*newenv*⟩ which is based on `tcbexternal` → P. 448. This enviroment takes *at least* one optional parameter and one mandatory parameter. These two parameters are passed to `tcbexternal` → P. 448. Further, the given ⟨*options*⟩ are always added to the option list of `tcbexternal` → P. 448.
The environment content is externalized and the external snippet is surrounded by an environment ⟨*env*⟩. All further parameters of ⟨*newenv*⟩ are given to ⟨*env*⟩ as parameters. The included image is prepended by ⟨*begin*⟩ and appended by ⟨*end*⟩.
`extikzpicture` → P. 451 is an example application for `\newtcbexternalizeenvironment`.

```
\newtcbexternalizeenvironment{extabular}{tabular}{}{\par\centering}{\par}

\begin{extabular}{example_tabular}{|l|p{6cm}|r|}\hline
A & B & C\\\hline
a & This table is externalized as snippet. Obviously,
  this only makes sense for highly complex tables.
& b\\\hline
\end{extabular}
```

A	B	C
a	This table is externalized as snippet. Obviously, this only makes sense for highly complex tables.	b

N 2015-03-11 `\renewtcbexternalizeenvironment{⟨newenv⟩}{⟨env⟩}{⟨options⟩}{⟨begin⟩}{⟨end⟩}`

Identical to `\newtcbexternalizeenvironment`, but the environment ⟨*newenv*⟩ is created by `\renewenvironment` instead of `\newenvironment`.

N 2015-03-11 `\newtcbexternalizetcolorbox{⟨newenv⟩}{⟨env⟩}{⟨options⟩}{⟨begin end options⟩}`

Creates a new environment ⟨*newenv*⟩ which is based on `tcbexternal` → P. 448. This enviroment takes *at least* one optional parameter and one mandatory parameter. These two parameters are passed to `tcbexternal` → P. 448. Further, the given ⟨*options*⟩ are always added to the option list of `tcbexternal` → P. 448.
The environment content is externalized and the external snippet is surrounded by an environment ⟨*env*⟩. All further parameters of ⟨*newenv*⟩ are given to ⟨*env*⟩ as parameters. **In contrast to `\newtcbexternalizeenvironment`, the environment ⟨*env*⟩ is intended to be based on `tcolorbox` → P. 12 or `tcblisting` → P. 299.**
The ⟨*begin end options*⟩ are options for settings the space before and after the included image using `/tcb/before` → P. 78, `/tcb/before skip` → P. 80, `/tcb/after` → P. 78, or `/tcb/after skip` → P. 80.

! Use the exact identical values for `/tcb/before` → P. 78 and `/tcb/after` → P. 78 inside ⟨*begin end options*⟩ as they where used for definition of ⟨*env*⟩! Otherwise, externalized and non-externalized version will have different spacings.

`extcolorbox` → P. 450 is an example application for`\newtcbexternalizetcolorbox`.

Definition in the preamble:

```
\newtcblisting{myownlisting}[2][]{
  enhanced,colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
  colbacktitle=red!50!yellow,before skip=6pt,after skip=6pt,
  title={#2},#1}

\newtcbexternalizetcolorbox{exmyownlisting}{myownlisting}{minipage}%
  {before skip=6pt,after skip=6pt}% same values as for mylisting
```

```
\begin{exmyownlisting}{example_mylisting}% <- name for the external file
  {My externalized example box}
This is my \LaTeX\ box.
\end{exmyownlisting}
```

My externalized example box

```
This is my \LaTeX\ box.
```

This is my LaTeX box.

N 2015-03-11 `\renewtcbexternalizetcolorbox{⟨newenv⟩}{⟨env⟩}{⟨options⟩}{⟨begin end options⟩}`

Identical to `\newtcbexternalizetcolorbox` → P. 455, but the environment ⟨*newenv*⟩ is created by `\renewenvironment` instead of `\newenvironment`.

N 2016-07-14 `\tcbiffileprocess{⟨condition⟩}{⟨source⟩}{⟨md5-file⟩}{⟨target⟩}{⟨true⟩}{⟨false⟩}`

This is a low-level macro which is internally used. The MD5 digest of a ⟨*source*⟩ file is compared with a stored MD5 digest from an auxiliary ⟨*md5-file*⟩. If they are not equal, the auxiliary ⟨*md5-file*⟩ is updated to store the current MD5 digest. Further,

- if ⟨*condition*⟩ equals `0`, ⟨*true*⟩ is executed.
- if ⟨*condition*⟩ equals `1`:
  If the current and stored MD5 digests were different, ⟨*true*⟩ is executed.
  Otherwise, if the ⟨*target*⟩ file is not existing, ⟨*true*⟩ is executed.
  Otherwise, if the ⟨*target*⟩ file is older than the ⟨*md5-file*⟩, ⟨*true*⟩ is executed.
  Otherwise, ⟨*false*⟩ is executed.
- if ⟨*condition*⟩ equals `2`, ⟨*false*⟩ is executed.

The intended processing purpose of the ⟨*true*⟩ code is to produce a ⟨*target*⟩ file from the given ⟨*source*⟩ file.

23.4 Troubleshooting and FAQ

- **I use the default settings, but the `external` subdirectory is not created.**
  Depending on operating system and compiler, an `external` subdirectory is automatically created or not. If not, create such a directory manually or add the following to your document[5]:

```
\ShellEscape{mkdir external}
```

  or

```
\ShellEscape{mkdir -p external}
```

  If the combination of `/tcb/external/prefix` → P. 447 and chosen snippet name points to another subdirectory than `external`, this has to be adapted.

- **I use the `minted` package and I get a cache directory for every externalized snippet.**
  To avoid this problem, there are several ways.

  – If you do not need `minted` inside the snippet code, you may use `\usepackage{minted}` *after* `\tcbEXTERNALIZE` → P. 447 or use `\tcbifexternal` → P. 454 to switch `minted` off for the external code. If `minted` is already included by another package, add the following to your preamble:

```
\tcbset{external/PassOptionsToPackage={draft}{minted}}
```

  – If `minted` is needed for the snippet code, caching can be switched off by adding the following to your preamble:

```
\tcbset{external/PassOptionsToPackage={cache=false}{minted}}
```

    Alternatively, the `cachedir` option of `minted` may be used to redirect the cache.

[5] The `shellesc` package is loaded automatically by the library.

24 Library documentation

This library has the single purpose to support LaTeX package documentations like this one. Actually, the visual nature follows the approach from Till Tantau's `pgf` [22] documentation. Typically, this library is assumed to be used in conjunction with the class `ltxdoc` or alike.

The library is loaded by a package option or inside the preamble by:

```
\tcbuselibrary{documentation}
```

This also loads the library listings, see Section 15 on page 298, the library skins, see Section 10 on page 148, the library xparse, see Section 22 on page 433, and a bunch of packages, namely `pifont`, `marvosym`, `makeidx`, `marginnote`, `refcount`, and `hyperref`.

N 2014-09-19

> The package `makeidx` is loaded only, if `\printindex` is *not* already defined. Therefore, one can include an alternative to `makeidx` like `imakeidx` *before* the library `documentation` is used.

> The package `marginnote` is loaded only, if `\marginnote` is *not* already defined.

> In contrast to other `tcolorbox` options, the option settings for documentation are typically not getting reset by `/tcb/reset` → P. 105, i.e. they keep their values for embedded boxes.

> In combination with DocStrip, `/tcb/verbatim ignore percent` → P. 127 may be helpful.

For UTF-8 support load (ignore this when using XeLaTeX):

```
\tcbuselibrary{listingsutf8,documentation}
```

For `minted` [12] support, load:

```
\tcbuselibrary{documentation,minted}
\tcbset{listing engine=minted}
```

24.1 Macros of the Library

`\begin{docCommand}[`⟨*options*⟩`]{`⟨*name*⟩`}{`⟨*parameters*⟩`}`
⟨*command description*⟩
`\end{docCommand}`

Documents a LaTeX macro with given ⟨*name*⟩ where ⟨*name*⟩ is written without backslash. The given ⟨*options*⟩ are set with `\tcbset` → P. 13. This macro takes mandatory or optional ⟨*parameters*⟩. It is automatically indexed and can be referenced with `\refCom` → P. 465`{`⟨*name*⟩`}`.

```
\begin{docCommand}{foomakedocSubKey}{\marg{name}\marg{key path}}
  Creates a new environment \meta{name} based on \refEnv{docKey} for the
  documentation of keys with the given \meta{key path}.
\end{docCommand}
```

`\foomakedocSubKey{`⟨*name*⟩`}{`⟨*key path*⟩`}`
Creates a new environment ⟨*name*⟩ based on `docKey` → P. 460 for the documentation of keys with the given ⟨*key path*⟩.

```
\begin{docCommand}[color definition=blue]{foomakedocSubKey*}%
    {\marg{name}\marg{key path}}
  Creates a new environment \meta{name} based on \refEnv{docKey} for the
  documentation of keys with the given \meta{key path}.
\end{docCommand}
```

\foomakedocSubKey*{⟨*name*⟩}{⟨*key path*⟩}

Creates a new environment ⟨*name*⟩ based on docKey → P. 460 for the documentation of keys with the given ⟨*key path*⟩.

\begin{docCommand*}[⟨*options*⟩]{⟨*name*⟩}{⟨*parameters*⟩}
⟨*command description*⟩
\end{docCommand*}

Identical to docCommand → P. 458, but without index entry.

\begin{docEnvironment}[⟨*options*⟩]{⟨*name*⟩}{⟨*parameters*⟩}
⟨*environment description*⟩
\end{docEnvironment}

Documents a LaTeX environment with given ⟨*name*⟩. The given ⟨*options*⟩ are set with \tcbset → P. 13. This environment takes mandatory or optional ⟨*parameters*⟩. It is automatically indexed and can be referenced with \refEnv → P. 465{⟨*name*⟩}.

```
\begin{docEnvironment}{foocolorbox}{\oarg{options}}
  This is the main environment to create an accentuated colored text box with
  rounded corners and, optionally, two parts.
\end{docEnvironment}
```

\begin{foocolorbox}[⟨*options*⟩]
⟨*environment description*⟩
\end{foocolorbox}

This is the main environment to create an accentuated colored text box with rounded corners and, optionally, two parts.

```
\begin{docEnvironment}%
    [doclang/environment content=My content text]%
    {foocolorbox*}{\oarg{options}}
  This is the main environment to create an accentuated colored text box with
  rounded corners and, optionally, two parts.
\end{docEnvironment}
```

\begin{foocolorbox*}[⟨*options*⟩]
⟨*My content text*⟩
\end{foocolorbox*}

This is the main environment to create an accentuated colored text box with rounded corners and, optionally, two parts.

\begin{docEnvironment*}[⟨*options*⟩]{⟨*name*⟩}{⟨*parameters*⟩}
⟨*environment description*⟩
\end{docEnvironment*}

Identical to docEnvironment, but without index entry.

U 2014-09-29 `\begin{docKey}[⟨key path⟩][⟨options⟩]{⟨name⟩}{⟨parameters⟩}{⟨description⟩}`
`⟨key description⟩`
`\end{docKey}`

Documents a key with given ⟨*name*⟩ and an optional ⟨*key path*⟩. The given ⟨*options*⟩ are set with `\tcbset` → P. 13. This key takes mandatory or optional ⟨*parameters*⟩ as value with a short ⟨*description*⟩. It is automatically indexed and can be referenced with `\refKey` → P. 466`{⟨name⟩}`.

```
\begin{docKey}[foo]{footitle}{=\meta{text}}{no default, initially empty}
  Creates a heading line with \meta{text} as content.
\end{docKey}
```

/foo/footitle=⟨*text*⟩ (no default, initially empty)
Creates a heading line with ⟨*text*⟩ as content.

U 2014-09-29 `\begin{docKey*}[⟨key path⟩][⟨options⟩]{⟨name⟩}{⟨parameters⟩}{⟨description⟩}`
`⟨key description⟩`
`\end{docKey*}`

Identical to `docKey`, but without index entry.

`\docValue{⟨name⟩}`

Documents a value with given ⟨*name*⟩. Typically, this is a value for a key. This value is automatically indexed.

```
A feasible value for \refKey{/foo/footitle} is \docValue{foovalue}.
```

A feasible value for /foo/footitle is foovalue.

`\docValue*{⟨name⟩}`

Identical to `\docValue`, but without index entry.

U 2014-10-09 `\docAuxCommand{⟨name⟩}`

Documents an auxiliary or minor LaTeX macro with given ⟨*name*⟩ where ⟨*name*⟩ is written without backslash. This macro is automatically indexed.

```
The macro \docAuxCommand{fooaux} holds some interesting data.
```

The macro \fooaux holds some interesting data.

U 2014-10-09 `\docAuxCommand*{⟨name⟩}`

Identical to `\docAuxCommand`, but without index entry.

`\docAuxEnvironment{⟨name⟩}`

Documents an auxiliary or minor LaTeX environment with given ⟨*name*⟩. This macro is automatically indexed.

```
The environment \docAuxEnvironment{fooauxenv} holds some interesting data.
```

The environment fooauxenv holds some interesting data.

`\docAuxEnvironment*[⟨key path⟩]{⟨name⟩}`

Identical to `\docAuxEnvironment`, but without index entry.

`\docAuxKey[`⟨*key path*⟩`]{`⟨*name*⟩`}`

Documents an auxiliary key with given ⟨*name*⟩ and an optional ⟨*key path*⟩. It is automatically indexed.

```
The key \docAuxKey[foo]{fooaux} holds some interesting data.
```

The key /foo/fooaux holds some interesting data.

`\docAuxKey*[`⟨*key path*⟩`]{`⟨*name*⟩`}`

Identical to \docAuxKey, but without index entry.

N 2015-01-08 `\docCounter{`⟨*name*⟩`}`

Documents a counter with given ⟨*name*⟩. The counter is automatically indexed.

```
The counter \docCounter{foocounter} can be used for computation.
```

The counter foocounter can be used for computation.

N 2015-01-08 `\docCounter*{`⟨*name*⟩`}`

Identical to \docCounter, but without index entry.

N 2015-01-08 `\docLength{`⟨*name*⟩`}`

Documents a counter with given ⟨*name*⟩. The counter is automatically indexed.

```
The length \docLength{foolength} can be used for computation.
```

The length \foolength can be used for computation.

N 2015-01-08 `\docLength*{`⟨*name*⟩`}`

Identical to \docLength, but without index entry.

`\docColor{`⟨*name*⟩`}`

Documents a color with given ⟨*name*⟩. The color is automatically indexed.

```
The color \docColor{foocolor} is available.
```

The color foocolor is available.

`\docColor*{`⟨*name*⟩`}`

Identical to \docColor, but without index entry.

`\cs{`⟨*name*⟩`}`

Macro from `ltxdoc` [3] to typeset a command word ⟨*name*⟩ where the backslash is prefixed. The library overwrites the original macro.

```
This is a \cs{foocommand}.
```

This is a \foocommand.

`\meta{`⟨*text*⟩`}`

Macro from `doc` [8] to typeset a meta ⟨*text*⟩. The library overwrites the original macro.

```
This is a \meta{text}.
```

This is a ⟨*text*⟩.

`\marg{`⟨*text*⟩`}`

Macro from `ltxdoc` [3] to typeset a ⟨*text*⟩ with curly brackets as a mandatory argument. The library overwrites the original macro.

```
This is a mandatory \marg{argument}.
```

This is a mandatory {⟨*argument*⟩}.

`\oarg{`⟨*text*⟩`}`

Macro from `ltxdoc` [3] to typeset a ⟨*text*⟩ with square brackets as an optional argument. The library overwrites the original macro.

```
This is an optional \oarg{argument}.
```

This is an optional [⟨*argument*⟩].

`\brackets{`⟨*text*⟩`}`

Sets the given ⟨*text*⟩ with curly brackets.

```
  Here we use \brackets{some text}.
```

Here we use {some text}.

U 2014-10-10 `\begin{dispExample}`
⟨*environment content*⟩
`\end{dispExample}`

Creates a colored box based on a `tcolorbox` → P. 12. It displays the environment content as source code in the upper part and as compiled text in the lower part of the box. The appearance is controlled by `/tcb/documentation listing style` → P. 468 and the style `/tcb/docexample` → P. 468. It may be changed by redefining this style.

```
\begin{dispExample}
This is a \LaTeX\ example.
\end{dispExample}
```

```
This is a \LaTeX\ example.
```

This is a LaTeX example.

U 2014-10-10 `\begin{dispExample*}`{⟨*options*⟩}
⟨*environment content*⟩
`\end{dispExample*}`

The starred version of `dispExample` takes `tcolorbox` → P. 12 ⟨*options*⟩ as parameter. These ⟨*options*⟩ are executed after `/tcb/docexample` → P. 468.

```
\begin{dispExample*}{sidebyside}
This is a \LaTeX\ example.
\end{dispExample*}
```

```
This is a \LaTeX\ example.
```

This is a LaTeX example.

```
\begin{dispListing}
 ⟨environment content⟩
\end{dispListing}
```

Creates a colored box based on a `tcolorbox` → P. 12. It displays the environment content as source code. The appearance is controlled by `/tcb/documentation listing style` → P. 468 and the style `/tcb/docexample` → P. 468. It may be changed by redefining this style.

```
\begin{dispListing}
This is a \LaTeX\ example.
\end{dispListing}
```

```
This is a \LaTeX\ example.
```

```
\begin{dispListing*}{⟨options⟩}
 ⟨environment content⟩
\end{dispListing*}
```

The starred version of `dispListing` takes `tcolorbox` → P. 12 ⟨*options*⟩ as parameter. These ⟨*options*⟩ are executed after `/tcb/docexample` → P. 468.

```
\begin{dispListing*}{title=My listing}
This is a \LaTeX\ example.
\end{dispListing*}
```

My listing

```
This is a \LaTeX\ example.
```

```
\begin{absquote}
 ⟨environment content⟩
\end{absquote}
```

Used to typeset an abstract as quoted and small text.

```
\begin{absquote}
|tcolorbox| provides an environment for colored and framed text boxes with a
heading line. Optionally, such a box can be split in an upper and a lower part.
\end{absquote}
```

> `tcolorbox` provides an environment for colored and framed text boxes with a heading line. Optionally, such a box can be split in an upper and a lower part.

`\tcbmakedocSubKey{`⟨*name*⟩`}{`⟨*key path*⟩`}`

Creates a new environment ⟨*name*⟩ based on docKey → P. 460 for the documentation of keys with the given ⟨*key path*⟩ as default. The new environment ⟨*name*⟩ takes the same parameters as docKey → P. 460 itself. A second starred environment ⟨*name*⟩ is also created, which is identical to ⟨*name*⟩ but without index entry.

```
\tcbmakedocSubKey{docFooKey}{foo}

\begin{docFooKey}{foodummy}{=\meta{nothing}}{no default, initially empty}
Some key.
\end{docFooKey}

\begin{docFooKey*}{foo another dummy}{=\meta{nothing}}{no default, initially empty}
Some key (not indexed).
\end{docFooKey*}
```

`/foo/foodummy=`⟨*nothing*⟩ (no default, initially empty)
Some key.

`/foo/foo another dummy=`⟨*nothing*⟩ (no default, initially empty)
Some key (not indexed).

`\refCom{`⟨*name*⟩`}`

References a documented LaTeX macro with given ⟨*name*⟩ where ⟨*name*⟩ is written without backslash. The page reference is suppressed if it links to the same page.

```
We have created \refCom{foomakedocSubKey} as an example.
```

We have created \foomakedocSubKey → P. 458 as an example.

`\refCom*{`⟨*name*⟩`}`

References a documented LaTeX macro with given ⟨*name*⟩ where ⟨*name*⟩ is written without backslash. There is no page reference.

```
We have created \refCom*{foomakedocSubKey} as an example.
```

We have created \foomakedocSubKey as an example.

`\refEnv{`⟨*name*⟩`}`

References a documented LaTeX environment with given ⟨*name*⟩. The page reference is suppressed if it links to the same page.

```
We have created \refEnv{foocolorbox} as an example.
```

We have created foocolorbox → P. 459 as an example.

`\refEnv*{`⟨*name*⟩`}`

References a documented LaTeX environment with given ⟨*name*⟩. There is no page reference.

```
We have created \refEnv*{foocolorbox} as an example.
```

We have created foocolorbox as an example.

`\refKey{`⟨*name*⟩`}`

References a documented key with given ⟨*name*⟩ where ⟨*name*⟩ is the full path name of the key. The page reference is suppressed if it links to the same page.

```
We have created \refKey{/foo/footitle} as an example.
```

We have created /foo/footitle → P. 460 as an example.

`\refKey*{`⟨*name*⟩`}`

References a documented key with given ⟨*name*⟩ where ⟨*name*⟩ is the full path name of the key. There is no page reference.

```
We have created \refKey*{/foo/footitle} as an example.
```

We have created /foo/footitle as an example.

`\refAux{`⟨*name*⟩`}`

References some auxiliary environment, key, value, or color. The hyperlink color is used, but there is no real link.

```
Some pages back, one can see \refAux{/foo/footitle} as an example.
```

Some pages back, one can see /foo/footitle as an example.

`\refAuxcs{`⟨*name*⟩`}`

References some auxiliary macro ⟨*name*⟩ where ⟨*name*⟩ is written without backslash. The hyperlink color is used, but there is no real link.

```
Some pages back, one can see \refAuxcs{fooaux} as an example.
```

Some pages back, one can see \fooaux as an example.

`\colDef{`⟨*text*⟩`}`

Sets ⟨*text*⟩ with the command color, see /tcb/color command → P. 470.

```
This is my \colDef{text}.
```

This is my text.

`\colOpt{`⟨*text*⟩`}`

Sets ⟨*text*⟩ with the option color, see /tcb/color option → P. 470.

```
This is my \colOpt{text}.
```

This is my text.

N 2014-09-19 `\tcbdocmarginnote[⟨options⟩]{⟨text⟩}`

Creates a `tcolorbox` note with the given ⟨*text*⟩ inside the margin using the `marginnote` package. The style of the `tcolorbox` is predefined and can be altered by `/tcb/doc marginnote` → P. 475 and the given ⟨*options*⟩.

```
Some text\tcbdocmarginnote{Note A}
which is commented by a note inside the margin.
Alternatively to |\tcbdocmarginnote|, you can always use
|\marginnote| with a |tcolorbox| directly.\par
This is further text%
\tcbdocmarginnote[colframe=blue!50!white,colback=blue!5!white]{Note B}
with another note.
```

Note A

Some text which is commented by a note inside the margin. Alternatively to `\tcbdocmarginnote`, you can always use `\marginnote` with a `tcolorbox` directly.

Note B

This is further text with another note.

N 2014-09-19 `\tcbdocnew{⟨date⟩}`

Auxiliary macro which typesets the `/tcb/doclang/new` → P. 471 text with the given ⟨*date*⟩. It may be redefined for customization.

```
\tcbdocnew{1981-10-29}.
% Next one is displayed in the margin:
\tcbdocmarginnote{\tcbdocnew{1978-02-09}}
```

New: 1978-02-09

New: 1981-10-29.

N 2014-09-19 `\tcbdocupdated{⟨date⟩}`

Auxiliary macro which typesets the `/tcb/doclang/updated` → P. 471 text with the given ⟨*date*⟩. It may be redefined for customization.

```
\tcbdocupdated{2014-09-19}.
```

Updated: 2014-09-19.

24.2 Option Keys of the Library

U 2015-03-16 **/tcb/docexample** (style, no value)

Sets the style for dispExample → P. 463 and dispListing → P. 464 with the colors ExampleBack and ExampleFrame. To change the appearance of the examples, this style can be redefined.

```
% Predefined style:
\tcbset{
  docexample/.style={colframe=ExampleFrame,colback=ExampleBack,
    before skip=\medskipamount,after skip=\medskipamount,
    fontlower=\footnotesize}
}
```

/tcb/documentation listing options=⟨*key list*⟩ (no default, initially **style=tcbdocumentation**)

Sets the options from the package **listings** [6]. They are used inside dispExample → P. 463 and dispListing → P. 464 to typeset the listings. Note that this is not identical to the key /tcb/listing options → P. 305 which is used for 'normal' listings.
Used for /tcb/listing engine → P. 310**=listings** only.

/tcb/documentation listing style=⟨*listing style*⟩ (no default, initially **tcbdocumentation**)

Abbreviation for **documentation listing options={style=...}**. This key sets a ⟨*style*⟩ for the **listings** package, see [6]. Note that this is not identical to the key /tcb/listing style → P. 305 which is used for 'normal' listings.
Used for /tcb/listing engine → P. 310**=listings** only.

/tcb/documentation minted options=⟨*minted style*⟩ (no default, initially **tabsize=2,fontsize=\small**)

Sets the options from the package **minted** [12] which are used during typesetting of the listing, if used. Note that this is not identical to the key /tcb/minted options → P. 308 which is used for 'normal' listings.
Used for /tcb/listing engine → P. 310**=minted** only.

/tcb/documentation minted style=⟨*key list*⟩ (no default, initially unset)

Sets a ⟨*style*⟩ known to **Pygments** [14] for the package **minted** [12], if used. Note that this is not identical to the key /tcb/minted style → P. 309 which is used for 'normal' listings.
Used for /tcb/listing engine → P. 310**=minted** only.

N 2017-04-24 **/tcb/documentation minted language=**⟨*programming language*⟩ (no default, initially **latex**)

Sets a ⟨*programming language*⟩ known to **Pygments** [14] for the package **minted** [12], if used. Note that this is not identical to the key /tcb/minted language → P. 308 which is used for 'normal' listings.
Used for /tcb/listing engine → P. 310**=minted** only.

! The following two keys are deprecated and without function (v3.50 and above). Use /tcb/before → P. 78 and /tcb/after → P. 78 with appropriate values instead. Also see /tcb/docexample.

U 2015-03-16 **/tcb/before example=**⟨*macros*⟩ (no default, initially empty)

Sets the ⟨*macros*⟩ which are executed before dispExample → P. 463 and dispListing → P. 464 additional to /tcb/before → P. 78.

deprecated

/tcb/after example=⟨*macros*⟩ (no default, initially empty)

Sets the ⟨*macros*⟩ which are executed after dispExample → P. 463 and dispListing → P. 464 additional to /tcb/after → P. 78.

deprecated

N 2017-04-25 **/tcb/keywords bold=true|false** (default **true**, initially **true**)

Keyword used in docEnvironment → P. 459, docCommand → P. 458, etc. are printed boldface (or not). Since the typewriter font is used, the effect may be invisible with Computer Modern fonts or similar which do not have a bold variant. Note that references to keywords are not printed boldface at all.

```
\LARGE
\docAuxCommand{fooaux}, \refCom{tcbset}

\tcbset{keywords bold=false}
\docAuxCommand{fooaux}, \refCom{tcbset}
```

\fooaux, \tcbset → P. 13
\fooaux, \tcbset → P. 13

N 2015-01-09 **/tcb/index command=**⟨*macro*⟩ (no default, initially **\index**)

Replaces the internally used **\index** macro by the given ⟨*macro*⟩. The ⟨*macro*⟩ has to take one mandatory argument like **\index**. This option is mutually exclusive with /tcb/index command name.

```
\tcbset{index command=\myindexcommand}
```

N 2015-01-09 **/tcb/index command name=**⟨*name*⟩ (no default, initially unset)

Replaces the internally used **\index** macro by **\index[**⟨*name*⟩**]**, i.e. **\index{...}** is replaced by **\index[**⟨*name*⟩**]{...}**. This option is intended to be used with **imakeidx** and is mutually exclusive with /tcb/index command.

```
\tcbset{index command name=mydoc}
```

/tcb/index format=⟨*format*⟩ (no default, initially **pgf**)

Determines the basic ⟨*format*⟩ of the generated index. Feasible values are:

- **pgfsection**: The index is formatted like in the **pgf** documentation (as a section).
- **pgfchapter**: The index is formatted like in the **pgf** documentation (as a chapter).
- **pgf**: Alias for **pgfsection**.
- **doc**: The index is assumed to be formatted by **doc** or **ltxdoc**. The usage of **makeindex** with **-s gind.ist** is assumed. The package **hypdoc** has to be loaded *before* **tcolorbox**.
- **off**: The index is not formatted by **tcolorbox**. Use this, if the index is formatted by other package like **imakeidx**.

/tcb/index actual=⟨*character*⟩ (no default, initially **@**)

Sets the character for 'actual' in automatic indexing.

/tcb/index quote=⟨*character*⟩ (no default, initially **"**)

Sets the character for 'quote' in automatic indexing.

/tcb/index level=⟨*character*⟩ (no default, initially **!**)

Sets the character for 'level' in automatic indexing.

/tcb/index default settings (style, no value)

Sets the **makeindex** default values for /tcb/index actual, /tcb/index quote, and /tcb/index level.

/tcb/index german settings (style, no value)

Sets the **makeindex** values recommended for German language texts. This is identical to setting the following:

```
\tcbset{index actual={=},index quote={!},index level={>}}
```

`/tcb/index annotate=true|false` (default `true`, initially `true`)

If set to `true`, the index entries are annotated with short descriptions given by `/tcb/doclang/environment` → P. 471, `/tcb/doclang/key` → P. 471, and others.

`/tcb/index colorize=true|false` (default `true`, initially `false`)

If set to `true`, the index entries colorized according to the color settings given by `/tcb/color environment`, `/tcb/color key`, and others.

`/tcb/color command=`⟨*color*⟩ (no default, initially `Definition`)

Sets the highlight color used by macro definitions.

`/tcb/color environment=`⟨*color*⟩ (no default, initially `Definition`)

Sets the highlight color used by environment definitions.

`/tcb/color key=`⟨*color*⟩ (no default, initially `Definition`)

Sets the highlight color used by key definitions.

`/tcb/color value=`⟨*color*⟩ (no default, initially `Definition`)

Sets the highlight color used by value definitions.

N 2015-01-08 `/tcb/color counter=`⟨*color*⟩ (no default, initially `Definition`)

Sets the highlight color used by counter definitions.

N 2015-01-08 `/tcb/color length=`⟨*color*⟩ (no default, initially `Definition`)

Sets the highlight color used by length definitions.

`/tcb/color color=`⟨*color*⟩ (no default, initially `Definition`)

Sets the highlight color used by color definitions.

`/tcb/color definition=`⟨*color*⟩ (no default, initially `Definition`)

Sets the highlight color for `/tcb/color command`, `/tcb/color environment`, `/tcb/color key`, `/tcb/color value`, `/tcb/color counter`, `/tcb/color length`, and `/tcb/color color`.

`/tcb/color option=`⟨*color*⟩ (no default, initially `Option`)

Sets the color used for optional arguments.

`/tcb/color hyperlink=`⟨*color*⟩ (no default, initially `Hyperlink`)

Sets the color for all hyper-links, i. e. all internal and external links.

The following keys are provided for language specific settings. The English language is predefined.

`/tcb/english language` (style, no value)
Sets all language specific settings to English.

`/tcb/doclang/color=`⟨*text*⟩ (no default, initially `color`)
Text used in the index for colors.

`/tcb/doclang/colors=`⟨*text*⟩ (no default, initially `Colors`)
Heading text in the index for colors.

N 2015-01-08 `/tcb/doclang/counter=`⟨*text*⟩ (no default, initially `counter`)
Text used in the index for counters.

N 2015-01-08 `/tcb/doclang/counters=`⟨*text*⟩ (no default, initially `Counters`)
Heading text in the index for counters.

`/tcb/doclang/environment=`⟨*text*⟩ (no default, initially `environment`)
Text used in the index for environments.

`/tcb/doclang/environments=`⟨*text*⟩ (no default, initially `Environments`)
Heading text in the index for environments.

`/tcb/doclang/environment content=`⟨*text*⟩ (no default, initially `environment content`)
Text used in `docEnvironment` → P. 459.

`/tcb/doclang/index=`⟨*text*⟩ (no default, initially `Index`)
Heading text for the index.

`/tcb/doclang/key=`⟨*text*⟩ (no default, initially `key`)
Text used in the index for keys.

`/tcb/doclang/keys=`⟨*text*⟩ (no default, initially `Keys`)
Heading text used in the index for keys.

N 2015-01-08 `/tcb/doclang/length=`⟨*text*⟩ (no default, initially `length`)
Text used in the index for lengths.

N 2015-01-08 `/tcb/doclang/lengths=`⟨*text*⟩ (no default, initially `Lengths`)
Heading text in the index for lengths.

N 2014-09-19 `/tcb/doclang/new=`⟨*text*⟩ (no default, initially `New`)
Announcement text for new content.

`/tcb/doclang/pageshort=`⟨*text*⟩ (no default, initially `P.`)
Short text for page references.

N 2014-09-19 `/tcb/doclang/updated=`⟨*text*⟩ (no default, initially `Updated`)
Announcement text for updated content.

`/tcb/doclang/value=`⟨*text*⟩ (no default, initially `value`)
Text used in the index for values.

`/tcb/doclang/values=`⟨*text*⟩ (no default, initially `Values`)
Heading text in the index for values.

`/tcb/doc left`=⟨*length*⟩ (no default, initially `2em`)

Sets the left hand offset of the documentation texts from `docCommand` → P. 458, `docEnvironment` → P. 459, `docKey` → P. 460, etc, to ⟨*length*⟩.

```
\begin{docCommand*}[doc left=2cm,doc left indent=-2cm]{myCommandA}{\marg{argument}}
  This is the documentation of \refCom{myCommandA} which takes one \meta{argument}.
  \refCom{myCommandA} does some funny things with its \meta{argument}.
\end{docCommand*}
```

`\myCommandA{`⟨*argument*⟩`}` (no default, initially `2em`)

This is the documentation of `\myCommandA` which takes one ⟨*argument*⟩. `\myCommandA` does some funny things with its ⟨*argument*⟩.

`/tcb/doc right`=⟨*length*⟩ (no default, initially `0em`)

Sets the right hand offset of the documentation texts from `docCommand` → P. 458, `docEnvironment` → P. 459, `docKey` → P. 460, etc, to ⟨*length*⟩.

```
\begin{docCommand*}[doc right=2cm]{myCommandB}{\marg{argument}}
  This is the documentation of \refCom{myCommandB} which takes one \meta{argument}.
  \refCom{myCommandB} does some funny things with its \meta{argument}.
\end{docCommand*}
```

`\myCommandB{`⟨*argument*⟩`}` (no default, initially `0em`)

This is the documentation of `\myCommandB` which takes one ⟨*argument*⟩. `\myCommandB` does some funny things with its ⟨*argument*⟩.

`/tcb/doc left indent`=⟨*length*⟩ (no default, initially `-2em`)

Sets the left hand indent of documentation heads from `docCommand` → P. 458, `docEnvironment` → P. 459, `docKey` → P. 460, etc, to ⟨*length*⟩.

```
\begin{docCommand*}[doc left indent=2cm]{myCommandC}{\marg{argument}}
  This is the documentation of \refCom{myCommandC} which takes one \meta{argument}.
  \refCom{myCommandC} does some funny things with its \meta{argument}.
\end{docCommand*}
```

`\myCommandC{`⟨*argument*⟩`}` (no default, initially `-2em`)

This is the documentation of `\myCommandC` which takes one ⟨*argument*⟩. `\myCommandC` does some funny things with its ⟨*argument*⟩.

`/tcb/doc right indent`=⟨*length*⟩ (no default, initially `0pt`)

Sets the right hand indent of documentation heads from `docCommand` → P. 458, `docEnvironment` → P. 459, `docKey` → P. 460, etc, to ⟨*length*⟩.

```
\begin{docCommand*}[doc right indent=-10mm,doc right=10mm,
    doc description=test value]{myCommandD}{\marg{argument}}
  This is the documentation of \refCom{myCommandD} which takes one \meta{argument}.
  \refCom{myCommandD} does some funny things with its \meta{argument}.
\end{docCommand*}
```

`\myCommandD{`⟨*argument*⟩`}` (test value)

This is the documentation of `\myCommandD` which takes one ⟨*argument*⟩. `\myCommandD` does some funny things with its ⟨*argument*⟩.

The head lines of the main documentation environments docCommand → P. 458, docEnvironment → P. 459, docKey → P. 460, etc, are set inside tcolorboxes. Options to these tcolorboxes can be given using the following keys.

/tcb/doc head command=⟨*options*⟩ (no default, initially empty)

Sets ⟨*options*⟩ for the head line of docCommand → P. 458 and docCommand* → P. 459.

```
\tcbset{doc head command={interior style={fill,left color=red!20!white,
  right color=blue!20!white}}}

\begin{docCommand*}{myCommandE}{\marg{argument}}
  This is the documentation of \refCom{myCommandE} which takes one \meta{argument}.
  \refCom{myCommandE} does some funny things with its \meta{argument}.
\end{docCommand*}
```

\myCommandE{⟨*argument*⟩} (no default, initially empty)

This is the documentation of \myCommandE which takes one ⟨*argument*⟩. \myCommandE does some funny things with its ⟨*argument*⟩.

/tcb/doc head environment=⟨*options*⟩ (no default, initially empty)

Sets ⟨*options*⟩ for the head line of docEnvironment → P. 459 and docEnvironment* → P. 459.

```
\tcbset{doc head environment={beamer,boxsep=2pt,arc=2pt,colback=green!20!white,
  after=\par\smallskip}}

\begin{docEnvironment*}{myEnvironment}{\marg{argument}}
  This is the documentation of \refEnv{myEnvironment} which
  takes one \meta{argument}.
\end{docEnvironment*}
```

\begin{myEnvironment}{⟨*argument*⟩} (no default, initially empty)
⟨*environment content*⟩
\end{myEnvironment}

This is the documentation of myEnvironment which takes one ⟨*argument*⟩.

/tcb/doc head key=⟨*options*⟩ (no default, initially empty)

Sets ⟨*options*⟩ for the head line of docKey → P. 460 and docKey* → P. 460.

```
\tcbset{doc head key={boxsep=4pt,arc=4pt,boxrule=0.6pt,
  frame style=fill,interior style=fill,colframe=green!50!black}}

\begin{docKey*}{/foo/myKey}{}{no value}
  This is the documentation of \refKey{/foo/myKey}.
\end{docKey*}
```

/foo/myKey (no value)

This is the documentation of /foo/myKey.

/tcb/doc head=⟨*options*⟩ (no default, initially empty)

Shortcut for setting the same ⟨*options*⟩ for /tcb/doc head command, /tcb/doc head environment, and /tcb/doc head key.

The description texts of the main documentation environments docCommand → P. 458, docEnvironment → P. 459, docKey → P. 460, etc, are set in a compact form without indention and parskip=0pt. This settings can overruled by using the following keys to insert code before (or after) the description texts.

N 2015-10-09 **/tcb/before doc body command=**⟨*code*⟩ (no default, initially empty)

Executes ⟨*code*⟩ before the description texts of docCommand → P. 458 and docCommand* → P. 459.

```
\tcbset{before doc body command={%
    \setlength{\parindent}{2.5em}%
    \setlength{\parskip}{1ex plus 0.75ex minus 0.25ex}%
}}

\begin{docCommand*}{myCommandG}{\marg{argument}}
  This is the documentation of \refCom{myCommandG} which takes one \meta{argument}.
  \refCom{myCommandG} does some funny things with its \meta{argument}.
\end{docCommand*}
```

\myCommandG{⟨*argument*⟩} (no default, initially empty)

This is the documentation of \myCommandG which takes one ⟨*argument*⟩. \myCommandG does some funny things with its ⟨*argument*⟩.

N 2015-10-09 **/tcb/after doc body command=**⟨*code*⟩ (no default, initially empty)

Executes ⟨*code*⟩ after the description texts of docCommand → P. 458 and docCommand* → P. 459.

```
\tcbset{after doc body command={%
    \hfill\nolinebreak[1]\hspace*{\fill}\textcolor{red}{$\diamondsuit$}%
}}

\begin{docCommand*}{myCommandH}{\marg{argument}}
  This is the documentation of \refCom{myCommandH} which takes one \meta{argument}.
  \refCom{myCommandH} does some funny things with its \meta{argument}.
\end{docCommand*}
```

\myCommandH{⟨*argument*⟩} (no default, initially empty)

This is the documentation of \myCommandH which takes one ⟨*argument*⟩. \myCommandH does some funny things with its ⟨*argument*⟩. ♢

N 2015-10-09 **/tcb/before doc body environment=**⟨*code*⟩ (no default, initially empty)

Executes ⟨*code*⟩ before the description texts of docEnvironment → P. 459 and docEnvironment* → P. 459.

N 2015-10-09 **/tcb/after doc body environment=**⟨*code*⟩ (no default, initially empty)

Executes ⟨*code*⟩ after the description texts of docEnvironment → P. 459 and docEnvironment* → P. 459.

N 2015-10-09 **/tcb/before doc body key=**⟨*code*⟩ (no default, initially empty)

Executes ⟨*code*⟩ before the description texts of docKey → P. 460 and docKey* → P. 460.

N 2015-10-09 **/tcb/after doc body key=**⟨*code*⟩ (no default, initially empty)

Executes ⟨*code*⟩ after the description texts of docKey → P. 460 and docKey* → P. 460.

N 2015-10-09 **/tcb/before doc body=**⟨*options*⟩ (no default, initially empty)

Shortcut for setting the same ⟨*options*⟩ for /tcb/before doc body command, /tcb/before doc body environment, and /tcb/before doc body key.

N 2015-10-09 **/tcb/after doc body=**⟨*options*⟩ (no default, initially empty)

Shortcut for setting the same ⟨*options*⟩ for /tcb/after doc body command, /tcb/after doc body environment, and /tcb/after doc body key.

`/tcb/doc description=`⟨*text*⟩ (no default, initially empty)

Sets a (short!) additional description ⟨*text*⟩ for `docCommand` → P. 458 or `docEnvironment` → P. 459. Such a description is mandatory for `docKey` → P. 460.

```
\begin{docCommand*}[doc description=my description]{myCommandF}{\marg{argument}}
  This is the documentation of \refCom{myCommandF} which takes one \meta{argument}.
  \refCom{myCommandF} does some funny things with its \meta{argument}.
\end{docCommand*}
```

`\myCommandF{`⟨*argument*⟩`}` (my description)

This is the documentation of `\myCommandF` which takes one ⟨*argument*⟩. `\myCommandF` does some funny things with its ⟨*argument*⟩.

! Note that the description ⟨*text*⟩ may overlap with the text on the left hand side if too long. Linebreaks can be used inside the ⟨*text*⟩.

`/tcb/doc into index=true|false` (default `true`, initially `true`)

If set to `false`, no index entries are written for the main documentation environments. The same effect is achieved by using e. g. `docCommand*` → P. 459 instead of `docCommand` → P. 458.

N 2014-09-19 `/tcb/doc marginnote=`⟨*options*⟩ (no default, initially empty)

Sets style ⟨*options*⟩ for the displayed box of the `\tcbdocmarginnote` → P. 467 command.

```
\tcbset{doc marginnote={colframe=blue!50!white,colback=blue!5!white}}%
This is some text\tcbdocmarginnote{Note A}
which is commented by a note inside the margin.
```

Note A

This is some text which is commented by a note inside the margin.

N 2014-09-19 `/tcb/doc new=`⟨*date*⟩ (style, no default)

Adds a a marginnote with a 'New: ⟨*data*⟩' message at the beginning of the upper box part. The intended use is inside the option list of `docCommand` → P. 458, `docEnvironment` → P. 459, etc.

```
\begin{docCommand}[doc new=2000-01-01]{foosomething}{\marg{text}}
Some command for something.
\end{docCommand}
```

New: 2000-01-01

`\foosomething{`⟨*text*⟩`}` (style, no default)

Some command for something.

N 2014-09-19 `/tcb/doc updated=`⟨*date*⟩ (style, no default)

Adds a marginnote with a 'Updated: ⟨*data*⟩' message at the beginning of the upper box part. See `/tcb/doc new`.

N 2014-09-19 `/tcb/doc new and updated={`⟨*new date*⟩`}{`⟨*update date*⟩`}` (style, no default)

Adds a marginnote with 'New: ⟨*new date*⟩' and 'Updated: ⟨*update data*⟩' messages at the beginning of the upper box part. See `/tcb/doc new`.

24.3 Predefined Colors of the Library

The following colors are predefined. They are used as default colors in some library commands.

`Option` , `Definition` , `ExampleFrame` , `ExampleBack` , `Hyperlink` .

A Picture Credits

The following pictures were used inside this documentation.

Basilica_5.png



http://commons.wikimedia.org/wiki/File:Basilica_5.png

lichtspiel.jpg



Photograph taken by Thomas F. Sturm.

crinklepaper.png



Created with GIMP.
http://www.gimp.org

pink_marble.png



Created with GIMP.
http://www.gimp.org

blueshade.png



Created with GIMP.
http://www.gimp.org

goldshade.png



Created with GIMP.
http://www.gimp.org

References

[1] Donald Arseneau. *The varwidth package*. Sept. 26, 2011.
http://mirrors.ctan.org/macros/latex/contrib/varwidth/varwidth-doc.pdf.

[2] Peter Breitenlohner. *The ε-TEX manual*. Version 2. Feb. 1998.
http://mirrors.ctan.org/systems/doc/etex/etex_man.pdf.

[3] David Carlisle. *The file ltxdoc.dtx for use with LaTeX 2ε*. Nov. 11, 2007.
http://mirror.ctan.org/macros/latex/base/ltxdoc.dtx.

[4] David Carlisle. *The tabularx package*. Oct. 28, 2014.
http://mirror.ctan.org/macros/latex/required/tools/tabularx.pdf.

[5] Toby Cubitt. *The cleveref Package*. Dec. 28, 2013.
http://mirror.ctan.org/macros/latex/contrib/cleveref/cleveref.pdf.

[6] Carsten Heinz, Brooks Moses, and Jobst Hoffmann. *The Listings Package*. Version 1.6. June 4, 2015.
http://mirror.ctan.org/macros/latex/contrib/listings/listings.pdf.

[7] Philipp Lehman and Joseph Wright. *The etoolbox Package*. Aug. 2, 2015.
http://mirror.ctan.org/macros/latex/contrib/etoolbox/etoolbox.pdf.

[8] Frank Mittelbach. *The doc and shortvrb Packages*. June 30, 2011.
http://mirror.ctan.org/macros/latex/base/doc.dtx.

[9] Frank Mittelbach. *An environment for multicolumn output*. Sept. 30, 2015.
http://mirror.ctan.org/macros/latex/required/tools/multicol.pdf.

[10] Heiko Oberdiek. *The listingsutf8 package*. Nov. 10, 2011.
http://mirror.ctan.org/macros/latex/contrib/oberdiek/listingsutf8.pdf.

[11] Heiko Oberdiek. *The bookmark package*. May 17, 2016.
http://mirrors.ctan.org/macros/latex/contrib/oberdiek/bookmark.pdf.

[12] Geoffrey M. Poore and Konrad Rudolph. *The minted package. Highlighted source code in LaTeX*. Sept. 9, 2015.
http://mirror.ctan.org/macros/latex/contrib/minted/minted.pdf.

[13] The LaTeX3 Project. *The xparse Package*. Oct. 14, 2015.
http://mirror.ctan.org/macros/latex/contrib/l3packages/xparse.pdf.

[14] *Pygments. Python syntax highlighter*. 2013.
http://pygments.org/.

[15] Sebastian Rahtz and Heiko Oberdiek. *Hypertext marks in LaTeX: a manual for hyperref*. Nov. 2012.
http://mirrors.ctan.org/macros/latex/contrib/hyperref/doc/manual.pdf.

[16] Will Robertson. *A couple of things involving environments*. May 4, 2014.
http://mirror.ctan.org/macros/latex/contrib/environ/environ.pdf.

[17] Rainer Schöpf, Bernd Raichle, and Chris Rowley. *A New Implementation of LaTeX's verbatim and verbatim* Environments*. Mar. 12, 2001.
http://mirror.ctan.org/macros/latex/required/tools/verbatim.pdf.

[18] Thomas F. Sturm. *Mathematik 1 (B.Eng.)* Vorlesungs-Skriptum. Neubiberg: Universität der Bundeswehr München, 2007.
http://www.unibw.de/bw/sturm.

[19] Thomas F. Sturm. *Mathematik 2 (B.Eng.)* Vorlesungs-Skriptum. Neubiberg: Universität der Bundeswehr München, 2008.
http://www.unibw.de/bw/sturm.

[20] Thomas F. Sturm. *Höhere Mathematik: Fortgeschrittene mathematische Methoden (M.Eng.)* Vorlesungs-Skriptum. Neubiberg: Universität der Bundeswehr München, 2010. http://www.unibw.de/bw/sturm.

[21] Thomas F. Sturm. *LaTeX – Einführung in das Textsatzsystem.* 10th edition. RRZN-Handbücher. Hannover: Regionales Rechenzentrum für Niedersachsen (RRZN), Mar. 2014. http://www.rrzn.uni-hannover.de/buch.html?&titel=latex.

[22] Till Tantau. *The TikZ and PGF Packages. Manual for version 3.0.1a.* Aug. 29, 2015. http://mirrors.ctan.org/graphics/pgf/base/doc/pgfmanual.pdf.

Index

- key, 447
! key, 447

0 value, 147
1 value, 147
2 value, 147

above key, 406
absquote environment, 464
add to height key, 55
add to list key, 99
add to natural height key, 55
add to width key, 34
adjust text key, 18
adjusted title key, 18
adjusted title after break key, 366
after key, 78
after app key, 424
after doc body key, 474
after doc body command key, 474
after doc body environment key, 474
after doc body key key, 474
after example key, 468
after lower key, 66
after lower app key, 424
after lower pre key, 424
after lower* key, 66
after pre key, 424
after skip key, 80
after title key, 64
after title app key, 423
after title pre key, 423
after upper key, 65
after upper app key, 423
after upper pre key, 423
after upper* key, 65
all key, 10
all value, 48, 49, 287, 368, 370
ams align key, 351
ams align lower key, 351
ams align upper key, 351
ams align* key, 351
ams align* lower key, 351
ams align* upper key, 351
ams equation key, 350
ams equation lower key, 350
ams equation upper key, 350
ams equation* key, 350
ams equation* lower key, 350
ams equation* upper key, 350
ams gather key, 352
ams gather lower key, 352
ams gather upper key, 352
ams gather* key, 352
ams gather* lower key, 352
ams gather* upper key, 352
ams nodisplayskip key, 353
ams nodisplayskip lower key, 353
ams nodisplayskip upper key, 353
arc key, 36
arc is angular key, 38
arc is curved key, 38
areasize value, 418
areasize* value, 418
as-is value, 255
at key, 407
at begin tikz key, 192
at begin tikz reset key, 192
at end tikz key, 192
at end tikz reset key, 192
attach boxed title to bottom key, 156
attach boxed title to bottom center key, 155
attach boxed title to bottom left key, 155
attach boxed title to bottom right key, 155
attach boxed title to bottom* key, 156
attach boxed title to top key, 156
attach boxed title to top center key, 155
attach boxed title to top left key, 155
attach boxed title to top right key, 155
attach boxed title to top* key, 156
attach title key, 20
attach title to upper key, 20
auto value, 97
auto counter key, 108
auto limited value, 97
auto outer arc key, 38
autoparskip key, 78

base value, 79
base color key, 269
baseline key, 79
baselineskip value, 368
beamer key, 228
beamer Skin, 228
beamerfirst Skin, 230
beamerlast Skin, 232
beamermiddle Skin, 231
bean arc key, 37
before key, 78
before app key, 424
before doc body key, 474
before doc body command key, 474
before doc body environment key, 474
before doc body key key, 474
before example key, 468
before lower key, 66
before lower app key, 424
before lower pre key, 424
before nobreak key, 81
before pre key, 424

before skip key, 80
before title key, 64
before title app key, 423
before title pre key, 423
before upper key, 65
before upper app key, 423
before upper pre key, 423
beforeafter skip key, 80
below key, 406
between key, 407
bicolor key, 219
bicolor Skin, 219
bicolorfirst Skin, 221
bicolorlast Skin, 223
bicolormiddle Skin, 222
blank key, 208
blanker key, 238
blankest key, 239
blend before title key, 113
blend before title code key, 114
blend into key, 112
bookmark key, 100
bookmark* key, 100
borderline key, 177
borderline east key, 180
borderline horizontal key, 181
borderline north key, 180
borderline south key, 180
borderline vertical key, 181
borderline west key, 180
both value, 123
bottom key, 43
bottom value, 33, 79, 117, 286
bottom seam value, 117
bottomrule key, 35
bottomrule at break key, 369
bottomsep at break key, 369
bottomtitle key, 43
box align key, 79
\boxarrayclear, 388
\boxarraygetbox, 392
\boxarraygetdepth, 393
\boxarraygetheight, 393
\boxarraygetsize, 390
\boxarraygettotalheight, 394
\boxarraygetwidth, 393
\boxarrayreset, 387
boxarraystore environment, 390
boxed title size key, 158
boxed title style key, 159
boxes key, 402
boxrule key, 36
boxsep key, 39
\brackets, 462
break value, 355
break at key, 367
breakable key, 9, 365
broken value, 165–167

capture key, 94
center key, 85
center value, 30, 33, 79, 117, 286
center lower key, 32
center seam value, 117
center title key, 32
center upper key, 32
change value, 355
change apart value, 355
change break value, 355
change standard value, 354
check odd page key, 101
circular arc key, 37
clear preamble key, 454
clear preclass key, 454
clip lower key, 176
clip title key, 175
clip upper key, 175
clip watermark key, 171
clipped value, 270
code key, 106
colback key, 27
colbacklower key, 220
colbacktitle key, 27
\colDef, 466
colframe key, 27
collower key, 28
colon value, 113
colon hang value, 113
\colOpt, 466
color key, 471
color color key, 470
color command key, 470
color counter key, 470
color definition key, 470
color environment key, 470
color from key, 269
color hyperlink key, 470
color key key, 470
color length key, 470
color option key, 470
color value key, 470
Colors
    Definition, 475
    ExampleBack, 475
    ExampleFrame, 475
    foocolor, 461
    Hyperlink, 475
    Option, 475
colors key, 471
colspacing key, 400
coltext key, 28
coltitle key, 28
column key, 404
column* key, 404
columns key, 400
colupper key, 28
comment key, 311
comment above listing key, 318
comment above* listing key, 318

comment and listing key, 314
comment only key, 311
comment outside listing key, 316
comment side listing key, 316
comment style key, 314
compilable listing key, 322
compiler key, 453
compress page key, 368
\consumeboxarray, 391
\consumetcboxarray, 391
copy value, 158
counter key, 471
Counters
    foocounter, 461
counters key, 471
coverage key, 401
Crefname key, 111
crefname key, 111
\cs, 462

dash value, 113
dash hang value, 113
\DeclareTCBInputListing, 443
\DeclareTCBListing, 441
\DeclareTCBox, 438
\DeclareTCBoxFit, 444
\DeclareTColorBox, 435
\DeclareTotalTCBox, 439
\DeclareTotalTCBoxFit, 445
\DeclareTotalTColorBox, 437
Definition color, 475
description color key, 344
description delimiters key, 344
description delimiters none key, 344
description delimiters parenthesis key, 344
description font key, 345
description formatter key, 345
detach title key, 20
direct value, 270
dispExample environment, 463
dispExample* environment, 463
dispListing environment, 464
dispListing* environment, 464
do not store to box array key, 390
doc value, 469
doc description key, 475
doc head key, 473
doc head command key, 473
doc head environment key, 473
doc head key key, 473
doc into index key, 475
doc left key, 472
doc left indent key, 472
doc marginnote key, 475
doc new key, 475
doc new and updated key, 475
doc right key, 472
doc right indent key, 472
doc updated key, 475
\docAuxCommand, 460
\docAuxCommand*, 460
\docAuxEnvironment, 460
\docAuxEnvironment*, 460
\docAuxKey, 461
\docAuxKey*, 461
\docColor, 461
\docColor*, 461
docCommand environment, 458
docCommand* environment, 459
\docCounter, 461
\docCounter*, 461
docEnvironment environment, 459
docEnvironment* environment, 459
docexample key, 468
docKey environment, 460
docKey* environment, 460
\docLength, 461
\docLength*, 461
documentation key, 10
documentation listing options key, 468
documentation listing style key, 468
documentation minted language key, 468
documentation minted options key, 468
documentation minted style key, 468
\docValue, 460
\docValue*, 460
downhill value, 48, 49
draft key, 248
draft Skin, 248
draftmode key, 203
draw method key, 270
drop fuzzy midday shadow key, 183
drop fuzzy shadow key, 182
drop fuzzy shadow east key, 186
drop fuzzy shadow north key, 186
drop fuzzy shadow northeast key, 186
drop fuzzy shadow northwest key, 186
drop fuzzy shadow south key, 185
drop fuzzy shadow southeast key, 185
drop fuzzy shadow southwest key, 185
drop fuzzy shadow west key, 185
drop large lifted shadow key, 187
drop lifted shadow key, 187
drop midday shadow key, 182
drop shadow key, 182
drop shadow east key, 185
drop shadow north key, 184
drop shadow northeast key, 185
drop shadow northwest key, 184
drop shadow south key, 184
drop shadow southeast key, 184
drop shadow southwest key, 184
drop shadow west key, 184
drop small lifted shadow key, 187

east fading, 270
east value, 48, 49
east size key, 267
east style key, 269

empty key, 237
empty Skin, 237
empty value, 135, 136
emptyfirst Skin, 240
emptylast Skin, 242
emptymiddle Skin, 241
enforce breakable key, 366
english language key, 471
enhanced key, 206
enhanced Skin, 206
enhanced jigsaw key, 213
enhanced jigsaw Skin, 213
enhanced standard key, 208
enhanced standard jigsaw key, 213
enhancedfirst Skin, 210
enhancedfirst jigsaw Skin, 214
enhancedlast Skin, 212
enhancedlast jigsaw Skin, 218
enhancedmiddle Skin, 211
enhancedmiddle jigsaw Skin, 215
enlarge bottom at break by key, 83
enlarge bottom by key, 83
enlarge bottom finally by key, 82
enlarge by key, 84
enlarge left by key, 83
enlarge right by key, 83
enlarge top at break by key, 83
enlarge top by key, 83
enlarge top initially by key, 82
enlargepage key, 367
enlargepage flexible key, 368
environment key, 453, 471
environment content key, 471
environment with percent key, 453
Environments
absquote, 464
boxarraystore, 390
dispExample, 463
dispExample*, 463
dispListing, 464
dispListing*, 464
docCommand, 458
docCommand*, 459
docEnvironment, 459
docEnvironment*, 459
docKey, 460
docKey*, 460
extcolorbox, 450
extikzpicture, 451
fooauxenv, 460
foocolorbox, 459
foocolorbox*, 459
posterboxenv, 403
tcbclipframe, 172
tcbclipinterior, 174
tcbcliptitle, 174
tcbexternal, 448
tcbinvclipframe, 173
tcbitemize, 280
tcblisting, 299
tcboutputlisting, 301
tcboxeditemize, 282
tcboxedraster, 281
tcbposter, 398
tcbraster, 279
tcbverbatimwrite, 126
tcbwritetemp, 126
tcolorbox, 12
environments key, 471
equal height group key, 61
evenpage value, 46, 86
every box key, 91
every box on higher layers key, 92
every box on layer n key, 92
every float key, 77
every listing line key, 306
every listing line* key, 306
ExampleBack color, 475
ExampleFrame color, 475
extcolorbox environment, 450
extend freelance key, 250
extend freelancefirst key, 250
extend freelancelast key, 250
extend freelancemiddle key, 250
external key, 10, 105
externalize key, 447
externalize example key, 452
externalize example! key, 452
externalize listing key, 452
externalize listing! key, 452
extikzpicture environment, 451
extras key, 371
extras broken key, 371
extras broken pre key, 432
extras first key, 371
extras first and middle key, 371
extras first and middle pre key, 432
extras first pre key, 432
extras last key, 371
extras last pre key, 432
extras middle key, 371
extras middle and last key, 371
extras middle and last pre key, 432
extras middle pre key, 432
extras pre key, 432
extras unbroken key, 371
extras unbroken and first key, 371
extras unbroken and first pre key, 432
extras unbroken and last key, 371
extras unbroken and last pre key, 432
extras unbroken pre key, 432
extrude bottom by key, 90
extrude by key, 90
extrude left by key, 89
extrude right by key, 89
extrude top by key, 90

fade in key, 271
fade out key, 271

Fadings
east, 270
north, 270
semi east, 270
semi north, 270
semi south, 270
semi west, 270
south, 270
west, 270
false value, 78, 81, 288, 365
fbox value, 44
figures value, 112
fill downwards key, 87
fill image opacity key, 262
fill image options key, 262
fill image scale key, 262
fill overzoom image key, 258
fill overzoom image* key, 258
fill overzoom picture key, 258
fill plain image key, 256
fill plain image* key, 256
fill plain picture key, 256
fill shrink image key, 260
fill shrink image* key, 260
fill shrink picture key, 260
fill stretch image key, 257
fill stretch image* key, 257
fill stretch picture key, 257
fill tile image key, 261
fill tile image* key, 261
fill tile picture key, 261
fill tile picture* key, 261
fill zoom image key, 259
fill zoom image* key, 259
fill zoom picture key, 259
final value, 420
finish key, 197
finish broken key, 198
finish broken pre key, 430
finish fading vignette key, 275
finish first key, 198
finish first and middle key, 198
finish first and middle pre key, 430
finish first pre key, 430
finish last key, 198
finish last pre key, 430
finish middle key, 198
finish middle and last key, 198
finish middle and last pre key, 430
finish middle pre key, 430
finish pre key, 430
finish raised fading vignette key, 274
finish unbroken key, 198
finish unbroken and first key, 198
finish unbroken and first pre key, 430
finish unbroken and last key, 198
finish unbroken and last pre key, 430
finish unbroken pre key, 430
finish vignette key, 274
first value, 165–167, 370
first and middle value, 165, 370
fit key, 412
fit algorithm key, 418
fit basedim key, 413
fit fontsize macros key, 414
fit height from key, 417
fit height plus key, 415
fit maxfontdiff key, 420
fit maxfontdiffgap key, 420
fit maxstep key, 420
fit maxwidthdiff key, 420
fit maxwidthdiffgap key, 420
fit skip key, 413
fit to key, 413
fit to height key, 413
fit warning key, 420
fit width from key, 416
fit width plus key, 415
fitbox value, 94
fitting key, 9
fixed height key, 405
flip title key, 156
float key, 76
float* key, 76
floatplacement key, 76
flush center value, 30, 32
flush left key, 85
flush left value, 30, 32
flush right key, 85
flush right value, 30, 32
flushleft lower key, 32
flushleft title key, 32
flushleft upper key, 32
flushright lower key, 32
flushright title key, 32
flushright upper key, 32
fontlower key, 29
fontsize key, 402
fontsize value, 418
fontsize* value, 418
fonttitle key, 29
fontupper key, 29
\fooaux, 460, 469
fooaux key, 461
fooauxenv environment, 460
foocolor color, 461
foocolorbox environment, 459
foocolorbox* environment, 459
foocounter counter, 461
foodummy key, 465
\foolength length, 461
\foomakedocSubKey, 458
\foomakedocSubKey*, 459
\foosomething, 475
footitle key, 460
foovalue value, 460
force remake key, 447
forced value, 46, 86

forced center value, 97
forced left value, 97
forced right value, 97
forces nobeforeafter key, 78
frame code key, 138
frame code app key, 430
frame code pre key, 430
frame empty key, 138
frame engine key, 135
frame hidden key, 149
frame style key, 148
frame style image key, 148
frame style tile key, 149
freelance key, 250
freelance Skin, 250
freelance value, 135, 136
freelancefirst Skin, 250
freelancelast Skin, 250
freelancemiddle Skin, 250
freeze extension key, 325
freeze file key, 325
freeze jpg key, 325
freeze none key, 325
freeze pdf key, 325
freeze png key, 325
fuzzy halo key, 183
fuzzy shadow key, 189

geometry nodes key, 137
graphical environment key, 135
graphics directory key, 254
graphics options key, 254
graphics orientation key, 255
graphics pages key, 254
grow sidewards by key, 85
grow to left by key, 84
grow to right by key, 84

halign key, 30
halign lower key, 31
halign title key, 32
halign upper key, 30
halo key, 183
hbox key, 94
hbox value, 94
hbox boxed title key, 163
height key, 53, 400
height fill key, 56
height fixed for key, 370
height from key, 54
height plus key, 53
highlight math key, 349
highlight math style key, 349
hooks key, 9
horizontal size key, 268
hybrid value, 418
hybrid* value, 418
Hyperlink color, 475
hyperlink key, 199
hyperlink interior key, 200
hyperlink node key, 200
hyperlink title key, 200
hyperref key, 199
hyperref interior key, 199
hyperref node key, 199
hyperref title key, 199
hypertarget key, 100
hyperurl key, 200
hyperurl interior key, 200
hyperurl node key, 200
hyperurl title key, 200
hyperurl* key, 200
hyperurl* interior key, 200
hyperurl* node key, 200
hyperurl* title key, 200
hyphenationfix key, 96

if odd page key, 101
if odd page or oneside key, 101
if odd page or oneside* key, 102
if odd page* key, 102
IfBooleanTF key, 434
\ifboxarrayempty, 392
IfNoValueTF key, 433
IfValueTF key, 434
ignore nobreak key, 81
ignored value, 24
image comment key, 311
\imagename, 252
\imagepage, 253
index key, 471
index actual key, 469
index annotate key, 470
index colorize key, 470
index command key, 469
index command name key, 469
index default settings key, 469
index format key, 469
index german settings key, 469
index level key, 469
index quote key, 469
inherit height key, 57
input source on error key, 453
inside node key, 267
interior code key, 139
interior code app key, 431
interior code pre key, 431
interior empty key, 139
interior engine key, 136
interior hidden key, 150
interior style key, 149
interior style image key, 150
interior style tile key, 150
interior titled code key, 138
interior titled code app key, 430
interior titled code pre key, 431
interior titled empty key, 138
interior titled engine key, 135
invisible key, 22
invisible value, 22, 24

justify value, 30

key key, 471
Keys
/foo/
fooaux, 461
foodummy, 465
footitle, 460
/tcb/
add to height, 55
add to list, 99
add to natural height, 55
add to width, 34
adjust text, 18
adjusted title, 18
adjusted title after break, 366
after, 78
after app, 424
after doc body, 474
after doc body command, 474
after doc body environment, 474
after doc body key, 474
after example, 468
after lower, 66
after lower app, 424
after lower pre, 424
after lower*, 66
after pre, 424
after skip, 80
after title, 64
after title app, 423
after title pre, 423
after upper, 65
after upper app, 423
after upper pre, 423
after upper*, 65
ams align, 351
ams align lower, 351
ams align upper, 351
ams align*, 351
ams align* lower, 351
ams align* upper, 351
ams equation, 350
ams equation lower, 350
ams equation upper, 350
ams equation*, 350
ams equation* lower, 350
ams equation* upper, 350
ams gather, 352
ams gather lower, 352
ams gather upper, 352
ams gather*, 352
ams gather* lower, 352
ams gather* upper, 352
ams nodisplayskip, 353
ams nodisplayskip lower, 353
ams nodisplayskip upper, 353
arc, 36
arc is angular, 38
arc is curved, 38
at begin tikz, 192
at begin tikz reset, 192
at end tikz, 192
at end tikz reset, 192
attach boxed title to bottom, 156
attach boxed title to bottom center, 155
attach boxed title to bottom left, 155
attach boxed title to bottom right, 155
attach boxed title to bottom*, 156
attach boxed title to top, 156
attach boxed title to top center, 155
attach boxed title to top left, 155
attach boxed title to top right, 155
attach boxed title to top*, 156
attach title, 20
attach title to upper, 20
auto outer arc, 38
autoparskip, 78
baseline, 79
beamer, 228
bean arc, 37
before, 78
before app, 424
before doc body, 474
before doc body command, 474
before doc body environment, 474
before doc body key, 474
before example, 468
before lower, 66
before lower app, 424
before lower pre, 424
before nobreak, 81
before pre, 424
before skip, 80
before title, 64
before title app, 423
before title pre, 423
before upper, 65
before upper app, 423
before upper pre, 423
beforeafter skip, 80
bicolor, 219
blank, 208
blanker, 238
blankest, 239
blend before title, 113
blend before title code, 114
bookmark, 100
bookmark*, 100
borderline, 177
borderline east, 180
borderline horizontal, 181
borderline north, 180
borderline south, 180

borderline vertical, 181
borderline west, 180
bottom, 43
bottomrule, 35
bottomrule at break, 369
bottomsep at break, 369
bottomtitle, 43
box align, 79
boxed title size, 158
boxed title style, 159
boxrule, 36
boxsep, 39
break at, 367
breakable, 365
capture, 94
center, 85
center lower, 32
center title, 32
center upper, 32
check odd page, 101
circular arc, 37
clip lower, 176
clip title, 175
clip upper, 175
clip watermark, 171
code, 106
colback, 27
colbacklower, 220
colbacktitle, 27
colframe, 27
collower, 28
color color, 470
color command, 470
color counter, 470
color definition, 470
color environment, 470
color hyperlink, 470
color key, 470
color length, 470
color option, 470
color value, 470
coltext, 28
coltitle, 28
colupper, 28
comment, 311
comment above listing, 318
comment above* listing, 318
comment and listing, 314
comment only, 311
comment outside listing, 316
comment side listing, 316
comment style, 314
compilable listing, 322
compress page, 368
description color, 344
description delimiters, 344
description delimiters none, 344
description delimiters parenthesis, 344
description font, 345
description formatter, 345
detach title, 20
do not store to box array, 390
doc description, 475
doc head, 473
doc head command, 473
doc head environment, 473
doc head key, 473
doc into index, 475
doc left, 472
doc left indent, 472
doc marginnote, 475
doc new, 475
doc new and updated, 475
doc right, 472
doc right indent, 472
doc updated, 475
docexample, 468
documentation listing options, 468
documentation listing style, 468
documentation minted language, 468
documentation minted options, 468
documentation minted style, 468
draft, 248
draftmode, 203
drop fuzzy midday shadow, 183
drop fuzzy shadow, 182
drop fuzzy shadow east, 186
drop fuzzy shadow north, 186
drop fuzzy shadow northeast, 186
drop fuzzy shadow northwest, 186
drop fuzzy shadow south, 185
drop fuzzy shadow southeast, 185
drop fuzzy shadow southwest, 185
drop fuzzy shadow west, 185
drop large lifted shadow, 187
drop lifted shadow, 187
drop midday shadow, 182
drop shadow, 182
drop shadow east, 185
drop shadow north, 184
drop shadow northeast, 185
drop shadow northwest, 184
drop shadow south, 184
drop shadow southeast, 184
drop shadow southwest, 184
drop shadow west, 184
drop small lifted shadow, 187
empty, 237
enforce breakable, 366
english language, 471
enhanced, 206
enhanced jigsaw, 213
enhanced standard, 208
enhanced standard jigsaw, 213
enlarge bottom at break by, 83
enlarge bottom by, 83
enlarge bottom finally by, 82

enlarge by, 84
enlarge left by, 83
enlarge right by, 83
enlarge top at break by, 83
enlarge top by, 83
enlarge top initially by, 82
enlargepage, 367
enlargepage flexible, 368
equal height group, 61
every box, 91
every box on higher layers, 92
every box on layer n, 92
every float, 77
every listing line, 306
every listing line*, 306
extend freelance, 250
extend freelancefirst, 250
extend freelancelast, 250
extend freelancemiddle, 250
external, 105
externalize example, 452
externalize example!, 452
externalize listing, 452
externalize listing!, 452
extras, 371
extras broken, 371
extras broken pre, 432
extras first, 371
extras first and middle, 371
extras first and middle pre, 432
extras first pre, 432
extras last, 371
extras last pre, 432
extras middle, 371
extras middle and last, 371
extras middle and last pre, 432
extras middle pre, 432
extras pre, 432
extras unbroken, 371
extras unbroken and first, 371
extras unbroken and first pre, 432
extras unbroken and last, 371
extras unbroken and last pre, 432
extras unbroken pre, 432
extrude bottom by, 90
extrude by, 90
extrude left by, 89
extrude right by, 89
extrude top by, 90
fill downwards, 87
finish, 197
finish broken, 198
finish broken pre, 430
finish fading vignette, 275
finish first, 198
finish first and middle, 198
finish first and middle pre, 430
finish first pre, 430
finish last, 198
finish last pre, 430
finish middle, 198
finish middle and last, 198
finish middle and last pre, 430
finish middle pre, 430
finish pre, 430
finish raised fading vignette, 274
finish unbroken, 198
finish unbroken and first, 198
finish unbroken and first pre, 430
finish unbroken and last, 198
finish unbroken and last pre, 430
finish unbroken pre, 430
finish vignette, 274
fit, 412
fit algorithm, 418
fit basedim, 413
fit fontsize macros, 414
fit height from, 417
fit height plus, 415
fit maxfontdiff, 420
fit maxfontdiffgap, 420
fit maxstep, 420
fit maxwidthdiff, 420
fit maxwidthdiffgap, 420
fit skip, 413
fit to, 413
fit to height, 413
fit warning, 420
fit width from, 416
fit width plus, 415
flip title, 156
float, 76
float*, 76
floatplacement, 76
flush left, 85
flush right, 85
flushleft lower, 32
flushleft title, 32
flushleft upper, 32
flushright lower, 32
flushright title, 32
flushright upper, 32
fontlower, 29
fonttitle, 29
fontupper, 29
forces nobeforeafter, 78
frame code, 138
frame code app, 430
frame code pre, 430
frame empty, 138
frame engine, 135
frame hidden, 149
frame style, 148
frame style image, 148
frame style tile, 149
freelance, 250
freeze extension, 325
freeze file, 325

freeze jpg, 325
freeze none, 325
freeze pdf, 325
freeze png, 325
fuzzy halo, 183
fuzzy shadow, 189
geometry nodes, 137
graphical environment, 135
graphics directory, 254
graphics options, 254
graphics orientation, 255
graphics pages, 254
grow sidewards by, 85
grow to left by, 84
grow to right by, 84
halign, 30
halign lower, 31
halign title, 32
halign upper, 30
halo, 183
hbox, 94
hbox boxed title, 163
height, 53
height fill, 56
height fixed for, 370
height from, 54
height plus, 53
highlight math, 349
highlight math style, 349
hyperlink, 199
hyperlink interior, 200
hyperlink node, 200
hyperlink title, 200
hyperref, 199
hyperref interior, 199
hyperref node, 199
hyperref title, 199
hypertarget, 100
hyperurl, 200
hyperurl interior, 200
hyperurl node, 200
hyperurl title, 200
hyperurl*, 200
hyperurl* interior, 200
hyperurl* node, 200
hyperurl* title, 200
hyphenationfix, 96
if odd page, 101
if odd page or oneside, 101
if odd page or oneside*, 102
if odd page*, 102
IfBooleanTF, 434
IfNoValueTF, 433
IfValueTF, 434
ignore nobreak, 81
image comment, 311
index actual, 469
index annotate, 470
index colorize, 470
index command, 469
index command name, 469
index default settings, 469
index format, 469
index german settings, 469
index level, 469
index quote, 469
inherit height, 57
interior code, 139
interior code app, 431
interior code pre, 431
interior empty, 139
interior engine, 136
interior hidden, 150
interior style, 149
interior style image, 150
interior style tile, 150
interior titled code, 138
interior titled code app, 430
interior titled code pre, 431
interior titled empty, 138
interior titled engine, 135
invisible, 22
keywords bold, 469
label, 98
label separator, 346
label type, 98
left, 39
left skip, 81
left*, 39
lefthand ratio, 120
lefthand width, 119
leftlower, 40
leftright skip, 81
leftrule, 35
lefttitle, 40
leftupper, 40
lifted shadow, 190
lines before break, 366
list entry, 99
list text, 99
listing above comment, 318
listing above text, 317
listing above* comment, 318
listing above* text, 317
listing and comment, 314
listing and text, 310
listing engine, 310
listing file, 310
listing inputencoding, 306
listing only, 310
listing options, 305
listing outside comment, 316
listing outside text, 315
listing remove caption, 306
listing side comment, 316
listing side text, 315
listing style, 305
listing utf8, 307

lower separated, 25
lowerbox, 24
marker, 215
math, 350
math lower, 350
math upper, 350
middle, 43
minimum for current equal height group, 62
minimum for equal height group, 62
minipage, 94
minipage boxed title, 163
minipage boxed title*, 163
minted language, 308
minted options, 308
minted style, 309
move upwards, 87
move upwards*, 87
nameref, 99
natural height, 53
no borderline, 179
no boxed title style, 162
no extras, 371
no extras first, 371
no extras last, 371
no extras middle, 371
no extras unbroken, 371
no finish, 198
no finish first, 198
no finish last, 198
no finish middle, 198
no finish unbroken, 198
no label type, 98
no listing options, 305
no overlay, 72
no process, 322
no recording, 128
no shadow, 182
no underlay, 195
no underlay boxed title, 196
no underlay first, 196
no underlay last, 196
no underlay middle, 196
no underlay unbroken, 196
no watermark, 167
nobeforeafter, 78
nofloat, 76
noparskip, 78
nophantom, 98
notitle, 18
notitle after break, 366
octogon arc, 37
on line, 96
only, 106
opacityback, 51
opacitybacktitle, 51
opacityfill, 51
opacityframe, 51
opacitylower, 52
opacitytext, 52
opacitytitle, 52
opacityupper, 52
outer arc, 38
overlay, 71
overlay app, 425
overlay broken, 72
overlay broken app, 426
overlay broken pre, 426
overlay first, 72
overlay first and middle, 72
overlay first and middle app, 426
overlay first and middle pre, 426
overlay first app, 425
overlay first pre, 425
overlay last, 72
overlay last app, 426
overlay last pre, 426
overlay middle, 72
overlay middle and last, 72
overlay middle and last app, 426
overlay middle and last pre, 426
overlay middle app, 426
overlay middle pre, 426
overlay pre, 425
overlay unbroken, 72
overlay unbroken and first, 72
overlay unbroken and first app, 426
overlay unbroken and first pre, 426
overlay unbroken and last, 72
overlay unbroken and last app, 426
overlay unbroken and last pre, 426
overlay unbroken app, 425
overlay unbroken pre, 425
oversize, 45
pad after break, 369
pad at break, 369
pad at break*, 369
pad before break, 369
pad before break*, 369
parbox, 95
parfillskip restore, 81
parskip, 78
pdf comment, 312
pdf extension, 314
phantom, 98
phantomlabel, 98
placeholder, 408
process code, 322
raster after skip, 284
raster before skip, 284
raster column n, 288
raster column skip, 285
raster columns, 283
raster equal height, 287
raster equal height group, 287
raster equal skip, 284
raster even column, 288
raster even number, 289

raster even row, 289
raster every box, 288
raster force size, 288
raster halign, 286
raster height, 284
raster left skip, 285
raster multicolumn, 290
raster multirow, 291
raster number n, 289
raster odd column, 288
raster odd number, 289
raster odd row, 288
raster reset, 288
raster right skip, 285
raster row m, 289
raster row m column n, 289
raster row skip, 285
raster rows, 283
raster valign, 286
raster width, 283
record, 128
remake, 105
remember, 193
remember as, 194
reset, 105
reset and store to box array, 390
reset box array, 387
right, 40
right skip, 81
right*, 41
righthand ratio, 120
righthand width, 119
rightlower, 42
rightrule, 35
righttitle, 41
rightupper, 41
rotate, 193
rounded corners, 49
run arara, 324
run biber, 324
run bibtex, 324
run dvips, 324
run latex, 324
run lualatex, 324
run makeindex, 324
run pdflatex, 322
run ps2pdf, 324
run system command, 322
run xelatex, 324
savedelimiter, 26
savelowerto, 24
saveto, 23
scale, 193
segmentation at break, 370
segmentation code, 139
segmentation code app, 431
segmentation code pre, 431
segmentation empty, 139
segmentation engine, 136
segmentation hidden, 151
segmentation style, 151
separator sign, 343
separator sign colon, 343
separator sign dash, 343
separator sign none, 343
shadow, 188
sharp corners, 48
sharpish corners, 49
shield externalize, 105
show bounding box, 179
shrink break goal, 368
shrink tight, 89
sidebyside, 116
sidebyside adapt, 123
sidebyside align, 117
sidebyside gap, 119
sidebyside switch, 125
size, 44
skin, 134
skin first, 134
skin first is subskin of, 141
skin last, 134
skin last is subskin of, 141
skin middle, 134
skin middle is subskin of, 141
smart shadow arc, 190
space, 58
space to, 59
space to both, 59
space to lower, 58
space to upper, 58
spartan, 247
split, 60
spread, 88
spread downwards, 88
spread inwards, 87
spread outwards, 87
spread sidewards, 88
spread upwards, 88
spread upwards*, 88
square, 58
squeezed title, 19
squeezed title*, 19
standard, 204
standard jigsaw, 205
step, 98
step and label, 98
store to box array, 388
subtitle style, 21
tabularx, 68
tabularx*, 68
tcbimage comment, 312
tcbox raise, 96
tcbox raise base, 96
tcbox width, 97
tempfile, 96
terminator sign, 345
terminator sign colon, 346

terminator sign dash, 346
terminator sign none, 346
text above listing, 317
text above* listing, 317
text and listing, 310
text fill, 67
text height, 54
text only, 311
text outside listing, 315
text side listing, 315
text width, 34
theorem, 349
theorem full label supplement, 347
theorem label supplement, 347
theorem name, 348
theorem name and number, 348
theorem number and name, 348
theorem style, 354
tikz, 192
tikz lower, 69
tikz reset, 192
tikz upper, 69
tikznode, 70
tikznode boxed title, 164
tikznode lower, 70
tikznode upper, 70
tile, 224
title, 18
title after break, 366
title code, 140
title code app, 431
title code pre, 431
title empty, 140
title engine, 136
title filled, 27
title hidden, 152
title style, 151
title style image, 152
title style tile, 152
titlerule, 36
titlerule style, 153
toggle enlargement, 86
toggle left and right, 46
top, 42
toprule, 35
toprule at break, 369
topsep at break, 369
toptitle, 42
unbreakable, 366
underlay, 195
underlay boxed title, 196
underlay boxed title pre, 429
underlay broken, 196
underlay broken pre, 429
underlay first, 196
underlay first and middle, 196
underlay first and middle pre, 429
underlay first pre, 429
underlay last, 196
underlay last pre, 429
underlay middle, 196
underlay middle and last, 196
underlay middle and last pre, 429
underlay middle pre, 429
underlay pre, 429
underlay raised fading vignette, 273
underlay raised shading vignette, 273
underlay shade in vignette, 273
underlay unbroken, 196
underlay unbroken and first, 196
underlay unbroken and first pre, 429
underlay unbroken and last, 196
underlay unbroken and last pre, 429
underlay unbroken pre, 429
underlay vignette, 272
upperbox, 22
use height from group, 63
valign, 33
valign lower, 33
valign scale limit, 33
valign upper, 33
varwidth boxed title, 164
varwidth boxed title*, 164
varwidth upper, 70
verbatim, 433
verbatim ignore percent, 127
vfill before first, 370
visible, 22
void, 107
watermark color, 170
watermark graphics, 166
watermark graphics app, 428
watermark graphics app on, 428
watermark graphics on, 166
watermark graphics pre, 428
watermark graphics pre on, 428
watermark opacity, 168
watermark overzoom, 169
watermark shrink, 169
watermark stretch, 170
watermark text, 165
watermark text app, 427
watermark text app on, 427
watermark text on, 165
watermark text pre, 427
watermark text pre on, 427
watermark tikz, 167
watermark tikz app, 428
watermark tikz app on, 428
watermark tikz on, 167
watermark tikz pre, 428
watermark tikz pre on, 428
watermark zoom, 168
widget, 233
width, 34

/tcb/boxtitle/
xshift, 157
yshift, 157
yshift*, 157
yshifttext, 157
/tcb/doclang/
color, 471
colors, 471
counter, 471
counters, 471
environment, 471
environment content, 471
environments, 471
index, 471
key, 471
keys, 471
length, 471
lengths, 471
new, 471
pageshort, 471
updated, 471
value, 471
values, 471
/tcb/external/
-, 447
!, 447
clear preamble, 454
clear preclass, 454
compiler, 453
environment, 453
environment with percent, 453
externalize, 447
force remake, 447
input source on error, 453
minipage, 453
name, 449
PassOptionsToClass, 454
PassOptionsToPackage, 454
plain, 453
preamble, 454
preamble tcbset, 454
preclass, 454
prefix, 447
runner, 447
runs, 453
safety, 453
/tcb/library/
all, 10
breakable, 9
documentation, 10
external, 10
fitting, 9
hooks, 9
listings, 9
listingsutf8, 9
magazine, 9
many, 10
minted, 9
most, 10
poster, 9
raster, 9
skins, 9
theorems, 9
vignette, 9
xparse, 10
/tcb/new/
auto counter, 108
blend into, 112
Crefname, 111
crefname, 111
list inside, 115
list type, 115
no counter, 109
number format, 110
number freestyle, 110
number within, 110
use counter, 109
use counter from, 109
use counter*, 109
/tcb/poster/
colspacing, 400
columns, 400
height, 400
prefix, 400
rows, 400
rowspacing, 400
showframe, 400
spacing, 400
width, 400
/tcb/posterloc/
above, 406
at, 407
below, 406
between, 407
column, 404
column*, 404
fixed height, 405
name, 404
row, 405
rowspan, 405
sequence, 408
span, 405
xshift, 409
yshift, 409
/tcb/posterset/
boxes, 402
coverage, 401
fontsize, 402
no coverage, 401
poster, 400
/tcb/vig/
base color, 269
color from, 269
draw method, 270
east size, 267
east style, 269
fade in, 271
fade out, 271

horizontal size, 268
inside node, 267
lower left corner, 266
lowered color, 269
north size, 267
north style, 268
outside node, 267
over node, 267
over node offset, 267
raised color, 269
scope, 269
semi fade in, 271
semi fade out, 271
size, 268
south size, 267
south style, 268
upper right corner, 266
vertical size, 268
west size, 268
west style, 269
xmax, 266
xmin, 266
ymax, 266
ymin, 266
/tikz/
fill image opacity, 262
fill image options, 262
fill image scale, 262
fill overzoom image, 258
fill overzoom image*, 258
fill overzoom picture, 258
fill plain image, 256
fill plain image*, 256
fill plain picture, 256
fill shrink image, 260
fill shrink image*, 260
fill shrink picture, 260
fill stretch image, 257
fill stretch image*, 257
fill stretch picture, 257
fill tile image, 261
fill tile image*, 261
fill tile picture, 261
fill tile picture*, 261
fill zoom image, 259
fill zoom image*, 259
fill zoom picture, 259
tcb fill frame, 154
tcb fill interior, 154
tcb fill title, 154
keys key, 471
keywords bold key, 469

label key, 98
label separator key, 346
label type key, 98
landscape value, 255
landscape* value, 255
last value, 165–167, 370
left key, 39
left value, 30, 123, 286
left skip key, 81
left* key, 39
lefthand ratio key, 120
lefthand width key, 119
leftlower key, 40
leftright skip key, 81
leftrule key, 35
lefttitle key, 40
leftupper key, 40
length key, 471
Lengths
\foolength, 461
lengths key, 471
lifted shadow key, 190
lines before break key, 366
list entry key, 99
list inside key, 115
list text key, 99
list type key, 115
listing above comment key, 318
listing above text key, 317
listing above* comment key, 318
listing above* text key, 317
listing and comment key, 314
listing and text key, 310
listing engine key, 310
listing file key, 310
listing inputencoding key, 306
listing only key, 310
listing options key, 305
listing outside comment key, 316
listing outside text key, 315
listing remove caption key, 306
listing side comment key, 316
listing side text key, 315
listing style key, 305
listing utf8 key, 307
listings key, 9
listings value, 112, 310
listingsutf8 key, 9
lower left corner key, 266
lower separated key, 25
lowerbox key, 24
lowered color key, 269

magazine key, 9
many key, 10
\marg, 462
margin value, 356
margin apart value, 356
margin break value, 356
marker key, 215
math key, 350
math lower key, 350
math upper key, 350
maximum value, 56
\meta, 462
middle key, 43
middle value, 165–167, 370

middle and last value, 165–167, 370
minimal value, 44
minimum center value, 97
minimum for current equal height group key, 62
minimum for equal height group key, 62
minimum left value, 97
minimum right value, 97
minipage key, 94, 453
minipage value, 94, 280
minipage boxed title key, 163
minipage boxed title* key, 163
minted key, 9
minted value, 310
minted language key, 308
minted options key, 308
minted style key, 309
most key, 10
move upwards key, 87
move upwards* key, 87

name key, 404, 449
nameref key, 99
natural height key, 53
new key, 471
\newboxarray, 387
\newtcbexternalizeenvironment, 455
\newtcbexternalizetcolorbox, 455
\NewTCBInputListing, 443
\newtcbinputlisting, 304
\NewTCBListing, 441
\newtcblisting, 302
\NewTCBox, 438
\newtcbox, 16
\NewTCBoxFit, 444
\newtcboxfit, 411
\newtcbtheorem, 339
\NewTColorBox, 436
\newtcolorbox, 15
\NewTotalTCBox, 440
\NewTotalTCBoxFit, 445
\NewTotalTColorBox, 437
no borderline key, 179
no boxed title style key, 162
no counter key, 109
no coverage key, 401
no extras key, 371
no extras first key, 371
no extras last key, 371
no extras middle key, 371
no extras unbroken key, 371
no finish key, 198
no finish first key, 198
no finish last key, 198
no finish middle key, 198
no finish unbroken key, 198
no label type key, 98
no listing options key, 305
no overlay key, 72
no process key, 322
no recording key, 128
no shadow key, 182
no underlay key, 195
no underlay boxed title key, 196
no underlay first key, 196
no underlay last key, 196
no underlay middle key, 196
no underlay unbroken key, 196
no watermark key, 167
nobeforeafter key, 78
nofloat key, 76
none value, 46, 86, 123, 287, 368, 370
noparskip key, 78
nophantom key, 98
normal value, 44, 158
north fading, 270
north value, 48, 49
north size key, 267
north style key, 268
northeast value, 48, 49
northwest value, 48, 49
notitle key, 18
notitle after break key, 366
number format key, 110
number freestyle key, 110
number within key, 110

\oarg, 462
octogon arc key, 37
off value, 420, 469
on value, 420
on line key, 96
only key, 106
opacityback key, 51
opacitybacktitle key, 51
opacityfill key, 51
opacityframe key, 51
opacitylower key, 52
opacitytext key, 52
opacitytitle key, 52
opacityupper key, 52
Option color, 475
outer arc key, 38
outside node key, 267
over node key, 267
over node offset key, 267
overlay key, 71
overlay app key, 425
overlay broken key, 72
overlay broken app key, 426
overlay broken pre key, 426
overlay first key, 72
overlay first and middle key, 72
overlay first and middle app key, 426
overlay first and middle pre key, 426
overlay first app key, 425
overlay first pre key, 425
overlay last key, 72
overlay last app key, 426
overlay last pre key, 426

overlay middle key, 72
overlay middle and last key, 72
overlay middle and last app key, 426
overlay middle and last pre key, 426
overlay middle app key, 426
overlay middle pre key, 426
overlay pre key, 425
overlay unbroken key, 72
overlay unbroken and first key, 72
overlay unbroken and first app key, 426
overlay unbroken and first pre key, 426
overlay unbroken and last key, 72
overlay unbroken and last app key, 426
overlay unbroken and last pre key, 426
overlay unbroken app key, 425
overlay unbroken pre key, 425
oversize key, 45

pad after break key, 369
pad at break key, 369
pad at break* key, 369
pad before break key, 369
pad before break* key, 369
pageshort key, 471
parbox key, 95
parfillskip restore key, 81
parskip key, 78
PassOptionsToClass key, 454
PassOptionsToPackage key, 454
path value, 135, 136
pathfirst value, 135, 136
pathfirstjigsaw value, 135
pathjigsaw value, 135
pathlast value, 135, 136
pathlastjigsaw value, 135
pathmiddle value, 135, 136
pathmiddlejigsaw value, 135
pdf comment key, 312
pdf extension key, 314
\pdfpages, 254
pgf value, 469
pgfchapter value, 469
pgfsection value, 469
phantom key, 98
phantomlabel key, 98
placeholder key, 408
plain key, 453
plain value, 354
plain apart value, 355
portrait value, 255
portrait* value, 255
poster key, 9, 400
\posterbox, 403
posterboxenv environment, 403
preamble key, 454
preamble tcbset key, 454
preclass key, 454
prefix key, 400, 447
process code key, 322
\ProvideTCBInputListing, 443
\ProvideTCBListing, 441
\ProvideTCBox, 438
\ProvideTCBoxFit, 444
\ProvideTColorBox, 436
\ProvideTotalTCBox, 440
\ProvideTotalTCBoxFit, 445
\ProvideTotalTColorBox, 437

raised color key, 269
raster key, 9
raster after skip key, 284
raster before skip key, 284
raster column n key, 288
raster column skip key, 285
raster columns key, 283
raster equal height key, 287
raster equal height group key, 287
raster equal skip key, 284
raster even column key, 288
raster even number key, 289
raster even row key, 289
raster every box key, 288
raster force size key, 288
raster halign key, 286
raster height key, 284
raster left skip key, 285
raster multicolumn key, 290
raster multirow key, 291
raster number n key, 289
raster odd column key, 288
raster odd number key, 289
raster odd row key, 288
raster reset key, 288
raster right skip key, 285
raster row m key, 289
raster row m column n key, 289
raster row skip key, 285
raster rows key, 283
raster valign key, 286
raster width key, 283
record key, 128
\refAux, 466
\refAuxcs, 466
\refCom, 465
\refCom*, 465
\refEnv, 465
\refEnv*, 465
\refKey, 466
\refKey*, 466
remake key, 105
remember key, 193
remember as key, 194
\renewtcbexternalizeenvironment, 455
\renewtcbexternalizetcolorbox, 456
\RenewTCBInputListing, 443
\renewtcbinputlisting, 304
\RenewTCBListing, 441
\renewtcblisting, 303
\RenewTCBox, 438
\renewtcbox, 16

\RenewTCBoxFit, 444
\renewtcboxfit, 411
\renewtcbtheorem, 340
\RenewTColorBox, 436
\renewtcolorbox, 15
\RenewTotalTCBox, 440
\RenewTotalTCBoxFit, 445
\RenewTotalTColorBox, 437
reset key, 105
reset and store to box array key, 390
reset box array key, 387
right key, 40
right value, 30, 123, 286
right skip key, 81
right* key, 41
righthand ratio key, 120
righthand width key, 119
rightlower key, 42
rightrule key, 35
righttitle key, 41
rightupper key, 41
rotate key, 193
rounded corners key, 49
row key, 405
rows key, 400
rows value, 287
rowspacing key, 400
rowspan key, 405
run arara key, 324
run biber key, 324
run bibtex key, 324
run dvips key, 324
run latex key, 324
run lualatex key, 324
run makeindex key, 324
run pdflatex key, 322
run ps2pdf key, 324
run system command key, 322
run xelatex key, 324
runner key, 447
runs key, 453

safety key, 453
savedelimiter key, 26
savelowerto key, 24
saveto key, 23
scale key, 193
scale value, 33
scale* value, 33
scope key, 269
segmentation at break key, 370
segmentation code key, 139
segmentation code app key, 431
segmentation code pre key, 431
segmentation empty key, 139
segmentation engine key, 136
segmentation hidden key, 151
segmentation style key, 151
semi east fading, 270
semi fade in key, 271
semi fade out key, 271
semi north fading, 270
semi south fading, 270
semi west fading, 270
separator sign key, 343
separator sign colon key, 343
separator sign dash key, 343
separator sign none key, 343
sequence key, 408
shadow key, 188
sharp corners key, 48
sharpish corners key, 49
shield externalize key, 105
show bounding box key, 179
showframe key, 400
shrink break goal key, 368
shrink tight key, 89
sidebyside key, 116
sidebyside adapt key, 123
sidebyside align key, 117
sidebyside gap key, 119
sidebyside switch key, 125
size key, 44, 268
skin key, 134
skin first key, 134
skin first is subskin of key, 141
skin last key, 134
skin last is subskin of key, 141
skin middle key, 134
skin middle is subskin of key, 141
Skins
    beamer, 228
    beamerfirst, 230
    beamerlast, 232
    beamermiddle, 231
    bicolor, 219
    bicolorfirst, 221
    bicolorlast, 223
    bicolormiddle, 222
    draft, 248
    empty, 237
    emptyfirst, 240
    emptylast, 242
    emptymiddle, 241
    enhanced, 206
    enhanced jigsaw, 213
    enhancedfirst, 210
    enhancedfirst jigsaw, 214
    enhancedlast, 212
    enhancedlast jigsaw, 218
    enhancedmiddle, 211
    enhancedmiddle jigsaw, 215
    freelance, 250
    freelancefirst, 250
    freelancelast, 250
    freelancemiddle, 250
    spartan, 247
    standard, 204
    standard jigsaw, 205

tile, 224
tilefirst, 225
tilelast, 227
tilemiddle, 226
widget, 233
widgetfirst, 234
widgetlast, 236
widgetmiddle, 235
skins key, 9
small value, 44
smart shadow arc key, 190
south fading, 270
south value, 48, 49
south size key, 267
south style key, 268
southeast value, 48, 49
southwest value, 48, 49
space key, 58
space to key, 59
space to both key, 59
space to lower key, 58
space to upper key, 58
spacing key, 400
span key, 405
spartan key, 247
spartan Skin, 247
spartan value, 135, 136
split key, 60
spread key, 88
spread downwards key, 88
spread inwards key, 87
spread outwards key, 87
spread sidewards key, 88
spread upwards key, 88
spread upwards* key, 88
square key, 58
squeeze value, 418
squeezed title key, 19
squeezed title* key, 19
standard key, 204
standard Skin, 204
standard value, 135, 136, 158, 354
standard jigsaw key, 205
standard jigsaw Skin, 205
step key, 98
step and label key, 98
store to box array key, 388
subtitle style key, 21

tables value, 112
tabularx key, 68
tabularx* key, 68
tcb fill frame key, 154
tcb fill interior key, 154
tcb fill title key, 154
\tcbbreak, 376
tcbclipframe environment, 172
tcbclipinterior environment, 174
tcbcliptitle environment, 174
\tcbcontinuedraftmode, 203
\tcbcounter, 108
\tcbdocmarginnote, 467
\tcbdocnew, 467
\tcbdocupdated, 467
tcbexternal environment, 448
\tcbEXTERNALIZE, 447
\tcbfitdim, 411–414
\tcbfitsteps, 412
\tcbfontsize, 411
\tcbheightfromgroup, 63
\tcbheightspace, 146
\tcbhighmath, 341
\tcbhypernode, 264
\tcbifexternal, 454
\tcbiffileprocess, 456
\tcbifoddpage, 103
\tcbifoddpageoroneside, 103
tcbimage comment key, 312
\tcbincludegraphics, 251
\tcbincludepdf, 253
\tcbinputlisting, 301
\tcbinputrecords, 128
\tcbinterruptdraftmode, 203
tcbinvclipframe environment, 173
\tcbitem, 280
tcbitemize environment, 280
\tcbline, 209
\tcbline*, 209
tcblisting environment, 299
\tcblistof, 115
\tcblower, 12
\tcbmakedocSubKey, 465
\tcbmaketheorem, 340
tcboutputlisting environment, 301
\tcbox, 14
tcbox raise key, 96
tcbox raise base key, 96
tcbox width key, 97
tcboxeditemize environment, 282
tcboxedraster environment, 281
\tcboxedtitleheight, 157
\tcboxedtitlewidth, 157
\tcboxfit, 410
\tcboxmath, 341
\tcboxverb, 440
\tcbpatcharcangular, 263
\tcbpatcharcround, 263
tcbposter environment, 398
\tcbpostercolspacing, 399
\tcbpostercolumns, 399
\tcbpostercolwidth, 399
\tcbposterheight, 399
\tcbposterrowheight, 399
\tcbposterrows, 399
\tcbposterrowspacing, 399
\tcbposterset, 399
\tcbposterwidth, 399
tcbraster environment, 279
\tcbrecord, 128

\tcbsegmentstate, 147
\tcbset, 13
\tcbsetforeverylayer, 13
\tcbsetmacrotoheightofnode, 264
\tcbsetmacrotowidthofnode, 264
\tcbsetmanagedlayers, 92
\tcbsettoheightofnode, 264
\tcbsettowidthofnode, 264
\tcbsidebyside, 122
\tcbstartdraftmode, 203
\tcbstartrecording, 128
\tcbstopdraftmode, 203
\tcbstoprecording, 128
\tcbsubskin, 141
\tcbsubtitle, 21
\tcbtextheight, 147
\tcbtextwidth, 146
\tcbtitle, 20
\tcbtitletext, 20
\tcbuselibrary, 9
\tcbuselistinglisting, 301
\tcbuselistingtext, 301
\tcbusetemp, 126
\tcbusetemplisting, 301
tcbverbatimwrite environment, 126
\tcbvignette, 265
tcbwritetemp environment, 126
tcolorbox environment, 12
\tcolorboxenvironment, 17
tempfile key, 96
terminator sign key, 345
terminator sign colon key, 346
terminator sign dash key, 346
terminator sign none key, 346
text above listing key, 317
text above* listing key, 317
text and listing key, 310
text fill key, 67
text height key, 54
text only key, 311
text outside listing key, 315
text side listing key, 315
text width key, 34
theorem key, 349
theorem full label supplement key, 347
theorem label supplement key, 347
theorem name key, 348
theorem name and number key, 348
theorem number and name key, 348
theorem style key, 354
theorems key, 9
\thetcbcounter, 108, 109
\thetcbrasternum, 279, 290
\thetcolorboxnumber, 104
\thetcolorboxpage, 104
tight value, 44
tikz key, 192
tikz lower key, 69
tikz reset key, 192
tikz upper key, 69
tikznode key, 70
tikznode boxed title key, 164
tikznode lower key, 70
tikznode upper key, 70
tile key, 224
tile Skin, 224
tilefirst Skin, 225
tilelast Skin, 227
tilemiddle Skin, 226
title key, 18
title value, 44, 158
title after break key, 366
title code key, 140
title code app key, 431
title code pre key, 431
title empty key, 140
title engine key, 136
title filled key, 27
title hidden key, 152
title style key, 151
title style image key, 152
title style tile key, 152
titlerule key, 36
titlerule style key, 153
toggle enlargement key, 86
toggle left and right key, 46
top key, 42
top value, 33, 79, 117, 286
top seam value, 117
toprule key, 35
toprule at break key, 369
topsep at break key, 369
toptitle key, 42
true value, 81, 365

unbreakable key, 366
unbroken value, 165–167
unbroken and first value, 165–167
underlay key, 195
underlay boxed title key, 196
underlay boxed title pre key, 429
underlay broken key, 196
underlay broken pre key, 429
underlay first key, 196
underlay first and middle key, 196
underlay first and middle pre key, 429
underlay first pre key, 429
underlay last key, 196
underlay last pre key, 429
underlay middle key, 196
underlay middle and last key, 196
underlay middle and last pre key, 429
underlay middle pre key, 429
underlay pre key, 429
underlay raised fading vignette key, 273
underlay raised shading vignette key, 273
underlay shade in vignette key, 273
underlay unbroken key, 196
underlay unbroken and first key, 196

underlay unbroken and first pre key, 429
underlay unbroken and last key, 196
underlay unbroken and last pre key, 429
underlay unbroken pre key, 429
underlay vignette key, 272
unlimited value, 364, 365
updated key, 471
uphill value, 48, 49
upper right corner key, 266
upperbox key, 22
use counter key, 109
use counter from key, 109
use counter* key, 109
use height from group key, 63
\useboxarray, 390
\usetcboxarray, 391

valign key, 33
valign lower key, 33
valign scale limit key, 33
valign upper key, 33
value key, 471
Values
0, 147
1, 147
2, 147
all, 48, 49, 287, 368, 370
areasize, 418
areasize*, 418
as-is, 255
auto, 97
auto limited, 97
base, 79
baselineskip, 368
both, 123
bottom, 33, 79, 117, 286
bottom seam, 117
break, 355
broken, 165–167
center, 30, 33, 79, 117, 286
center seam, 117
change, 355
change apart, 355
change break, 355
change standard, 354
clipped, 270
colon, 113
colon hang, 113
copy, 158
dash, 113
dash hang, 113
direct, 270
doc, 469
downhill, 48, 49
east, 48, 49
empty, 135, 136
evenpage, 46, 86
false, 78, 81, 288, 365
fbox, 44
figures, 112
final, 420
first, 165–167, 370
first and middle, 165, 370
fitbox, 94
flush center, 30, 32
flush left, 30, 32
flush right, 30, 32
fontsize, 418
fontsize*, 418
foovalue, 460
forced, 46, 86
forced center, 97
forced left, 97
forced right, 97
freelance, 135, 136
hbox, 94
hybrid, 418
hybrid*, 418
ignored, 24
invisible, 22, 24
justify, 30
landscape, 255
landscape*, 255
last, 165–167, 370
left, 30, 123, 286
listings, 112, 310
margin, 356
margin apart, 356
margin break, 356
maximum, 56
middle, 165–167, 370
middle and last, 165–167, 370
minimal, 44
minimum center, 97
minimum left, 97
minimum right, 97
minipage, 94, 280
minted, 310
none, 46, 86, 123, 287, 368, 370
normal, 44, 158
north, 48, 49
northeast, 48, 49
northwest, 48, 49
off, 420, 469
on, 420
path, 135, 136
pathfirst, 135, 136
pathfirstjigsaw, 135
pathjigsaw, 135
pathlast, 135, 136
pathlastjigsaw, 135
pathmiddle, 135, 136
pathmiddlejigsaw, 135
pgf, 469
pgfchapter, 469
pgfsection, 469
plain, 354
plain apart, 355
portrait, 255

portrait*, 255
right, 30, 123, 286
rows, 287
scale, 33
scale*, 33
small, 44
south, 48, 49
southeast, 48, 49
southwest, 48, 49
spartan, 135, 136
squeeze, 418
standard, 135, 136, 158, 354
tables, 112
tight, 44
title, 44, 158
top, 33, 79, 117, 286
top seam, 117
true, 81, 365
unbroken, 165–167
unbroken and first, 165–167
unlimited, 364, 365
uphill, 48, 49
visible, 22, 24
west, 48, 49
values key, 471
varwidth boxed title key, 164
varwidth boxed title* key, 164
varwidth upper key, 70
verbatim key, 433
verbatim ignore percent key, 127
vertical size key, 268
vfill before first key, 370
vignette key, 9
visible key, 22
visible value, 22, 24
void key, 107

watermark color key, 170
watermark graphics key, 166
watermark graphics app key, 428
watermark graphics app on key, 428
watermark graphics on key, 166
watermark graphics pre key, 428
watermark graphics pre on key, 428
watermark opacity key, 168
watermark overzoom key, 169
watermark shrink key, 169
watermark stretch key, 170
watermark text key, 165
watermark text app key, 427
watermark text app on key, 427
watermark text on key, 165
watermark text pre key, 427
watermark text pre on key, 427
watermark tikz key, 167
watermark tikz app key, 428
watermark tikz app on key, 428
watermark tikz on key, 167
watermark tikz pre key, 428
watermark tikz pre on key, 428
watermark zoom key, 168
west fading, 270
west value, 48, 49
west size key, 268
west style key, 269
widget key, 233
widget Skin, 233
widgetfirst Skin, 234
widgetlast Skin, 236
widgetmiddle Skin, 235
width key, 34, 400

xmax key, 266
xmin key, 266
xparse key, 10
xshift key, 157, 409

ymax key, 266
ymin key, 266
yshift key, 157, 409
yshift* key, 157
yshifttext key, 157